

Cloud, Big Data and Mobile

Home Slides Videos About Harish

Thursday, September 5, 2013

Exploring Amazon RDS MySQL Second Tier Read Replica


AWS recently introduced Second Tier Replica for RDS MySQL. You can use this feature to shift the load from primary master DB to the replica in first tier and prepare your application for handling extremely high level of read traffic. In this post we are going to explore this feature in following aspects :

- Steps to configure Multi-Tiered Amazon RDS MySQL Read replicas
- Second Tier Read Replica Deployment architectures
- Important Points to note

Amazon RDS MySQL version 5.6.12 on AWS WEST region was used.


Steps to configure Multi- Tiered Amazon RDS MySQL Read Replicas

Configuration steps for the following architecture is given in this post :



Step 1: Creating Read Replica from Master and Place at Tier 1:

To create RDS MySQL Read replica navigate to the dashboard of Amazon RDS, select the Amazon RDS MySQL Master(named "sampledb") and use the option of "Create Read Replica".



Name the newly created Amazon RDS Read replica as "sampledb-level1" and place it in Tier 1. The Tier 1 Amazon RDS MySQL read Replica can be created in same AZ of Master or in a different AZ for High Availability. When the Tier replica is placed in Different AZ , you should factor few extra milliseconds of latency during replication.



Explore the status from Master DB: Post successful creation of the Tier 1 Read Replica, You can see the Read Replica Id's from exploring the details of the Master DB. Illustrated in Below Screen shot :

Need consulting help ? Email me @
harish11g.aws@gmail.com
Connect @ [Twitter](#) / [Linkedin](#)

Search

Popular Posts - Week

- 25 Best Practice Tips for architecting your Amazon VPC
- Dissecting Amazon ELB : 18 things you should know
- Overcoming Outages in AWS : High Availability Architectures
- Caching architectures using Memcached & Amazon ElastiCache
- ElastiCache Redis : How to Backup & Launch from RDB Snapshots ?
- Comparison Analysis: Amazon ELB vs HAProxy EC2
- Load Balancing Amazon RDS Read Replica's using HAProxy
- Exploring Amazon Availability Zones
- Part 1: Understanding Amazon Elastic Block Store
- Part 7: AWS High Availability Patterns : Multi Region Architecture

Tags

AWS (161) Amazon web services (103) Amazon EC2 (102) Cloud computing (97) Architecture (66) High Availability (45) Availability Zones (32) BigData (29) Tips (29) Configuration (27) Amazon S3 (25) Amazon VPC (25) AWS Region (23) Amazon Elastic Load Balancing (23) Caching (23) EC2 (22) Amazon ELB (21) EBS (20) Performance (19) Cost Savings (18) CloudSearch (17) RDS (17) elasticache (17) Apache Solr (16) Load Balancing (16) Auto Scaling (15) ELB (15) Replication (15) Mobile (14) Search (14) Amazon SQS (13) Memcached (13) autoscaling (13) Amazon AutoScaling (12) Solr (12) Amazon CloudSearch (11) Amazon CloudWatch (11) Amazon DynamoDB (11) Comparison (11) HAProxy (11) Scaling (11) Elastic IP (10) ElastiCache (10) Amazon Glacier (9) ecommerce (9) Cloudfront (8) Hadoop (8) Akamai (7) MySQL (7) Route53 (7) Sharding (7) Varnish (7) EBS-Optimized (6) Geospatial (6) MapReduce (6) PLOPS (6) Apache SolrCloud (5) DR (5) LBR (5) Multi AZ (5) Presentation (5) Redis (5) WordPress (5) Clustering (4) Nginx (4) S3 (4) Zookeeper (4) Chef (3) Compilation (3) Hive (3) IOPS (3) Infographic (3) Latency Based Routing (3) Mahout (3) Mobile cloud (3) NAT (3) Security (3) Session Synchron (3) UltraDNS (3) snapshots (3) High IO (2) Jgroups (2) Rightscale (2) Terracotta (2) flume (2) Awards (1) BAAS (1) Cloud Stack (1) IIT-DOMS (1) RabbitMQ (1) Rackspace (1) SecureCloud (1) Social Media (1) chukwa (1) mobile cloud computing (1)

Harish Videos



powered by YouTube

Categories

- Compilation
- Configuration
- Cost Savings

Endpoint: sampledb-ckkagpekzjb-us-west-2-rds.amazonaws.com:3306 (available)		
Configuration Details	Security and Network	Instance and IOPS
DB Name: sampledb	Availability Zone: us-west-2a	Storage: 10 GB
Engine: mysql5.6.12	VPC ID: vpc-92327cta	Instance Class: db.t1.micro
Username: sampledb	Subnet Group: sample [Complete]	IOPS: disabled
Option Group(s): default:mysql-5.6 [in-sync]	Subnets: subnet-28337d40, subnet-5e337d36	
Character Set: default	Security Groups: default [active]	
Parameter Group: default:mysql5.6 [in-sync]		
Availability and Durability: Read Master	Maintenance Details	
Replication State: -	Minor Version Upgrade: Yes	
Replication Error: -	Maintenance Window: sat06:12-sat06:42	
Multi AZ: Yes	Backup Window: 06:13-06:43	
Secondary Zone: us-west-2b		
Automated Backups: Enabled (1 Day)		
Latest Restore Time: 2013 September 3 10:55:00 UTC+5:30		
Read Replica Ids: sampledb-level1		

Explore the status from Tier 1 Read Replica : When you explore the Tier 1 Read Replica details, you will find it is pointing to the Master DB. Illustrated in Below Screen Shot :

Endpoint: sampledb-level1-ckkagpekzjb-us-west-2-rds.amazonaws.com:3306 (available)		
Configuration Details	Security and Network	Instance and IOPS
DB Name: sampledb	Availability Zone: us-west-2a	Storage: 10 GB
Engine: mysql5.6.12	VPC ID: vpc-92327cta	Instance Class: db.t1.micro
Username: sampledb	Subnet Group: sample [Complete]	IOPS: disabled
Option Group(s): default:mysql-5.6 [in-sync]	Subnets: subnet-28337d40, subnet-5e337d36	
Character Set: default	Security Groups: default [active]	
Parameter Group: default:mysql5.6 [in-sync]		
Availability and Durability: Read Replica	Maintenance Details	
Read Replica Source: sampledb	Minor Version Upgrade: Yes	
Replication State: replicating	Maintenance Window: sat06:12-sat06:42	
Replication Error: -	Backup Window: 06:13-06:43	
Multi AZ: No		
Secondary Zone: -		
Automated Backups: Enabled (1 Day)		
Latest Restore Time: 2013 September 3 10:20:00 UTC+5:30		

Step 2: Creating Second Tier Read Replica from Tier 1 Read replica :

To create Second Tier Read replica navigate to the dashboard of Amazon RDS, select the Amazon RDS Tier 1 Read Replica (sampledb-level1) as the source and use the option of "Create Read Replica".

RDS Dashboard

Database

Instances

Reserved Purchases

Snapshots

Security Groups

Parameter Groups

Option Groups

Subnet Groups

Events

Event Subscriptions

Create Read Replica DB Instance

You are creating a replica DB instance from a source DB instance. This new DB instance will have the source DB instance's DB Security Groups and DB Parameter Groups.

Read Replica Source: sampledb-level1

DB Instance Identifier: sampledb-level2 (db.mysqlinstance)

DB Instance Class: db.t1.micro

Storage Type: Standard

Auto Minor Version Upgrade: Yes No

Database Port: 3306 (default: 3306)

Availability Zone: us-west-2a

Publicly Accessible: Yes No

Name the newly created Amazon RDS Read replica as "sampledb-level2" and place it in Second Tier 2. The Second Tier -2 Amazon RDS MySQL read Replica can be created in same AZ of Tier 1/Master or in a different AZ for High Availability.

Explore the status from Tier 2 Read Replica : When you explore the Tier 2 Read Replica details, you will find it is pointing to the Tier 1 - sampledb-level1 as replication source. Illustrated in Below Screen Shot :

Endpoint: sampledb-level2-ckkagpekzjb-us-west-2-rds.amazonaws.com:3306 (available)		
Configuration Details	Security and Network	Instance and IOPS
DB Name: sampledb	Availability Zone: us-west-2a	Storage: 10 GB
Engine: mysql5.6.12	VPC ID: vpc-92327cta	Instance Class: db.t1.micro
Username: sampledb	Subnet Group: sample [Complete]	IOPS: disabled
Option Group(s): default:mysql-5.6 [in-sync]	Subnets: subnet-28337d40, subnet-5e337d36	
Character Set: default	Security Groups: default [active]	
Parameter Group: default:mysql5.6 [in-sync]		
Availability and Durability: Read Replica	Maintenance Details	
Read Replica Source: sampledb-level1	Minor Version Upgrade: No	
Replication State: replicating	Maintenance Window: sat06:12-sat06:42	
Replication Error: -	Backup Window: Disabled	
Multi AZ: No		
Secondary Zone: Disabled		
Automated Backups: Disabled		
Latest Restore Time: -		

To Load Balance AWS RDS Read Replica's Refer this article : <http://harish11g.blogspot.com/2013/08/Load-balancing-Amazon-RDS-MySQL-read-replica-slaves-using-HAProxy.html>

Second Tier Read Replica Deployment Architectures


One of the main complexity behind Multi-Level replication is that, if Tier 1 Read Replica if not properly architected/placed, it can be a single point of failure. Imagine a case where you need 4 Read Replicas for your Master DB. You can take following approaches as illustrated below while designing your infrastructure for this requirement.

Security

Translate


Select Language

Powered by Google Translate



In Architecture-1, Tier-1 Read replica is a Single Point of Failure. Instead if you split Tier-1 itself into two separate fleets it offers better availability than architecture-1. Since both Tier-1 RR put replication load on Master DB, you can bypass this using Hot Standby instance. Benefits of this approach are explained below in the best practice architecture.

Best Practice High Availability Architecture for Second Tier Read Replica:



Condition 1 - Master DB Failure : Hot Standby becomes new master and Tier-1 Read Replicas point automatically to new source

Condition 2- Tier-1 Read Replica Failure : Entire Tier-1 and Associated Tier-2 has to be recreated. The Alternate Active Fleet of Tier-1+Tier-2 will serve the requests for high availability.

Condition 3 - Tier-2 Read Replica Failure : Only the non performing Tier-2 Read Replica instance has to be recreated

Condition 4- AZ NW problem: In event AZ-3 is failed, Requests are served by alternate fleet of Tier-1+Tier-2 in another AZ(AZ-4).

Multi-AZ Hot Standby Implementation is a recommended best practice when it comes to Multi-tiered Read replica implementation

- It is recommended to create Tier 1 Read Replicas from Multi-AZ DB instance to offload read queries from the source master DB instance for high traffic sites. If the source instance of a Multi-AZ deployment fails over to the secondary, any associated read replicas will be switched to use the secondary as their replication source automatically. This model guarantees high availability.
- Also when you initiate the creation of a Tier 1 read replica, Amazon RDS takes the DB Snapshot of your Standby DB instance (instead of Source DB) and begins replication. This model saves I/O suspension on your source DB during the snapshot process

Other Points to Note:

Note :

To Load Balance AWS RDS Read Replica's Refer this article : <http://harish11g.blogspot.com/2013/08/Load-balancing-Amazon-RDS-MySQL-read-replica-slaves-using-HAProxy.html>

P1) Circular replication are not allowed in this tiered replica creation process.

P2) Third Tier cannot be created. Actually in production, very rarely we need third tier and it is not an important feature


P3) When the "X" Tier replica is placed in Different AZ, you should factor a few extra milliseconds of latency during replication.

P4) Before a DB instance (Master or Tier 1) can serve as a replication source, you must enable automatic backups on the source DB instance by setting the backup retention period to a value other than 0. This requirement does not apply to second tier replica as they are not source DB instance for another read replica. So create "Read Replica" option will appear only when the Backup Retention is set to minimum of 1 day for any level Read Replica creation. When we "create Read Replica" by default RR is created with Backup Retention set to 0. Use the modify option illustrated in below screenshot and set the Backup Retention Period. :

P5) We have used t1.micro as RDS DB for article explanatory purpose. For production use cases please use proper instance types after proper capacity planning.

P6) AWS has released Parallel replica creation process, where you can create multiple Tier 1 and Tier 2 replicas in parallel. Since you no longer need to wait for one replica creation before starting the next one, it becomes easy to create multiple RR quickly. Without this feature, it would take hours to create a large Multi-tiered Replica setup.

P7) If a replica lags too far behind for your environment, the normal practice is to scale up or consider deleting and recreating the read replica. Imagine you have architecture where there are two Tier 1 and three Second Tier RR as illustrated in below architecture:



Now since Tier -1 RR is lagging, you are planning to delete and recreate the same. When you delete the Tier-1 RR, All the Second Tier Read Replica's will now become Standalone, Single AZ DB's. Once you have recreated the Tier -1 RR again and managed to retain the original end point as well, you cannot re-point these Second Tier RR to Tier -1 again. You need to recreate all 3 second tier from the Tier -1 again. For a application with heavy DB dependency and read traffic, it means 1/2 of the fleet is now down. This can lead to uncomfortable performance situation. This is not a ideal condition and AWS RDS team can take this in their Road Map. For such cases, it is better to create a new Tier -1 and Second tier fleet first, update your LB/App configs and then delete the old lagging fleet

P8) Why it is better to have Multi-tiered Read Replica as the last resort in your architecture ?

8.a) Currently 30 Read Replica can be created overall for a master in two tiers. 30 Read replica is more than sufficient and usually turns out to be costly architecture approach. Use this approach only for cases, which demand heavy read and when application code cannot accommodate changes and are highly DB dependent.

8.b) It is recommended in DB world to stay away from Multi-level replication as much possible. Your architecture will be much simpler with one master and "X" replica slaves, rather than having tiered replica's. As we observed in above deployment architectures, the second tier replica slave will be a trouble to manage in event of replication delay, crashes and network problems affecting the Tier-1 RR or the Master DB.

8.c) In case your application code can be redesigned, it is recommended to take following approaches before resorting to Second Tier replicas architecture

- Functional partition the RDS MySQL with Hot Stand By and Read Replica's
- Re-balance the DB load by using alternate data stores provided by AWS like DynamoDB, ElastiCache, CloudSearch etc.

If the above methods does not work for you, take the Second tier Read replica approach.

Thanks Senthil and Ram of 8KMiles for taking part in this analysis.

Posted by [Harish Ganesan](#)



[+1](#) +4 Recommend this on Google

Labels: [Amazon web services](#), [Architecture](#), [AWS](#), [Cloud computing](#), [Configuration](#), [High Availability](#), [Multi AZ](#), [MySQL](#), [RDS](#)

No comments:

[Post a Comment](#)

[Newer Post](#)

[Home](#)

[Older Post](#)

Subscribe to: [Post Comments \(Atom\)](#)

Need Consulting help ?

Name

Email *

Message *

[Send](#)

DISCLAIMER

All posts, comments, views expressed in this blog are my own and does not represent the positions or views of my past, present or future employers. The intention of this blog is to share my experience and views. Content is subject to change without any notice. While I would do my best to quote the original author or copyright owners wherever I reference them, if you find any of the content / images violating copyright, please let me know and I will act upon it immediately. Lastly, I encourage you to share the content of this blog in general with other online communities for non-commercial and educational purposes.

Followers

Join this site

with Google Friend Connect



Members (83)



Already a member? [Sign in](#)

My Presentations / Webinars / Conferences

Speaker at Cloud Connect 2013: Lock,Stock and X Smoking EC2's
Speaker at INTEROP 2012: Overcoming outages in public clouds- High Availability patterns
Speaker at Cloud Connect 2012: How enterprises are leveraging mobile + cloud computing ?
Speaker at Cloud Developer Conference 2012 :The Art of Infrastructure Elasticity
Speaker at RACSS 2012 Conference: Overview of Amazon Web Services
Presenter: Architecting your Mobile Application for the Cloud
Presenter: Prepare your IT infrastructure for Thanksgiving in AWS
Speaker at AWS Cloud Tour 2011 : Scale new business peaks with Amazon AutoScaling
Speaker at Cloud Developer Conference 2011 :High Availability architectures in AWS
NASSCOM Emergeout 2010 panelist : Selling strategies in the new Economy
Speaker at NASSCOM Emerge 2009 : Virtual Sourcing leveraging Cloud
Speaker at AWS 201: Breakout Track speaker Singapore 2012
Speaker at Cloud Computing Summit ,India 2012 : The Business Value of Mobile Cloud Computing
Guest Speaker at IIT-DOMS on Cloud Computing
Speaker at CSI IT2020:Big Data track
Workshop on Amazon Web Services @ VIT, Vellore

My Articles

[HighScalability.com - 7 tips for saving money on Amazon](#)
[Article on InformationWeek](#)
[DataQuest India - From being buzzwords to reality](#)
[InformationWeek India Print Issue March 2011](#)
[CloudStory.in Introduction to BigData articles](#)
[1 2 3](#)
[Cloudstory.in "Hive for Retail Analysis"](#)
[Cloudstory.in "Route53 and Geo Distributed Architectures"](#)
[HighScalability.com "The art of Infrastructure Elasticity"](#)
[Sitepoint.com "Amazon ElastiCache on Steroids"](#)
[Newvem.com "Dissecting Amazon ELB : 18 Facts you should know"](#)
[Article on Sify](#)
[Article on Rediff](#)

SlideShares

Popular Posts - All Time

[Dissecting Amazon ELB : 18 things you should know](#)
[25 Best Practice Tips for architecting your Amazon VPC](#)
[Overcoming Outages in AWS : High Availability Architectures](#)
[Caching architectures using Memcached & Amazon ElastiCache](#)
[Comparison Analysis:Amazon ELB vs HAProxy EC2](#)
[High Availability @ Load Balancing Layer-HAProxy / ELB](#)
[Architecting an Highly Available and Scalable WordPress Site in AWS](#)
[Load Balancing Amazon RDS Read Replica's using HAProxy](#)
[Configuring Apache Mahout and a Clustering Example](#)
[Part 1: Understanding Amazon Elastic Block Store](#)

Awesome Inc. template. Powered by [Blogger](#).