

3.2 BINARY SEARCH TREES




- ▶ BSTs
- ▶ ordered operations
- ▶ deletion

Binary search trees


Definition. A BST is a **binary tree** in **symmetric order**.

A **binary tree** is either:

- Empty.
- Two disjoint binary trees (left and right).



Anatomy of a binary tree



Anatomy of a binary search tree

Symmetric order. Each node has a key, and every node's key is:

- Larger than all keys in its left subtree.
- Smaller than all keys in its right subtree.

- ▶ BSTs
- ▶ ordered operations
- ▶ deletion

BST representation in Java

Java definition. A BST is a reference to a root **Node**.


A **Node** is comprised of four fields:

- A **Key** and a **value**.
- A reference to the left and right subtree.

smaller keys larger keys

```
private class Node
{
    private Key key;
    private Value val;
    private Node left, right;
    public Node(Key key, Value val)
    {
        this.key = key;
        this.val = val;
    }
}
```

Key and Value are generic types; Key is Comparable



Binary search tree

BST implementation (skeleton)

```
public class BST<Key extends Comparable<Key>, Value>
{
    private Node root;

    private class Node
    { /* see previous slide */ }

    public void put(Key key, Value val)
    { /* see next slides */ }

    public Value get(Key key)
    { /* see next slides */ }

    public void delete(Key key)
    { /* see next slides */ }

    public Iterable<Key> iterator()
    { /* see next slides */ }
}
```

← root of BST


5

BST search and insert demo

6

BST search

Get. Return value corresponding to given key, or null if no such key.



7

BST search: Java implementation

Get. Return value corresponding to given key, or null if no such key.

```
public Value get(Key key)
{
    Node x = root;
    while (x != null)
    {
        int cmp = key.compareTo(x.key);
        if (cmp < 0) x = x.left;
        else if (cmp > 0) x = x.right;
        else if (cmp == 0) return x.val;
    }
    return null;
}
```

Cost. Number of compares is equal to 1 + depth of node.


8

BST insert

Put. Associate value with key.

Search for key, then two cases:

- Key in tree \Rightarrow reset value.
- Key not in tree \Rightarrow add new node.



9

BST insert: Java implementation

Put. Associate value with key.

```
public void put(Key key, Value val)
{ root = put(root, key, val); }


private Node put(Node x, Key key, Value val)
{
    if (x == null) return new Node(key, val);
    int cmp = key.compareTo(x.key);
    if (cmp < 0)
        x.left = put(x.left, key, val);
    else if (cmp > 0)
        x.right = put(x.right, key, val);
    else if (cmp == 0)
        x.val = val;
    return x;
}
```

concise, but tricky,
recursive code;
read carefully!

Cost. Number of compares is equal to 1 + depth of node.

10


BST trace: standard indexing client



11

Tree shape

- Many BSTs correspond to same set of keys.
- Number of compares for search/insert is equal to 1 + depth of node.




Remark. Tree shape depends on order of insertion.

12

BST insertion: random order


Observation. If keys inserted in random order, tree stays relatively flat.



13

BST insertion: random order visualization


Ex. Insert keys in random order.



14

Correspondence between BSTs and quicksort partitioning

Q	U	I	C	K	S	O	R	T	E	X	A	M	P	L	E
E	R	A	T	E	S	L	P	U	I	M	Q	C	X	O	K
E	C	A	I	E	K	L	P	U	T	M	Q	R	X	O	S
A	C	E	I	E	K	L	P	U	T	M	Q	R	X	O	S
A	C	E	I	E	K	L	P	U	T	M	Q	R	X	O	S
A	C	E	I	E	K	L	P	U	T	M	Q	R	X	O	S
A	C	E	E	I	K	L	P	U	T	M	Q	R	X	O	S
A	C	E	E	I	K	L	P	U	T	M	Q	R	X	O	S
A	C	E	E	I	K	L	P	O	R	M	Q	S	X	U	T
A	C	E	E	I	K	L	P	O	M	Q	R	S	X	U	T
A	C	E	E	I	K	L	M	O	P	Q	R	S	X	U	T
A	C	E	E	I	K	L	M	O	P	Q	R	S	X	U	T
A	C	E	E	I	K	L	M	O	P	Q	R	S	X	U	T
A	C	E	E	I	K	L	M	O	P	Q	R	S	X	U	T
A	C	E	E	I	K	L	M	O	P	Q	R	S	X	U	T
A	C	E	E	I	K	L	M	O	P	Q	R	S	X	U	T
A	C	E	E	I	K	L	M	O	P	Q	R	S	X	U	T
A	C	E	E	I	K	L	M	O	P	Q	R	S	X	U	T
A	C	E	E	I	K	L	M	O	P	Q	R	S	X	U	T



Remark. Correspondence is 1-1 if array has no duplicate keys.

15

BSTs: mathematical analysis

Proposition. If keys are inserted in **random** order, the expected number of compares for a search/insert is $\sim 2 \ln N$.

Pf. 1-1 correspondence with quicksort partitioning.

Proposition. [Reed, 2003] If keys are inserted in random order, expected height of tree is $\sim 4.311 \ln N$.

But... Worst-case height is N .
(exponentially small chance when keys are inserted in random order)

16

ST implementations: summary

implementation	guarantee		average case		ordered ops?	operations on keys
	search	insert	search hit	insert		
sequential search (unordered list)	N	N	N/2	N	no	<code>equals()</code>
binary search (ordered array)	$\lg N$	N	$\lg N$	N/2	yes	<code>compareTo()</code>
BST	N	N	$1.39 \lg N$	$1.39 \lg N$?	<code>compareTo()</code>

17

► BSTs

► ordered operations


► deletion

18

Minimum and maximum

Minimum. Smallest key in table.

Maximum. Largest key in table.




Q. How to find the min / max?

19

Floor and ceiling

Floor. Largest key \leq to a given key.

Ceiling. Smallest key \geq to a given key.



Q. How to find the floor / ceiling?

20

Computing the floor

Case 1. [k equals the key at root]


The floor of k is k .

Case 2. [k is less than the key at root]

The floor of k is in the left subtree.

Case 3. [k is greater than the key at root]

The floor of k is in the right subtree
(if there is **any** key $\leq k$ in right subtree);
otherwise it is the key in the root.



Computing the floor


```
public Key floor(Key key)
{
    Node x = floor(root, key);
    if (x == null) return null;
    return x.key;
}

private Node floor(Node x, Key key)
{
    if (x == null) return null;
    int cmp = key.compareTo(x.key);

    if (cmp == 0) return x;


    if (cmp < 0) return floor(x.left, key);

    Node t = floor(x.right, key);
    if (t != null) return t;
    else return x;
}
```



Subtree counts

In each node, we store the number of nodes in the subtree rooted at that node.
To implement `size()`, return the count at the root.



Remark. This facilitates efficient implementation of `rank()` and `select()`.

BST implementation: subtree counts

```
private class Node
{
    private Key key;
    private Value val;
    private Node left;
    private Node right;
    private int N;
}
```

number of nodes
in subtree

```
public int size()
{ return size(root); }


private int size(Node x)
{
    if (x == null) return 0;
    return x.N;
}
```

```
private Node put(Node x, Key key, Value val)
{
    if (x == null) return new Node(key, val);
    int cmp = key.compareTo(x.key);
    if (cmp < 0) x.left = put(x.left, key, val);
    else if (cmp > 0) x.right = put(x.right, key, val);
    else if (cmp == 0) x.val = val;
    x.N = 1 + size(x.left) + size(x.right);
    return x;
}
```

Rank

Rank. How many keys $< k$?

Easy recursive algorithm (4 cases!)



```
public int rank(Key key)
{
    return rank(key, root);
}

private int rank(Key key, Node x)
{
    if (x == null) return 0;
    int cmp = key.compareTo(x.key);
    if (cmp < 0) return rank(key, x.left);
    else if (cmp > 0) return 1 + size(x.left) + rank(key, x.right);
    else if (cmp == 0) return size(x.left);
}
```


25

Selection

Select. Key of given rank.

```
public Key select(int k)
{
    if (k < 0) return null;
    if (k >= size()) return null;
    Node x = select(root, k);
    return x.key;
}

private Node select(Node x, int k)
{
    if (x == null) return null;
    int t = size(x.left);
    if (t > k)
        return select(x.left, k);
    else if (t < k)
        return select(x.right, k-t-1);
    else if (t == k)
        return x;
}
```




26

Inorder traversal

- Traverse left subtree.
- Enqueue key.
- Traverse right subtree.

```
public Iterable<Key> keys()
{
    Queue<Key> q = new Queue<Key>();
    inorder(root, q);
    return q;
}

private void inorder(Node x, Queue<Key> q)
{
    if (x == null) return;
    inorder(x.left, q);
    q.enqueue(x.key);
    inorder(x.right, q);
}
```



Property. Inorder traversal of a BST yields keys in ascending order.

27

Inorder traversal

- Traverse left subtree.
- Enqueue key.
- Traverse right subtree.

```

inorder(S)
  inorder(E)
    inorder(A)
      enqueue A
    inorder(C)
      enqueue C
  enqueue E
inorder(R)
  inorder(H)
    enqueue H
  inorder(M)
    enqueue M
  enqueue R
enqueue S
inorder(X)
  enqueue X

```

recursive calls

A
C
E

H

M
R
S

Y

queue

S
S E
S E A


S E A C

S E R
S E R H

S E R H M

S X

function call stack



28

BST: ordered symbol table operations summary

	sequential search	binary search	BST
search	N	$\lg N$	h
insert	1	N	h
min / max	N	1	h
floor / ceiling	N	$\lg N$	h
rank	N	$\lg N$	h
select	N	1	h
ordered iteration	$N \log N$	N	N

h = height of BST
(proportional to $\log N$
if keys inserted in random order)

worst-case running time of ordered symbol table operations

29

- ▶ BSTs
- ▶ ordered operations
- ▶ deletion

30

ST implementations: summary

implementation	guarantee			average case			ordered iteration?	operations on keys
	search	insert	delete	search hit	insert	delete		
sequential search (linked list)	N	N	N	$N/2$	N	$N/2$	no	<code>equals()</code>
binary search (ordered array)	$\lg N$	N	N	$\lg N$	$N/2$	$N/2$	yes	<code>compareTo()</code>
BST	N	N	N	$1.39 \lg N$	$1.39 \lg N$???	yes	<code>compareTo()</code>


Next. Deletion in BSTs.

31

BST deletion: lazy approach

To remove a node with a given key:

- Set its value to null.
- Leave key in tree to guide searches (but don't consider it equal to search key).



Cost. $\sim 2 \ln N'$ per insert, search, and delete (if keys in random order), where N' is the number of key-value pairs ever inserted in the BST.

Unsatisfactory solution. Tombstone overload.

32


Deleting the minimum

To delete the minimum key:

- Go left until finding a node with a null left link.
- Replace that node by its right link.
- Update subtree counts.

```
public void deleteMin()
{ root = deleteMin(root); }

private Node deleteMin(Node x)
{
    if (x.left == null) return x.right;
    x.left = deleteMin(x.left);
    x.N = 1 + size(x.left) + size(x.right);
    return x;
}
```




33

Hibbard deletion

To delete a node with key k : search for node t containing key k .

Case 0. [0 children] Delete t by setting parent link to null.




34

Hibbard deletion

To delete a node with key k : search for node t containing key k .

Case 1. [1 child] Delete t by replacing parent link.



35


Hibbard deletion

To delete a node with key k : search for node t containing key k .

Case 2. [2 children]

- Find successor x of t .
- Delete the minimum in t 's right subtree.
- Put x in t 's spot.

- ← x has no left child
- ← but don't garbage collect x
- ← still a BST



36

```

public void delete(Key key)
{ root = delete(root, key); }

private Node delete(Node x, Key key) {
    if (x == null) return null;
    int cmp = key.compareTo(x.key);
    if (cmp < 0) x.left = delete(x.left, key);
    else if (cmp > 0) x.right = delete(x.right, key);
    else {
        if (x.right == null) return x.left;

        Node t = x;
        x = min(t.right);
        x.right = deleteMin(t.right);
        x.left = t.left;
    }
    x.N = size(x.left) + size(x.right) + 1;
    return x;
}

```

search for key


no right child

replace with successor

update subtree counts

37

Unsatisfactory solution. Not symmetric.



Surprising consequence. Trees not random (!) $\Rightarrow \sqrt{N}$ per op.
 Longstanding open problem. Simple and efficient delete for BSTs.

38

ST implementations: summary

implementation	guarantee			average case			ordered iteration?	operations on keys
	search	insert	delete	search hit	insert	delete		
sequential search (linked list)	N	N	N	N/2	N	N/2	no	equals()
binary search (ordered array)	lg N	N	N	lg N	N/2	N/2	yes	compareTo()
BST	N	N	N	1.39 lg N	1.39 lg N	\sqrt{N}	yes	compareTo()

other operations also become \sqrt{N}
if deletions allowed

Next lecture. Guarantee logarithmic performance for all operations.

39