

GMR INSTITUTE OF TECHNOLOGY
An Autonomous Institute Affiliated to JNTU-GV, VIJAYANAGARAM
GMR NAGAR, RAJAM - 532 127
SRIKAKULAM DIST., ANDHRA PRADESH, INDIA

SIMULATION OF OVERCURRENT RELAY

A Augmented Experiment submitted in partial fulfilment of the requirement of the course

Experiment Done Using MATLAB

Submitted by :-Batch1 on 07/03/23

❖ A.Gunasree	20341A0202
❖ A.Taruni	20341A0203
❖ A.Pratyusha	20341A0204
❖ A.Anil kumar	20341A0205
❖ A.Alekya	20341A0206
❖ B.Ashish	20341A0207
❖ B.Venkata Lakshmi	20341A0208

Under the esteemed guidance of

Dr. Rajesh Kumar Patnaik Associate Professor,

Dr. P. Praveen Kumar Asst.Professor

Department of Electrical and Electronics Engineering

GMR Institute of Technology

GMR Institute of Technology

An Autonomous institute affiliated to J.N.T. University,

Kakinada NAAC” A” Graded,

NBA Accredited,

ISO 9001:2008 Certified institution G.M.R. Nagar,

Rajam-532127, Srikakulam, A.P

CERTIFICATE

This is to certify that the mini project entitled is **“SIMULATION OF OVERCURRENT RELAY”** being submitted by :

- A.Gunasree 20341A0202
- A.Taruni 20341A0203
- A.Pratyusha 20341A0204
- A.Anil kumar 20341A0205
- A.Alekya 20341A0206
- B.Ashish 20341A0207
- B.Venkata Lakshmi 20341A0208

has been carried out as a bonafied work in practical fulfilment of the requirements for the completion of the course **“Experiment Done Using MATLAB”** in Semester- VI of our Third year B.Tech.

Signature of course instructor

Dr. Rajesh Kumar Patnaik
Associate. Professor,
Department of Electrical and Electronics Eng.

Signature of head of department

Dr . P. Ramana
Professor and Head of The Department,
Department of Electrical and Electronics Eng.


AUGMENTED EXPERIMENT

SIMULATION OF OVERCURRENT RELAY

AIM: Simulation of over current relay using matlab/Simulink

TOOLS REQUIRED: Matlab or Simulink software.

CIRCUIT DIAGRAM:



INTRODUCTION.

An overcurrent monitoring relay, as its name directly implies, is a device that monitors the current flowing through a conductor or device, and reacts if the current exceeds a predetermined threshold. Overcurrent relays are used in many different applications and systems in order to help protect against electrical faults.

The electrical faults include short circuits and overloading. Overcurrent relays can provide protection against all of these faults by detecting when the current exceeds a safe level and then either automatically disconnect the circuit or sending a signal to another device that will take action to protect the circuit.

Ideally, this type of current relay consists of two main components: a sensing device and a control device. The sensing device is used to detect the current flowing through the circuit, while the control element determines the tripping current, usually based on user settings.

5. Connect the scopes to view the fault occurrence in the relay due to over current
6. Check the output voltage and current scopes for different fault currents.
7. Log the signals to the data inspector and check the fault currents.

WAVE FORMS:




Fig: Three phase fault current in the overcurrent relay

RESULT:

Hence, the overcurrent relay operated when there is the fault in the relay circuit.