

▼ Building Machine Learning Classifiers: Building a basic Random Forest model

▼ Read in & clean text

```
import nltk
import pandas as pd
import re
from sklearn.feature_extraction.text import TfidfVectorizer
import string

stopwords = nltk.corpus.stopwords.words('english')
ps = nltk.PorterStemmer()

data = pd.read_csv("SMSSpamCollection.tsv", sep='\t')
data.columns = ['label', 'body_text']

def count_punct(text):
    count = sum([1 for char in text if char in string.punctuation])
    return round(count/(len(text) - text.count(" ")), 3)*100

data['body_len'] = data['body_text'].apply(lambda x: len(x) - x.count(" "))
data['punct%'] = data['body_text'].apply(lambda x: count_punct(x))

def clean_text(text):
    text = "".join([word.lower() for word in text if word not in string.punctuation])
    tokens = re.split('\W+', text)
    text = [ps.stem(word) for word in tokens if word not in stopwords]
    return text

tfidf_vect = TfidfVectorizer(analyzer=clean_text)
X_tfidf = tfidf_vect.fit_transform(data['body_text'])

X_features = pd.concat([data['body_len'], data['punct%'], pd.DataFrame(X_tfidf.toarray())], axis=1)
X_features.head()
```

	body_len	punct%	0	1	2	3	4	5	6	7	...	8094	8095	8096	8097	8098	8099	8100
0	128	4.7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0.0	0.0	0.0	0.0	0.0	0.0
1	49	4.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0.0	0.0	0.0	0.0	0.0	0.0
2	62	3.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0.0	0.0	0.0	0.0	0.0	0.0
3	28	7.1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0.0	0.0	0.0	0.0	0.0	0.0
4	135	4.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0.0	0.0	0.0	0.0	0.0	0.0

▼ Explore RandomForestClassifier Attributes & Hyperparameters

```
from sklearn.ensemble import RandomForestClassifier
```

```
print(dir(RandomForestClassifier))
print(RandomForestClassifier())
```

```
['__abstractmethods__', '__class__', '__delattr__', '__dict__', '__dir__', '__doc__', '__eq__', '__format__', '__ge__', '__getattribute__', '__gt__', '__hash__', '__init__', '__init_subclass__', '__le__', '__lt__', '__module__', '__ne__', '__new__', '__reduce__', '__reduce_ex__', '__repr__', '__setattr__', '__sizeof__', '__str__', '__subclasshook__', '__weakref__', '_get_params', '_set_params', '_validate_params', 'bootstrap', 'class_weight', 'criterion', 'max_depth', 'max_features', 'max_leaf_nodes', 'min_impurity_decrease', 'min_impurity_split', 'min_samples_leaf', 'min_samples_split', 'min_weight_fraction_leaf', 'n_estimators', 'n_jobs', 'oob_score', 'random_state', 'verbose', 'warm_start']
RandomForestClassifier(bootstrap=True, class_weight=None, criterion='gini',
                        max_depth=None, max_features='auto', max_leaf_nodes=None,
                        min_impurity_decrease=0.0, min_impurity_split=None,
                        min_samples_leaf=1, min_samples_split=2,
                        min_weight_fraction_leaf=0.0, n_estimators=10, n_jobs=1,
                        oob_score=False, random_state=None, verbose=0,
                        warm_start=False)
```

▼ Explore RandomForestClassifier through Cross-Validation

```
from sklearn.model_selection import KFold, cross_val_score
```

```
rf = RandomForestClassifier(n_jobs=-1)
k_fold = KFold(n_splits=5)
cross_val_score(rf, X_features, data['label'], cv=k_fold, scoring='accuracy', n_jobs=-1)
```

```
array([ 0.96947935,  0.97486535,  0.97124888,  0.95507637,  0.96855346])
```

Colab paid products - [Cancel contracts here](#)

