

▼ Building Machine Learning Classifiers: Model selection

▼ Read in & clean text

```
import nltk
import pandas as pd
import re
from sklearn.feature_extraction.text import TfidfVectorizer
import string

stopwords = nltk.corpus.stopwords.words('english')
ps = nltk.PorterStemmer()

data = pd.read_csv("SMSSpamCollection.tsv", sep='\t')
data.columns = ['label', 'body_text']

def count_punct(text):
    count = sum([1 for char in text if char in string.punctuation])
    return round(count/(len(text) - text.count(" ")), 3)*100

data['body_len'] = data['body_text'].apply(lambda x: len(x) - x.count(" "))
data['punct%'] = data['body_text'].apply(lambda x: count_punct(x))

def clean_text(text):
    text = "".join([word.lower() for word in text if word not in string.punctuation])
    tokens = re.split('\W+', text)
    text = [ps.stem(word) for word in tokens if word not in stopwords]
    return text
```

▼ Split into train/test

```
from sklearn.model_selection import train_test_split

X_train, X_test, y_train, y_test = train_test_split(data[['body_text', 'body_len', 'punct%']], data['label'], test_size=0.2)
```

▼ Vectorize text

```
tfidf_vect = TfidfVectorizer(analyzer=clean_text)
tfidf_vect_fit = tfidf_vect.fit(X_train['body_text'])
```

```
tfidf_train = tfidf_vect_fit.transform(X_train['body_text'])
tfidf_test = tfidf_vect_fit.transform(X_test['body_text'])
```

```
X_train_vect = pd.concat([X_train[['body_len', 'punct%']].reset_index(drop=True),
                          pd.DataFrame(tfidf_train.toarray())], axis=1)
X_test_vect = pd.concat([X_test[['body_len', 'punct%']].reset_index(drop=True),
                         pd.DataFrame(tfidf_test.toarray())], axis=1)
```

```
X_train_vect.head()
```

	body_len	punct%	0	1	2	3	4	5	6	7	...	7085	7086	7087	7088	7089	7090	7091	7092	7093	7094
0	51	2.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
1	20	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
2	30	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
3	102	4.9	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
4	33	3.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	...	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

5 rows × 7097 columns

▼ Final evaluation of models

```
from sklearn.ensemble import RandomForestClassifier, GradientBoostingClassifier
from sklearn.metrics import precision_recall_fscore_support as score
import time
```

```
rf = RandomForestClassifier(n_estimators=150, max_depth=None, n_jobs=-1)
```

```
rf_model = rf.fit(X_train_vect, y_train)
y_pred = rf_model.predict(X_test_vect)
```

```
precision, recall, fscore, train_support = score(y_test, y_pred, pos_label='spam', average='binary')
print('Precision: {} / Recall: {} / Accuracy: {}'.format(
    round(precision, 3), round(recall, 3), round((y_pred==y_test).sum()/len(y_pred), 3)))
```

```
gb = GradientBoostingClassifier(n_estimators=150, max_depth=11)
```

```
gb_model = gb.fit(X_train_vect, y_train)
y_pred = gb_model.predict(X_test_vect)
```

```
precision, recall, fscore, train_support = score(y_test, y_pred, pos_label='spam', average='binary')
print('Precision: {} / Recall: {} / Accuracy: {}'.format(
    round(precision, 3), round(recall, 3), round((y_pred==y_test).sum()/len(y_pred), 3)))
```