

7 6 5 IF IN DOUBT.....PLEASE ASK! 3 2 1

ITEM	QTY	DESCRIPTION	MATERIAL	CANRIG PART No.
1	1	CHANNEL, UPN 160 X 65 X 18.8 X 8763 LG	ASTM A572 Gr. 50 / S355JR	

F

E

D

C

B

A

2X 80 $\left[3\frac{1}{8}\right]$ x 45°

8763 [345]

160 $\left[6\frac{5}{16}\right]$

65 $\left[2\frac{9}{16}\right]$

WELDING PROCEDURE AS PER CANRIG SPECIFICATION - ENG 704, UNLESS NOTED OTHERWISE			INITIAL DESIGN		
CONFIDENTIAL AND PROPRIETARY. THE USE, REPRODUCTION OR DISTRIBUTION WITHOUT PRIOR WRITTEN CONSENT IS PROHIBITED. ALL RIGHTS RESERVED.	UNLESS OTHERWISE SPECIFIED INTERPRET DRAWING PER ASME Y14.5-1994 INTERPRET CASTINGS AND FORGINGS PER ASME Y14.8-1996 REMOVE SHARP CORNERS AND BURRS ✓ RUN OUT .003 — STRAIGHTNESS .005 IN 5 INCHES ⊥ PERPENDICULARITY .010 IN 5 INCHES // PARALLELISM .010 IN 5 INCHES ≡ FLATNESS .010 or as Shown 125/ MACHINED SURFACES MIN. RADIUS UNLESS SHOWN = 0.03 MAX.	TOLERANCE - UNLESS OTHERWISE SPECIFIED FABRICATING [IMPERIAL] FABRICATING [METRIC] 0 to 24" ± 1/16" 0 TO 610 mm ± 1 mm 24" to 60" ± 1/8" 610 TO 1525 ± 3 mm 60 to 120" ± 3/16" 1525 TO 3048 ± 5 mm 120" to 280" ± 1/4" 3048 TO 7112 ± 7 mm 280" & OVER ± 1/2" 7112 & OVER ± 13 mm MACHINING [IMPERIAL] MACHINING [METRIC] DECIMAL .x ± .030" DECIMAL x. ± .8 mm .xx ± .015" .xx ± .40 mm .xxx ± .005" .xxx ± .13 mm ANGULAR MACHINING ± 1° FABRICATION ± 2°	MODELED	ITC	2019/01/24
			DRAWN	ITC	2018/03/14
			CHECKED	G.Young	2019-04-25
			APPROVED	T.Burke	2019/01/15
			RELEASE DATE	2019-05-01	
			REVISION		
			MODELED	K.Balasubramanian	2019-04-09
			DRAWN	K.Balasubramanian	2019-04-09
			CHECKED	G.Young	2019-04-25
			APPROVED	T.Burke	2019-04-29
			REVISION	RELEASE DATE	

A	PRODUCTION RELEASE	3286
REV	REVISION DESCRIPTION	ECN

SHEET 1 OF 1 THIRD ANGLE PROJECTION		
DO NOT SCALE DRAWING		
SHEET SIZE C		
CHANNEL, RAMP MID BOTTOM RAIL, PC4100		
EST. WEIGHT 167 Kg [367.4 lbs]	SCALE 1:4	DT34608 REV A

7 6 5 IF IN DOUBT.....PLEASE ASK! 3 2 1