

Exercise 1 for MA-INF 2201 Computer Vision WS16/17
24.10.2016
Submission on 30.10.2016

1. Rectangles and Integral Images

Read the image `bonn.png` and convert it into a gray image. Generate 100 random rectangles within the image and display the image with the rectangles. For each rectangle, compute the average intensity by

- (a) summing up each pixel value inside of the rectangle, i.e., $\frac{1}{|R|} \sum_{p \in R} I(p)$,
- (b) computing an integral image without using the function `integral`,
- (c) computing an integral image using the function `integral`,

and compare the runtime for the three versions in seconds using `getTickCount` and repeating the computation of the sum for 10 times. Use the command line (`std::cout`) to print the results.

(2 Points)

2. Histogram Equalization

Read the image `bonn.png`, convert it into a gray image, and display it. Perform histogram equalization

- (a) using `equalizeHist`
- (b) without using `equalizeHist`

and display both results. Compute the absolute pixelwise difference between the results using `absdiff`. Print the maximum pixel error using `minMaxLoc`.

(2 Points)

3. Convolution Theorem

Proof that convolutions are in the continuous case associative.

(2 Points)

4. 2D Filtering

Read the image `bonn.png`, convert it into a gray image, and display it. Filter the image with a Gaussian kernel with $\sigma = 2\sqrt{2}$

- (a) using `GaussianBlur`
- (b) using `filter2D` without using `getGaussianKernel`
- (c) using `sepFilter2D` without using `getGaussianKernel`

and display the three results. Compute the absolute pixel-wise difference between all pairs (there are three pairs) and print the maximum pixel error for each pair.

(2 Points)

5. More on Convolution

Proof that convolution two times with a Gaussian kernel with standard deviation σ is the same as convolution once with a Gaussian kernel with standard deviation $\sqrt{2}\sigma$.

(2 Points)

Hint:

$$\int_{-\infty}^{\infty} e^{(-Au^2+Bu+C)} du = \sqrt{\frac{\pi}{A}} e^{\left(\frac{B^2}{4A}+C\right)}$$

6. Multiple Gaussian Filters

Read the image `bonn.png`, convert it into a gray image, and display it. Filter the image

- (a) twice with a Gaussian kernel with $\sigma = 2$
- (b) once with a Gaussian kernel with $\sigma = 2\sqrt{2}$

and display both results, compute the absolute pixel-wise difference between the results, and print the maximum pixel error.

(2 Points)

7. Denoising

Read the image `bonn.png`, convert it into a gray image, add 30% (the chance that a pixel is converted into a black or white pixel is 30%) salt and pepper noise, and display it. Filter the image by

- (a) a Gaussian kernel
- (b) Median filter `medianBlur`
- (c) Bilateral filter `bilateralFilter`

and display the three results. Select the filter parameters that give the best visual results.

(2 Points)

8. Separability of Filters

Read the image `bonn.png` and convert it into a gray image.

- (a) Filter the images using the two 2D filter kernels given below.
- (b) Use the class `SVD` of OpenCV to separate each kernel. If a kernel is not separable, use an approximation by taking only the highest singular value. Filter the images with the obtained 1D kernels and display the results.
- (c) Compute the absolute pixel-wise difference between the results of (a) and (b), and print the maximum pixel error.

(6 Points)

0.0113	0.0838	0.0113	-0.8984	0.1472	1.1410
0.0838	0.6193	0.0838	-1.9075	0.1566	2.1359
0.0113	0.0838	0.0113	-0.8659	0.0573	1.0337

kernel 1

kernel 2