INPUT / THREE THINGS YOU SUPPLY



PDF or image
the evidence



Schema / template
the requested fields

Optional task
"Extract every ordered item."

1 / PREPARE: normalize PDF, count pages, inspect text

Page images
rendered when needed

Embedded text
if the PDF contains it

MinerU text + tables
optional cached parse*

2 / ROUTE: follow the decisions from left to right

Specialized layout? — yes → **3A / LAYOUT**

no → **Enough PDF text?** — yes → **3B / TEXT PDF**

no → **Scan has ≤ 12 pages?** — yes → **3C / SHORT SCAN**

no → **3D / LONG SCAN**

3A / LAYOUT



Column crops or
ruled row bands
↓ extraction model

One layout JSON

3B / TEXT PDF



Embedded text +
page images
when allowed
↓ primary reader

One primary JSON

3C / SHORT SCAN



Images → primary
Parse* → parse reader
Full scan → one-shot

Up to 3 JSONs
A B C

3D / LONG SCAN



Primary reader first;
then parse reader*
(no one-shot)

Primary + parse*

4 / CHECK EACH JSON SEPARATELY (code; no model calls)

Checks for this reading source ↓ checked JSON(s)

Checks for this reading source ↓ checked JSON(s)

Checks for this reading source ↓ checked JSON(s)

Checks for this reading source ↓ checked JSON(s)

5 / SELECT ONE COMPLETE CHECKED READING

Return layout
directly

Return primary
directly

Multiple: quorum
compare A, B, C
and keep one

Prefer parse
if successful
else return primary

6 / FORMAT AND RETURN

Extracted JSON
restore template shape if supplied

Routing / selection report
readings used; selected candidate

Only one route runs. Short scans keep successful candidates: one returns directly, several enter the quorum, none raises an error. Long scans also fail if no reading succeeds.

* Parse reading needs cached pages and adequate cache coverage. A parse is evidence, not task JSON. The detailed reader uses cached parse text only at $\geq 90\%$ page-count coverage.

This is the main API flow. Checks are conditional repairs, not proof of correctness. Quorum chooses a whole candidate; it does not assemble fields from different candidates.