

INTOZI Vehicle Registry/Unregistry Document

Application: Vehicle Registry / Unregistry

Version: 1.1

Overview

This document describes the API integration used to manage vehicle data in the **Ikshana Watchlist Registry**. It covers adding new vehicle records, retrieving existing watchlist records, and updating existing vehicle records. The same integration supports the vehicle registry/unregistry workflow through the watchlist data APIs.

Authentication: Every API request must include the required `x-api-key` HTTP header.

Authentication

All API requests must include the following header:

Required Header

`x-api-key: <API_KEY>`

API Summary

Method	API	Purpose
POST	manage_watchlist_anpr_app_db_data	Add a new vehicle record to the Ikshana Watchlist Registry.
POST	get_watchlist_anpr_app_db_data	Retrieve vehicle records currently present in the watchlist.
PUT	manage_watchlist_anpr_app_db_data	Update an existing vehicle record in the Ikshana Watchlist Registry.
DELETE	manage_watchlist_anpr_app_db_data	Delete vehicle records.

1. Add Vehicle to Watchlist Registry

Method: POST

API: `manage_watchlist_anpr_app_db_data`

This API is used to add vehicle data to the Ikshana Watchlist Registry.

Request Format

```
{
  "vehicle_number": "KA01MN7823",
  "vehicle_category_name": 1,
  "person_name": "Rohit Sharma",
  "mobile_number": "9123456780",
  "make_model": "Toyota Fortuner",
  "remarks": "Guest vehicle",
  "custom_field_data": [
    {
      "field_id": 1,
      "custom_field_value": "['Camera10', 'Camera12']"
    },
    {
      "field_id": 2,
      "custom_field_value": "DLF Parking"
    }
  ]
}
```

Field Requirements

Required: vehicle_number, vehicle_category_name, custom_field_data

Optional: person_name, mobile_number, make_model, remarks

If `custom_field_data` is not sent in the request, Ikshana will use the default value assigned to the custom field.

Request Fields

Field Name	Data Type	Description
vehicle_number	String	Vehicle registration number.
vehicle_category_name	Integer	Vehicle category value supplied to the API.
person_name	String	Name associated with the vehicle.
mobile_number	String	Mobile number associated with the vehicle/person.
make_model	String	Vehicle make and model.
remarks	String	Additional remarks for the vehicle record.
custom_field_data	Array	Contains custom field information associated with the vehicle.
field_id	Integer	Identifier of the custom field.
custom_field_value	String	Value assigned to the custom field. In the supplied example, it contains a list of camera names.

Important: field_id 2 represents device_name. field_id 3 represents group_id (society/group identifier). The custom-field group_id is independent of the ANPR watchlist database group's own group_id. Do not confuse the custom field group_id with the actual ANPR watchlist group relationship.

Response

```
{
  "id": 1,
  "vehicle_number": "KA01MN7823",
  "person_name": "Rohit Sharma",
  "mobile_number": "9123456780",
  "make_model": "Toyota Fortuner",
  "vehicle_category": 1,
  "vehicle_category_name": "Guest",
  "valid_from": null,
  "valid_to": null,
  "remarks": "Guest vehicle",
  "email": null,
  "vehicle_image": {},
  "created_datetime": "2026-10-05T17:10:27.909344",
  "modified_datetime": "2026-10-05T17:10:27.909349",
  "custom_fields": [
    {
      "id": 1,
      "field_name": "device_name",
      "value": "['Camera10', 'Camera12']",
      "type": "List",
      "field_id": 1,
      "options": []
    },
    {
      "id": 2,
      "field_name": "group_id",
      "value": "DLF Parking",
      "type": "Text",
      "field_id": 2
    }
  ],
  "encryption": false
}
```

2. Retrieve Watchlist Data

Method: POST

API: `get_watchlist_anpr_app_db_data`

This API is used to retrieve the vehicle data currently present in the watchlist. The response contains the available watchlist records along with their custom fields.

Request Payload

```
{
  "page": "1",
  "page_size": "12",
  "group": 1
}
```

Response

```
{
  "status": 200,
  "message": "Success",
  "count": 1,
  "data": [
    {
      "id": 1,
      "vehicle_number": "KA01MN7823",
      "person_name": "Rohit Sharma",
      "mobile_number": "9123456780",
      "make_model": "Toyota Fortuner",
      "vehicle_category": 1,
      "vehicle_category_name": "Guest",
      "valid_from": null,
      "valid_to": null,
      "remarks": "Guest vehicle",
      "email": null,
      "vehicle_image": {},
      "created_datetime": "2026-10-05T17:10:27.909344",
      "modified_datetime": "2026-10-05T17:10:27.909349",
      "custom_fields": [
        {
          "id": 1,
          "field_name": "device_name",
          "value": "['Camera10', 'Camera12']",
          "type": "List",
          "field_id": 1,
          "options": []
        },
        {
          "id": 2,
          "field_name": "group_id",
          "value": "DLF Parking",
          "type": "Text",
          "field_id": 2
        }
      ],
      "encryption": false
    }
  ]
}
```

Custom Fields in Response

```
{
  "custom_fields": [
    {
      "id": 1,
      "field_name": "device_name",
      "value": "['Camera10', 'Camera12']",
      "type": "List",
      "field_id": 1,
      "options": []
    },
    {
      "id": 2,
      "field_name": "group_id",
      "value": "DLF Parking",
      "type": "Text",
      "field_id": 2
    }
  ]
}
```

field_id 1 represents device_name (camera/device name). field_id 2 represents group_id (society/group identifier). The custom-field group_id is independent of the ANPR watchlist database group's own group_id.

For updates, the response custom-field id corresponds to the request-side field_data_id, while value contains the custom field value.

3. Update Existing Vehicle Data

Method: PUT

API: manage_watchlist_anpr_app_db_data

This API is used to update an existing vehicle record in the watchlist. The existing record is identified using anpr_wl_id.

Request Format

```
{
  "anpr_wl_id": 1,
  "vehicle_category_name": 1,
  "person_name": "Rohit Sharma",
  "mobile_number": "9123456780",
  "make_model": "Toyota Fortuner",
  "remarks": "Guest vehicle",
  "image_updated": 0,
  "custom_field_data": [
    {
      "field_id": 1,
      "field_data_id": 1,
      "custom_field_val": "['Camera14']"
    },
    {
      "field_id": 2,
      "field_data_id": 2,
      "custom_field_val": "DLF Parking"
    }
  ]
}
```

Use field_data_id to identify an existing custom-field data entry. The response custom-field id maps to request field_data_id.

1,

2,

Custom Field Mapping

When mapping custom-field data, the response custom-field id corresponds to request field_data_id, while response value corresponds to request custom_field_value. field_id 1 represents device_name (camera/device name) and field_id 2 represents group_id. The custom-field group_id is independent of the ANPR watchlist database group's own group_id.

Request Field	Response Field	Meaning
field_data_id	id	The request's field_data_id corresponds to the response custom-field id .
custom_field_value	value	The request's custom_field_value corresponds to the response custom-field value .

Field Requirements

Required: anpr_wl_id, vehicle_category_name

Optional: person_name, mobile_number, make_model, remarks

Read-only: vehicle_number (cannot be modified)

Update Fields

Field Name	Data Type	Description
anpr_wl_id	Integer	ID of the existing watchlist vehicle record to update.
vehicle_category_name	Integer	Vehicle category value supplied to the API.
person_name	String	Name associated with the vehicle.
mobile_number	String	Mobile number associated with the vehicle/person.
make_model	String	Updated vehicle make and model.
remarks	String	Updated remarks for the vehicle record.
image_updated	Integer	Image update indicator supplied in the request.
field_id	Integer	Identifier of the custom field.
field_data_id	Integer	Identifier of the existing custom-field data entry.
custom_field_value	String	Updated value for the custom field.

Response

```
{
  "status": 200,
  "message": "Success",
  "count": 1,
  "data": [
    {
      "id": 1,
      "vehicle_number": "KA01MN7823",
      "person_name": "Rohit Sharma",
      "mobile_number": "9123456780",
      "make_model": "Toyota Fortuner",
      "vehicle_category": 1,
      "vehicle_category_name": "Guest",
      "valid_from": null,
      "valid_to": null,
      "remarks": "Guest vehicle",
      "email": null,
      "vehicle_image": {},
      "created_datetime": "2026-10-05T17:10:27.909344",
      "modified_datetime": "2026-10-05T17:10:27.909349",
      "custom_fields": [
        {
          "id": 1,
          "field_name": "device_name",
          "value": "['Camera14']",
          "type": "List",
          "field_id": 1,
          "options": []
        },
        {
          "id": 2,
          "field_name": "group_id",
          "value": "DLF Parking",
          "type": "Text",
          "field_id": 2
        }
      ],
      "encryption": false
    }
  ]
}
```

4. Delete Registered Vehicle

Method: DELETE

API: manage_watchlist_anpr_app_db_data

This API is used to delete vehicle records from the registry. The data_id array contains the IDs of the vehicle records to delete.

Request Body

```
{
  "data_id": [1, 2, 3]
}
```

data_id contains the IDs of the vehicle records to delete.

Response Handling

A successful response indicates that the requested vehicle records were processed for deletion.

Integration Flow

1. Authenticate using x-api-key.

2. Add the vehicle using POST `manage_watchlist_anpr_app_db_data`.

3. Store Device Name and society/group as separate custom fields.

4. Retrieve records using POST `get_watchlist_anpr_app_db_data`.

5. Use the returned vehicle ID for updates.

6. Use `field_data_id` when updating existing custom fields. `field_id` 1 represents `device_name` (camera/device name) and `field_id` 2 represents `group_id`.

7. Delete records using DELETE `manage_watchlist_anpr_app_db_data` with `data_id`.