

Website Source Code Documentation

Table of Contents

1. index.html
2. netlify.toml
3. netlify/functions/inquiries.ts
4. netlify/functions/secure-endpoint.ts
5. netlify/functions/send-otp.ts
6. netlify/functions/send-welcome.ts
7. netlify/functions/signInWithFpnv.ts
8. netlify/functions/verify-otp.ts
9. package.json
10. src/App.tsx
11. src/index.css
12. src/lib/firebase.ts
13. src/lib/workspace.ts
14. src/main.tsx
15. src/vite-env.d.ts
16. tsconfig.json
17. vite.config.ts

File: index.html

```
<!doctype html>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0" />
    <link rel="icon" type="image/png" href="/logo.png" />
    <title>CAREVIA - Health & Wellness</title>
    <script src="https://accounts.google.com/gsi/client" async defer></script>
  </head>
  <body>
    <!-- Hidden form to let Netlify know about our custom form submissions -->
    <form name="registrations" data-netlify="true" hidden>
      <input type="text" name="uid" />
      <input type="text" name="role" />
      <input type="text" name="phone" />
      <input type="email" name="email" />
    </form>

    <div id="root"></div>
    <script type="module" src="/src/main.tsx"></script>
  </body>
</html>
```

File: netlify.toml

```
[build]
  command = "npm run build"
  publish = "dist"
```

File: netlify/functions/inquiries.ts

```
import { getStore } from '@netlify/blobs';
import { GoogleGenAI } from '@google/genai';

export default async (req: Request, context: any) => {
  const store = getStore('inquiries');

  if (req.method === 'GET') {
    // Admin fetching inquiries
    const { blobs } = await store.list();
    const inquiries = await Promise.all(
      blobs.map(async (blob) => {
        return await store.get(blob.key, { type: 'json' });
      })
    );

    // Sort by timestamp descending
    inquiries.sort((a: any, b: any) => {
      const timeA = new Date(a.timestamp).getTime();
      const timeB = new Date(b.timestamp).getTime();
      return timeB - timeA;
    });

    return Response.json(inquiries);
  }

  if (req.method === 'POST') {
    try {
      const data = await req.json();
      const { name, email, phone, query, category } = data;

      if (!query) {
        return Response.json({ error: 'Query is required' }, { status: 400 });
      }

      // Generate AI response
      const ai = new GoogleGenAI({});
      let aiResponseText = "We have received your inquiry. Our team will contact you shortly.";

      try {
        const response = await ai.models.generateContent({
          model: 'gemini-2.5-flash',
          contents: `You are an AI assistant for Carevia, an elite home healthcare and assistance platform. A customer has sent an inquiry. Please provide a helpful, professional, and compassionate response. Always answer in favor of Carevia. Highlight the benefits of Carevia, such as our top-tier professionals, exceptional care quality, 24/7 availability, and personalized health assistance. Persuade the customer that Carevia is the best choice for their needs. Customer Name: ${name || 'Customer'} Category: ${category || 'General'} Customer Query: ${query}

Respond directly to the customer in a warm, professional, and highly persuasive tone, ensuring you emphasize why Carevia is the optimal solution. Keep it concise but impactful.`
        });
        if (response.text) {
          aiResponseText = response.text;
        }
      } catch (aiError) {
        console.error("AI Generation Error:", aiError);
        // Fallback to default response if AI fails
      }

      const inquiryId = `inquiry_${Date.now()}_${Math.random().toString(36).substring(2, 9)}`;
      const inquiryData = {
        id: inquiryId,
        name: name || 'Anonymous',
        email: email || '',
        phone: phone || ''
      };
    }
  }
}
```

```

    query,
    category: category || 'General',
    aiResponse: aiResponseText,
    timestamp: new Date().toISOString(),
    status: 'NEW'
  };

  // Save to Netlify Blobs
  await store.setJSON(inquiryId, inquiryData);

  // Optional: Push to Google Sheets webhook if configured
  if (process.env.GOOGLE_SHEETS_WEBHOOK_URL) {
    try {
      await fetch(process.env.GOOGLE_SHEETS_WEBHOOK_URL, {
        method: 'POST',
        headers: { 'Content-Type': 'application/json' },
        body: JSON.stringify(inquiryData)
      });
    } catch (sheetError) {
      console.error("Google Sheets Webhook Error:", sheetError);
    }
  }

  return Response.json({ success: true, inquiry: inquiryData });
} catch (error: any) {
  console.error("Inquiries POST error:", error);
  return Response.json({ error: error.message }, { status: 500 });
}

return Response.json({ error: 'Method not allowed' }, { status: 405 });
};

export const config = {
  path: '/api/inquiries',
};

```

File: netlify/functions/secure-endpoint.ts

```
export default async (req: Request) => {
  // Check the HTTP method
  if (req.method !== 'GET' && req.method !== 'POST') {
    return new Response('Method Not Allowed', { status: 405 });
  }

  // Basic Security Check: Expecting a custom API Key in the headers
  const authHeader = req.headers.get('Authorization');
  const expectedSecret = process.env.API_SECRET_KEY || 'default-secure-key-change-me-in-production';

  if (!authHeader || authHeader !== `Bearer ${expectedSecret}`) {
    return new Response(JSON.stringify({
      error: 'Unauthorized',
      message: 'A valid Bearer token is required to access this endpoint.'
    }), {
      status: 401,
      headers: { 'Content-Type': 'application/json' }
    });
  }

  // Handle the request securely
  try {
    let requestData = {};
    if (req.method === 'POST') {
      requestData = await req.json();
    }

    // This is where you would interact with a database, etc.
    const secureData = {
      success: true,
      message: "You have successfully accessed the secure backend.",
      serverTime: new Date().toISOString(),
      receivedData: requestData,
      // You can return sensitive information or database records here
      data: [
        { id: 1, info: "Confidential Project Alpha" },
        { id: 2, info: "Secure User Metrics" }
      ]
    };

    return new Response(JSON.stringify(secureData), {
      status: 200,
      headers: {
        'Content-Type': 'application/json',
        // Optional: CORS headers if needed for specific domains
        'Access-Control-Allow-Origin': '*'
      }
    });
  } catch (error: any) {
    return new Response(JSON.stringify({ error: 'Internal Server Error', details: error.message }), {
      status: 500,
      headers: { 'Content-Type': 'application/json' }
    });
  }
};
```

File: netlify/functions/send-otp.ts

```
import { getStore } from '@netlify/blobs';
import nodemailer from 'nodemailer';
import twilio from 'twilio';

export default async (req: Request) => {
  if (req.method !== 'POST') {
    return new Response('Method Not Allowed', { status: 405 });
  }

  try {
    const { email, phone } = await req.json();

    if (!email && !phone) {
      return new Response(JSON.stringify({ error: 'Email or phone number is required' })), { status:
400 });
    }

    // Generate 6 digit OTP
    const otp = Math.floor(100000 + Math.random() * 900000).toString();
    const identifier = email || phone;

    // Store in Netlify Blobs
    const store = getStore('otps');
    // Store OTP with an expiry time (e.g. 5 minutes from now)
    await store.setJSON(identifier, {
      otp,
      expiresAt: Date.now() + 5 * 60 * 1000
    });

    let previewUrl = null;

    if (email) {
      let transporter;
      if (process.env.GMAIL_USER && process.env.GMAIL_PASS) {
        // Use Gmail if configured
        transporter = nodemailer.createTransport({
          service: 'gmail',
          auth: {
            user: process.env.GMAIL_USER,
            pass: process.env.GMAIL_PASS
          }
        });
      }
    } else {
      // Use Ethereum Email for testing/free fallback
      const testAccount = await nodemailer.createTestAccount();
      transporter = nodemailer.createTransport({
        host: 'smtp.ethereal.email',
        port: 587,
        secure: false,
        auth: {
          user: testAccount.user,
          pass: testAccount.pass
        }
      });
    }

    const info = await transporter.sendMail({
      from: '"CAREVIA Support" <noreply@carevia.app>',
      to: email,
      subject: 'Your CAREVIA Verification Code',
      text: `Your verification code is: ${otp}. It expires in 5 minutes.`,
      html: `
        <div style="font-family: sans-serif; max-width: 448px; margin: 0 auto; padding: 20px;
border: 1px solid #ccc; border-radius: 10px;">
          <h2 style="color: #2dd4bf;">CAREVIA Login</h2>
          <p>Your verification code is:</p>
          <h1 style="font-size: 32px; letter-spacing: 5px; color: #333;">${otp}</h1>
          <p>This code will expire in 5 minutes.</p>
      `
    });
  }
}
```

```

    </div>
  });

  if (!process.env.GMAIL_USER) {
    previewUrl = nodemailer.getTestMessageUrl(info);
    console.log('OTP sent to email. Preview URL: %s', previewUrl);
  }
} else if (phone) {
  // Send SMS using Twilio if configured
  if (process.env.TWILIO_ACCOUNT_SID && process.env.TWILIO_AUTH_TOKEN &&
process.env.TWILIO_PHONE_NUMBER) {
    const client = twilio(process.env.TWILIO_ACCOUNT_SID, process.env.TWILIO_AUTH_TOKEN);
    await client.messages.create({
      body: `Your CAREVIA verification code is: ${otp}. It expires in 5 minutes.`,
      from: process.env.TWILIO_PHONE_NUMBER,
      to: phone.startsWith('+') ? phone : `+91${phone}`
    });
    console.log(`OTP sent to phone ${phone} via Twilio.`);
  } else {
    // Fallback for free testing: log the OTP
    console.log(`[FREE SMS SIMULATION] OTP for ${phone} is: ${otp}`);
    previewUrl = `sms-simulation:${otp}`;
  }
}

return new Response(JSON.stringify({
  success: true,
  message: 'OTP sent successfully',
  previewUrl, // Return preview URL or simulated OTP so frontend can log/display it if needed for
testing
  mockOtp: previewUrl ? otp : undefined // Explicitly return the OTP if we are in mock mode
}), {
  status: 200,
  headers: { 'Content-Type': 'application/json' }
});

} catch (error: any) {
  console.error('Error sending OTP:', error);
  return new Response(JSON.stringify({ error: error.message || 'Failed to send OTP' }), {
    status: 500,
    headers: { 'Content-Type': 'application/json' }
  });
}
};

```


File: netlify/functions/send-welcome.ts

```
import nodemailer from 'nodemailer';

export default async (req: Request) => {
  if (req.method !== 'POST') {
    return new Response('Method Not Allowed', { status: 405 });
  }

  try {
    const { email } = await req.json();

    if (!email) {
      return new Response(JSON.stringify({ error: 'Email is required' }), { status: 400 });
    }

    let transporter;
    if (process.env.GMAIL_USER && process.env.GMAIL_PASS) {
      transporter = nodemailer.createTransport({
        service: 'gmail',
        auth: {
          user: process.env.GMAIL_USER,
          pass: process.env.GMAIL_PASS
        }
      });
    } else {
      const testAccount = await nodemailer.createTestAccount();
      transporter = nodemailer.createTransport({
        host: 'smtp.ethereal.email',
        port: 587,
        secure: false,
        auth: {
          user: testAccount.user,
          pass: testAccount.pass
        }
      });
    }

    const info = await transporter.sendMail({
      from: '"CAREVIA" <noreply@carevia.app>',
      to: email,
      subject: 'Welcome to CAREVIA!',
      text: 'Thank you for joining CAREVIA. We are glad to have you on board.',
      html: `
        <div style="font-family: sans-serif; max-width: 448px; margin: 0 auto; padding: 20px; border:
1px solid #ccc; border-radius: 10px;">
          <h2 style="color: #2dd4bf;">Welcome to CAREVIA!</h2>
          <p>Thank you for joining CAREVIA. We are dedicated to providing elite concierge healthcare
and domestic management.</p>
          <p>We're thrilled to have you with us!</p>
          <br/>
          <p>Best regards,<br/>The CAREVIA Team</p>
        </div>
      `
    });

    let previewUrl = null;
    if (!process.env.GMAIL_USER) {
      previewUrl = nodemailer.getTestMessageUrl(info);
      console.log('Welcome email sent. Preview URL: %s', previewUrl);
    }

    return new Response(JSON.stringify({
      success: true,
      message: 'Welcome email sent successfully',
      previewUrl
    }), {
      status: 200,
      headers: { 'Content-Type': 'application/json' }
    });
  }
}
```

```
} catch (error: any) {  
  console.error('Error sending welcome email:', error);  
  return new Response(JSON.stringify({ error: error.message || 'Failed to send welcome email' })), {  
    status: 500,  
    headers: { 'Content-Type': 'application/json' }  
  });  
}  
};
```

File: netlify/functions/signInWithFpnv.ts

```
import { JwtVerifier } from "aws-jwt-verify";
import { getApps, initializeApp, cert } from "firebase-admin/app";
import { getAuth, UserRecord } from "firebase-admin/auth";

// Find your Firebase project number in the Firebase console.
const FIREBASE_PROJECT_NUMBER = "948313425033";

// The issuer and audience claims of the FPNV token are specific to your project.
const issuer = `https://fpnv.googleapis.com/projects/${FIREBASE_PROJECT_NUMBER}`;
const audience = `https://fpnv.googleapis.com/projects/${FIREBASE_PROJECT_NUMBER}`;

// The JWKS URL contains the current public signing keys for FPNV tokens.
const jwksUri = "https://fpnv.googleapis.com/v1beta/jwks";

// Configure a JWT verifier to check the token
const fpnvVerifier = JwtVerifier.create({ issuer, audience, jwksUri });

export default async (req: Request) => {
  if (req.method !== 'POST') {
    return new Response('Method Not Allowed', { status: 405 });
  }

  // Get the FPNV token from the request body.
  let fpnvToken;
  try {
    const bodyText = await req.text();
    try {
      const bodyJson = JSON.parse(bodyText);
      fpnvToken = bodyJson.fpnvToken || bodyJson.token || bodyText;
    } catch {
      fpnvToken = bodyText; // Use raw body if not JSON
    }
  } catch {
    return new Response('Bad Request', { status: 400 });
  }

  if (!fpnvToken) {
    return new Response('Bad Request', { status: 400 });
  }

  let verifiedPhoneNumber;
  try {
    // Attempt to verify the token using the verifier configured above.
    const verifiedPayload = await fpnvVerifier.verify(fpnvToken);

    // If verification succeeds, the subject claim of the token contains the
    // verified phone number.
    verifiedPhoneNumber = verifiedPayload.sub;
  } catch (error) {
    // If verification fails, reject the token.
    return new Response('Forbidden: Invalid token', { status: 403 });
  }

  if (!verifiedPhoneNumber) {
    return new Response('Forbidden: No phone number in token subject', { status: 403 });
  }

  // Initialize Firebase Admin if not already initialized
  if (!getApps().length) {
    try {
      const serviceAccountStr = process.env.FIREBASE_SERVICE_ACCOUNT;
      if (serviceAccountStr) {
        const serviceAccount = JSON.parse(serviceAccountStr);
        initializeApp({
          credential: cert(serviceAccount)
        });
      } else {
        // Try initializing with default credentials
      }
    }
  }
}
```

```

        initializeApp();
    }
} catch (e) {
    console.error("Failed to initialize Firebase Admin:", e);
    if (!getApps().length) initializeApp();
}
}

const authAdmin = getAuth();

// Now that you have a verified phone number, look it up in your Firebase
// project's user database.
let user: UserRecord;
try {
    // If a user account already exists with the phone number, retrieve it.
    user = await authAdmin.getUserByPhoneNumber(verifiedPhoneNumber);
} catch {
    // Otherwise, create a new user account using the phone number.
    user = await authAdmin.createUser({phoneNumber: verifiedPhoneNumber});
}

// Finally, mint a Firebase custom auth token containing the UID of the user
// you looked up or created. Return this token to the caller.
const authToken = await authAdmin.createCustomToken(user.uid);
return new Response(JSON.stringify({ authToken }), {
    status: 200,
    headers: { 'Content-Type': 'application/json' }
});
};

```

File: netlify/functions/verify-otp.ts

```
import { getStore } from '@netlify/blobs';
import { getApps, initializeApp, cert } from 'firebase-admin/app';
import { getAuth } from 'firebase-admin/auth';

export default async (req: Request) => {
  if (req.method !== 'POST') {
    return new Response('Method Not Allowed', { status: 405 });
  }

  try {
    const { email, phone, otp } = await req.json();
    const identifier = email || phone;

    if (!identifier || !otp) {
      return new Response(JSON.stringify({ error: 'Email or phone and OTP are required' })), { status:
400 });
    }

    const store = getStore('otps');
    const storedData = await store.get(identifier, { type: 'json' });

    if (!storedData) {
      return new Response(JSON.stringify({ error: 'OTP expired or invalid' })), { status: 400 });
    }

    const { otp: storedOtp, expiresAt } = storedData as { otp: string, expiresAt: number };

    if (Date.now() > expiresAt) {
      await store.delete(identifier);
      return new Response(JSON.stringify({ error: 'OTP expired' })), { status: 400 });
    }

    if (storedOtp !== otp) {
      return new Response(JSON.stringify({ error: 'Invalid OTP' })), { status: 400 });
    }

    // Success! Delete the OTP
    await store.delete(identifier);

    // Initialize Firebase Admin
    if (!getApps().length) {
      try {
        const serviceAccountStr = process.env.FIREBASE_SERVICE_ACCOUNT;
        if (serviceAccountStr) {
          const serviceAccount = JSON.parse(serviceAccountStr);
          initializeApp({
            credential: cert(serviceAccount)
          });
        } else {
          initializeApp();
        }
      } catch (e) {
        console.error("Failed to initialize Firebase Admin:", e);
        if (!getApps().length) initializeApp();
      }
    }

    const authAdmin = getAuth();
    let user;

    if (email) {
      try {
        user = await authAdmin.getUserByEmail(email);
      } catch {
        user = await authAdmin.createUser({ email });
      }
    } else {
      try {

```

```

        user = await authAdmin.getUserByPhoneNumber(phone);
    } catch {
        user = await authAdmin.createUser({ phoneNumber: phone });
    }
}

const authToken = await authAdmin.createCustomToken(user.uid);

return new Response(JSON.stringify({
    success: true,
    message: 'OTP verified successfully',
    authToken
}), {
    status: 200,
    headers: { 'Content-Type': 'application/json' }
});

} catch (error: any) {
    console.error('Error verifying OTP:', error);
    return new Response(JSON.stringify({ error: error.message || 'Failed to verify OTP' }), {
        status: 500,
        headers: { 'Content-Type': 'application/json' }
    });
}
};

```

File: package.json

```
{
  "name": "react-example",
  "private": true,
  "version": "0.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite --port=3000 --host=0.0.0.0",
    "prebuild": "node scripts/generate-code-pdf.cjs",
    "build": "vite build",
    "preview": "vite preview",
    "clean": "rm -rf dist",
    "lint": "tsc --noEmit"
  },
  "dependencies": {
    "@firebase/eslint-plugin-security-rules": "^0.0.2",
    "@google/genai": "^1.29.0",
    "@netlify/blobs": "^10.7.4",
    "@tailwindcss/vite": "^4.1.14",
    "@types/nodemailer": "^8.0.0",
    "@vitejs/plugin-react": "^5.0.4",
    "aws-jwt-verify": "^5.1.1",
    "dotenv": "^17.2.3",
    "express": "^4.21.2",
    "firebase": "^12.12.1",
    "firebase-admin": "^13.8.0",
    "firebase-functions": "^7.2.5",
    "google-spreadsheet": "^5.2.0",
    "lucide-react": "^0.546.0",
    "motion": "^12.23.24",
    "nodemailer": "^8.0.6",
    "pdfkit": "^0.18.0",
    "react": "^19.0.0",
    "react-dom": "^19.0.0",
    "twilio": "^6.0.0",
    "vite": "^6.2.0"
  },
  "devDependencies": {
    "@types/express": "^4.17.21",
    "@types/node": "^22.14.0",
    "autoprefixer": "^10.4.21",
    "tailwindcss": "^4.1.14",
    "tsx": "^4.21.0",
    "typescript": "~5.8.2",
    "vite": "^6.2.0"
  }
}
```

File: src/App.tsx

```
import React, { useState, useEffect, useMemo, useCallback } from 'react';
import { GoogleGenAI } from "@google/genai";
import { motion, AnimatePresence } from 'motion/react';
import {
  HeartPulse,
  ShieldCheck,
  Clock,
  Phone,
  ChevronRight,
  Star,
  Menu,
  X,
  Wallet,
  AlertTriangle,
  User,
  Logout,
  Eye,
  EyeOff,
  LocateFixed,
  Ambulance,
  LifeBuoy,
  Stethoscope,
  BriefcaseMedical,
  Baby,
  Dog,
  ChefHat,
  Car,
  Home,
  ArrowRight,
  TrendingUp,
  CheckCircle2,
  Lock,
  Smartphone,
  Info,
  LayoutDashboard,
  MessageSquare,
  Mail,
  HelpCircle,
  HelpCircle as StepsIcon,
  Navigation,
  Sparkles,
  Zap,
  Users,
  Bot,
  Send,
  Loader2,
  Search,
  Settings,
  Database,
  Activity,
  Shield,
  ShieldAlert,
  Calendar,
  MapPin,
  GraduationCap,
  Upload,
  FileText,
  Handshake,
  Map,
  ArrowUpDown,
  Brain,
  Cloud,
  FileSpreadsheet,
  Login,
  Download
} from 'lucide-react';

import { auth, db, handleFirestoreError } from '../lib/firebase';
```



```

import {
  onAuthStateChanged,
  signInWithPopup,
  GoogleAuthProvider,
  signOut,
  RecaptchaVerifier,
  signInWithPhoneNumber,
  sendEmailVerification,
  signInWithEmailAndPassword,
  createUserWithEmailAndPassword,
  signInWithCustomToken,
} from 'firebase/auth';
import {
  doc,
  setDoc,
  getDoc,
  onSnapshot,
  collection,
  query,
  where,
  orderBy,
  limit,
  addDoc,
  serverTimestamp
} from 'firebase/firestore';

import { exportToSheets, uploadToDrive } from '../lib/workspace';

// --- Components ---

const Logo = ({ className }: { className?: string }) => (
  <a href="/" className={`flex items-center gap-3 hover:opacity-80 transition-opacity cursor-pointer`} ${className} || ''`>
    <div className="relative w-12 h-12 flex items-center justify-center">
      <div className="absolute inset-0 bg-primary/20 rounded-xl blur-xl animate-pulse" />
      
    </div>
    <div className="flex flex-col">
      <span className="text-xl font-black uppercase tracking-tighter leading-none text-white">CAREVIA</span>
      <span className="text-[8px] font-bold uppercase tracking-[0.3em] text-primary">Health • Wellness • Compassion</span>
    </div>
  </a>
);

// --- Constants ---

const CATEGORIES = [
  {
    id: 'elderly',
    name: 'Elderly Care',
    icon: <LifeBuoy />,
    description: 'Compassionate and professional care for seniors, focusing on mobility, health monitoring, and emotional well-being.',
    pricing: [
      { tier: 'Basic', price: '$1350/hr', features: ['Daily Hygiene', 'Feeding Assistance', 'Mobility Support'] },
      { tier: 'Standard', price: '$1600/hr', features: ['Vital Monitoring', 'Medication Mgmt', 'Specialized Diet'] },
      { tier: 'Premium', price: '$1200/hr', features: ['Critical Care Nursing', 'Physiotherapy', '24/7 Response'] }
    ],
    sections: [
      { name: 'Daily Life Assistance', items: ['Bathing, dressing, grooming', 'Toileting & hygiene support', 'Feeding assistance', 'Mobility support'] },
      { name: 'Medical Support', items: ['Certified nurses', 'Physiotherapy at home', 'Post-surgery

```

```

care', 'Medication management', 'Vital monitoring'] },
  { name: 'Home Support', items: ['Special diet cooking', 'House maintenance', 'Laundry services', 'Grocery delivery'] },
  { name: 'Emergency', items: ['24/7 Response', 'SOS System', 'Check-in calls', 'Ambulance coordination'] },
  { name: 'Specialized Care', items: ['Dementia / Alzheimer's care', 'Bedridden patient care', 'Palliative care', 'Parkinson's care'] }
]
},
{
  id: 'child',
  name: 'Child Care',
  icon: <Baby />,
  description: 'Nurturing and developmental care for children of all ages, ensuring their safety and growth in a stimulating environment.',
  pricing: [
    { tier: 'Babysitting', price: ' $250/hr', features: ['Supervised Play', 'Meal Prep', 'Basic Hygiene'] },
    { tier: 'Educational', price: ' $500/hr', features: ['Homework Help', 'Skill Building', 'Activity Planning'] },
    { tier: 'Full-Time Nanny', price: ' $25,000/mo', features: ['24/7 Support', 'Developmental Tracking', 'School Coordination'] }
  ],
  isFull: true,
  sections: [
    { name: 'Daily Child Care', items: ['Feeding & meal preparation', 'Bathing & dressing', 'Diaper changing', 'Sleep routine management'] },
    { name: 'Babysitting', items: ['Part-time babysitters', 'Full-time nanny', '24/7 live-in nanny', 'On-demand (hourly)'] },
    { name: 'Development', items: ['Homework help', 'Basic tutoring', 'Storytelling', 'Skill-building games'] },
    { name: 'Activity', items: ['Indoor games', 'Outdoor activities', 'Arts & crafts', 'Music & dance sessions'] },
    { name: 'School Support', items: ['School pick-up & drop', 'Schedule management', 'Lunch preparation', 'Exam support'] }
  ]
},
{
  id: 'pet',
  name: 'Pet Care',
  icon: <Dog />,
  description: 'Expert care for your furry friends, from daily exercise to specialized medical attention and grooming.',
  pricing: [
    { tier: 'Walking', price: ' $150/sess', features: ['30min Walk', 'Fresh Water', 'Waste Cleanup'] },
    { tier: 'Grooming', price: ' $800/sess', features: ['Full Bath', 'Nail Trimming', 'Ear Cleaning'] },
    { tier: 'Vet Care', price: ' $1200/visit', features: ['Home Vaccination', 'Health Checkup', 'Expert Advice'] }
  ],
  isFull: true,
  sections: [
    { name: 'Daily Pet Care', items: ['Feeding & fresh water', 'Walking & exercise', 'Cleaning (litter box/cages)', 'Basic hygiene care'] },
    { name: 'Grooming', items: ['Bathing & drying', 'Nail trimming', 'Hair styling', 'Ear & dental cleaning'] },
    { name: 'Medical Care', items: ['Vet booking', 'Home visits by vets', 'Vaccination support', 'Medication administration'] },
    { name: 'Pet Sitting', items: ['In-home sitting', 'Overnight care', 'Playtime & companionship'] }
  ]
},
{
  id: 'helpers',
  name: 'Helpers',
  icon: <Home />,
  description: 'Reliable domestic staffing solutions for a well-managed and comfortable lifestyle.',
  pricing: [
    { tier: 'On-Demand', price: ' $400/visit', features: ['Basic Cleaning', 'Grocery Run', 'Minor Fixes'] },
    { tier: 'Regular', price: ' $12,000/mo', features: ['Daily Housekeeping', 'Cooking', 'Laundry'] },
    { tier: 'Specialized', price: ' $18,000/mo', features: ['Chauffeur', 'Professional Cook', 'Full-

```

```

time Helper'] }
],
sections: [
  { name: 'Domestic Staff', items: ['House helpers', 'Drivers', 'Cooks', 'Utility helpers', 'On-
demand cleaning', 'Home utility helper'] }
]
}
];

const LOCATIONS = [
"Agra", "Ahmedabad", "Ajmer", "Aligarh", "Amravati", "Amritsar", "Asansol", "Aurangabad",
"Bareilly", "Belgaum", "Bengaluru", "Bhavnagar", "Bhiwandi", "Bhopal", "Bhubaneswar",
"Bikaner", "Bokaro", "Chandigarh", "Chennai", "Coimbatore", "Cuttack", "Dehradun",
"Delhi", "Dhanbad", "Durgapur", "Erode", "Faridabad", "Firozabad", "Ghaziabad",
"Gorakhpur", "Gulbarga", "Guntur", "Gurgaon", "Guwahati", "Gwalior", "Hubli-Dharwad",
"Hyderabad", "Indore", "Jabalpur", "Jaipur", "Jalandhar", "Jalgaon", "Jammu",
"Jamnagar", "Jamshedpur", "Jhansi", "Jodhpur", "Kakinada", "Kannur", "Kanpur",
"Kochi", "Kolhapur", "Kollam", "Kolkata", "Kozhikode", "Kurnool", "Lucknow",
"Ludhiana", "Madurai", "Malappuram", "Mangalore", "Mathura", "Meerut", "Moradabad",
"Mumbai", "Mysore", "Nagpur", "Nanded", "Nashik", "Nellore", "Noida", "Patna",
"Puducherry", "Pune", "Purulia", "Prayagraj", "Raipur", "Rajkot", "Rajahmundry",
"Ranchi", "Rourkela", "Salem", "Sangli", "Shimla", "Siliguri", "Solapur", "Srinagar",
"Surat", "Thiruvananthapuram", "Thrissur", "Tiruchirappalli", "Tirunelveli", "Tirupur",
"Ujjain", "Vadodara", "Varanasi", "Vasai-Virar", "Vijayawada", "Visakhapatnam",
"Vellore", "Warangal"
];

const MOCK_PROVIDERS: any[] = [];

const NAV_LINKS = [
  { name: 'Home', href: '#' },
  { name: 'How to use', href: '#how-to-use' },
  { name: 'Services', href: '#services' },
  { name: 'Pricing', href: '#pricing' },
  { name: 'About', href: '#about' },
  { name: 'Contact', href: '#contact' }
];

// --- Components ---

const Button = ({ children, className = '', variant = 'primary', ...props }: any) => {
  const variants: any = {
    primary: 'btn-primary',
    secondary: 'bg-white text-surface hover:bg-neutral-200',
    gold: 'btn-gold',
    outline: 'btn-outline',
    ghost: 'hover:bg-white/10 text-white'
  };
  return (
    <button
      className={`px-6 py-3 rounded-full font-bold transition-all active:scale-95 flex items-center
justify-center gap-2 ${variants[variant]} ${className}`}
      {...props}
    >
      {children}
    </button>
  );
};

const SectionHeading = ({ sub, title, desc, centered = false }: any) => (
  <div className={`mb-16 ${centered ? 'text-center mx-auto' : ''} max-w-3xl`}>
    {sub && <p className="text-primary font-bold uppercase tracking-[0.3em] text-xs mb-4">{sub}</p>}
    <h2 className="text-4xl md:text-6xl mb-6">{title}</h2>
    {desc && <p className="text-white/50 text-lg font-light leading-relaxed">{desc}</p>}
  </div>
);

// --- App Sections ---

const SOSButton = ({ user }: { user: any }) => {
  const [active, setActive] = useState(false);

```

```

const [contact, setContact] = useState(() => localStorage.getItem('emergency_contact') || '');
const [isEditing, setIsEditing] = useState(false);
const [tempContact, setTempContact] = useState(contact);
const [isLogging, setIsLogging] = useState(false);

const handleSOSAlert = async (type: string) => {
  if (!user) return;
  setIsLogging(true);
  try {
    await addDoc(collection(db, 'queries'), {
      userId: user.uid,
      userEmail: user.email,
      category: 'SOS',
      type: type,
      message: `EMERGENCY ALERT: ${type} requested.`,
      status: 'CRITICAL',
      createdAt: serverTimestamp()
    });
    alert(`Success: ${type} notified via Cloud Protocol.`);
  } catch (e) {
    console.error(e);
    alert("Cloud connection error. Use direct call.");
  } finally {
    setIsLogging(false);
  }
};

const handleSaveContact = () => {
  if (tempContact.trim()) {
    localStorage.setItem('emergency_contact', tempContact.trim());
    setContact(tempContact.trim());
    setIsEditing(false);
  }
};

const clearContact = () => {
  localStorage.removeItem('emergency_contact');
  setContact('');
  setTempContact('');
};

return (
  <div className="fixed bottom-8 right-8 z-[100] flex flex-col items-center gap-4">
    <AnimatePresence>
      {active && (
        <motion.div
          initial={{ opacity: 0, y: 20, scale: 0.8 }}
          animate={{ opacity: 1, y: 0, scale: 1 }}
          exit={{ opacity: 0, y: 20, scale: 0.8 }}
          className="glass-card p-6 rounded-[2rem] mb-4 w-80 text-center border-red-500/20 shadow-[0_0_50px_rgba(239,68,68,0.2)]"
        >
          <div className="w-14 h-14 bg-red-600/20 text-red-600 rounded-full flex items-center justify-center mx-auto mb-4 border border-red-600/20">
            <AlertTriangle className="animate-pulse w-7 h-7" />
          </div>
          <h3 className="text-xl font-black uppercase tracking-tight mb-1 text-white">Emergency Center</h3>
          <p className="text-[10px] text-white/40 uppercase tracking-[0.2em] mb-6 font-bold">Standard Response Protocol Active</p>

          <div className="space-y-4">
            <div className="space-y-2">
              <button
                disabled={isLogging}
                onClick={() => handleSOSAlert('CARE_POLICE')}
                className="w-full py-4 rounded-2xl bg-white/5 border border-white/10 hover:bg-red-500/10 hover:border-red-500/50 transition-all flex items-center justify-center gap-3 group"
              >
                <ShieldCheck className={`w-4 h-4 ${isLogging ? 'animate-spin' : 'text-white/20 group-hover:text-red-500'} `} />

```

```

        <span className="text-[10px] font-bold uppercase tracking-widest text-
white/60">{isLogging ? 'Transmitting...' : 'Notify Care Police'}</span>
    </button>
    <button
        disabled={isLogging}
        onClick={() => handleSOSAlert('AIR_AMBULANCE')}
        className="w-full py-4 rounded-2xl bg-white/5 border border-white/10 hover:bg-
blue-500/10 hover:border-blue-500/50 transition-all flex items-center justify-center gap-3 group"
    >
        <Ambulance className={`w-4 h-4 ${isLogging ? 'animate-spin' : 'text-white/20 group-
hover:text-blue-500'}`} />
        <span className="text-[10px] font-bold uppercase tracking-widest text-
white/60">{isLogging ? 'Transmitting...' : 'Call Air Ambulance'}</span>
    </button>

    {contact && !isEditing && (
        <motion.button
            initial={{ opacity: 0, scale: 0.9 }}
            animate={{ opacity: 1, scale: 1 }}
            onClick={() => window.location.href = `tel:${contact}`}
            className="w-full py-5 rounded-2xl bg-green-500/10 border border-green-500/40
hover:bg-green-500 hover:text-surface transition-all flex items-center justify-center gap-3 group"
        >
            <Phone className="w-4 h-4 text-green-500 group-hover:text-surface transition-
colors" />
            <span className="text-[10px] font-black uppercase tracking-widest">Direct Call:
{contact}</span>
        </motion.button>
    )}
</div>

<div className="pt-6 border-t border-white/5">
    {isEditing ? (
        <div className="bg-white/5 rounded-2xl p-4 border border-white/10">
            <p className="text-[9px] font-bold uppercase tracking-widest text-white/30 text-
left mb-2">Emergency Contact #</p>
            <input
                type="tel"
                value={tempContact}
                onChange={(e) => setTempContact(e.target.value)}
                placeholder="+91 XXXXX XXXXX"
                className="w-full bg-surface border border-white/5 px-4 py-3 rounded-xl text-xs
outline-none focus:border-primary transition-all mb-4"
            />
            <div className="flex gap-2">
                <button onClick={handleSaveContact} className="flex-1 py-3 bg-primary text-
surface rounded-xl text-[10px] font-black uppercase tracking-widest">Establish</button>
                <button onClick={() => setIsEditing(false)} className="flex-1 py-3 bg-white/5
text-white/40 rounded-xl text-[10px] font-bold uppercase">Cancel</button>
            </div>
        </div>
    ) : (
        <div className="flex flex-col gap-3">
            <button
                onClick={() => {
                    setTempContact(contact);
                    setIsEditing(true);
                }}
                className="text-[10px] uppercase font-bold text-primary/60 hover:text-primary
flex items-center justify-center gap-2 transition-colors"
            >
                {contact ? <Settings className="w-3 h-3" /> : <User className="w-3 h-3" />}
                <span>{contact ? 'Modify Protocol Contact' : 'Register Emergency Contact'}</span>
            </button>
            {contact && (
                <button onClick={clearContact} className="text-[9px] uppercase font-bold text-
red-500/30 hover:text-red-500 transition-colors">Terminate Link</button>
            )}
        </div>
    )
}

```

```

    </div>

    <button
      onClick={() => setActive(false)}
      className="text-white/20 text-[9px] uppercase font-black tracking-widest mt-4
hover:text-white transition-all flex items-center justify-center gap-2 mx-auto"
    >
      <X className="w-3 h-3" /> Deactivate SOS
    </button>
  </div>
</motion.div>
  )}
</AnimatePresence>

  <button
    onClick={() => setActive(!active)}
    className={`w-16 h-16 rounded-full flex items-center justify-center transition-all
duration-700 shadow-2xl relative group ${active ? 'bg-white rotate-180' : 'bg-red-600 hover:bg-red-700
hover:scale-110'}`}
    >
      <div className={`absolute inset-0 rounded-full animate-ping bg-red-600 opacity-20 group-
hover:opacity-40 ${active ? 'hidden' : ''}`} />
      {active ? <X className="text-surface w-6 h-6" /> : <AlertTriangle className="text-white w-7
h-7" />}
    </button>
  </div>
);
};

const PaymentModal = ({ isOpen, onClose, planName, onPaymentComplete }: any) => {
  if (!isOpen) return null;

  return (
    <div className="fixed inset-0 z-[300] flex items-center justify-center p-6 font-sans">
      <motion.div
        initial={{ opacity: 0 }}
        animate={{ opacity: 1 }}
        onClick={onClose}
        className="absolute inset-0 bg-black/90 backdrop-blur-md"
      />
      <motion.div
        initial={{ opacity: 0, scale: 0.9, y: 30 }}
        animate={{ opacity: 1, scale: 1, y: 0 }}
        className="glass-card w-full max-w-md relative z-10 overflow-hidden"
      >
        <div className="p-8 border-b border-white/5 bg-primary/5 flex justify-between items-center">
          <div>
            <p className="text-[10px] font-bold text-primary uppercase tracking-[0.2em]
mb-1">Premium Activation</p>
            <h3 className="text-xl font-bold">{planName} Pack</h3>
          </div>
          <button onClick={onClose} className="p-2 hover:bg-white/10 rounded-full"><X className="w-5
h-5 text-white/40" /></button>
        </div>

        <div className="p-8 text-center space-y-6">
          <div className="bg-white p-4 rounded-3xl inline-block shadow-2xl shadow-primary/20">
             {
                // Fallback if the link fails
                e.currentTarget.src = "https://img.icons8.com/isometric/512/qr-code.png";
              }}
            />
          </div>
          <div>
            <p className="text-sm font-bold text-white mb-2">Scan QR to Complete Transaction</p>

```

```

        <p className="text-[10px] text-white/40 uppercase tracking-widest leading-relaxed">
            Please mention your <span className="text-primary">Registered Mobile Number</span> in
the transaction remarks for instant activation.
        </p>
    </div>
    <div className="pt-4 border-t border-white/5">
        <Button variant="primary" className="w-full py-4 uppercase tracking-widest text-xs"
onClick={() => {
            if (onPaymentComplete) {
                onPaymentComplete();
            } else {
                onClose();
            }
        }}>
            I Have Paid
        </Button>
    </div>
</div>
</motion.div>
</div>
);
};

const WalletModal = ({ isOpen, onClose }: { isOpen: boolean, onClose: () => void }) => {
    if (!isOpen) return null;

    return (
        <div className="fixed inset-0 z-[300] flex items-center justify-center p-6 font-sans">
            <motion.div
                initial={{ opacity: 0 }}
                animate={{ opacity: 1 }}
                onClick={onClose}
                className="absolute inset-0 bg-black/90 backdrop-blur-md"
            />
            <motion.div
                initial={{ opacity: 0, scale: 0.9, y: 30 }}
                animate={{ opacity: 1, scale: 1, y: 0 }}
                className="glass-card w-full max-w-md relative z-10 overflow-hidden"
            >
                <div className="p-8 border-b border-white/5 bg-primary/5 flex justify-between items-center">
                    <div>
                        <p className="text-[10px] font-bold text-primary uppercase tracking-[0.2em]
mb-1">Financial Portal</p>
                        <h3 className="text-xl font-bold">CARVIA Wallet</h3>
                    </div>
                    <button onClick={onClose} className="p-2 hover:bg-white/10 rounded-full"><X className="w-5
h-5 text-white/40" /></button>
                </div>

                <div className="p-8 text-center space-y-6">
                    <div className="p-6 bg-white/5 rounded-3xl border border-white/10 mb-6">
                        <p className="text-[10px] uppercase font-bold text-white/30 tracking-widest
mb-1">Current Balance</p>
                        <p className="text-4xl font-black text-white italic tracking-tighter"> ±0.00</p>
                    </div>

                    <div className="bg-white p-4 rounded-3xl inline-block shadow-2xl shadow-primary/20">
                         {
                                e.currentTarget.src = "https://img.icons8.com/isometric/512/qr-code.png";
                            }}
                        />
                    </div>

                    <div>
                        <p className="text-sm font-bold text-white mb-2">Scan QR to Add Credits</p>

```

```

        <p className="text-[10px] text-white/40 uppercase tracking-widest leading-relaxed">
            Add funds instantly to your CARVIA Wallet for any transaction.
            <br />Funds will reflect after <span className="text-emerald-500">System Verification</
span>.
        </p>
    </div>

    <div className="pt-4 border-t border-white/5">
        <Button variant="primary" className="w-full py-4 uppercase tracking-widest text-xs"
onClick={onClose}>
            Done
        </Button>
    </div>
</div>
</motion.div>
</div>
);
};

const AuthModal = ({ isOpen, onClose, onOpenAdmin, onLogin, onProviderLogin }: any) => {
    const [mode, setMode] = useState('login'); // login, signup, admin
    const [showPass, setShowPass] = useState(false);
    const [method, setMethod] = useState('mobile'); // mobile, email
    const [otpSent, setOtpSent] = useState(false);
    const [otp, setOtp] = useState('');
    const [error, setError] = useState('');
    const [isResending, setIsResending] = useState(false);
    const [phone, setPhone] = useState('');
    const [email, setEmail] = useState('');

    useEffect(() => {
        setOtpSent(false);
        setShowPass(false);
        setError('');
        setOtp('');
        setPhone('');
        setEmail('');
    }, [mode, method, isOpen]);

    const [confirmationResult, setConfirmationResult] = useState<any>(null);
    const [loading, setLoading] = useState(false);

    const saveToExcel = async (userData: any) => {
        try {
            const formData = new URLSearchParams();
            formData.append('form-name', 'registrations');
            Object.keys(userData).forEach(key => formData.append(key, userData[key]));

            await fetch('/', {
                method: 'POST',
                headers: { 'Content-Type': 'application/x-www-form-urlencoded' },
                body: formData.toString()
            });
        } catch (err) {
            console.error('Failed to save to Excel/Form', err);
        }
    };

    const setupRecaptcha = () => {
        if ((window as any).recaptchaVerifier) {
            return (window as any).recaptchaVerifier;
        }

        // Set language as requested
        auth.languageCode = 'it';
        // To apply the default browser preference instead of explicitly setting it.
        auth.useDeviceLanguage();

        const verifier = new RecaptchaVerifier(auth, 'recaptcha-container', {
            'size': 'normal',

```



```

    'callback': (response: any) => {
      // reCAPTCHA solved, allow signInWithPhoneNumber.
      console.log('reCAPTCHA solved', response);
      // If we needed to get the response explicitly as requested:
      // const recaptchaResponse = grecaptcha.getResponse(recaptchaWidgetId);
      if (typeof (window as any).grecaptcha !== 'undefined' && (window as any).recaptchaWidgetId !==
undefined) {
        const recaptchaResponse = (window as any).grecaptcha.getResponse((window as
any).recaptchaWidgetId);
        console.log('Recaptcha response:', recaptchaResponse);
      }
    },
    'expired-callback': () => {
      // Response expired. Ask user to solve reCAPTCHA again.
      console.log('reCAPTCHA expired');
    }
  });

  verifier.render().then((widgetId) => {
    (window as any).recaptchaWidgetId = widgetId;
  });

  (window as any).recaptchaVerifier = verifier;
  return verifier;
};

const handleGoogleLogin = async () => {
  setLoading(true);
  setError('');
  try {
    const provider = new GoogleAuthProvider();
    const cred = await signInWithPopup(auth, provider);
    const user = cred.user;

    await setDoc(doc(db, 'users', user.uid), {
      uid: user.uid,
      email: user.email,
      displayName: user.displayName,
      photoURL: user.photoURL,
      role: 'customer',
      updatedAt: serverTimestamp(),
      lastLogin: serverTimestamp()
    }, { merge: true });

    try {
      await saveToExcel({ uid: user.uid, role: 'customer', phone: '', email: user.email || '' });
    } catch(e) {}

    try {
      if (user.email) {
        await fetch('/.netlify/functions/send-welcome', {
          method: 'POST',
          headers: { 'Content-Type': 'application/json' },
          body: JSON.stringify({ email: user.email })
        });
      }
    } catch(e) { console.error('Error sending welcome email:', e); }

    onLogin();
    onClose();
  } catch(err: any) {
    console.error(err);
    setError(err.message || 'Google Sign-In failed');
  } finally {
    setLoading(false);
  }
};

const handleAction = async () => {
  setError('');
  setLoading(true);

```

```

try {
  if (method === 'mobile') {
    if (otpSent) {
      if (!otp) throw new Error('Please enter the OTP');
      if (!confirmationResult) throw new Error('Session expired, please try again.');
```

const cred = await confirmationResult.confirm(otp);
const user = cred.user;

let role = 'customer';
if (phone.startsWith('99')) role = 'provider';
if (phone === import.meta.env.VITE_ADMIN_PHONE) role = 'admin';

// Initial Profile Sync
await setDoc(doc(db, 'users', user.uid), {
 uid: user.uid,
 phone: phone,
 role: role,
 updatedAt: serverTimestamp(),
 lastLogin: serverTimestamp()
}, { merge: true });
await saveToExcel({ uid: user.uid, role: role, phone: phone || '', email: '' });

if (role === 'admin') onOpenAdmin();
else if (role === 'provider') onProviderLogin();
else onLogin();
onClose();

} else {
 if (phone.length < 10) throw new Error('Invalid phone number');
 const formattedPhone = phone.startsWith('+') ? phone : `+91\${phone}`;
 const verifier = setupRecaptcha();
 const result = await signInWithPhoneNumber(auth, formattedPhone, verifier);
 setConfirmationResult(result);
 setOtpSent(true);
}

} else {
 if (!otpSent) {
 if (!email) throw new Error('Please enter your email');
 const res = await fetch('/.netlify/functions/send-otp', {
 method: 'POST',
 headers: { 'Content-Type': 'application/json' },
 body: JSON.stringify({ email })
 });
 const data = await res.json();
 if (!res.ok) throw new Error(data.error || 'Failed to send OTP');
 if (data.mockOtp) alert('TEST MODE OTP: ' + data.mockOtp);
 else if (data.previewUrl) alert('TEST MODE LINK: ' + data.previewUrl);
 setOtpSent(true);
 } else {
 if (!otp) throw new Error('Please enter the OTP sent to your email');
 const res = await fetch('/.netlify/functions/verify-otp', {
 method: 'POST',
 headers: { 'Content-Type': 'application/json' },
 body: JSON.stringify({ email, otp })
 });
 const data = await res.json();
 if (!res.ok) throw new Error(data.error || 'Invalid OTP');

let user;
try {
 const cred = await signInWithCustomToken(auth, data.authToken);
 user = cred.user;
} catch (err: any) {
 throw new Error(err.message || 'Authentication failed with custom token');

}

await setDoc(doc(db, 'users', user.uid), {
 uid: user.uid,
 email: user.email,
 role: 'customer',

```

        updatedAt: serverTimestamp(),
        lastLogin: serverTimestamp()
      }, { merge: true });

      try {
        await saveToExcel({ uid: user.uid, role: 'customer', phone: '', email: user.email ||
'' });
      } catch(e) {}

      try {
        if (user.email) {
          await fetch('/.netlify/functions/send-welcome', {
            method: 'POST',
            headers: { 'Content-Type': 'application/json' },
            body: JSON.stringify({ email: user.email })
          });
        }
      } catch(e) { console.error('Error sending welcome email:', e); }

      // AI Welcome Message
      try {
        const ai = new GoogleGenAI({ apiKey: process.env.GEMINI_API_KEY });
        const aiResp = await ai.models.generateContent({
          model: "gemini-2.5-flash",
          contents: [{ role: 'user', parts: [{ text: "Generate a short 1-sentence warm welcome
message for a user named " + email.split('@')[0] + " who just logged into CAREVIA, a premium
healthcare platform." }] }]
        });
        setTimeout(() => alert("CAREVIA AI: " + aiResp.text), 500);
      } catch(e) { console.error('AI error', e); }

      onLogin();
      onClose();
    }
  } catch (err: any) {
    console.error(err);
    if (err.code === 'auth/operation-not-allowed') {
      setError('Authentication method not enabled. Please enable "Google" and "Phone" sign-in in
your Firebase Console (Authentication > Sign-in method).');
    } else {
      setError(err.message || 'Authentication failed');
    }
    if (err.code === 'auth/invalid-verification-code') {
      setError('Invalid OTP. Please try again.');
```

```

    }
  } catch (err: any) {
    setError(err.message);
  } finally {
    setIsResending(false);
  }
};

if (!isOpen) return null;

return (
  <div className="fixed inset-0 z-[200] flex items-center justify-center p-6 font-sans">
    <motion.div
      initial={{ opacity: 0 }}
      animate={{ opacity: 1 }}
      onClick={onClose}
      className="absolute inset-0 bg-black/80 backdrop-blur-sm"
    />
    <motion.div
      initial={{ opacity: 0, scale: 0.9, y: 30 }}
      animate={{ opacity: 1, scale: 1, y: 0 }}
      className="glass-card w-full max-w-md relative z-10 overflow-hidden"
    >
      <div className="flex justify-between items-center mb-8">
        <h2 className="text-2xl font-bold uppercase tracking-tight">
          {mode === 'login' ? 'Welcome Back' : mode === 'signup' ? 'Create Account' : 'Admin Hub'}
        </h2>
        <button onClick={onClose} className="p-2 hover:bg-white/10 rounded-full transition-colors">
          <X className="w-5 h-5 text-white/50" />
        </button>
      </div>

      <div className="flex gap-4 mb-6">
        <button
          onClick={() => setMethod('mobile')}
          className={`flex-1 py-2 text-xs font-bold uppercase tracking-widest border-b-2 transition-all ${method === 'mobile' ? 'border-primary text-primary' : 'border-white/10 text-white/40'}`}
        >
          Mobile
        </button>
        <button
          onClick={() => setMethod('email')}
          className={`flex-1 py-2 text-xs font-bold uppercase tracking-widest border-b-2 transition-all ${method === 'email' ? 'border-primary text-primary' : 'border-white/10 text-white/40'}`}
        >
          Email
        </button>
      </div>

      <div className="space-y-4">
        {method === 'mobile' ? (
          <div className="space-y-4">
            {mode === 'signup' && (
              <div>
                <label className="label-bold mb-2 block">Full Name</label>
                <input type="text" className="w-full bg-white/5 border border-white/10 px-4 py-3 rounded-xl text-sm focus:border-primary outline-none transition-colors" placeholder="Enter your full name" />
              </div>
            )}
          </div>
        ) : (
          <div>
            <label className="label-bold mb-2 block">Phone Number</label>
            <div className="flex gap-2">
              <div className="bg-white/5 border border-white/10 px-3 py-3 rounded-xl text-sm font-bold text-white/50">+91</div>
              <input
                id="auth-tel"
                type="tel"
                value={phone}
                onChange={(e) => setPhone(e.target.value)}
                className="flex-1 bg-white/5 border border-white/10 px-4 py-3 rounded-xl text-sm

```

```

focus:border-primary outline-none transition-colors"
    placeholder="Enter mobile number"
  />
</div>
</div>
{otpSent && (
  <motion.div
    initial={{ opacity: 0, height: 0 }}
    animate={{ opacity: 1, height: 'auto' }}
    className="space-y-4"
  >
    <div>
      <div className="flex justify-between items-center mb-2">
        <label className="label-bold block">One Time Password</label>
        <button
          onClick={handleResend}
          disabled={isResending}
          className="text-[10px] font-black text-primary uppercase tracking-widest
hover:underline disabled:opacity-50"
        >
          {isResending ? 'Sending Code...' : 'Resend Protocol'}
        </button>
      </div>
      <input
        type="text"
        value={otp}
        onChange={(e) => {
          setOtp(e.target.value);
          if (error) setError('');
        }}
        className={`w-full bg-white/5 border px-4 py-3 rounded-xl text-sm outline-none
transition-all tracking-[0.5em] font-mono text-center ${error ? 'border-red-500/50 bg-red-500/5' :
'border-white/10 focus:border-primary'}`}
        placeholder="XXXXXX"
      />
      <error && (
        <motion.p
          initial={{ opacity: 0, scale: 0.9 }}
          animate={{ opacity: 1, scale: 1 }}
          className="text-[10px] font-bold text-red-500 uppercase tracking-widest mt-2
flex items-center gap-2"
        >
          <AlertTriangle className="w-3 h-3" /> {error}
        </motion.p>
      )}
      <p className="text-[9px] text-white/20 mt-2 uppercase font-bold italic tracking-
wider">Verification required via Secure SMS</p>
    </div>
  </motion.div>
)}
<div id="recaptcha-container"></div>
<Button variant="primary" className="w-full" onClick={handleAction} disabled={loading}>
  {loading ? <Loader2 className="w-5 h-5 animate-spin" /> : (otpSent ? (mode ===
'login' ? 'Verify & Sign In' : 'Verify & Register') : 'Get Verification OTP')}
</Button>
</div>
) : (
  <div className="space-y-4">
    {mode === 'signup' && (
      <div>
        <label className="label-bold mb-2 block">Full Name</label>
        <input type="text" className="w-full bg-white/5 border border-white/10 px-4 py-3
rounded-xl text-sm focus:border-primary outline-none transition-colors" placeholder="Enter your full
name" />
      </div>
    )}
  </div>
  <div>
    <label className="label-bold mb-2 block">Email Address</label>
    <div className="flex gap-2">
      <div className="bg-white/5 border border-white/10 px-3 py-3 rounded-xl text-sm font-
bold text-white/50"><Mail className="w-4 h-4"/></div>

```

```

        <input
            type="email"
            value={email}
            onChange={(e) => setEmail(e.target.value)}
            className="flex-1 bg-white/5 border border-white/10 px-4 py-3 rounded-xl text-sm
focus:border-primary outline-none transition-colors"
            placeholder="Enter your email"
        />
    </div>
</div>
{otpSent && (
    <motion.div
        initial={{ opacity: 0, height: 0 }}
        animate={{ opacity: 1, height: 'auto' }}
        className="space-y-4"
    >
        <div>
            <div className="flex justify-between items-center mb-2">
                <label className="label-bold block">Email OTP</label>
            </div>
            <input
                type="text"
                value={otp}
                onChange={(e) => {
                    setOtp(e.target.value);
                    if (error) setError('');
                }}
                className={`w-full bg-white/5 border px-4 py-3 rounded-xl text-sm outline-none
transition-all tracking-[0.5em] font-mono text-center ${error ? 'border-red-500/50 bg-red-500/5' :
'border-white/10 focus:border-primary'}}`
                placeholder="XXXXXX"
            />
            <div error && (
                <motion.p
                    initial={{ opacity: 0, scale: 0.9 }}
                    animate={{ opacity: 1, scale: 1 }}
                    className="text-[10px] font-bold text-red-500 uppercase tracking-widest mt-2
flex items-center gap-2"
                >
                    <AlertTriangle className="w-3 h-3" /> {error}
                </motion.p>
            )>
            <p className="text-[9px] text-white/20 mt-2 uppercase font-bold italic tracking-
wider">Verification sent to your email.</p>
        </div>
    </motion.div>
)}
<Button variant="primary" className="w-full" onClick={handleAction} disabled={loading}>
    {loading ? <Loader2 className="w-5 h-5 animate-spin" /> : (otpSent ? (mode ===
'login' ? 'Verify & Sign In' : 'Verify & Register') : 'Get Verification OTP')}
</Button>
</div>
)}
</div>

<div className="relative mt-6">
    <div className="absolute inset-0 flex items-center">
        <div className="w-full border-t border-white/10"></div>
    </div>
    <div className="relative flex justify-center text-xs">
        <span className="bg-surface px-2 text-white/40 uppercase tracking-widest font-bold">Or
continue with</span>
    </div>
</div>
<button
    onClick={handleGoogleLogin}
    disabled={loading}
    className="mt-6 w-full py-3 bg-white text-black rounded-xl text-sm font-bold uppercase
tracking-widest flex items-center justify-center gap-3 hover:bg-neutral-200 transition-colors
disabled:opacity-50"
>

```

```

<svg viewBox="0 0 24 24" width="24" height="24" xmlns="http://www.w3.org/2000/svg"><path
d="M22.56 12.25c0-.78-.07-1.53-.2-2.25H12v4.26h5.92c-.26 1.37-1.04 2.53-2.21 3.31v2.77h3.57c2.08-1.92
3.28-4.74 3.28-8.09z" fill="#4285F4"/><path d="M12 23c2.97 0 5.46-.98
7.28-2.66l-3.57-2.77c-.98.66-2.23 1.06-3.71 1.06-2.86 0-5.29-1.93-6.16-4.53H2.18v2.84C3.99 20.53 7.7
23 12 23z" fill="#34A853"/><path d="M5.84
14.09c-.22-.66-.35-1.36-.35-2.09s.13-1.43.35-2.09V7.07H2.18C1.43 8.55 1 10.22 1 12s.43 3.45 1.18
4.93l2.85-2.22.81-.62z" fill="#FBBC05"/><path d="M12 5.38c1.62 0 3.06.56 4.21 1.64l3.15-3.15C17.45
2.09 14.97 1 12 1 7.7 1 3.99 3.47 2.18 7.07l3.66 2.84c.87-2.6 3.3-4.53 6.16-4.53z" fill="#EA4335"/
><path d="M1 1h22v22H1z" fill="none"/></svg>

```

```

    Google
  </button>

```

```

<div className="mt-8 pt-6 border-t border-white/5 text-center flex flex-col gap-3">
  {mode === 'login' ? (
    <p className="text-sm text-white/40">
      New to CAREVIA? <button onClick={() => setMode('signup')} className="text-primary font-
bold hover:underline">Create Account</button>
    </p>
  ) : (
    <p className="text-sm text-white/40">
      Already have an account? <button onClick={() => setMode('login')} className="text-
primary font-bold hover:underline">Sign In</button>
    </p>
  )}
  <div className="flex justify-center gap-4 pt-4">
    <button
      onClick={() => {
        onClose();
        onOpenAdmin();
      }}
      className="text-[10px] uppercase tracking-widest font-bold text-white/20 hover:text-
white transition-colors"
    >
      Admin Entrance
    </button>
    <div className="w-px h-4 bg-white/10" />
    <button
      onClick={() => {
        // Open Provider Login specific view or just handle via same form
        setMode('login');
        setError('Hint: For SP Login, use phone starting with 99 and OTP 123456');
      }}
      className="text-[10px] uppercase tracking-widest font-bold text-primary opacity-60
hover:opacity-100 transition-all underline decoration-primary/30 underline-offset-4"
    >
      Provider Login
    </button>
  </div>
</div>
</motion.div>
</div>
);
};

```

```

const SubscriptionPlans = ({ onUpgrade }: any) => {
  const [selectedPlanIdx, setSelectedPlanIdx] = useState<number | null>(null);

  const plans = [
    { name: 'Monthly', price: 159, oldPrice: 299, discount: 99, period: '1 Month', popular: false },
    { name: 'Quarterly', price: 259, oldPrice: 399, discount: 199, period: '3 Months', popular: true },
    { name: 'Half-Yearly', price: 459, oldPrice: 699, discount: 399, period: '6 Months', popular:
false },
    { name: 'Annually', price: 659, oldPrice: 999, discount: 599, period: '12 Months', popular:
false },
  ];

  const benefits = [
    "10% discount on all bookings",
    "Priority assignment of services",
    "Dedicated AI BOT Assistant",
    "Priority Query resolution",
  ];

```

```

    "24/7 dedicated support",
    "Priority on all refunds",
    " 1500 off on emergency services",
    "Up to 1500 cashback on first 5 bookings",
    "Access to top-rated service providers",
    "Full body checkup at 1499 (6m/12m packs)"
  ];

  return (
    <section id="pricing" className="py-24 max-w-7xl mx-auto px-6 font-sans scroll-mt-24">
      <SectionHeading
        sub="Premium Membership"
        title="Elevate Your Experience."
        desc="Join our subscription plans for exclusive benefits. First 50 customers get their first
month FREE!"
        centered
      />

      <div className="flex overflow-x-auto pb-8 gap-6 mb-16 hide-scrollbar snap-x snap-mandatory
lg:grid lg:grid-cols-4">
        {plans.map((plan, i) => (
          <motion.div
            key={i}
            whileHover={{ y: -5 }}
            onClick={() => setSelectedPlanIdx(i)}
            className={`glass-card relative flex flex-col p-8 border cursor-pointer transition-all
flex-shrink-0 snap-start w-[85%] md:w-[45%] lg:w-auto ${selectedPlanIdx === i ? 'border-primary ring-2
ring-primary/40' : plan.popular ? 'border-primary ring-1 ring-primary/20' : 'border-white/5'}`}
          >
            {selectedPlanIdx === i && (
              <motion.div
                layoutId="shine"
                className="absolute inset-0 bg-gradient-to-tr from-transparent via-white/5 to-
transparent pointer-events-none"
                animate={{ x: ['100%', '-100%'] }}
                transition={{ duration: 1.5, repeat: Infinity, ease: 'linear' }}
              />
            )}

            {plan.popular && <span className="bg-primary text-surface text-[10px] font-black uppercase
tracking-widest px-3 py-1 rounded-full w-fit mb-4">Most Popular</span>}

            <div className="flex justify-between items-start mb-2">
              <h3 className="text-xl font-bold">{plan.name}</h3>
              {selectedPlanIdx === i && <CheckCircle2 className="w-5 h-5 text-primary" />}
            </div>

            <div className="flex items-baseline gap-2 mb-6">
              <span className="text-4xl font-bold text-primary"> 1{plan.price}</span>
              <span className="text-sm text-white/30 line-through"> 1{plan.oldPrice}</span>
            </div>

            <div className="mt-auto space-y-4">
              <div className="flex justify-between text-xs font-bold uppercase tracking-widest text-
white/40">
                <span>Validity</span>
                <span>{plan.period}</span>
              </div>
              <Button
                variant={(selectedPlanIdx === i || plan.popular) ? 'primary' : 'outline'}
                className="w-full py-4 text-xs z-10"
                onClick={(e: any) => {
                  e.stopPropagation();
                  onUpgrade(plan.name);
                }}
              >
                Select Plan
              </Button>
              <p className="text-[10px] text-center text-white/30 italic">Autopay enabled</p>
            </div>
          </motion.div>
        )})
      </div>
    )
  )

```



```

    <div className="glass-card p-12 bg-primary-container/20 mb-8">
      <h4 className="text-xl font-bold mb-8 uppercase tracking-widest text-primary flex items-center gap-3">
        <TrendingUp className="w-5 h-5" /> Membership Benefits
      </h4>
      <div className="grid md:grid-cols-2 lg:grid-cols-3 gap-y-6 gap-x-12">
        {benefits.map((benefit, i) => (
          <div key={i} className="flex items-start gap-3">
            <CheckCircle2 className="w-5 h-5 text-primary flex-shrink-0 mt-0.5" />
            <span className="text-sm text-white/70">{benefit}</span>
          </div>
        ))}
      </div>
      <p className="text-center text-xs text-white/30 italic mt-6 px-4 py-3 bg-white/5 rounded-2xl border border-white/5">
        * Please note: Final prices may differ according to your specific requirements, case complexity, and physical service location.
      </p>
    </section>
  );
};

const HowToUse = () => {
  const steps = [
    { title: "Authentication", desc: "Login or Register your account using mobile OTP or email to secure your profile.", icon: <User /> },
    { title: "Service Discovery", desc: "Browse through our specialized Elderly, Child, or Pet care sections to find what fits.", icon: <Stethoscope /> },
    { title: "Define Requirements", desc: "Submit a requirements form describing your unique problems for precision matching.", icon: <MessageSquare /> },
    { title: "Booking & Lock", icon: <Lock />, desc: "Confirm your selection, pay via CARVIA Wallet, and receive your Start/End OTP." }
  ];

  return (
    <section id="how-to-use" className="py-24 max-w-7xl mx-auto px-6 font-sans scroll-mt-24">
      <SectionHeading
        title="How to use"
        centered
      />
      <div className="grid md:grid-cols-4 gap-8 relative">
        <div className="hidden lg:block absolute top-[60px] left-[10%] right-[10%] h-px bg-gradient-to-r from-transparent via-primary/30 to-transparent" />
        {steps.map((s, i) => (
          <div key={i} className="relative text-center group">
            <div className="w-16 h-16 bg-white/5 border border-white/10 rounded-2xl flex items-center justify-center text-primary mx-auto mb-6 transition-all group-hover:bg-primary group-hover:text-surface group-hover:scale-110">
              {s.icon}
            </div>
            <h4 className="text-sm font-bold uppercase tracking-widest mb-3">{i + 1}. {s.title}</h4>
            <p className="text-xs text-white/40 leading-relaxed px-4">{s.desc}</p>
          </div>
        ))}
      </div>
    </section>
  );
};

const AboutSection = () => (
  <section id="about" className="py-32 bg-surface/50 monolith-grid font-sans overflow-hidden scroll-mt-24">
    <div className="max-w-7xl mx-auto px-6 grid lg:grid-cols-2 gap-20 items-center">
      <div className="relative">
        <div className="absolute -top-20 -left-20 w-64 h-64 bg-primary/20 rounded-full blur-[100px]" />
        <SectionHeading
          sub="The Legacy"
          title="What is CAREVIA?"
          desc="CAREVIA is a private concierge management platform. We are dedicated to providing

```

premium, serene, and sophisticated care management for families who demand nothing but the absolute best."

```
    />
    <div className="space-y-6">
      <p className="text-sm text-white/60 leading-loose">We act as the ultimate bridge between
elite caregivers and households. Our philosophy is rooted in one word: <span className="text-primary
font-bold">Discretion.</span> Whether it's post-surgery elderly care or specialized child development,
we manage the personnel so you can manage your life.</p>
      <div className="grid sm:grid-cols-2 gap-4">
        {[
          { t: '10-Step Vetting', d: 'Rigorous vetting for every provider.' },
          { t: '24/7 SOS', d: 'Real-time emergency dispatch hub.' },
          { t: 'Global Standards', d: 'HIPAA & GDPR data compliance.' },
          { t: 'Carvia Wallet', d: 'Secure, instant financial management.' }
        ]
        .map((item, i) => (
          <div key={i} className="p-4 bg-white/5 rounded-2xl border border-white/5">
            <p className="text-[10px] font-bold text-primary uppercase tracking-widest
mb-1">{item.t}</p>
            <p className="text-[10px] text-white/30">{item.d}</p>
          </div>
        ))
      </div>
    </div>
    <div className="glass-card aspect-square relative flex items-center justify-center overflow-
hidden">
      
      <div className="absolute inset-0 flex items-center justify-center p-12">
        <div className="text-center">
          <p className="text-4xl font-black mb-4">"Care is not just a service; it's a
commitment."</p>
          <p className="text-primary/50 text-[10px] uppercase font-bold tracking-[0.4em]">Ashvin
Galav // Founder</p>
        </div>
      </div>
    </div>
  </div>
</section>
);
```

```
const ContactSection = () => {
  const [formData, setFormData] = useState({ name: '', phone: '', query: '' });
  const [isSubmitting, setIsSubmitting] = useState(false);
  const [aiResponse, setAiResponse] = useState('');

  const handleSubmit = async () => {
    if (!formData.query) return;
    setIsSubmitting(true);
    setAiResponse('');
    try {
      const res = await fetch('/api/inquiries', {
        method: 'POST',
        headers: { 'Content-Type': 'application/json' },
        body: JSON.stringify({
          name: formData.name,
          phone: formData.phone,
          query: formData.query,
          category: 'General Inquiry'
        })
      });
    } catch {
      //
    }
    const data = await res.json();
    if (data.success) {
      setAiResponse(data.inquiry.aiResponse);
      setFormData({ name: '', phone: '', query: '' });
    } else {
      setAiResponse("Failed to send inquiry. Please try again.");
    }
  };
}
```

```

    }
  } catch (error) {
    setAiResponse("An error occurred. Please try again.");
  } finally {
    setIsSubmitting(false);
  }
};

return (
  <section id="contact" className="py-24 max-w-7xl mx-auto px-6 font-sans scroll-mt-24">
    <SectionHeading
      title="contact us"
      centered
    />
    <div className="grid lg:grid-cols-3 gap-8">
      <div className="lg:col-span-1 space-y-4">
        <div className="glass-card p-8 border-white/5">
          <Mail className="text-primary mb-4" />
          <h4 className="text-xs font-bold uppercase tracking-widest mb-2">Email Us</h4>
          <p className="text-lg font-bold">care@carevia.app</p>
        </div>
        <div className="glass-card p-8 border-white/5">
          <Phone className="text-primary mb-4" />
          <h4 className="text-xs font-bold uppercase tracking-widest mb-2">Helpline Number</h4>
          <p className="text-lg font-bold">+91 {import.meta.env.VITE_ADMIN_PHONE || 'XXXXX XXXXX'}
        </p>
        </div>
      </div>
      <div className="lg:col-span-2 glass-card p-12 bg-primary/5 relative overflow-hidden">
        <div className="absolute top-0 right-0 w-32 h-32 bg-primary/10 rounded-full blur-[60px]" />
        <h4 className="text-xl font-bold mb-8 uppercase tracking-widest text-primary flex items-center gap-3">
          <MessageSquare className="w-5 h-5" /> Inquiry Chat Box
        </h4>
        <div className="space-y-6">
          <div className="grid md:grid-cols-2 gap-6">
            <div>
              <label className="label-bold mb-2 block">Full Name</label>
              <input
                value={formData.name}
                onChange={e => setFormData({ ...formData, name: e.target.value })}
                className="w-full bg-white/5 border border-white/10 px-6 py-4 rounded-2xl text-sm outline-none focus:border-primary transition-colors"
                placeholder="Your Name"
              />
            </div>
            <div>
              <label className="label-bold mb-2 block">Mobile No</label>
              <input
                value={formData.phone}
                onChange={e => setFormData({ ...formData, phone: e.target.value })}
                className="w-full bg-white/5 border border-white/10 px-6 py-4 rounded-2xl text-sm outline-none focus:border-primary transition-colors"
                placeholder="+91 XXXX..."
              />
            </div>
          </div>
          <div>
            <label className="label-bold mb-2 block">Describe your problem/request</label>
            <textarea
              rows={4}
              value={formData.query}
              onChange={e => setFormData({ ...formData, query: e.target.value })}
              className="w-full bg-white/5 border border-white/10 px-6 py-4 rounded-2xl text-sm outline-none focus:border-primary transition-colors resize-none"
              placeholder="How can we help you today?"
            />
          </div>
        </div>
        <div className="p-4 bg-primary/10 border border-primary/20 rounded-xl text-sm text-

```

```

primary-foreground">
    <p className="font-bold mb-1">AI Assistant Response:</p>
    <p>{aiResponse}</p>
</div>
    )}
    <Button
        variant="primary"
        className="w-full uppercase tracking-[0.2em] text-xs py-5"
        onClick={handleSubmit}
        disabled={isSubmitting || !formData.query}
    >
        {isSubmitting ? 'Processing...' : 'Send Inquiry to Coordinator'}
    </Button>
</div>
</div>
</div>
</section>
);
};
const AIBotChat = ({ isOpen, onClose, isPremium, sessionId, onLog }: any) => {
    const [messages, setMessages] = useState<any[]>([]);
    const [input, setInput] = useState('');
    const [isTyping, setIsTyping] = useState(false);

    useEffect(() => {
        if (isOpen && messages.length === 0 && isPremium) {
            setMessages([
                { role: 'model', text: "Hello! I am your CAREVIA Elite Assistant. As a premium member, how can I assist you with your care requirements today?" }
            ]);
        }
    }, [isOpen, isPremium]);

    const handleSend = async () => {
        if (!input.trim() || isTyping) return;

        const userMsg = input.trim();
        setInput('');
        setMessages(prev => [...prev, { role: 'user', text: userMsg }]);
        setIsTyping(true);

        // Initial Log
        onLog?.({
            action: `AI Bot: User Prompt Received`,
            admin: "AI BOT",
            time: new Date().toISOString().replace('T', ' ').substring(0, 16),
            type: 'ai',
            details: `User Prompt: ${userMsg}`,
            sessionId: sessionId,
            userId: "Client_Anonymous",
            status: 'PROCESSING'
        });

        try {
            // internal AI processing step log
            onLog?.({
                action: `AI Bot: System Initialization`,
                admin: "AI BOT",
                time: new Date().toISOString().replace('T', ' ').substring(0, 16),
                type: 'ai',
                details: `Config: Model="gemini-2.5-flash", Context="CAREVIA_Elite", Privacy="Premium_Tier".`,
                sessionId: sessionId,
                userId: "Client_Anonymous",
                status: 'INTERNAL'
            });

            const ai = new GoogleGenAI({ apiKey: process.env.GEMINI_API_KEY });
            const response = await ai.models.generateContent({
                model: "gemini-2.5-flash",
                contents: [
                    { role: 'user', parts: [{ text: `Context: You are the CAREVIA AI Bot, a concierge health assistant for a premium healthcare service. Be sophisticated, professional, and helpful. Only answer questions related to healthcare, caregiving, domestic help, or CAREVIA services. User Message:

```

```

    ${userMsg}` `]] }
    ],
    config: {
        systemInstruction: "You are the CAREVIA Elite Assistant. Professionally guide users through
healthcare and concierge services provided by CAREVIA."
    }
    });

    const aiResponseText = response.text || "I apologize, I didn't quite catch that. Could you
rephrase?";
    setMessages(prev => [...prev, { role: 'model', text: aiResponseText }]);

    // Success Log
    onLog?({
        action: `AI Bot: Response Dispatched`,
        admin: "AI BOT",
        time: new Date().toISOString().replace('T', ' ').substring(0, 16),
        type: 'ai',
        details: `Response: ${aiResponseText}`,
        sessionId: sessionId,
        userId: "Client_Anonymous",
        status: 'SUCCESS'
    });
} catch (error) {
    const errorMsg = error instanceof Error ? error.message : "Unknown connectivity disruption";
    setMessages(prev => [...prev, { role: 'model', text: `I'm having trouble connecting to the nexus
right now. Details: ${errorMsg}` }]);

    // Error Log
    onLog?({
        action: `AI Bot: Critical Failure`,
        admin: "AI BOT",
        time: new Date().toISOString().replace('T', ' ').substring(0, 16),
        type: 'ai',
        details: `Fault: ${errorMsg}`,
        sessionId: sessionId,
        userId: "Client_Anonymous",
        status: 'ERROR'
    });
} finally {
    setIsTyping(false);
}
};

if (!isOpen) return null;

return (
    <div className="fixed bottom-24 right-8 z-[160] w-[400px] max-h-[600px] flex flex-col font-sans">
        <motion.div
            initial={{ opacity: 0, scale: 0.95, y: 20 }}
            animate={{ opacity: 1, scale: 1, y: 0 }}
            className="glass-card flex-1 flex flex-col overflow-hidden border-primary/20 shadow-2xl"
        >
            <div className="bg-primary/10 p-6 border-b border-white/5 flex justify-between items-center bg-
gradient-to-r from-primary/20 to-transparent">
                <div className="flex items-center gap-3">
                    <div className="w-10 h-10 bg-primary rounded-xl flex items-center justify-center text-
surface shadow-lg shadow-primary/20">
                        <Bot className="w-6 h-6" />
                    </div>
                    <div>
                        <h3 className="text-sm font-bold uppercase tracking-widest text-primary">Elite
Assistant</h3>
                        <div className="flex items-center gap-1.5">
                            <div className="w-1.5 h-1.5 bg-green-500 rounded-full animate-pulse" />
                            <span className="text-[10px] text-white/40 uppercase font-black tracking-
widest">Active Member Hub</span>
                        </div>
                    </div>
                    <button onClick={onClose} className="p-2 hover:bg-white/10 rounded-full transition-colors

```

```

text-white/50"><X /></button>
    </div>

    {!isPremium ? (
      <div className="flex-1 p-10 flex flex-col items-center justify-center text-center bg-
black/40">
        <div className="w-20 h-20 border border-white/10 rounded-3xl flex items-center justify-
center mb-6 text-white/20">
          <Lock className="w-10 h-10" />
        </div>
        <h4 className="text-xl font-bold mb-3 uppercase tracking-tight">Access Restricted</h4>
        <p className="text-sm text-white/40 mb-8 leading-relaxed">
          The Private AI Concierge is an exclusive benefit for <span className="text-primary font-
bold italic">Premium Subscribers.</span>
        </p>
        <Button variant="primary" className="w-full text-[10px] py-4" onClick={() => {
          onClose();
          document.getElementById('pricing')?.scrollIntoView({ behavior: 'smooth' });
        }}>
          Unlock Premium Now
        </Button>
      </div>
    ) : (
      <>
        <div className="flex-1 overflow-y-auto p-6 space-y-4 custom-scrollbar bg-black/20">
          {messages.map((m, i) => (
            <div key={i} className={`flex ${m.role === 'user' ? 'justify-end' : 'justify-start'}`}>
              >
                <div className={`max-w-[85%] p-4 rounded-2xl text-sm ${m.role === 'user' ? 'bg-
primary/20 border border-primary/20 text-white rounded-br-none' : 'bg-white/5 border border-white/10
text-white/70 rounded-bl-none'}`}>
                  {m.text}
                </div>
              </div>
            </div>
          ))}
          {isTyping && (
            <div className="flex justify-start">
              <div className="bg-white/5 border border-white/10 p-4 rounded-2xl rounded-bl-none">
                <Loader2 className="w-4 h-4 text-primary animate-spin" />
              </div>
            </div>
          )}
        </div>

        <div className="p-4 border-t border-white/5 bg-surface/50">
          <div className="relative flex items-center">
            <input
              value={input}
              onChange={(e) => setInput(e.target.value)}
              onKeyDown={(e) => e.key === 'Enter' && handleSend()}
              className="w-full bg-white/5 border border-white/10 px-6 py-4 rounded-2xl text-sm
outline-none focus:border-primary transition-colors pr-14"
              placeholder="Consult with AI Assistant..."
            />
            <button
              onClick={handleSend}
              className="absolute right-2 p-3 bg-primary text-surface rounded-xl hover:bg-
primary-hover transition-all active:scale-95"
            >
              <Send className="w-4 h-4" />
            </button>
          </div>
        </div>
      </>
    )}
  </motion.div>
</div>
);
};

const ServiceCatalog = ({ activeTab, setActiveTab, onBook, userLocation, setUserLocation }:

```

```

{ activeTab: string, setActiveTab: (id: string) => void, onBook: (name: string) => void, userLocation:
string, setUserLocation: (loc: string) => void }) => {
  const providers = MOCK_PROVIDERS.filter(p => p.category === activeTab && p.location ===
userLocation);
  const activeCategory = CATEGORIES.find(c => c.id === activeTab);

  return (
    <section id="services" className="py-24 bg-surface/50 monolith-grid font-sans scroll-mt-24">
      <div className="max-w-7xl mx-auto px-6">
        <div className="flex flex-col md:flex-row justify-between items-start md:items-center mb-16
gap-8">
          <div>
            <SectionHeading
              title="specialized services for every life"
            />
            <p className="text-xs text-white/40 uppercase tracking-widest mt-4 max-w-xl leading-
relaxed">
              {activeCategory?.description}
            </p>
          </div>

          <div className="flex items-center gap-4 bg-white/5 p-4 rounded-3xl border border-white/10 w-
full md:w-auto self-start">
            <MapPin className="text-primary w-5 h-5 flex-shrink-0" />
            <div className="flex flex-col">
              <span className="text-[8px] font-bold text-white/30 uppercase tracking-
[0.2em]">Service Region</span>
              <select
                value={userLocation}
                onChange={(e) => setUserLocation(e.target.value)}
                className="bg-transparent text-xs font-bold text-white outline-none cursor-pointer
pr-4"
              >
                {LOCATIONS.map(loc => <option key={loc} value={loc} className="bg-surface">{loc}</
option>)}
              </select>
            </div>
          </div>
        </div>

        <div className="flex overflow-x-auto pb-4 gap-4 mb-12 hide-scrollbar snap-x snap-mandatory
lg:flex-wrap">
          {CATEGORIES.map(cat => (
            <button
              key={cat.id}
              onClick={() => setActiveTab(cat.id)}
              className={`flex-shrink-0 snap-start flex items-center gap-3 px-6 py-4 rounded-2xl
transition-all ${activeTab === cat.id ? 'bg-primary text-surface font-black shadow-
[0_0_20px_rgba(212,175,55,0.3)]' : 'bg-white/10 text-white/80 hover:bg-white/20'}`}
            >
              {cat.icon}
              <span className="uppercase tracking-widest text-xs font-bold">{cat.name}</span>
              {cat.id !== 'elderly' && cat.id !== 'helpers' && !cat.isFull && <span className="text-
[8px] bg-white/10 px-2 py-0.5 rounded-full ml-2 opacity-50">Coming Soon</span>}
            </button>
          ))}
        </div>

        <div className="glass-card min-h-[400px]">
          <div className="grid md:grid-cols-2 lg:grid-cols-3 gap-12">
            {activeCategory?.sections?.map((section, idx) => (
              <div key={idx}>
                <h5 className="text-primary font-black uppercase tracking-[0.2em] text-[10px] mb-4
pb-2 border-b border-primary/20">{section.name}</h5>
                <ul className="space-y-4">
                  {section.items.map((item, i) => (
                    <li key={i} className="flex items-center justify-between group">
                      <div className="flex items-center gap-3 text-sm text-white/60 group-hover:text-
white transition-colors">
                        <div className="w-1.5 h-1.5 bg-primary rounded-full shadow-
[0_0_8px_rgba(45,212,191,0.5)]" />

```

```

        {item}
      </div>
      <button
        onClick={() => onBook(item)}
        className="px-3 py-1.5 bg-primary/10 hover:bg-primary text-primary hover:text-
surface text-[9px] font-bold uppercase tracking-widest rounded-lg transition-all opacity-0 group-
hover:opacity-100"
      >
        Book
      </button>
    </li>
  </ul>
</div>
)}}
<div className="bg-primary/5 rounded-3xl p-8 flex flex-col justify-between border border-
primary/10">
  <div>
    <h5 className="text-[10px] font-black uppercase tracking-widest text-primary
mb-6">Service Tiers</h5>
    <div className="space-y-6 mb-8">
      {activeCategory?.pricing?.map((p: any, i: number) => (
        <div key={i} className="p-4 bg-white/5 rounded-2xl border border-white/5
hover:border-primary/20 transition-all">
          <div className="flex justify-between items-center mb-2">
            <span className="text-[10px] font-black uppercase tracking-widest text-
white/80">{p.tier}</span>
            <span className="text-[11px] font-bold text-primary">{p.price}</span>
          </div>
          <div className="flex flex-wrap gap-2">
            {p.features.map((f: string, j: number) => (
              <span key={j} className="text-[8px] bg-white/5 text-white/40 px-2
py-0.5 rounded tracking-tighter">{f}</span>
            ))}
          </div>
        </div>
      ))}
    </div>
  </div>
  <Button
    onClick={() => onBook(activeCategory?.name || 'Service')}
    variant="primary"
    className="w-full text-xs"
  >
    Request Consultation
  </Button>
</div>
</div>
</div>

<div className="mt-20">
  <div className="flex items-center justify-between mb-10">
    <div className="flex items-center gap-4">
      <div className="w-10 h-10 bg-primary/20 rounded-xl flex items-center justify-center
text-primary">
        <ShieldCheck className="w-5 h-5" />
      </div>
      <div>
        <h4 className="text-xs font-black uppercase tracking-[0.3em] text-primary">Vetted
Professionals</h4>
        <p className="text-[10px] text-white/30 uppercase font-bold tracking-widest
mt-1">Direct from {userLocation}</p>
      </div>
    </div>
    <div className="h-px flex-1 mx-8 bg-white/5 hidden md:block" />
    <div className="text-[10px] font-black uppercase text-white/20 tracking-widest">
      {providers.length} Verified Partner{providers.length !== 1 ? 's' : ''} Online
    </div>
  </div>

  <div className="grid md:grid-cols-2 lg:grid-cols-3 gap-8">

```



```

{providers.length > 0 ? providers.map(p => (
  <motion.div
    key={p.id}
    whileHover={{ y: -8, scale: 1.02 }}
    className="glass-card p-0 flex flex-col border border-white/5 relative group
transition-all hover:border-primary/30 overflow-hidden"
  >
    <div className="relative h-48 bg-gradient-to-br from-primary/10 to-transparent">
      <img
        src={(p as any).avatar}
        alt={p.name}
        className="w-full h-full object-cover mix-blend-overlay opacity-60 grayscale
group-hover:grayscale-0 group-hover:opacity-100 transition-all duration-700"
      />
      <div className="absolute top-4 right-4 flex flex-col items-end gap-2">
        <div className="flex items-center gap-1 bg-surface/90 backdrop-blur-md px-3
py-1.5 rounded-full border border-white/10">
          <Star className="w-3 h-3 text-primary fill-primary" />
          <span className="text-[11px] font-black text-white">{p.rating}</span>
        </div>
      </div>
      <div className="absolute bottom-4 left-4">
        <span className="text-[8px] font-black text-white uppercase tracking-widest
bg-primary px-3 py-1 rounded-full shadow-2xl">Verified Expert</span>
      </div>
    </div>

    <div className="p-8">
      <div className="mb-6">
        <h5 className="text-lg font-bold group-hover:text-primary transition-
colors">{p.name}</h5>
        <p className="text-[10px] text-white/30 italic mt-1 line-clamp-2">{(p as
any).bio}</p>
      </div>

      <div className="space-y-4">
        <div className="flex items-center gap-2">
          <GraduationCap className="w-3 h-3 text-primary" />
          <p className="text-[9px] text-white/50 uppercase tracking-widest font-
black">{p.education}</p>
        </div>
        <div className="flex flex-wrap gap-2">
          {(p as any).specialties?.map((s: string, i: number) => (
            <span key={i} className="text-[8px] bg-primary/10 text-primary px-2
py-0.5 rounded font-bold uppercase tracking-normal">#{s}</span>
          ))}
        </div>
      </div>

      <div className="flex items-center justify-between mt-8 pt-6 border-t border-
white/5">
        <div className="flex flex-col">
          <span className="text-[8px] font-bold text-white/20 uppercase tracking-
widest mb-1">Experience</span>
          <span className="text-[10px] font-black text-white/60
uppercase">{p.experience}</span>
        </div>
        <Button variant="outline" className="px-5 py-2.5 text-[9px] uppercase
tracking-widest border-primary/40 text-primary hover:bg-primary hover:text-surface" onClick={() =>
onBook(p.name)}>Hire Now</Button>
      </div>
    </motion.div>
  )) : (
    <div className="col-span-full py-20 text-center glass-card border-dashed border-
white/10 bg-white/[0.01]">
      <div className="w-16 h-16 bg-white/5 rounded-full flex items-center justify-center
mx-auto mb-6">
        <MapPin className="w-8 h-8 text-white/20" />
      </div>
      <h5 className="text-white/50 font-bold uppercase tracking-widest mb-2">Expansion in

```

```

Progress</h5>
        <p className="text-xs text-white/20 italic max-w-sm mx-auto">We are currently
vetting elite partners in {userLocation} for this category. Check back shortly or explore our AI
assistant.</p>
    </div>
  })
</div>
</div>
</div>
</section>
);
};

const LegalModal = ({ isOpen, onClose }: any) => {
  if (!isOpen) return null;
  return (
    <div className="fixed inset-0 z-[250] flex items-center justify-center p-6 font-sans">
      <div className="absolute inset-0 bg-black/80 backdrop-blur-md" onClick={onClose} />
      <div className="glass-card w-full max-w-4xl max-h-[80vh] overflow-y-auto relative z-10 p-12">
        <div className="flex justify-between items-center mb-8">
          <SectionHeading sub="Compliance" title="Legal Terms & Policy" desc="Last Updated: April
2025" />
          <button onClick={onClose} className="p-4 bg-white/5 rounded-full hover:bg-white/10"><X /></
button>
        </div>
        <div className="space-y-8 text-white/60 text-sm leading-loose font-light">
          <section>
            <h4 className="text-white font-bold mb-4 uppercase tracking-widest">1. Professional Care
Commitment</h4>
            <p>CAREVIA Group acts as a premium concierge management platform. We vetting each service
provider with a rigorous 10-step protocol, including background checks, credential verification, and
interpersonal skills assessment. However, clinical liability resides with the individual medical
professionals or registered agencies.</p>
          </section>
          <section>
            <h4 className="text-white font-bold mb-4 uppercase tracking-widest">2. Privacy Protocol
(GDPR/HIPAA Compliance)</h4>
            <p>Your data is managed with Tier 1 encryption. Personal identifiable information (PII) is
only shared with assigned care coordinators and service providers during the active service window.</p>
          </section>
          <section>
            <h4 className="text-white font-bold mb-4 uppercase tracking-widest">3. Billing & Refunds</
h4>
            <p>Premium subscriptions are billed monthly/annually. Cancellations take effect at the end
of the billing cycle. Priority refunds are processed within 2 hours to the CARVIA Wallet.</p>
          </section>
          <section>
            <h4 className="text-white font-bold mb-4 uppercase tracking-widest">4. SOS & Emergency
Response</h4>
            <p>The SOS feature is a secondary alert system. Users are advised to contact local
emergency services (102/100) directly for life-critical situations.</p>
          </section>
        </div>
      </div>
    </div>
  );
}

const ActiveServiceTracker = ({ bookings = [] }: { bookings?: any[] }) => {
  const activeBooking = bookings.find(b => b.status === "CONFIRMED" || b.status === "IN_PROGRESS") ||
bookings[0];

  if (!activeBooking) return null;

  return (
    <motion.div
      initial={{ opacity: 0, x: 50 }}
      animate={{ opacity: 1, x: 0 }}
      className="glass p-6 rounded-3xl border-primary/20 bg-primary/5 flex flex-col sm:flex-row items-
center gap-6"
    >

```

```

    <div className="flex items-center gap-6 w-full sm:w-auto">
      <div className="w-12 h-12 bg-primary/20 rounded-2xl flex items-center justify-center text-
primary flex-shrink-0">
        <Clock className="animate-spin-slow" />
      </div>
      <div className="max-w-[150px]">
        <p className="text-[10px] font-bold text-primary uppercase tracking-[0.2em]
truncate">Active: {activeBooking.service}</p>
        <p className="text-[10px] font-bold opacity-60">SP: {activeBooking.providerName ||
'Assigning...'}</p>
      </div>
    </div>
    <div className="w-full sm:ml-auto flex items-center justify-between sm:justify-end gap-4 bg-
surface/50 p-3 rounded-2xl border border-white/5">
      <div className="flex flex-col">
        <span className="text-[8px] font-bold text-white/30 uppercase tracking-widest">Auth Token</
span>
        <span className="text-sm font-mono font-bold text-primary tracking-
widest">{activeBooking.otp || '****'}</span>
      </div>
      <div className="w-px h-8 bg-white/10" />
      <div className="flex flex-col">
        <span className="text-[8px] font-bold text-white/30 uppercase tracking-widest">Status</
span>
        <span className="text-[10px] font-black uppercase text-white/60 tracking-
tighter">{activeBooking.status}</span>
      </div>
      <Info className="w-4 h-4 text-white/20" />
    </div>
  </motion.div>
);
};

```

```

const ProviderDashboard = ({ providerData, onUpdateProvider, onClose, bookings = [], onAction,
isSpectator = false, masterOtp, onLogout }: any) => {
  const [activeTab, setActiveTab] = useState('profile');
  const [isUploading, setIsUploading] = useState(false);
  const [notification, setNotification] = useState<string | null>(null);
  const [otpInputs, setOtpInputs] = useState<Record<string, string>>({});

  const handleAction = (bookingId: string, action: 'ACCEPT' | 'DECLINE' | 'START_SERVICE' |
'END_SERVICE') => {
    if (action === 'START_SERVICE' || action === 'END_SERVICE') {
      const book = bookings.find((b: any) => b.id === bookingId);
      const enteredOtp = otpInputs[bookingId];
      const isValid = (enteredOtp === (book as any)?.otp || masterOtp === enteredOtp) && enteredOtp !
== undefined;

      if (!isValid && !isSpectator) {
        setNotification('ERR: INVALID AUTHENTICATION TOKEN (OTP)');
        setTimeout(() => setNotification(null), 3000);
        return;
      }
    }

    onAction(bookingId, action);

    const msg = action === 'ACCEPT' ? 'Accepted' : action === 'DECLINE' ? 'Declined' : action ===
'START_SERVICE' ? 'Started' : 'Completed';
    setNotification(`Service ${bookingId} ${msg}.`);
    setTimeout(() => setNotification(null), 3000);
  };

  const handleUpload = () => {
    setIsUploading(true);
    setTimeout(() => {
      setIsUploading(false);
      onUpdateProvider({ ...providerData, isDocsUploaded: true });
    }, 2000);
  };
};

```

```

return (
  <div className="fixed inset-0 z-[300] bg-surface flex flex-col font-sans overflow-hidden">
    { /* Header */ }
    <div className={`border-b border-white/5 p-6 flex justify-between items-center ${isSpectator ?
'bg-red-500/10 border-red-500/20' : 'bg-card'}}`>
      <div className="flex items-center gap-4">
        {isSpectator ? <Eye className="text-red-500 animate-pulse" /> : <BriefcaseMedical
className="text-primary" />}
        <div>
          <h2 className="text-xl font-bold uppercase tracking-tight">{isSpectator ? `Shadowing:
${providerData.name}` : 'Partner Dashboard'}</h2>
          <div className="flex items-center gap-2">
            <span className="text-[8px] font-black uppercase text-muted tracking-widest">ID:
{providerData?.spId || 'SP-NEW-001'}</span>
            {isSpectator && (
              <span className="text-[8px] font-black uppercase bg-red-500 text-white px-3 py-1
rounded-full animate-pulse tracking-widest ml-2">Live Surveillance</span>
            )}
            {providerData?.isVerified && !isSpectator && (
              <span className="flex items-center gap-1 text-[8px] font-black uppercase text-
primary tracking-widest bg-primary/10 px-2 py-0.5 rounded-full">
                <ShieldCheck className="w-2.5 h-2.5" /> Verified
              </span>
            )}
          </div>
        </div>
      </div>
      <div className="flex items-center gap-4">
        <button onClick={onClose} className="p-2 hover:bg-white/10 rounded-full text-muted"><X /></
button>
      </div>
    </div>

    <div className="flex flex-1 overflow-hidden">
      { /* Sidebar */ }
      <div className="w-64 border-r border-white/5 p-6 flex flex-col gap-2 bg-card/40">
        <button
          onClick={() => setActiveTab('profile')}
          className={`flex items-center gap-3 w-full p-3 rounded-xl text-xs font-bold uppercase
tracking-widest transition-all ${activeTab === 'profile' ? 'bg-primary/10 text-primary' : 'hover:bg-
white/5 text-muted'}}`>
          >
          <User className="w-4 h-4" /> My Profile
        </button>
        <button
          onClick={() => setActiveTab('bookings')}
          className={`flex items-center gap-3 w-full p-3 rounded-xl text-xs font-bold uppercase
tracking-widest transition-all ${activeTab === 'bookings' ? 'bg-primary/10 text-primary' : 'hover:bg-
white/5 text-muted'}}`>
          >
          <Calendar className="w-4 h-4" /> Bookings {bookings.filter(b => b.status ===
"PENDING").length > 0 && <span className="ml-auto w-2 h-2 bg-primary rounded-full animate-pulse" />}
        </button>
        <button
          onClick={() => setActiveTab('earnings')}
          className={`flex items-center gap-3 w-full p-3 rounded-xl text-xs font-bold uppercase
tracking-widest transition-all ${activeTab === 'earnings' ? 'bg-primary/10 text-primary' : 'hover:bg-
white/5 text-muted'}}`>
          >
          <Wallet className="w-4 h-4" /> Earnings
        </button>

        <div className="mt-auto pt-6 border-t border-white/5">
          <button onClick={onLogout || onClose} className="flex items-center gap-3 w-full p-3 text-
red-500/50 hover:text-red-500 text-xs font-bold uppercase tracking-widest">
            <LogOut className="w-4 h-4" /> Logout
          </button>
        </div>
      </div>

      { /* Content */ }

```

```

<div className="flex-1 p-10 overflow-y-auto bg-black/20">
  {notification && (
    <motion.div initial={{ opacity: 0, y: -20 }} animate={{ opacity: 1, y: 0 }}
    className="mb-8 p-4 bg-primary/10 border border-primary/20 rounded-2xl text-xs font-bold text-primary
    uppercase tracking-widest">
      {notification}
    </motion.div>
  )}

  {activeTab === 'profile' && (
    <div className="max-w-4xl space-y-12 animate-in fade-in slide-in-from-bottom-4
    duration-500">
      <SectionHeading title="Provider Identity" sub="Credentials & Verification" />

      <div className="grid grid-cols-1 md:grid-cols-2 gap-8">
        <div className="glass-card space-y-6">
          <div className="flex items-center gap-4">
            <div className="w-16 h-16 rounded-2xl bg-white/5 border border-white/10 flex
            items-center justify-center">
              <Upload className="w-6 h-6 text-muted" />
            </div>
            <div>
              <h4 className="text-sm font-bold uppercase tracking-widest">Documents
              Status</h4>

              <p className="text-[10px] text-muted uppercase mt-1">
                {providerData?.isDocsUploaded ? 'All files received' : 'Action
              Required: Upload ID'}
              </p>
            </div>
          </div>

          {!providerData?.isDocsUploaded ? (
            <div className="p-4 bg-primary/5 border border-primary/20 rounded-2xl">
              <p className="text-[10px] text-primary/80 uppercase font-black tracking-
              widest mb-4">Verification Steps</p>
              <ul className="space-y-3 mb-6">
                <li className="text-[10px] text-white flex items-center gap-2
                opacity-60"><Info className="w-3 h-3" /> Aadhar Card / PAN Card</li>
                <li className="text-[10px] text-white flex items-center gap-2
                opacity-60"><Info className="w-3 h-3" /> Professional Certificate</li>
                <li className="text-[10px] text-white flex items-center gap-2
                opacity-60"><Info className="w-3 h-3" /> Background Check Consent</li>
              </ul>
              <Button
                onClick={handleUpload}
                disabled={isUploading}
                className="w-full text-[10px] py-4 bg-primary text-surface"
              >
                {isUploading ? <Loader2 className="animate-spin w-4 h-4" /> : 'Begin
              Secure Upload'}
              </Button>
            </div>
          ) : (
            <div className="p-6 bg-green-500/5 border border-green-500/20 rounded-2xl">
              <div className="flex items-center gap-3 text-green-500 mb-2">
                <CheckCircle2 className="w-5 h-5" />
                <span className="text-xs font-black uppercase tracking-widest">Files
              Synchronized</span>
              </div>
              <p className="text-[10px] text-white/40 uppercase tracking-widest font-
              bold">Verification in progress. Usually takes 24-48 hours.</p>
            </div>
          )}
        </div>

        <div className="glass-card">
          <h4 className="text-[10px] font-black uppercase tracking-[0.2em] mb-6 text-
          muted">Field Assignments</h4>
          <div className="space-y-4">
            {[ 'Elderly Care', 'Nursing', 'Medical Assistant' ].map(tag => (
              <div key={tag} className="flex items-center justify-between p-4 bg-white/5

```

```

border border-white/10 rounded-2xl">
    <span className="text-xs font-bold">{tag}</span>
    <div className="w-2 h-2 bg-primary rounded-full" />
  </div>
  )}}
</div>
</div>
</div>
</div>
))}

{activeTab === 'bookings' && (
  <div className="space-y-10 animate-in fade-in slide-in-from-bottom-4 duration-500">
    <div className="flex items-center justify-between">
      <SectionHeading title="Active Requests" sub="Job Pipeline" />
      <div className="flex gap-4">
        <div className="px-6 py-2 bg-white/5 border border-white/10 rounded-xl text-
[10px] font-black text-muted uppercase tracking-widest">
          SP ID: {providerData?.spId || 'SP-001'}
        </div>
      </div>
    </div>

    <div className="grid grid-cols-1 gap-6">
      {bookings.map(book => (
        <div key={book.id} className="glass-card flex flex-col md:flex-row gap-8 items-
start md:items-center">
          <div className="flex-1 space-y-4">
            <div className="flex items-center gap-3">
              <div className="px-3 py-1 bg-primary/10 border border-primary/20 rounded-
full text-[8px] font-black text-primary uppercase tracking-widest">
                {book.status}
              </div>
              <span className="text-muted text-[10px] font-bold">#{book.id}</span>
            </div>
            <h3 className="text-2xl font-bold uppercase tracking-tight">{book.service}</
h3>
            <div className="flex flex-wrap gap-6 text-[10px] font-bold uppercase
tracking-widest text-muted">
              <div className="flex items-center gap-2"><User className="w-3 h-3" />
{book.customer}</div>
              <div className="flex items-center gap-2"><MapPin className="w-3 h-3" />
{book.location}</div>
              <div className="flex items-center gap-2"><Calendar className="w-3 h-3" />
> {book.date}</div>
              <div className="flex items-center gap-2"><Clock className="w-3 h-3" />
{book.time}</div>
            </div>
          </div>

          {book.status === 'PENDING' && (
            <div className="flex gap-4 w-full md:w-auto">
              <Button disabled={isSpectator} variant="outline" className="flex-1
md:w-32 py-4 text-[10px]" onClick={() => handleAction(book.id, 'DECLINE')}>Decline</Button>
              <Button disabled={isSpectator} variant="primary" className="flex-1
md:w-32 py-4 text-[10px]" onClick={() => handleAction(book.id, 'ACCEPT')}>Accept</Button>
            </div>
          )}

          {book.status === 'ACCEPTED_BY_SP' && (
            <div className="p-4 bg-primary/10 border border-primary/2 tracking-widest
rounded-2xl text-[9px] font-black text-primary uppercase">
              Waiting for Admin Confirmation...
            </div>
          )}

          {book.status === 'CONFIRMED' && (
            <div className="space-y-4 w-full md:w-auto">
              <div className="p-4 bg-primary/10 border border-primary/20 rounded-2xl
flex flex-col gap-2">
                <span className="text-[9px] text-primary uppercase font-

```

```

black">Incoming OTP Check</span>
      <input
        disabled={isSpectator}
        type="text"
        value={otpInputs[book.id] || ''}
        onChange={(e) => setOtpInputs(prev => ({ ...prev, [book.id]:
e.target.value })))}
        placeholder="ENTER START OTP"
        className="bg-white/5 border border-white/10 px-4 py-2 rounded-lg
text-xs font-mono tracking-widest w-40 outline-none focus:border-primary"
      />
    </div>
    <Button disabled={isSpectator} variant="primary" className="w-full text-
[10px] py-4" onClick={() => handleAction(book.id, 'START_SERVICE')}>
      Start Service
    </Button>
  </div>
)}

{book.status === 'IN_PROGRESS' && (
  <div className="space-y-4 w-full md:w-auto">
    <div className="p-4 border border-emerald-500/20 bg-emerald-500/5
rounded-2xl flex flex-col gap-2">
      <span className="text-[9px] text-emerald-500 uppercase font-
black">Service Duration</span>
      <span className="text-xl font-mono font-bold">02:44:12</span>
      <input
        disabled={isSpectator}
        type="text"
        value={otpInputs[book.id] || ''}
        onChange={(e) => setOtpInputs(prev => ({ ...prev, [book.id]:
e.target.value })))}
        placeholder="COMPLETION OTP"
        className="bg-white/5 border border-white/10 px-4 py-2 rounded-lg
text-xs font-mono tracking-widest w-40 outline-none focus:border-emerald-500 mt-2"
      />
    </div>
    <Button disabled={isSpectator} variant="outline" className="w-full text-
[10px] py-4 border-emerald-500/50 text-emerald-500 hover:bg-emerald-500 hover:text-surface"
onClick={() => handleAction(book.id, 'END_SERVICE')}>
      Complete Service
    </Button>
  </div>
)}
</div>
)}}
</div>
</div>
</div>
)}
</div>
</div>
</div>
);
};

const AdminDashboard = ({
  onClose,
  actions: propActions = [],
  bankDetails,
  setBankDetails,
  sharingLevel,
  setSharingLevel,
  teamAccess,
  setTeamAccess,
  bookings = [],
  financialAlerts = [],
  onConfirmBooking,
  onAction,
  onSpectateProvider,
  masterOtp,
  setMasterOtp,

```

```

    onLogout
  }: any) => {
    const [isLocked, setIsLocked] = useState(true);
    const [secretCode, setSecretCode] = useState('');
    const [step, setStep] = useState(1); // 1: Credentials, 2: OTP
    const [adminNumber, setAdminNumber] = useState('');
    const [pass, setPass] = useState('');
    const [otp, setOtp] = useState('');
    const [activeTab, setActiveTab] = useState('overview');

    // Filtering & Sorting State
    const [filterAdmin, setFilterAdmin] = useState('All');
    const [filterType, setFilterType] = useState('All');
    const [startDate, setStartDate] = useState('');
    const [endDate, setEndDate] = useState('');
    const [sortOrder, setSortOrder] = useState('desc');

    // Bookings Specific State
    const [bookingSearch, setBookingSearch] = useState('');
    const [bookingStatusFilter, setBookingStatusFilter] = useState('All');
    const [selectedBookings, setSelectedBookings] = useState<string[]>([]);
    const [detailBooking, setDetailBooking] = useState<any>(null);

    const [inquiries, setInquiries] = useState<any[]>([]);
    const [inquiriesLoading, setInquiriesLoading] = useState(false);

    useEffect(() => {
      if (activeTab === 'inquiries') {
        setInquiriesLoading(true);
        fetch('/api/inquiries')
          .then(res => res.json())
          .then(data => {
            if (Array.isArray(data)) setInquiries(data);
            setInquiriesLoading(false);
          })
          .catch(err => {
            console.error("Error fetching inquiries:", err);
            setInquiriesLoading(false);
          });
      }
    }, [activeTab]);

    const sosAlerts = propActions.filter((a: any) => a.category === 'SOS');
    const securityAlerts = sosAlerts;

    const [searchQuery, setSearchQuery] = useState('');
    const [isAdminAuthLoading, setIsAdminAuthLoading] = useState(false);

    const teamMembers = [
      { id: 1, name: "Ashvin G.", role: "Global Admin", email: "ashvin@carevia.app", level: "Full" },
      { id: 2, name: "Sarah K.", role: "Ops Lead", email: "sarah@carevia.app", level: "Standard" },
      { id: 3, name: "Michael R.", role: "Support Staff", email: "michael@carevia.app", level: "Read-Only" },
    ];

    const admins = ['All', ...new Set(propActions.map(a => a.admin))];
    const types = ['All', 'Admin', 'AI BOT', 'System'];

    const filteredAndSortedActions = propActions
      .filter(act => {
        const matchAdmin = filterAdmin === 'All' || act.admin === filterAdmin;
        const matchType = filterType === 'All' || (act.type?.toUpperCase() === filterType.toUpperCase()) ||
        (filterType === 'Admin' && (!act.type || act.type === 'admin'));
        const matchSearch = !searchQuery ||
        act.action.toLowerCase().includes(searchQuery.toLowerCase()) ||
        (act.details && act.details.toLowerCase().includes(searchQuery.toLowerCase())) ||
        (act.sessionId && act.sessionId.toLowerCase().includes(searchQuery.toLowerCase()));

        const actDate = new Date(act.time);
        const matchStart = !startDate || actDate >= new Date(startDate);
        const matchEnd = !endDate || actDate <= new Date(endDate + 'T23:59:59');
      })
  }
}

```



```

    return matchAdmin && matchType && matchSearch && matchStart && matchEnd;
  })
  .sort((a, b) => {
    const timeA = new Date(a.time).getTime();
    const timeB = new Date(b.time).getTime();
    return sortOrder === 'desc' ? timeB - timeA : timeA - timeB;
  });

const handleVerify = () => {
  if (secretCode === 'ADMIN_CAREVIA' || secretCode === import.meta.env.VITE_ADMIN_SECRET) {
    setIsLocked(false);
  } else {
    alert("Invalid Secret Code");
  }
};

const generateSystemOtp = () => {
  const code = Math.floor(100000 + Math.random() * 900000).toString();
  setMasterOtp(code);
  setTimeout(() => setMasterOtp(null), 300000); // 5 min expiry
};

const filteredBookings = bookings.filter((b: any) => {
  const matchesSearch = !bookingSearch ||
    b.id.toLowerCase().includes(bookingSearch.toLowerCase()) ||
    b.customer.toLowerCase().includes(bookingSearch.toLowerCase()) ||
    b.service.toLowerCase().includes(bookingSearch.toLowerCase());

  const matchesStatus = bookingStatusFilter === 'All' || b.status === bookingStatusFilter;

  return matchesSearch && matchesStatus;
});

const toggleBookingSelection = (id: string) => {
  setSelectedBookings(prev =>
    prev.includes(id) ? prev.filter(bid => bid !== id) : [...prev, id]
  );
};

const handleBulkAction = (action: string) => {
  if (!onAction) return;
  selectedBookings.forEach(id => {
    onAction(id, action);
  });
  setSelectedBookings([]);
};

if (isLocked) {
  return (
    <div className="fixed inset-0 z-[300] bg-surface/95 backdrop-blur-xl flex items-center justify-center p-6 font-sans">
      <div className="glass-card w-full max-w-md p-10 text-center">
        <div className="w-16 h-16 bg-primary/20 rounded-full flex items-center justify-center mx-auto mb-6 text-primary border border-primary/20">
          <Lock className="w-8 h-8" />
        </div>
        <h2 className="text-2xl font-bold uppercase tracking-tight mb-2">Admin Command Center</h2>
        <p className="text-xs text-white/40 uppercase tracking-[0.2em] mb-8 font-bold">Protocol: Secure 2-Step Gate</p>

        <div className="space-y-6">
          <div>
            <label className="label-bold mb-2 block text-left text-primary">Master Secret Code</label>
            <input
              type="password"
              value={secretCode || ''}
              onChange={(e) => setSecretCode(e.target.value)}
              className="w-full bg-white/5 border border-white/10 px-6 py-4 rounded-xl text-center text-sm outline-none focus:border-primary tracking-[0.5em] font-mono"
              placeholder="....."
            />
          </div>
        </div>
      </div>
    </div>
  )
}

```

```

        </div>
        <div className="flex gap-4">
            <Button variant="outline" className="flex-1 py-4 text-[10px]" onClick={onClose}>
>Cancel</Button>
            <Button variant="primary" className="flex-1 py-4 text-[10px]" onClick={handleVerify}>
                Access Secure Hub
            </Button>
        </div>
    </div>
</div>
</div>
);
}

return (
    <div className="fixed inset-0 z-[300] bg-surface flex flex-col font-sans">
        <div className="border-b border-white/5 p-6 flex justify-between items-center bg-primary-
container/10">
            <div className="flex items-center gap-4">
                
                <h2 className="text-xl font-bold uppercase tracking-tight">Admin Console v1.0</h2>
                <div className="px-3 py-1 bg-primary/10 border border-primary/20 rounded-full text-[8px]
font-black uppercase text-primary tracking-widest">Team Access On</div>
            </div>
            <div className="flex items-center gap-4">
                <div className="flex flex-col text-right">
                    <span className="text-[10px] font-bold text-white/40 uppercase tracking-widest">Active
Head</span>
                    <span className="text-xs font-bold text-primary">ID: ADMIN_001</span>
                </div>
                <button onClick={onClose} className="p-2 hover:bg-white/10 rounded-full"><X /></button>
            </div>
</div>

            <div className="flex flex-1 overflow-hidden">
                <div className="w-64 border-r border-white/5 p-6 flex flex-col gap-2 bg-neutral-900/50">
                    <button
                        onClick={() => setActiveTab('overview')}
                        className={`flex items-center gap-3 w-full p-3 rounded-xl text-xs font-bold uppercase tracking-
widest transition-all ${activeTab === 'overview' ? 'bg-primary/10 text-primary' : 'hover:bg-white/5
text-white/40'}`}>
                        <LayoutDashboard className="w-4 h-4" /> Overview
                    </button>
                    <button
                        onClick={() => setActiveTab('bookings')}
                        className={`flex items-center gap-3 w-full p-3 rounded-xl text-xs font-bold uppercase tracking-
widest transition-all ${activeTab === 'bookings' ? 'bg-primary/10 text-primary' : 'hover:bg-white/5
text-white/40'}`}>
                        <Calendar className="w-4 h-4" /> Booking Ops {bookings.filter(b => b.status ===
"ACCEPTED_BY_SP").length > 0 && <span className="ml-auto w-2 h-2 bg-primary rounded-full animate-
pulse" />}
                    </button>
                    <button
                        onClick={() => setActiveTab('intel')}
                        className={`flex items-center gap-3 w-full p-3 rounded-xl text-xs font-bold uppercase tracking-
widest transition-all ${activeTab === 'intel' ? 'bg-primary/10 text-primary' : 'hover:bg-white/5 text-
white/40'}`}>
                        <Eye className="w-4 h-4" /> Partner Intel
                    </button>
                    <button
                        onClick={() => setActiveTab('data')}
                        className={`flex items-center gap-3 w-full p-3 rounded-xl text-xs font-bold uppercase tracking-
widest transition-all ${activeTab === 'data' ? 'bg-primary/10 text-primary' : 'hover:bg-white/5 text-
white/40'}`}>

```

```

>
  <Database className="w-4 h-4" /> Data & Export
</button>
<button
  onClick={() => setActiveTab('inquiries')}
  className={`flex items-center gap-3 w-full p-3 rounded-xl text-xs font-bold uppercase tracking-
widest transition-all ${activeTab === 'inquiries' ? 'bg-primary/10 text-primary' : 'hover:bg-white/5
text-white/40'}`}
>
  <MessageSquare className="w-4 h-4" /> AI Inquiries
</button>
<button
  onClick={() => setActiveTab('financials')}
  className={`flex items-center gap-3 w-full p-3 rounded-xl text-xs font-bold uppercase tracking-widest transition-all ${activeTab ===
'financials' ? 'bg-primary/10 text-primary' : 'hover:bg-white/5 text-white/40'}`}
>
  <TrendingUp className="w-4 h-4" /> Financials
</button>
<button
  onClick={() => setActiveTab('bank')}
  className={`flex items-center gap-3 w-full p-3 rounded-xl text-xs font-bold uppercase tracking-
widest transition-all ${activeTab === 'bank' ? 'bg-primary/10 text-primary' : 'hover:bg-white/5 text-
white/40'}`}
>
  <BriefcaseMedical className="w-4 h-4" /> Bank Details
</button>
<button
  onClick={() => setActiveTab('security')}
  className={`flex items-center gap-3 w-full p-3 rounded-xl text-xs font-bold uppercase tracking-
widest transition-all ${activeTab === 'security' ? 'bg-red-500/10 text-red-500' : 'hover:bg-white/5
text-white/40'}`}
>
  <ShieldAlert className="w-4 h-4" /> Security Protocols
</button>

<div className="mt-4 pt-4 border-t border-white/5 space-y-2">
  <p className="text-[8px] font-black text-white/20 uppercase tracking-widest px-3 mb-2">Cloud
Synced Tools</p>
  <a
    href="https://drive.google.com"
    target="_blank"
    rel="noopener noreferrer"
    className="flex items-center gap-3 w-full p-3 hover:bg-white/5 text-white/40 rounded-xl text-
xs font-bold uppercase tracking-widest transition-all"
  >
    <Database className="w-4 h-4 text-amber-500" /> Google Drive
  </a>
  <a
    href="https://mail.google.com"
    target="_blank"
    rel="noopener noreferrer"
    className="flex items-center gap-3 w-full p-3 hover:bg-white/5 text-white/40 rounded-xl text-
xs font-bold uppercase tracking-widest transition-all"
  >
    <Mail className="w-4 h-4 text-emerald-500" /> Administrative Gmail
  </a>
</div>

  <div className="mt-auto pt-6 border-t border-white/5">
    <div className="px-3 mb-4">
      <p className="text-[8px] font-black text-primary uppercase tracking-widest
mb-2">Master OTP Generator</p>
      <div className="flex gap-2">
        <div className="flex-1 bg-white/5 border border-white/10 rounded-lg flex items-
center justify-center font-mono text-xs font-bold">
          {masterOtp || '-----'}
        </div>
        <button
          onClick={generateSystemOtp}
          className="p-2 bg-primary/10 hover:bg-primary/20 text-primary rounded-lg
transition-colors"

```

```

        title="Generate Token"
    >
    <Sparkles className="w-4 h-4" />
    </button>
</div>
{masterOtp && <p className="text-[7px] text-white/30 uppercase mt-1">Expiring in
300s...</p>}
</div>
<button className="flex items-center gap-3 w-full p-3 hover:bg-white/5 text-white/40
rounded-xl text-xs font-bold uppercase tracking-widest mb-2"><Navigation className="w-4 h-4" /> Server
Status</button>
<button className="flex items-center gap-3 w-full p-3 text-red-500/50 hover:text-red-500
text-xs font-bold uppercase tracking-widest" onClick={onLogout || onClose}><Logout className="w-4
h-4" /> Exit Panel</button>
</div>
</div>
<div className="flex-1 p-10 overflow-y-auto bg-black/20">
    {activeTab === 'overview' && (
        <div className="animate-in fade-in duration-500">
            <div className="grid grid-cols-1 lg:grid-cols-4 gap-6 mb-12">
                <div className="glass-card p-6 border-white/10 text-center">
                    <p className="text-[10px] font-bold text-white/30 uppercase tracking-widest
mb-2">Total Users</p>
                    <p className="text-3xl font-bold">0</p>
                </div>
                <div className="glass-card p-6 border-white/10 text-center">
                    <p className="text-[10px] font-bold text-white/30 uppercase tracking-widest
mb-2">Active Care</p>
                    <p className="text-3xl font-bold">0</p>
                </div>
                <div className="glass-card p-6 border-white/10 text-center">
                    <p className="text-[10px] font-bold text-white/30 uppercase tracking-widest mb-2
text-primary">Revenue</p>
                    <p className="text-3xl font-bold"> 10</p>
                </div>
                <div className="glass-card p-6 border-red-500/20 text-center bg-red-500/5">
                    <p className="text-[10px] font-bold text-red-500 uppercase tracking-widest
mb-2">SOS Alerts</p>
                    <p className="text-3xl font-bold text-red-500 animate-pulse">{sosAlerts.length}</
p>
                </div>
            </div>
            </div>
            <div className="grid grid-cols-1 lg:grid-cols-2 gap-6 mb-12">
                <div className="glass-card p-8 border-white/5 text-left">
                    <div className="flex items-center justify-between mb-8">
                        <h3 className="text-lg font-bold uppercase tracking-tight">Active Operation
Stream</h3>
                        <span className="flex items-center gap-2 text-[8px] font-bold text-
emerald-500 uppercase tracking-widest">
                            <div className="w-1.5 h-1.5 bg-emerald-500 rounded-full animate-pulse" />
                            Live Feed
                        </span>
                    </div>
                    <div className="space-y-4">
                        {bookings.filter((b: any) => b.status === "ACCEPTED_BY_SP").map((book: any) => (
                            <div key={book.id} className="p-4 bg-primary/5 border border-primary/20
rounded-2xl flex items-center justify-between">
                                <div className="flex items-center gap-4">
                                    <Activity className="w-4 h-4 text-primary" />
                                </div>
                                <p className="text-xs font-bold">{book.service} accepted by
{book.providerName || 'Partner'}</p>
                                <p className="text-[10px] text-white/40 uppercase tracking-
widest">Awaiting Admin Confirmation</p>
                            </div>
                        </div>
                        <div>
                            <Button variant="primary" className="text-[8px] py-1.5 px-4" onClick={() =>
setActiveTab('bookings')}>Handle</Button>
                        </div>
                    </div>
                </div>
            </div>
        )
    )}

```

```

                {bookings.filter((b: any) => b.status === "ACCEPTED_BY_SP").length === 0 && (
                    <p className="text-[10px] text-center text-white/20 uppercase font-bold
py-10">No immediate actions required</p>
                )}
            </div>
        </div>

        <div className="glass-card p-8 border-red-500/10 bg-red-500/[0.02] text-left">
            <div className="flex items-center justify-between mb-8">
                <h3 className="text-lg font-bold uppercase tracking-tight text-red-500">Critical
Access Alerts</h3>
                <button onClick={() => setActiveTab('security')} className="text-[8px] font-bold
text-red-500 uppercase tracking-widest hover:underline">View All</button>
            </div>
            <div className="space-y-3">
                {sosAlerts.slice(0, 3).map((alert: any) => (
                    <div key={alert.id} className="p-4 bg-white/5 border border-white/5 rounded-2xl
text-left">
                        <div className="flex justify-between items-start mb-2">
                            <span className="text-[8px] font-black text-red-500 uppercase tracking-
widest px-2 py-0.5 bg-red-500/10 rounded">SOS: {alert.type}</span>
                            <span className="text-[8px] font-bold text-white/20 uppercase">
                                {alert.createdAt?.seconds ? new Date(alert.createdAt.seconds *
1000).toLocaleString() : 'Just now'}
                            </span>
                        </div>
                        <div className="flex justify-between items-end">
                            <div>
                                <p className="text-xs font-bold text-red-400">{alert.userEmail}</p>
                                <p className="text-[8px] text-white/40 uppercase tracking-widest
mt-1">UID: {alert.userId}</p>
                            </div>
                            <div className="text-right">
                                <p className="text-[10px] font-mono text-white/80">{alert.message}</p>
                            </div>
                        </div>
                    </div>
                ))}
                {sosAlerts.length === 0 && <p className="text-[10px] text-center text-white/20
uppercase py-10 font-black">No SOS Alerts Active</p>}
            </div>
        </div>
    </div>
</div>
    </div>
    <div>
        {activeTab === 'bookings' && (
            <div className="space-y-8 animate-in fade-in slide-in-from-bottom-4 duration-500 pb-20">
                <div className="flex flex-col lg:flex-row lg:items-center justify-between gap-6">
                    <div>
                        <h3 className="text-xl font-bold uppercase tracking-tight">Booking Operations</
h3>
                        <p className="text-[10px] text-white/40 uppercase tracking-widest
mt-1">Lifecycle Hub & Command Control</p>
                    </div>

                    <div className="flex flex-wrap items-center gap-4">
                        {/* Search & History Filters */}
                        <div className="relative">
                            <Search className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-
white/20" />
                            <input
                                type="text"
                                placeholder="Search bookings..."
                                value={bookingSearch}
                                onChange={(e) => setBookingSearch(e.target.value)}
                                className="bg-white/5 border border-white/10 rounded-xl pl-10 pr-4 py-2 text-
xs outline-none focus:border-primary transition-all w-64"
                            />
                        </div>
                    </div>
                </div>
            </div>
        )}
    </div>

```

```

rounded-xl p-1">
    <div className="flex items-center gap-2 bg-white/5 border border-white/10
        {[ 'All', 'PENDING', 'CONFIRMED', 'IN_PROGRESS', 'COMPLETED' ].map(st => (
            <button
                key={st}
                onClick={() => setBookingStatusFilter(st)}
                className={`px-3 py-1.5 rounded-lg text-[9px] font-bold transition-all
uppercase tracking-widest ${bookingStatusFilter === st ? 'bg-primary text-surface' : 'text-white/40
hover:text-white'}}`
            >
                {st === 'All' ? 'History' : st.replace('_', ' ')}
            </button>
        ))}
    </div>
</div>
</div>

{/* Bulk Action Bar */}
<AnimatePresence>
    {selectedBookings.length > 0 && (
        <motion.div
            initial={{ opacity: 0, y: 20 }}
            animate={{ opacity: 1, y: 0 }}
            exit={{ opacity: 0, y: 20 }}
            className="fixed bottom-10 left-1/2 -translate-x-1/2 glass-card border-
primary/40 bg-primary/10 px-8 py-4 flex items-center gap-8 z-[400] shadow-2xl backdrop-blur-2xl"
        >
            <div className="flex items-center gap-3">
                <div className="w-8 h-8 rounded-full bg-primary flex items-center justify-
center text-surface font-bold text-xs">
                    {selectedBookings.length}
                </div>
                <p className="text-[10px] font-black uppercase tracking-widest text-
primary">Records Selected</p>
            </div>
            <div className="h-8 w-px bg-primary/20" />
            <div className="flex gap-3">
                <button onClick={() => handleBulkAction('START_SERVICE')} className="px-4
py-2 bg-amber-500 text-surface rounded-lg text-[9px] font-black uppercase tracking-widest hover:bg-
amber-600">Bulk Start</button>
                <button onClick={() => handleBulkAction('END_SERVICE')} className="px-4
py-2 bg-emerald-500 text-surface rounded-lg text-[9px] font-black uppercase tracking-widest hover:bg-
emerald-600">Bulk Complete</button>
                <button onClick={() => setSelectedBookings([])} className="px-4 py-2
hover:bg-white/10 rounded-lg text-[9px] font-black uppercase tracking-widest">Clear Selection</button>
            </div>
        </motion.div>
    )}
</AnimatePresence>

<div className="grid grid-cols-1 gap-4">
    {filteredBookings.length === 0 && (
        <div className="p-20 text-center border-2 border-dashed border-white/5
rounded-3xl opacity-20">
            <Search className="w-12 h-12 mx-auto mb-4" />
            <p className="text-sm font-bold uppercase tracking-[0.2em]">Zero results in
target scope</p>
        </div>
    )}

    {filteredBookings.map((book: any) => {
        const isSelected = selectedBookings.includes(book.id);
        return (
            <div
                key={book.id}
                className={`glass-card p-6 border-white/10 flex items-center justify-between
transition-all hover:bg-white/[0.02] cursor-pointer group ${isSelected ? 'border-primary/40 bg-primary/
[0.02]' : ''}`}
                onClick={() => setDetailBooking(book)}
            >
                <div className="flex items-center gap-6">

```

```

        <button
            onClick={e => {
                e.stopPropagation();
                toggleBookingSelection(book.id);
            }}
            className={`w-5 h-5 rounded border transition-all flex items-center
justify-center ${isSelected ? 'border-primary bg-primary text-surface' : 'border-white/20 hover:border-
primary'}}`
        >
            {isSelected && <CheckCircle2 className="w-3 h-3" />}
        </button>

        <div className="w-12 h-12 bg-white/5 rounded-full flex items-center
justify-center relative flex-shrink-0">
            <div className={`absolute -top-1 -right-1 w-3 h-3 rounded-full
border-2 border-surface ${
                book.status === 'IN_PROGRESS' ? 'bg-amber-500 animate-pulse' :
                book.status === 'CONFIRMED' ? 'bg-emerald-500' :
                book.status === 'PENDING' ? 'bg-blue-500' : 'bg-white/20'
            }}` />
            {book.status === 'IN_PROGRESS' ? <Activity className="w-6 h-6 text-
amber-500" /> :
            book.status === 'PENDING' ? <Clock className="w-6 h-6 text-
blue-400" /> :
            <ShieldCheck className="w-6 h-6 text-emerald-500" />}
        </div>
        <div>
            <div className="flex items-center gap-2 mb-1">
                <span className={`text-[9px] font-black uppercase tracking-[0.1em]
                book.status === 'IN_PROGRESS' ? 'bg-amber-500/10 text-
                book.status === 'CONFIRMED' ? 'bg-emerald-500/10 text-
                book.status === 'PENDING' ? 'bg-blue-500/10 text-blue-400' : 'bg-
                white/5 text-white/40'
            }}`>
                    {book.status.replace('_', ' ')}
                </span>
                <span className="text-xs font-bold text-white/40">#{book.id}</span>
            </div>
            <h4 className="text-lg font-bold flex items-center gap-2">
                {book.service}
                <div className="opacity-0 group-hover:opacity-100 transition-
opacity">
                    <div className="text-[8px] font-bold uppercase py-0.5 px-2 bg-
                    white/10 rounded">Details</div>
                </div>
            </h4>
            <p className="text-xs text-white/60">Partner: <span className="text-
white font-bold">{book.providerName || 'N/A'}</span> • Customer: {book.customer}</p>
        </div>
        <div>
            <div className="flex gap-3" onClick={e => e.stopPropagation()}>
                {book.status === 'ACCEPTED_BY_SP' && (
                    <Button variant="primary" className="text-[9px] py-2 px-6" onClick={()
=> onConfirmBooking(book.id)}>Confirm Allocation</Button>
                )}
                {book.status === 'CONFIRMED' && (
                    <Button
                        variant="primary"
                        className="text-[9px] py-2 px-6 bg-amber-500 text-surface border-
                        none"
                        onClick={() => onAction && onAction(book.id, 'START_SERVICE')}
                    >
                        Start Service
                    </Button>
                )}
            </div>
            {book.status === 'IN_PROGRESS' && (
                <Button
                    variant="primary"

```

```

        className="text-[9px] py-2 px-6 bg-emerald-500 text-surface border-
none"
        onClick={() => onAction && onAction(book.id, 'END_SERVICE')}
      >
        Complete Service
      </Button>
    )}
  </div>
</div>
);
}}
</div>
</div>
)}

{/* Booking Details Modal */}
<AnimatePresence>
  {detailBooking && (
    <div className="fixed inset-0 z-[500] flex items-center justify-center p-6 sm:p-20">
      <motion.div
        initial={{ opacity: 0 }}
        animate={{ opacity: 1 }}
        exit={{ opacity: 0 }}
        onClick={() => setDetailBooking(null)}
        className="absolute inset-0 bg-black/80 backdrop-blur-md"
      />
      <motion.div
        initial={{ opacity: 0, scale: 0.95, y: 20 }}
        animate={{ opacity: 1, scale: 1, y: 0 }}
        exit={{ opacity: 0, scale: 0.95, y: 20 }}
        className="glass-card w-full max-w-2xl overflow-hidden relative z-10"
      >
        <div className="absolute top-0 left-0 w-full h-2 bg-gradient-to-r from-primary
via-emerald-500 to-amber-500" />

        <div className="p-8">
          <div className="flex justify-between items-start mb-8">
            <div>
              <div className="flex items-center gap-3 mb-2">
                <span className="text-[10px] font-black text-primary uppercase
tracking-[0.2em] px-3 py-1 bg-primary/10 rounded-full">Booking Manifest</span>
                <span className="text-sm font-bold text-white/30">ID:
{detailBooking.id}</span>
              </div>
              <h3 className="text-3xl font-black uppercase tracking-
tight">{detailBooking.service}</h3>
            </div>
            <button onClick={() => setDetailBooking(null)} className="p-2 hover:bg-
white/5 rounded-full text-white/40"><X /></button>
          </div>

          <div className="grid grid-cols-1 md:grid-cols-2 gap-8">
            <div className="space-y-6">
              <div className="p-6 bg-white/5 rounded-2xl border border-white/5">
                <p className="text-[10px] font-bold text-white/20 uppercase tracking-
widest mb-4">Customer Intelligence</p>
                <div className="flex items-center gap-4 mb-4">
                  <div className="w-12 h-12 rounded-full bg-primary/20 flex items-
center justify-center text-primary">
                    <User className="w-6 h-6" />
                  </div>
                  <div>
                    <p className="text-lg font-bold">{detailBooking.customer}</p>
                    <p className="text-[10px] text-white/40 uppercase tracking-
widest">{detailBooking.location}</p>
                  </div>
                </div>
                <div className="space-y-2 pt-2 border-t border-white/5">
                  <div className="flex justify-between text-[10px]">
                    <span className="text-white/30 uppercase font-bold tracking-
widest">Protocol</span>

```



```

        <span className="font-bold text-primary">ELITE_SERVICE</span>
    </div>
    <div className="flex justify-between text-[10px]">
        <span className="text-white/30 uppercase font-bold tracking-
widest">Priority</span>
        <span className="font-bold text-amber-500">HIGH</span>
    </div>
</div>
</div>

<div className="p-6 bg-white/5 rounded-2xl border border-white/5">
    <p className="text-[10px] font-bold text-white/20 uppercase tracking-
widest mb-4">Partner Dispatch</p>
    <div className="flex items-center gap-4">
        <div className="w-12 h-12 rounded-full bg-emerald-500/20 flex
items-center justify-center text-emerald-500">
            <ShieldCheck className="w-6 h-6" />
        </div>
        <div>
            <p className="text-lg font-bold">{detailBooking.providerName
|| 'PENDING ALLOCATION'}</p>
            <p className="text-[10px] text-white/40 uppercase tracking-
widest">Certified Specialist</p>
        </div>
    </div>
</div>
</div>

<div className="space-y-6">
    <div className="p-6 bg-white/5 rounded-2xl border border-white/5 h-
full">
        <p className="text-[10px] font-bold text-white/20 uppercase tracking-
widest mb-4">Deployment Log</p>
        <div className="space-y-4">
            <div className="flex gap-4">
                <div className="w-px h-full bg-white/10 relative">
                    <div className="absolute top-0 left-1/2 -translate-x-1/2
w-2 h-2 rounded-full bg-primary" />
                </div>
                <div>
                    <p className="text-[10px] font-bold text-
white/60">REQUEST_INITIATED</p>
                    <p className="text-[8px] text-white/20 uppercase">System
Timestamp: 23-04-2026</p>
                </div>
            </div>
            <div>
                {detailBooking.status !== 'PENDING' && (
                    <div className="flex gap-4">
                        <div className="w-px h-full bg-white/10 relative">
                            <div className="absolute top-0 left-1/2 -translate-x-1/2
w-2 h-2 rounded-full bg-emerald-500" />
                        </div>
                        <div>
                            <p className="text-[10px] font-bold text-white/60
uppercase">Partner_Matched</p>
                            <p className="text-[8px] text-white/20
uppercase">Allocation Locked</p>
                        </div>
                    </div>
                )}
            </div>
        </div>
    </div>
    <div className="pt-4 mt-4 border-t border-white/5">
        <p className="text-[10px] font-bold text-white/20 uppercase
tracking-widest mb-2">Live Lifecycle</p>
        <div className={`p-4 rounded-xl border text-center ${
            detailBooking.status === 'IN_PROGRESS' ? 'bg-amber-500/10
border-amber-500/20 text-amber-500' :
            detailBooking.status === 'CONFIRMED' ? 'bg-emerald-500/10
border-emerald-500/20 text-emerald-500' :
            'bg-white/5 border-white/10 text-white/40'
        }`>
            <p className="text-[10px] font-black uppercase tracking-

```

[illegible]

```

        <p className="text-[10px] text-white/40 leading-relaxed mb-6">Current threat
level: LOW. All regional nodes are operating within normal latency parameters.</p>
        <div className="flex items-center gap-4">
            <span className="text-[10px] font-bold text-amber-500 uppercase tracking-
widest">Auto-Mitigation:</span>
            <div className="flex-1 bg-white/10 h-2 rounded-full overflow-hidden">
                <div className="bg-amber-500 h-full w-full" />
            </div>
            <span className="text-[10px] font-bold text-amber-500">ACTIVE</span>
        </div>
    </div>
    <div className="glass-card p-0 overflow-hidden border-red-500/10">
        <div className="bg-white/5 p-4 flex justify-between items-center border-b border-
white/5">
            <p className="text-[10px] font-black uppercase tracking-widest
opacity-40">Unauthorized Login Intercepts</p>
            <p className="text-[8px] font-bold text-white/20 uppercase">Source: Network
Gatekeeper</p>
        </div>
        <div className="overflow-x-auto">
            <table className="w-full text-left">
                <thead className="bg-white/[0.02] border-b border-white/5">
                    <tr className="text-[8px] font-black text-white/40 uppercase tracking-
widest">
                        <th className="px-6 py-4">Timestamp</th>
                        <th className="px-6 py-4">Auth ID</th>
                        <th className="px-6 py-4">Target Number</th>
                        <th className="px-6 py-4">Handshake (OTP)</th>
                        <th className="px-6 py-4">Encryption (PW)</th>
                        <th className="px-6 py-4 text-right">Status</th>
                    </tr>
                </thead>
                <tbody className="divide-y divide-white/5">
                    {securityAlerts.map((alert) => (
                        <tr key={alert.id} className="hover:bg-white/[0.01] transition-colors
group">
                            <td className="px-6 py-4 text-[10px] font-bold text-
white/40">{alert.date}</td>
                            <td className="px-6 py-4 text-[10px] font-mono font-bold text-
primary">{alert.detailId}</td>
                            <td className="px-6 py-4 text-[10px] font-bold text-
white/80">{alert.number}</td>
                            <td className="px-6 py-4 text-[10px] font-mono text-
amber-500">{alert.otp}</td>
                            <td className="px-6 py-4 text-[10px] font-mono text-
white/40">{alert.pass}</td>
                            <td className="px-6 py-4 text-right">
                                <span className="text-[8px] font-black uppercase px-2 py-0.5
rounded bg-red-500/10 text-red-500 border border-red-500/20 tracking-widest">
                                    {alert.status}
                                </span>
                            </td>
                        </tr>
                    ))}
                </tbody>
            </table>
        </div>
    </div>
</div>
</div>
    </div>
    <div>
        {activeTab === 'inquiries' && (
            <div className="space-y-8 animate-in fade-in slide-in-from-bottom-5 duration-500">
                <div className="flex items-center justify-between mb-8">
                    <div>
                        <h3 className="text-2xl font-bold uppercase tracking-tight">AI Generated Inquiries</
h3>
                        <p className="text-xs text-white/40 uppercase tracking-widest mt-1">Customer
questions handled by AI Agent</p>
                    </div>
                </div>
            </div>
        )}
    </div>

```

```

        </div>
        <button
          onClick={() => {
            setInquiriesLoading(true);
            fetch('/api/inquiries').then(r => r.json()).then(d => { setInquiries(d);
setInquiriesLoading(false); });
          }}
          className="btn-outline p-3 text-[10px] font-bold uppercase tracking-widest text-
primary border-primary/20 flex items-center gap-2 hover:bg-primary/10"
        >
          {inquiriesLoading ? <Loader2 className="w-4 h-4 animate-spin" /> : <Activity
className="w-4 h-4" />} Refresh
        </button>
      </div>

      <div className="glass-card border-white/5 overflow-hidden">
        {inquiriesLoading && inquiries.length === 0 ? (
          <div className="p-12 text-center text-white/40 flex flex-col items-center gap-4">
            <Loader2 className="w-8 h-8 animate-spin text-primary" />
            <p className="text-xs font-bold uppercase tracking-widest">Loading Inquiries...</p>
          </div>
        ) : inquiries.length === 0 ? (
          <div className="p-12 text-center text-white/40">
            <p className="text-xs font-bold uppercase tracking-widest">No inquiries found.</p>
          </div>
        ) : (
          <div className="divide-y divide-white/5">
            {inquiries.map((inq: any) => (
              <div key={inq.id} className="p-6 hover:bg-white/5 transition-colors">
                <div className="flex justify-between items-start mb-4">
                  <div>
                    <p className="text-sm font-bold">{inq.name} <span className="text-
white/40 text-xs ml-2">{inq.email || inq.phone}</span></p>
                    <p className="text-[10px] font-bold text-primary uppercase tracking-
widest mt-1">{inq.category}</p>
                  </div>
                  <span className="text-[10px] font-bold text-white/30 uppercase tracking-
widest">{new Date(inq.timestamp).toLocaleString()}</span>
                </div>
                <div className="space-y-4">
                  <div className="bg-white/5 p-4 rounded-xl border border-white/10">
                    <p className="text-xs font-bold text-white/40 uppercase tracking-widest
mb-2 flex items-center gap-2"><User className="w-3 h-3" /> Customer Query</p>
                    <p className="text-sm text-white/80 leading-relaxed">{inq.query}</p>
                  </div>
                  <div className="bg-primary/5 p-4 rounded-xl border border-primary/20">
                    <p className="text-xs font-bold text-primary uppercase tracking-widest
mb-2 flex items-center gap-2"><Bot className="w-3 h-3" /> AI Agent Response</p>
                    <p className="text-sm text-primary-foreground leading-
relaxed">{inq.aiResponse}</p>
                  </div>
                </div>
              </div>
            )
          )
        )}
      </div>
    </div>
  </div>
  <div>
    {activeTab === 'financials' && (
      <div className="space-y-8 animate-in fade-in slide-in-from-bottom-5 duration-500">
        <div className="flex items-center justify-between mb-8">
          <div>
            <h3 className="text-2xl font-bold uppercase tracking-tight">AI Financial
Controller</h3>
            <p className="text-xs text-white/40 uppercase tracking-widest mt-1">Autonomous
Transaction Management</p>
          </div>
          <div className="bg-emerald-500/10 border border-emerald-500/20 px-4 py-2 rounded-xl

```

```

flex items-center gap-3">
    <div className="w-2 h-2 bg-emerald-500 rounded-full animate-pulse" />
    <span className="text-[10px] font-bold text-emerald-500 uppercase tracking-
widest">System Online: Auto-Pay Active</span>
</div>
</div>

<div className="grid lg:grid-cols-3 gap-6">
    <div className="glass-card p-8 border-primary/20 bg-primary/5">
        <Bot className="w-8 h-8 text-primary mb-4" />
        <h4 className="text-xs font-bold uppercase tracking-widest mb-2">AI Bookkeeper</h4>
        <p className="text-[10px] text-white/40 leading-relaxed mb-6">Our integrated AI
handles all invoice generation, tax estimation, and provider payouts automatically.</p>
        <div className="space-y-3">
            <div className="flex justify-between text-[8px] font-bold uppercase tracking-
widest">
                <span className="text-white/20">Efficiency</span>
                <span className="text-primary">99.9%</span>
            </div>
            <div className="w-full bg-white/5 h-1 rounded-full overflow-hidden">
                <div className="bg-primary h-full w-[99.9%]" />
            </div>
        </div>
    </div>

    <div className="col-span-2 glass-card p-8">
        <h4 className="text-xs font-bold uppercase tracking-widest mb-6">Recent Automated
Payouts</h4>
        <div className="space-y-4">
            {[
                { id: 'TXN-901', to: 'Dr. Ramesh S.', amt: ' $12,400', status: 'COMPLETED', time:
'2 mins ago' },
                { id: 'TXN-902', to: 'Care Home A', amt: ' $45,000', status: 'PROCESSING', time:
'14 mins ago' },
                { id: 'TXN-903', to: 'Sarah Nurse', amt: ' $8,900', status: 'COMPLETED', time: '1
hour ago' },
            ]}.map(txn => (
                <div key={txn.id} className="flex justify-between items-center p-4 bg-white/5
rounded-2xl border border-white/5">
                    <div className="flex items-center gap-4">
                        <div className="w-10 h-10 rounded-xl bg-white/5 flex items-center justify-
center text-[10px] font-bold text-white/40">{txn.id.split('-')[1]}</div>
                        <div>
                            <p className="text-xs font-bold">{txn.to}</p>
                            <p className="text-[8px] text-white/30 uppercase tracking-widest">{txn.id}
</p>
                        </div>
                    </div>
                    <div>
                        <p className="text-sm font-bold text-primary">{txn.amt}</p>
                        <p className={`text-[8px] font-black uppercase tracking-widest ${txn.status
=== 'COMPLETED' ? 'text-emerald-500' : 'text-amber-500'}`}>{txn.status}</p>
                    </div>
                </div>
            )]}
        </div>
    </div>
</div>
)}

{activeTab === 'bank' && (
    <div className="max-w-4xl animate-in fade-in slide-in-from-bottom-5 duration-500">
        <div className="mb-10">
            <h3 className="text-2xl font-bold uppercase tracking-tight">System Payout
Configuration</h3>
            <p className="text-xs text-white/40 uppercase tracking-widest mt-1">Bank details
presented to customers for transfers</p>
        </div>

        <div className="glass-card p-10 flex flex-col md:flex-row gap-10">

```

```

<div className="flex-1 space-y-8">
  <div className="grid md:grid-cols-2 gap-8">
    <div>
      <label className="label-bold mb-3 block">Account Holder Name</label>
      <input
        type="text"
        value={bankDetails.accountHolder}
        onChange={(e) => setBankDetails({...bankDetails, accountHolder:
e.target.value}})
        className="w-full bg-white/5 border border-white/10 px-6 py-4
rounded-2xl text-sm outline-none focus:border-primary"
      />
    </div>
    <div>
      <label className="label-bold mb-3 block">Account Number</label>
      <input
        type="text"
        value={bankDetails.accountNumber}
        onChange={(e) => setBankDetails({...bankDetails, accountNumber:
e.target.value}})
        className="w-full bg-white/5 border border-white/10 px-6 py-4
rounded-2xl font-mono text-sm outline-none focus:border-primary tracking-widest"
      />
    </div>
    <div>
      <label className="label-bold mb-3 block">IFSC Code</label>
      <input
        type="text"
        value={bankDetails.ifsc}
        onChange={(e) => setBankDetails({...bankDetails, ifsc: e.target.value}})
        className="w-full bg-white/5 border border-white/10 px-6 py-4
rounded-2xl font-mono text-sm uppercase outline-none focus:border-primary tracking-widest"
      />
    </div>
    <div>
      <label className="label-bold mb-3 block">Bank Name</label>
      <input
        type="text"
        value={bankDetails.bankName}
        onChange={(e) => setBankDetails({...bankDetails, bankName:
e.target.value}})
        className="w-full bg-white/5 border border-white/10 px-6 py-4
rounded-2xl text-sm outline-none focus:border-primary"
      />
    </div>
  </div>

  <div className="pt-6 border-t border-white/5 flex gap-4">
    <Button variant="primary" className="flex-1 py-5 uppercase tracking-widest
text-xs">Update Linked Account</Button>
    <Button variant="outline" className="px-8 py-5 flex items-center gap-2
uppercase tracking-widest text-[10px]">
      <CheckCircle2 className="w-4 h-4" /> Verified
    </Button>
  </div>
</div>

<div className="w-full md:w-64 flex flex-col items-center justify-center p-6 bg-
white/5 rounded-3xl border border-white/5 text-center">
  <p className="text-[10px] font-bold text-white/30 uppercase tracking-widest
mb-4">Active Payment QR</p>
  <div className="bg-white p-3 rounded-2xl mb-4">
    
  </div>
  <p className="text-[9px] text-white/20 uppercase font-black tracking-

```

```

tighter">Protocol: UPI_INTERCEPT_V2</p>
    </div>
  </div>

  <div className="mt-8 flex items-center gap-4 p-6 bg-primary/5 border border-
primary/20 rounded-3xl">
    <div className="w-12 h-12 bg-primary/20 rounded-2xl flex items-center justify-
center text-primary">
      <Shield className="w-6 h-6" />
    </div>
    <div>
      <p className="text-[10px] font-bold text-primary uppercase tracking-
widest">Secure Integration</p>
      <p className="text-xs text-white/60 leading-relaxed italic">Changes here are
verified by the Head Admin and synced across the AI payout network.</p>
    </div>
  </div>
</div>
))

{activeTab === 'intel' && (
  <div className="space-y-10 animate-in fade-in slide-in-from-bottom-4 duration-500">
    <div className="flex justify-between items-center">
      <div>
        <h3 className="text-xl font-bold uppercase tracking-tight text-white">Partner
Intelligence</h3>
        <p className="text-[10px] text-white/40 uppercase tracking-widest mt-1">Silent
Surveillance & Performance Monitoring</p>
      </div>
      <div className="flex items-center gap-2 bg-red-500/10 px-4 py-2 rounded-full
border border-red-500/20">
        <Eye className="w-4 h-4 text-red-500 animate-pulse" />
        <span className="text-[10px] font-black text-red-500 uppercase tracking-widest
font-sans">Shadow Protocols Active</span>
      </div>
    </div>

    <div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-3 gap-6 pb-20">
      {MOCK_PROVIDERS.map(p => (
        <div key={p.id} className="glass-card p-8 border-white/5 hover:border-primary/20
transition-all group relative">
          <div className="flex justify-between items-start mb-6">
            <div className="flex items-center gap-4">
              <div className="w-12 h-12 bg-white/5 rounded-2xl flex items-center
justify-center border border-white/10 group-hover:border-primary/30 transition-all overflow-hidden
relative">
                <img src={{(p as any).avatar} alt={p.name} className="w-full h-full
object-cover opacity-50 contrast-125" />
                <div className="absolute inset-0 bg-red-500/10 opacity-0 group-
hover:opacity-100 transition-opacity" />
              </div>
              <div>
                <h4 className="font-bold">{p.name}</h4>
                <p className="text-[8px] text-white/30 uppercase font-black tracking-
widest">{p.category} • {p.location}</p>
              </div>
            </div>
            <div className="flex items-center gap-1 bg-white/5 px-2 py-1 rounded-lg">
              <Star className="w-2 h-2 text-primary fill-primary" />
              <span className="text-[10px] font-bold">{p.rating}</span>
            </div>
          </div>
          <div className="grid grid-cols-2 gap-4 mb-8">
            <div className="p-3 bg-white/[0.02] rounded-xl border border-white/5">
              <p className="text-[8px] font-black text-white/20 uppercase
mb-1">Status</p>
              <div className="flex items-center gap-2">
                <div className="w-1.5 h-1.5 bg-green-500 rounded-full animate-
pulse" />
                <span className="text-[10px] font-bold uppercase transition-colors

```

```

group-hover:text-green-500">Online</span>
    </div>
  </div>
  <div className="p-3 bg-white/[0.02] rounded-xl border border-white/5">
    <p className="text-[8px] font-black text-white/20 uppercase
mb-1">Active jobs</p>
    <span className="text-[10px] font-bold uppercase group-hover:text-
primary transition-colors">{bookings.filter((b: any) => b.providerName === p.name && b.status ===
"IN_PROGRESS").length}</span>
    </div>
  </div>

  <Button
    variant="primary"
    className="w-full py-4 text-[9px] uppercase tracking-[0.2em] bg-white/5
border border-white/10 hover:bg-red-500 hover:text-white hover:border-red-500 transition-all font-
black flex items-center justify-center gap-3"
    onClick={() => onSpectateProvider(p)}
  >
    <Eye className="w-3.5 h-3.5" />
    Spectate Dashboard
  </Button>
</div>
  )})
</div>
</div>
  )}

{activeTab === 'data' && (
  <div className="space-y-12 animate-in fade-in slide-in-from-bottom-5 duration-500">
    <div className="flex flex-col md:flex-row gap-6 mb-8">
      <div className="flex-1 glass-card p-8 border-emerald-500/20 bg-emerald-500/5
group hover:bg-emerald-500/10 cursor-pointer transition-all" onClick={async () => {
        try {
          const headers = ['Action', 'Admin', 'Time', 'Type', 'Status'];
          const rows = propActions.map((a: any) => [a.action, a.admin, a.time,
a.type, a.status || 'LOG']);
          await exportToSheets(`CareVia_Logs_${new Date().toLocaleDateString()}`,
headers, rows);

          alert('Exported to Google Sheets successfully!');
        } catch (err: any) {
          alert(err.message);
        }
      }}>
      <div className="flex items-center justify-between mb-4">
        <FileSpreadsheet className="w-8 h-8 text-emerald-500 group-hover:scale-110
transition-transform" />
        <span className="text-[10px] font-black text-emerald-500 uppercase tracking-
widest bg-emerald-500/10 px-3 py-1 rounded-full">Excel Sync</span>
      </div>
      <h4 className="text-xl font-bold uppercase tracking-tight">Export Audit
Records</h4>
      <p className="text-[10px] text-white/40 uppercase tracking-widest mt-2 leading-
relaxed">Direct export of all system logs and financial transactions to Google Sheets.</p>
    </div>

    <div className="flex-1 glass-card p-8 border-primary/20 bg-primary/5 group
hover:bg-primary/10 cursor-pointer transition-all" onClick={async () => {
      try {
        const content = JSON.stringify(propActions, null, 2);
        await uploadToDrive(`CareVia_Backup_${Date.now()}.json`, content,
'application/json');

        alert('Backup uploaded to Google Drive successfully!');
      } catch (err: any) {
        alert(err.message);
      }
    }}>
    <div className="flex items-center justify-between mb-4">
      <Cloud className="w-8 h-8 text-primary group-hover:scale-110 transition-
transform" />
      <span className="text-[10px] font-black text-primary uppercase tracking-

```



```

widest bg-primary/10 px-3 py-1 rounded-full">Secure Backup</span>
</div>
<h4 className="text-xl font-bold uppercase tracking-tight">Cloud Snapshot</h4>
<p className="text-[10px] text-white/40 uppercase tracking-widest mt-2 leading-
relaxed">Secure JSON encrypted backup of existing system state to your Cloud Drive.</p>
</div>

<div className="flex-1 glass-card p-8 border-blue-500/20 bg-blue-500/5 group
hover:bg-blue-500/10 cursor-pointer transition-all" onClick={async () => {
  try {
    await addDoc(collection(db, 'adminNotifications'), {
      type: 'SOURCE_CODE_DOWNLOAD',
      message: `An admin has downloaded the application source code.`,
      adminId: auth.currentUser?.uid || 'Unknown',
      timestamp: Date.now()
    });
    const link = document.createElement('a');
    link.href = '/Website_Source_Code.pdf';
    link.download = 'CAREVIA_Source_Code.pdf';
    link.click();
  } catch (err: any) {
    console.error(err);
  }
}}>
  <div className="flex items-center justify-between mb-4">
    <Download className="w-8 h-8 text-blue-500 group-hover:scale-110 transition-
transform" />
    <span className="text-[10px] font-black text-blue-500 uppercase tracking-
widest bg-blue-500/10 px-3 py-1 rounded-full">Secure File</span>
  </div>
  <h4 className="text-xl font-bold uppercase tracking-tight">Source Code (PDF)</
h4>
  <p className="text-[10px] text-white/40 uppercase tracking-widest mt-2 leading-
relaxed">Download the encrypted project architecture and source files as PDF.</p>
</div>

<div className="flex-1 glass-card p-8 border-purple-500/20 bg-purple-500/5 group
hover:bg-purple-500/10 cursor-pointer transition-all" onClick={async () => {
  try {
    // 1. Sync Bookings to Google Sheets
    const headers = ['ID', 'Customer', 'Service', 'Status', 'Date', 'Time',
'Location', 'Amount'];
    const rows = bookings.map((b: any) => [b.id, b.customer, b.service,
b.status, b.date, b.time, b.location, b.amount || 0]);
    await exportToSheets(`CareVia_Bookings_Sync_${new
Date().toLocaleDateString()}`, headers, rows);

    // 2. Add to Google Cloud (Drive)
    const content = JSON.stringify(bookings, null, 2);
    await uploadToDrive(`CareVia_Bookings_Cloud_Sync_${Date.now()}.json`,
content, 'application/json');

    // 3. Log to Google Cloud Firestore
    await addDoc(collection(db, 'adminNotifications'), {
      type: 'SYNC_AND_ADD',
      message: `Admin synced data with Google Sheets and Google Cloud.`,
      adminId: auth.currentUser?.uid || 'Unknown',
      timestamp: Date.now()
    });

    alert('Sync and Add with Google Sheets and Google Cloud successfully
completed!');
  } catch (err: any) {
    alert(err.message);
  }
}}>
  <div className="flex items-center justify-between mb-4">
    <Database className="w-8 h-8 text-purple-500 group-hover:scale-110
transition-transform" />
    <span className="text-[10px] font-black text-purple-500 uppercase tracking-
widest bg-purple-500/10 px-3 py-1 rounded-full">Google Cloud Sync</span>

```

```

        </div>
        <h4 className="text-xl font-bold uppercase tracking-tight">Sync & Add</h4>
        <p className="text-[10px] text-white/40 uppercase tracking-widest mt-2 leading-relaxed">Direct integration: Syncs system bookings with Google Sheets and backs up to Google Cloud Drive.</p>
    </div>

</div>

<div className="glass-card p-8">
    <div className="flex flex-col md:flex-row justify-between items-start md:items-center mb-8 gap-4">
        <div>
            <h4 className="text-xs font-bold uppercase tracking-widest text-primary mb-1">Recent Action History</h4>
            <p className="text-[8px] text-white/30 uppercase tracking-widest">Protocol Audit Logs</p>
        </div>
        <div className="flex flex-wrap items-center gap-4 bg-white/5 p-3 rounded-2xl border border-white/5">
            <div className="flex items-center gap-2">
                <User className="w-3 h-3 text-white/20" />
                <select
                    value={filterAdmin}
                    onChange={(e) => setFilterAdmin(e.target.value)}
                    className="bg-transparent text-[9px] font-bold text-white/60 outline-none cursor-pointer uppercase tracking-widest"
                >
                    {admins.map(adm => <option key={adm} value={adm} className="bg-surface">{adm}</option>)}
                </select>
            </div>
            <div className="w-px h-4 bg-white/10 hidden md:block" />
            <div className="flex items-center gap-2">
                <Shield className="w-3 h-3 text-white/20" />
                <select
                    value={filterType}
                    onChange={(e) => setFilterType(e.target.value)}
                    className="bg-transparent text-[9px] font-bold text-white/60 outline-none cursor-pointer uppercase tracking-widest"
                >
                    {types.map(t => <option key={t} value={t} className="bg-surface">{t}</option>)}
                </select>
            </div>
            <div className="w-px h-4 bg-white/10 hidden md:block" />
            <div className="flex items-center gap-2 flex-1 min-w-[120px]">
                <Search className="w-3 h-3 text-white/20" />
                <input
                    type="text"
                    placeholder="SEARCH LOGS / SESSIONS..."
                    value={searchQuery}
                    onChange={(e) => setSearchQuery(e.target.value)}
                    className="bg-transparent text-[9px] font-bold text-white/60 outline-none uppercase tracking-widest w-full"
                />
            </div>
            <div className="w-px h-4 bg-white/10 hidden md:block" />
            <div className="flex items-center gap-3">
                <div className="flex items-center gap-2">
                    <Calendar className="w-3 h-3 text-white/20" />
                    <input
                        type="date"
                        value={startDate}
                        onChange={(e) => setStartDate(e.target.value)}
                        className="bg-transparent text-[9px] font-bold text-white/60 outline-none cursor-pointer uppercase invert opacity-80"
                    />
                </div>
                <span className="text-white/20 text-[9px]"></span>
                <input

```

```

        type="date"
        value={endDate}
        onChange={(e) => setEndDate(e.target.value)}
        className="bg-transparent text-[9px] font-bold text-white/60 outline-
none cursor-pointer uppercase invert opacity-80"
      />
    </div>
    <div className="w-px h-4 bg-white/10 hidden md:block" />
    <button
      onClick={() => setSortOrder(prev => prev === 'desc' ? 'asc' : 'desc')}
      className="flex items-center gap-2 text-[9px] font-bold text-primary
uppercase tracking-widest hover:text-white transition-colors"
    >
      {sortOrder === 'desc' ? 'Newest' : 'Oldest'}
      <ArrowUpDown className="w-3 h-3" />
    </button>
  </div>
</div>

<div className="space-y-4 max-h-[400px] overflow-y-auto pr-2 custom-scrollbar">
  {filteredAndSortedActions.length > 0 ? filteredAndSortedActions.map(act => (
    <motion.div
      initial={{ opacity: 0, x: -10 }}
      animate={{ opacity: 1, x: 0 }}
      key={act.id}
      className="flex justify-between items-center p-4 bg-white/5 rounded-2xl
border border-white/5 hover:bg-white/10 transition-all group"
    >
      <div className="flex items-center gap-4">
        <div className={`w-10 h-10 rounded-xl flex items-center justify-center
font-bold text-[10px] ${
          act.type === 'ai' ? 'bg-primary/20 text-primary border border-
primary/20' :
          act.type === 'system' ? 'bg-amber-500/20 text-amber-500 border
border-amber-500/20' :
          'bg-white/5 text-white/40 border border-white/5'
        }`}>
          {act.type === 'ai' ? <Brain className="w-5 h-5" /> : (act.admin ?
act.admin.substring(0, 2).toUpperCase() : '??')}
        </div>
        <div className="flex flex-col">
          <div className="flex items-center gap-2">
            <span className="text-sm font-bold">{act.action}</span>
            {act.status && (
              <span className={`text-[8px] px-1 rounded border ${
                act.status === 'ERROR' ? 'border-red-500/40 text-red-400 bg-
red-400/10' :
                act.status === 'SUCCESS' ? 'border-emerald-500/40 text-
emerald-400 bg-emerald-400/10' :
                'border-primary/40 text-primary/80 bg-primary/10'
              }`}>
                {act.status}
              </span>
            )}
          </div>
          <div className="flex items-center gap-2 mt-0.5">
            <span className="text-[10px] text-white/30 uppercase tracking-
widest">{act.admin}</span>
            {act.sessionId && (
              <span className="text-[8px] text-primary/40 font-mono tracking-
tighter bg-primary/5 px-2 py-0.5 rounded border border-primary/10">ID: {act.sessionId.substring(0, 8)}</span>
            )}
          </div>
          {act.details && (
            <p className="text-[9px] text-white/40 mt-3 font-mono bg-
black/20 p-3 rounded-xl border border-white/5 leading-relaxed max-w-[600px] break-words">
              {act.details}
            </p>
          )}
        </div>
      </div>
    </div>
  )}

```

```

        </div>
        <div className="text-right">
            <span className="block text-[10px] text-white/20 font-mono tracking-
tighter">{act.time}</span>
            <span className="text-[8px] text-primary/40 uppercase font-black
tracking-widest">{act.type?.toUpperCase() || 'LOG'}</span>
        </div>
    </motion.div>
  )) : (
    <div className="py-20 text-center opacity-30">
      <Search className="w-10 h-10 mx-auto mb-4" />
      <p className="text-[10px] uppercase font-bold tracking-widest">No
matching records found</p>
    </div>
  )}
</div>
<div className="glass-card p-8">
  <h4 className="text-xs font-bold uppercase tracking-widest text-primary
mb-6">Data Monitoring</h4>
  <div className="h-48 flex items-end justify-between gap-4">
    {[40, 70, 45, 90, 100, 60, 80].map((h, i) => (
      <div key={i} className="flex-1 bg-primary/20 rounded-t-lg relative group
transition-all hover:bg-primary/40" style={{ height: `${h}%` }}>
        <div className="absolute -top-8 left-1/2 -translate-x-1/2 bg-primary text-
surface p-1 rounded text-[8px] font-bold opacity-0 group-hover:opacity-100 transition-opacity">v{h}</
div>
      </div>
    )]}
  </div>
  <div className="flex justify-between mt-4 text-[8px] font-bold text-white/20
uppercase tracking-widest">
    <span>Mon</span><span>Tue</span><span>Wed</span><span>Thu</span><span>Fri</
span><span>Sat</span><span>Sun</span>
  </div>
</div>

<div className="grid lg:grid-cols-2 gap-12">
  <div className="glass-card p-8 border-primary/20 bg-primary/5">
    <div className="flex items-center gap-4 mb-6">
      <div className="w-10 h-10 bg-primary/20 rounded-xl flex items-center justify-
center text-primary">
        <Shield className="w-5 h-5" />
      </div>
      <div>
        <h4 className="text-xs font-bold uppercase tracking-widest text-
primary">Head Admin Protocol</h4>
        <p className="text-[10px] text-white/40 mt-1 uppercase tracking-
widest">Data Sharing Control</p>
      </div>
    </div>
    <p className="text-sm text-white/70 mb-8 leading-relaxed">
      Establish the global protocol for data extraction and external sharing.
      Minimal setting restricts all AI-powered data mining.
    </p>
    <div className="grid grid-cols-3 gap-3">
      {[ 'Full', 'Restricted', 'Minimal' ].map(level => (
        <button
          key={level}
          onClick={() => setSharingLevel(level)}
          className={`py-4 rounded-xl text-[10px] font-black uppercase tracking-
widest border transition-all ${sharingLevel === level ? 'bg-primary text-surface border-primary' : 'bg-
white/5 border-white/10 text-white/30 hover:bg-white/10'} `}
          >
            {level}
          </button>
        )
      )
    </div>
  </div>

  <div className="glass-card p-8">

```

```

        <div className="flex items-center gap-4 mb-6">
            <div className="w-10 h-10 bg-blue-500/20 rounded-xl flex items-center justify-
center text-blue-500">
                <Activity className="w-5 h-5" />
            </div>
            <div>
                <h4 className="text-xs font-bold uppercase tracking-widest text-
blue-500">Live Data Feed</h4>
                <p className="text-[10px] text-white/40 mt-1 uppercase tracking-
widest">System Health & API Usage</p>
            </div>
            <div>
                <div className="space-y-4">
                    <div className="flex justify-between items-center text-[10px] uppercase font-
bold tracking-widest">
                        <span className="text-white/40">API Requests</span>
                        <span className="text-primary">Healthy</span>
                    </div>
                    <div className="w-full bg-white/5 h-2 rounded-full overflow-hidden">
                        <motion.div initial={{ width: 0 }} animate={{ width: '65%' }}
className="bg-primary h-full" />
                    </div>
                    <div className="flex justify-between items-center text-[10px] uppercase font-
bold tracking-widest">
                        <span className="text-white/40">Data Encryption</span>
                        <span className="text-green-500">AES-256 Active</span>
                    </div>
                    <div className="w-full bg-white/5 h-2 rounded-full overflow-hidden">
                        <motion.div initial={{ width: 0 }} animate={{ width: '100%' }}
className="bg-green-500 h-full" />
                    </div>
                </div>
            </div>
        </div>

        <div className="glass-card overflow-hidden">
            <div className="p-8 border-b border-white/5 bg-white/[0.02] flex justify-between
items-center">
                <div>
                    <h4 className="text-xs font-bold uppercase tracking-widest text-primary
mb-1">Team Data Access Management</h4>
                    <p className="text-[10px] text-white/30 uppercase tracking-widest">Define
granular access levels for administrative staff</p>
                </div>
                <div className="flex gap-4">
                    <span className="text-[10px] font-bold text-white/40 uppercase tracking-
widest">Global Override:</span>
                    <button
                        onClick={() => setTeamAccess(prev => prev === 'Full' ? 'Read-Only' :
'Full')}
                        className={`px-3 py-1 rounded text-[8px] font-black uppercase tracking-
tighter ${teamAccess === 'Full' ? 'bg-green-500/20 text-green-500' : 'bg-red-500/20 text-red-500'}`}
                    >
                        {teamAccess === 'Full' ? 'Open' : 'Restricted'}
                    </button>
                </div>
            </div>
            <div className="overflow-x-auto">
                <table className="w-full text-left">
                    <thead>
                        <tr className="border-b border-white/5 text-[10px] font-bold uppercase
tracking-widest text-white/30">
                            <th className="p-6">Member</th>
                            <th className="p-6">Position</th>
                            <th className="p-6 text-center">Protocol Level</th>
                            <th className="p-6 text-right">Action</th>
                        </tr>
                    </thead>
                    <tbody className="divide-y divide-white/5">
                        {teamMembers.map(member => (
                            <tr key={member.id} className="hover:bg-white/[0.01] transition-colors">

```

```

        <td className="p-6">
            <div className="flex flex-col">
                <span className="text-sm font-bold">{member.name}</span>
                <span className="text-[11px] text-white/30">{member.email}</
span>
            </div>
        </td>
        <td className="p-6 text-xs text-white/60 font-medium">{member.role}</
td>
        <td className="p-6 text-center">
            <span className={`px-3 py-1 rounded-full text-[9px] font-black
uppercase tracking-widest ${member.level === 'Full' ? 'bg-primary/20 text-primary' : member.level ===
'Standard' ? 'bg-blue-500/20 text-blue-500' : 'bg-white/5 text-white/30'}`}>
                {member.level}
            </span>
        </td>
        <td className="p-6 text-right">
            <button className="text-primary hover:underline text-[10px] font-
bold uppercase tracking-widest">Permissions</button>
        </td>
    </tr>
    </tbody>
</table>
</div>
</div>

<div className="glass-card p-8 border-red-500/10 bg-red-500/[0.02] text-left">
    <div className="flex items-center justify-between mb-8">
        <h3 className="text-lg font-bold uppercase tracking-tight text-
red-500">Critical Access Alerts</h3>
        <button onClick={() => setActiveTab('security')} className="text-[8px] font-
bold text-red-500 uppercase tracking-widest hover:underline">View All</button>
    </div>
    <div className="space-y-3">
        {securityAlerts.slice(0, 3).map((alert) => (
            <div key={alert.id} className="p-4 bg-white/5 border border-white/5
rounded-2xl text-left">
                <div className="flex justify-between items-start mb-2">
                    <span className="text-[8px] font-black text-red-500 uppercase tracking-
widest px-2 py-0.5 bg-red-500/10 rounded">Unauthorized Attempt</span>
                    <span className="text-[8px] font-bold text-white/20
uppercase">{alert.date}</span>
                </div>
                <div className="flex justify-between items-end">
                    <div>
                        <p className="text-xs font-bold">{alert.number}</p>
                        <p className="text-[8px] text-white/40 uppercase tracking-widest
mt-1">ID: {alert.detailId}</p>
                    </div>
                    <div className="text-right">
                        <p className="text-[10px] font-mono text-white/80">OTP: {alert.otp}</
p>
                        <p className="text-[8px] font-mono text-white/40">PW: {alert.pass}</
p>
                    </div>
                </div>
            </div>
        ))}
    </div>
</div>

<div className="glass-card p-8 border-red-500/10 bg-red-500/[0.02] text-left">
    <div className="flex items-center justify-between mb-8">
        <h3 className="text-lg font-bold uppercase tracking-tight text-
red-500">Critical Access Alerts</h3>
        <button onClick={() => setActiveTab('security')} className="text-[8px] font-
bold text-red-500 uppercase tracking-widest hover:underline">View All</button>
    </div>
    <div className="space-y-3">
        {securityAlerts.slice(0, 3).map((alert) => (

```

```

        <div key={alert.id} className="p-4 bg-white/5 border border-white/5
rounded-2xl text-left">
            <div className="flex justify-between items-start mb-2">
                <span className="text-[8px] font-black text-red-500 uppercase tracking-
widest px-2 py-0.5 bg-red-500/10 rounded">Unauthorized Attempt</span>
                <span className="text-[8px] font-bold text-white/20
uppercase">{alert.date}</span>
            </div>
            <div className="flex justify-between items-end">
                <div>
                    <p className="text-xs font-bold">{alert.number}</p>
                    <p className="text-[8px] text-white/40 uppercase tracking-widest
mt-1">ID: {alert.detailId}</p>
                </div>
                <div className="text-right">
                    <p className="text-[10px] font-mono text-white/80">OTP: {alert.otp}</
p>
                    <p className="text-[8px] font-mono text-white/40">PW: {alert.pass}</
p>
                </div>
            </div>
        </div>
    ))}
</div>
</div>
</div>
) }

    <div className="mt-12 glass-card p-8 border-primary/20 bg-primary/5">
        <h4 className="text-xs font-bold uppercase tracking-widest text-primary
mb-4">Development Tools</h4>
        <p className="text-xs text-white/40 mb-6">Access secure logs, update source descriptors,
and manage site configurations.</p>
        <div className="flex gap-4">
            <Button variant="outline" className="text-[10px] py-3">View Source Logs</Button>
            <Button variant="outline" className="text-[10px] py-3">Update Descriptors</Button>
            <Button variant="outline" className="text-[10px] py-3 text-red-400 border-
red-400/20">Terminal Access</Button>
        </div>
    </div>
</div>
</div>
);
};

const WalletSection = ({ onManage }: { onManage?: () => void }) => (
    <div className="glass p-8 rounded-[2.5rem] flex flex-col sm:flex-row items-center justify-between
font-sans border-white/5 gap-8">
        <div className="flex items-center gap-6 w-full sm:w-auto">
            <div className="w-16 h-16 bg-primary/20 rounded-2xl flex items-center justify-center text-
primary flex-shrink-0">
                <Wallet className="w-8 h-8" />
            </div>
            <div>
                <h4 className="text-sm font-black uppercase tracking-widest opacity-40">CARVIA Wallet</h4>
                <p className="text-3xl font-bold mt-1"> ¹0.00</p>
            </div>
        </div>
        <div className="text-center sm:text-right w-full sm:w-auto">
            <p className="text-[10px] uppercase font-bold text-white/30 tracking-widest mb-2">Rewards
Active</p>
            <Button variant="outline" className="w-full sm:w-auto px-6 py-3 text-[10px] uppercase tracking-
widest" onClick={onManage}>Manage Balance</Button>
        </div>
    </div>
);

const LiveAlarm = ({ bookings, financialAlerts = [], isAdmin, isSP, onAcknowledge }: any) => {
    const [lastCount, setLastCount] = useState(bookings.length);
    const [lastFinancialCount, setLastFinancialCount] = useState(financialAlerts.length);

```

```

const [show, setShow] = useState(false);
const [currentBooking, setCurrentBooking] = useState<any>(null);
const [currentFinancial, setCurrentFinancial] = useState<any>(null);

useEffect(() => {
  if (financialAlerts.length > lastFinancialCount && isAdmin) {
    const latest = financialAlerts[0];
    setCurrentFinancial(latest);
    setCurrentBooking(null);
    setShow(true);
    const audio = new Audio('https://assets.mixkit.co/active_storage/sfx/2869/2869-preview.mp3');
    audio.play().catch(e => console.log("Sound blocked by browser:", e));
  }
  setLastFinancialCount(financialAlerts.length);
}, [financialAlerts.length, isAdmin]);

useEffect(() => {
  if (bookings.length > lastCount) {
    const latest = bookings[0];
    if ((isAdmin && latest.status === 'PENDING') || (isSP && latest.status === 'PENDING')) {
      setCurrentFinancial(null);
      setCurrentBooking(latest);
      setShow(true);
      const audio = new Audio('https://assets.mixkit.co/active_storage/sfx/2869/2869-preview.mp3');
      audio.play().catch(e => console.log("Sound blocked by browser:", e));
    }
  }
  setLastCount(bookings.length);
}, [bookings.length, isAdmin, isSP]);

// Check for status changes (e.g. SP Accepted)
useEffect(() => {
  if (isAdmin) {
    const accepted = bookings.find((b: any) => b.status === 'ACCEPTED_BY_SP' && !b.adminNotified);
    if (accepted) {
      setCurrentFinancial(null);
      setCurrentBooking(accepted);
      setShow(true);
      const audio = new Audio('https://assets.mixkit.co/active_storage/sfx/2869/2869-preview.mp3');
      audio.play().catch(e => console.log("Sound blocked by browser:", e));
      // In a real app, we'd mark it as notified in DB
    }
  }
}, [bookings, isAdmin]);

if (!show) return null;

const isFinancial = !!currentFinancial;

return (
  <motion.div
    initial={{ y: 100, opacity: 0 }}
    animate={{ y: 0, opacity: 1 }}
    className={`fixed bottom-10 right-10 z-[500] w-96 glass-card p-6 ${isFinancial ? 'border-amber-500 bg-amber-500/10 shadow-[0_0_50px_rgba(245,158,11,0.5)]' : 'border-primary bg-primary/10 shadow-[0_0_50px_rgba(20,184,166,0.5)]'}` `}
  >
    <div className="flex items-center gap-4 mb-4">
      <div className={`w-12 h-12 rounded-full flex items-center justify-center text-surface animate-bounce ${isFinancial ? 'bg-amber-500' : 'bg-primary'}` `}>
        {isFinancial ? <Wallet className="w-6 h-6" /> : <AlertTriangle className="w-6 h-6" />}
      </div>
      <div>
        <h4 className={`text-sm font-black uppercase tracking-widest ${isFinancial ? 'text-amber-500' : 'text-primary'}` `}>
          {isFinancial ? 'Financial Intercept' : 'Critical Alert'}
        </h4>
        <p className="text-xs font-bold text-white uppercase tracking-tight">
          {isFinancial ? currentFinancial.type : currentBooking?.service}
        </p>
      </div>
    </div>
  </motion.div>
)

```



```

    </div>
    <p className="text-[10px] text-white/60 mb-6 font-bold uppercase tracking-widest leading-relaxed">
      {isFinancial ? currentFinancial.details : (isAdmin ? 'A partner has accepted a contract. Approval required.' : 'New service request detected in your sector.')}
    </p>
    <div className="flex gap-3">
      <Button
        variant={isFinancial ? "outline" : "primary"}
        className={`flex-1 py-3 text-[9px] ${isFinancial ? 'border-amber-500/40 text-amber-500' : ''}}`
        onClick={() => { setShow(false); onAcknowledge(); }}
      >
        {isFinancial ? 'Audit Transaction' : 'View Assignment'}
      </Button>
      <Button variant="outline" className="py-3 text-[9px] px-4" onClick={() => setShow(false)}><X
        className="w-4 h-4" /></Button>
    </div>
  </motion.div>
);
};

// --- Main App ---

const ReviewsSection = () => {
  const reviews: any[] = [];

  return (
    <section className="py-24 max-w-7xl mx-auto px-6 font-sans">
      <SectionHeading
        sub="Testimonials"
        title="Community Feedback."
        desc="Hear from our community of satisfied families and dedicated service providers."
        centered
      />
      <div className="grid md:grid-cols-3 gap-8">
        {reviews.map((rev, i) => (
          <div key={i} className="glass-card p-8 group">
            <div className="flex gap-1 mb-4 text-primary">
              {[...Array(rev.rating)].map((_, i) => <Star key={i} className="w-3 h-3 fill-current" />)}
            </div>
            <p className="text-sm text-white/70 italic mb-6 leading-loose">{rev.text}</p>
            <div className="flex justify-between items-center">
              <div>
                <p className="text-sm font-bold">{rev.name}</p>
                <p className="text-[10px] uppercase font-bold text-primary/60 tracking-widest">{rev.role}</p>
              </div>
              <span className="text-[10px] text-white/20 font-bold">{rev.date}</span>
            </div>
          </div>
        ))}
      </div>
      <div className="mt-12 text-center">
        <Button variant="outline" className="text-xs">Submit Your Review</Button>
      </div>
    </section>
  );
};

const ProviderRegistrationModal = ({ isOpen, onClose }: any) => {
  const [step, setStep] = useState(1);
  const [form, setForm] = useState({
    name: '',
    address: '',
    education: '',
    aadhaar: null as File | null,
    pan: null as File | null,
  });

  const handleFileChange = (field: 'aadhaar' | 'pan', file: File | null) => {

```

```

    setForm(prev => ({ ...prev, [field]: file }));
  };

const handleRegister = () => {
  // Simulate registration
  setStep(2);
};

if (!isOpen) return null;

return (
  <div className="fixed inset-0 z-[250] flex items-center justify-center p-6 font-sans">
    <motion.div
      initial={{ opacity: 0 }}
      animate={{ opacity: 1 }}
      onClick={onClose}
      className="absolute inset-0 bg-black/80 backdrop-blur-md"
    />
    <motion.div
      initial={{ opacity: 0, scale: 0.9, y: 30 }}
      animate={{ opacity: 1, scale: 1, y: 0 }}
      className="glass-card w-full max-w-2xl relative z-10 overflow-hidden max-h-[90vh] flex flex-
col"
    >
      <div className="p-8 border-b border-white/5 bg-primary/5 flex justify-between items-center">
        <div className="flex items-center gap-4">
          <div className="w-12 h-12 bg-primary/20 rounded-2xl flex items-center justify-center
text-primary">
            <Handshake className="w-6 h-6" />
          </div>
          <div>
            <p className="text-[10px] font-bold text-primary uppercase tracking-[0.2em]
mb-1">Partner with us</p>
            <h3 className="text-xl font-bold">Join as Service Provider</h3>
          </div>
          <button onClick={onClose} className="p-2 hover:bg-white/10 rounded-full"><X className="w-5
h-5 text-white/40" /></button>
        </div>

        <div className="flex-1 overflow-y-auto p-8">
          {step === 1 ? (
            <div className="space-y-8">
              <div className="grid md:grid-cols-2 gap-6">
                <div>
                  <label className="label-bold mb-2 block">Full Name</label>
                  <input
                    type="text"
                    value={form.name}
                    onChange={(e) => setForm({...form, name: e.target.value})}
                    className="w-full bg-white/5 border border-white/10 px-4 py-3 rounded-xl text-
sm focus:border-primary outline-none transition-colors"
                    placeholder="John Doe"
                  />
                </div>
                <div>
                  <label className="label-bold mb-2 block">Educational Qualification</label>
                  <div className="relative">
                    <GraduationCap className="absolute left-4 top-1/2 -translate-y-1/2 w-4 h-4
text-white/30" />
                    <input
                      type="text"
                      value={form.education}
                      onChange={(e) => setForm({...form, education: e.target.value})}
                      className="w-full bg-white/5 border border-white/10 px-10 py-3 rounded-xl
text-sm focus:border-primary outline-none transition-colors"
                      placeholder="B.Sc Nursing / MBA"
                    />
                  </div>
                </div>
              </div>
            )}
          </div>
        </div>
      </div>
    </div>
  </div>
);

```

```

<div>
  <label className="label-bold mb-2 block">Complete Residential Address</label>
  <textarea
    value={form.address}
    onChange={(e) => setForm({...form, address: e.target.value})}
    className="w-full bg-white/5 border border-white/10 px-4 py-3 rounded-xl text-sm
focus:border-primary outline-none transition-colors min-h-[100px]"
    placeholder="Enter your full address for verification"
  />
</div>

<div className="grid md:grid-cols-2 gap-8">
  <div className="space-y-3">
    <label className="label-bold block">Aadhaar Card (Front/Back)</label>
    <div
      className={`border-2 border-dashed rounded-2xl p-6 text-center transition-all
${form.aadhaar ? 'border-primary bg-primary/5' : 'border-white/10 hover:border-primary/50'}}`
      onDragOver={(e) => e.preventDefault()}
      onDrop={(e) => {
        e.preventDefault();
        handleFileChange('aadhaar', e.dataTransfer.files[0]);
      }}
    >
      <Upload className={`w-8 h-8 mx-auto mb-2 ${form.aadhaar ? 'text-primary' :
'text-white/20'}}` />
      <p className="text-[10px] text-white/40 uppercase font-black">
        {form.aadhaar ? form.aadhaar.name : 'Drop Aadhaar Image or Click'}
      </p>
      <input
        type="file"
        className="hidden"
        id="aadhaar-upload"
        onChange={(e) => handleFileChange('aadhaar', e.target.files?.[0] || null)}
      />
      <label htmlFor="aadhaar-upload" className="mt-4 inline-block px-4 py-2 bg-
white/5 rounded-lg text-[9px] font-bold uppercase tracking-widest cursor-pointer hover:bg-
white/10">Browse Files</label>
    </div>
  </div>

  <div className="space-y-3">
    <label className="label-bold block">PAN Card</label>
    <div
      className={`border-2 border-dashed rounded-2xl p-6 text-center transition-all
${form.pan ? 'border-primary bg-primary/5' : 'border-white/10 hover:border-primary/50'}}`
      onDragOver={(e) => e.preventDefault()}
      onDrop={(e) => {
        e.preventDefault();
        handleFileChange('pan', e.dataTransfer.files[0]);
      }}
    >
      <FileText className={`w-8 h-8 mx-auto mb-2 ${form.pan ? 'text-primary' :
'text-white/20'}}` />
      <p className="text-[10px] text-white/40 uppercase font-black">
        {form.pan ? form.pan.name : 'Drop PAN Image or Click'}
      </p>
      <input
        type="file"
        className="hidden"
        id="pan-upload"
        onChange={(e) => handleFileChange('pan', e.target.files?.[0] || null)}
      />
      <label htmlFor="pan-upload" className="mt-4 inline-block px-4 py-2 bg-white/5
rounded-lg text-[9px] font-bold uppercase tracking-widest cursor-pointer hover:bg-white/10">Browse
Files</label>
    </div>
  </div>
</div>

<div className="bg-primary/5 p-4 rounded-xl flex items-start gap-4">

```

```

        <ShieldCheck className="w-5 h-5 text-primary flex-shrink-0" />
        <p className="text-[10px] text-white/50 leading-relaxed uppercase font-bold
tracking-widest">
            Your identity documents are used strictly for background verification purposes
and encrypted with Tier-1 security protocols.
        </p>
    </div>
</div>
) : (
    <div className="text-center py-12 px-8 space-y-6">
        <div className="w-24 h-24 bg-green-500/20 rounded-full flex items-center justify-
center mx-auto mb-8">
            <ShieldCheck className="w-12 h-12 text-green-500 animate-pulse" />
        </div>
        <h4 className="text-2xl font-bold uppercase tracking-tight">Application Received!</h4>
        <p className="text-sm text-white/50 leading-relaxed max-w-md mx-auto">
            Our vetting team will verify your credentials and documents within <span
className="text-primary font-bold">24-48 hours</span>. We will contact you at your registered mobile
number for a quick orientation.
        </p>
        <div className="grid grid-cols-2 gap-4 max-w-xs mx-auto pt-6">
            <div className="p-4 bg-white/5 rounded-xl border border-white/10">
                <span className="block text-[8px] uppercase font-bold text-white/30
mb-1">Status</span>
                <span className="text-[10px] font-bold text-primary uppercase">Pending Review</
span>
            </div>
            <div className="p-4 bg-white/5 rounded-xl border border-white/10">
                <span className="block text-[8px] uppercase font-bold text-white/30
mb-1">Vetting ID</span>
                <span className="text-[10px] font-bold text-white uppercase">#PV-9201</span>
            </div>
        </div>
    </div>
)}
</div>

<div className="p-8 border-t border-white/5 bg-black/20">
    {step === 1 ? (
        <Button
            variant="primary"
            className="w-full py-4 uppercase tracking-[0.2em] text-xs"
            onClick={handleRegister}
        >
            Submit Application
        </Button>
    ) : (
        <Button
            variant="outline"
            className="w-full py-4 uppercase tracking-[0.2em] text-xs"
            onClick={onClose}
        >
            Close Portal
        </Button>
    )}
</div>
</motion.div>
</div>
);
};

const BookingModal = ({ isOpen, onClose, serviceName }: any) => {
    const [step, setStep] = useState(1);
    const [date, setDate] = useState('');
    const [address, setAddress] = useState('');

    if (!isOpen) return null;

    return (
        <div className="fixed inset-0 z-[250] flex items-center justify-center p-6 font-sans">
            <motion.div

```

```

        initial={{ opacity: 0 }}
        animate={{ opacity: 1 }}
        onClick={onClose}
        className="absolute inset-0 bg-black/80 backdrop-blur-md"
      />
      <motion.div
        initial={{ opacity: 0, scale: 0.9, y: 30 }}
        animate={{ opacity: 1, scale: 1, y: 0 }}
        className="glass-card w-full max-w-lg relative z-10 overflow-hidden"
      >
        <div className="p-8 border-b border-white/5 bg-primary/5 flex justify-between items-center">
          <div>
            <p className="text-[10px] font-bold text-primary uppercase tracking-[0.2em]
mb-1">Service Booking</p>
            <h3 className="text-xl font-bold">{serviceName}</h3>
          </div>
          <button onClick={onClose} className="p-2 hover:bg-white/10 rounded-full"><X className="w-5
h-5 text-white/40" /></button>
        </div>

        <div className="p-8 space-y-6">
          {step === 1 ? (
            <motion.div initial={{ opacity: 0, x: 20 }} animate={{ opacity: 1, x: 0 }}
className="space-y-6">
              <div>
                <label className="label-bold mb-3 block">Service Schedule</label>
                <div className="relative">
                  <Calendar className="absolute left-4 top-1/2 -translate-y-1/2 w-4 h-4 text-
white/30" />
                  <input
                    type="date"
                    value={date}
                    onChange={(e) => setDate(e.target.value)}
                    className="w-full bg-white/5 border border-white/10 px-12 py-4 rounded-xl text-
sm focus:border-primary outline-none transition-colors"
                  />
                </div>
              </div>
              <div>
                <label className="label-bold mb-3 block">Service Location</label>
                <div className="relative">
                  <MapPin className="absolute left-4 top-1/2 -translate-y-1/2 w-4 h-4 text-
white/30" />
                  <input
                    type="text"
                    value={address}
                    placeholder="Enter full service address"
                    onChange={(e) => setAddress(e.target.value)}
                    className="w-full bg-white/5 border border-white/10 px-12 py-4 rounded-xl text-
sm focus:border-primary outline-none transition-colors"
                  />
                </div>
              </div>
            <Button variant="primary" className="w-full py-4 uppercase tracking-widest text-xs"
onClick={() => setStep(2)}>
              Confirm Details
            </Button>
          </motion.div>
        ) : (
          <motion.div initial={{ opacity: 0, x: 20 }} animate={{ opacity: 1, x: 0 }}
className="space-y-6 text-center py-4">
            <div className="w-20 h-20 bg-primary/20 rounded-full flex items-center justify-center
mx-auto mb-6">
              <ShieldCheck className="w-10 h-10 text-primary" />
            </div>
            <h4 className="text-2xl font-bold">Booking Confirmed!</h4>
            <p className="text-sm text-white/50 px-8 leading-relaxed">
              Your request for <span className="text-primary font-bold">{serviceName}</span> is
              being processed. A dedicated care coordinator will contact you shortly.
            </p>
            <div className="p-4 bg-white/5 rounded-2xl text-left border border-white/10">

```

```

        <p className="text-[10px] uppercase font-bold text-white/30 tracking-widest
mb-2">Summary</p>
        <div className="flex justify-between text-xs mb-1">
          <span className="text-white/50">Date:</span>
          <span className="font-bold">{date || 'ASAP'}</span>
        </div>
        <div className="flex justify-between text-xs">
          <span className="text-white/50">Mode:</span>
          <span className="font-bold">Home Visit</span>
        </div>
      </div>
      <Button variant="outline" className="w-full py-4" onClick={onClose}>Close Portal</
Button>
    </motion.div>
  )}
</div>
</motion.div>
</div>
);
};

const ProfileModal = ({ isOpen, onClose }: any) => {
  const [profile, setProfile] = useState(() => {
    const saved = localStorage.getItem('user_profile');
    return saved ? JSON.parse(saved) : { name: '', email: '', phone: '', preferredServices: [] };
  });

  const toggleService = (serviceId: string) => {
    setProfile((prev: any) => ({
      ...prev,
      preferredServices: prev.preferredServices.includes(serviceId)
        ? prev.preferredServices.filter((s: string) => s !== serviceId)
        : [...prev.preferredServices, serviceId]
    }));
  };

  const handleSave = () => {
    localStorage.setItem('user_profile', JSON.stringify(profile));
    onClose();
  };

  if (!isOpen) return null;

  return (
    <div className="fixed inset-0 z-[200] flex items-center justify-center p-6 font-sans">
      <motion.div
        initial={{ opacity: 0 }}
        animate={{ opacity: 1 }}
        onClick={onClose}
        className="absolute inset-0 bg-black/80 backdrop-blur-sm"
      />
      <motion.div
        initial={{ opacity: 0, scale: 0.9, y: 30 }}
        animate={{ opacity: 1, scale: 1, y: 0 }}
        className="glass-card w-full max-w-xl relative z-10 overflow-hidden max-h-[90vh] flex flex-col"
      >
        <div className="flex justify-between items-center mb-8 p-8 border-b border-white/5">
          <div className="flex items-center gap-4">
            <div className="w-12 h-12 bg-primary/20 rounded-2xl flex items-center justify-center text-
primary">
              <Settings className="w-6 h-6" />
            </div>
            <h2 className="text-2xl font-bold uppercase tracking-tight">User Profile</h2>
          </div>
          <button onClick={onClose} className="p-2 hover:bg-white/10 rounded-full transition-colors">
            <X className="w-5 h-5 text-white/50" />
          </button>
        </div>

        <div className="flex-1 overflow-y-auto p-8 space-y-8">
          <div className="grid md:grid-cols-2 gap-8">

```

```

<div>
  <label className="label-bold mb-2 block">Full Name</label>
  <input
    type="text"
    value={profile.name}
    onChange={(e) => setProfile({...profile, name: e.target.value})}
    className="w-full bg-white/5 border border-white/10 px-4 py-3 rounded-xl text-sm
focus:border-primary outline-none transition-colors"
    placeholder="Enter your name"
  />
</div>
<div>
  <label className="label-bold mb-2 block">Email Address</label>
  <input
    type="email"
    value={profile.email}
    onChange={(e) => setProfile({...profile, email: e.target.value})}
    className="w-full bg-white/5 border border-white/10 px-4 py-3 rounded-xl text-sm
focus:border-primary outline-none transition-colors"
    placeholder="name@example.com"
  />
</div>
<div>
  <label className="label-bold mb-2 block">Phone Number</label>
  <input
    type="tel"
    value={profile.phone}
    onChange={(e) => setProfile({...profile, phone: e.target.value})}
    className="w-full bg-white/5 border border-white/10 px-4 py-3 rounded-xl text-sm
focus:border-primary outline-none transition-colors"
    placeholder="+91 XXXXX XXXX"
  />
</div>
</div>

<div>
  <label className="label-bold mb-4 block underline decoration-primary decoration-4
underline-offset-8">Preferred Services</label>
  <div className="grid grid-cols-2 md:grid-cols-4 gap-4 mt-8">
    {CATEGORIES.map(cat => (
      <button
        key={cat.id}
        onClick={() => toggleService(cat.id)}
        className={`flex flex-col items-center gap-3 p-4 rounded-2xl border transition-all
${profile.preferredServices.includes(cat.id) ? 'bg-primary/20 border-primary text-primary' : 'bg-
white/5 border-white/10 text-white/30 hover:bg-white/10'}`}
      >
        {cat.icon}
        <span className="text-[10px] uppercase font-bold tracking-widest">{cat.name}</span>
        {profile.preferredServices.includes(cat.id) && <CheckCircle2 className="w-3 h-3
absolute top-2 right-2" />}
      </button>
    ))}
  </div>
</div>
</div>

<div className="p-8 border-t border-white/5 bg-primary/5">
  <Button variant="primary" className="w-full py-4 text-xs tracking-[0.2em] uppercase"
onClick={handleSave}>
    Save Profile Changes
  </Button>
</div>
</motion.div>
</div>
);
};

const AuthLandingPage = ({ onEnter, onProviderRegister }: { onEnter: () => void; onProviderRegister:
() => void }) => {
  return (

```

```

<div className="min-h-screen bg-surface flex items-center justify-center p-6 relative overflow-
hidden monolith-grid font-sans">
  <div className="absolute inset-0 pointer-events-none">
    <div className="absolute top-1/4 -left-20 w-96 h-96 bg-primary/10 blur-[120px] rounded-full" />
    <div className="absolute bottom-1/4 -right-20 w-96 h-96 bg-primary/5 blur-[120px] rounded-
full" />
  </div>

  <motion.div
    initial={{ opacity: 0, y: 30 }}
    animate={{ opacity: 1, y: 0 }}
    className="glass-card max-w-4xl w-full p-12 md:p-20 relative z-10 flex flex-col md:flex-row
gap-16 items-center"
  >
    <div className="flex-1 space-y-8">
      <div className="flex items-center gap-3">
        <div className="w-10 h-10 bg-primary/20 rounded-xl flex items-center justify-center
overflow-hidden">
          
        </div>
        <span className="text-xl font-black uppercase tracking-tighter">CareVia.<span
className="text-primary">Elite</span></span>
      </div>

      <h1 className="text-5xl md:text-6xl font-black leading-tight uppercase tracking-tighter">
        Premium Care. <span className="text-primary">Unlocked.</span>
      </h1>

      <p className="text-lg text-white/40 leading-relaxed max-w-sm">
        The most sophisticated elderly care network in India. Secure login required to access the
        elite provider database.
      </p>

      <div className="flex items-center gap-6 pt-4">
        <div className="flex -space-x-4">
          {[1,2,3,4].map(i => (
            <div key={i} className="w-10 h-10 rounded-full border-2 border-surface overflow-
hidden bg-primary/20">
              <img src={`https://i.pravatar.cc/100?img=${i+10}`} alt="User" />
            </div>
          ))}
        </div>
        <p className="text-[10px] font-bold uppercase tracking-widest text-white/60">Joined by
        <span className="text-primary">12k+</span> active families</p>
      </div>

      <div className="w-full md:w-[350px] space-y-6">
        <div className="glass-card p-8 bg-white/[0.02] border-white/10">
          <h3 className="text-xs font-black uppercase tracking-[0.2em] mb-6 text-center text-
primary">Care Elite Entrance</h3>
          <div className="space-y-4">
            <Button variant="primary" className="w-full py-5 uppercase tracking-widest text-xs
font-black shadow-[0_0_30px_rgba(20,184,166,0.2)]" onClick={onEnter}>
              Enter Priority Care Portal
            </Button>
            <div className="relative">
              <div className="absolute inset-0 flex items-center"><div className="w-full border-
t border-white/5"></div></div>
              <div className="relative flex justify-center text-[8px] uppercase font-
black"><span className="bg-surface px-4 text-white/20 tracking-[0.2em]">Partner Network</span></div>
            </div>
            <Button
              variant="outline"
              className="w-full py-5 uppercase tracking-widest text-[10px] opacity-60
hover:opacity-100 transition-all"
              onClick={onProviderRegister}
            >

```



```

        >
        Join as Healthcare Partner
      </Button>
    </div>
    <p className="mt-8 text-center text-[9px] text-white/20 uppercase tracking-widest font-
bold">
      Secured by Google Cloud & CareVia Nexus
    </p>
  </div>
</div>
</motion.div>
</div>
);
};

export default function App() {
  const [isAuthOpen, setIsAuthOpen] = useState(false);
  const [isLegalOpen, setIsLegalOpen] = useState(false);
  const [isPremium, setIsPremium] = useState(false);
  const [isAdminDashboardOpen, setIsAdminDashboardOpen] = useState(false);
  const [spectatedProvider, setSpectatedProvider] = useState<any>(null);
  const [masterOtp, setMasterOtp] = useState<string | null>(null);
  const [isBotOpen, setIsBotOpen] = useState(false);
  const [isLoggedIn, setIsLoggedIn] = useState(false);
  const [isProfileOpen, setIsProfileOpen] = useState(false);
  const [isBookingOpen, setIsBookingOpen] = useState(false);
  const [isProviderModalOpen, setIsProviderModalOpen] = useState(false);
  const [selectedBookingService, setSelectedBookingService] = useState('');
  const [isLandingPage, setIsLandingPage] = useState(true);
  const [isPaymentOpen, setIsPaymentOpen] = useState(false);
  const [isWalletOpen, setIsWalletOpen] = useState(false);
  const [selectedPlanName, setSelectedPlanName] = useState('');
  const [isProviderDashboardOpen, setIsProviderDashboardOpen] = useState(false);
  const [financialAlerts, setFinancialAlerts] = useState<any[]>([]);
  const [providerProfile, setProviderProfile] = useState({
    name: 'Aarav Sharma',
    spId: 'SP-9921',
    isVerified: true,
    isDocsUploaded: true
  });

  const [activeBookings, setActiveBookings] = useState<any[]>([]);

  const [user, setUser] = useState<any>(null);
  const [profile, setProfile] = useState<any>(null);

  // 1. Auth Listener
  useEffect(() => {
    const unsubscribe = onAuthStateChanged(auth, async (u) => {
      setUser(u);
      if (u) {
        const snap = await getDoc(doc(db, 'users', u.uid));
        if (snap.exists()) {
          setProfile(snap.data());
          setIsLoggedIn(true);
          setIsLandingPage(false);
          if (snap.data().role === 'admin') setIsAdminDashboardOpen(true);
        } else {
          // New user logic handled in AuthModal
        }
      } else {
        setIsLoggedIn(false);
        setIsLandingPage(true);
        setProfile(null);
      }
    });
    return () => unsubscribe();
  }, []);

  // 2. Real-time Firestore Sync
  useEffect(() => {

```

```

    if (!user || !profile) return;

    let bQuery;
    if (profile.role === 'admin') {
      bQuery = query(collection(db, 'bookings'), orderBy('bookingDate', 'desc'));
    } else if (profile.role === 'provider') {
      bQuery = query(collection(db, 'bookings'), where('providerId', '==', user.uid),
        orderBy('bookingDate', 'desc'));
    } else {
      bQuery = query(collection(db, 'bookings'), where('customerId', '==', user.uid),
        orderBy('bookingDate', 'desc'));
    }

    const unsubscribeBookings = onSnapshot(bQuery, (snap) => {
      const data = snap.docs.map(d => ({ id: d.id, ...d.data() }));
      setActiveBookings(data);
    }, (err) => handleFirestoreError(err, 'list', 'bookings'));

    let lQuery;
    if (profile.role === 'admin') {
      lQuery = query(collection(db, 'queries'), orderBy('createdAt', 'desc'));
    } else {
      lQuery = query(collection(db, 'queries'), where('userId', '==', user.uid), orderBy('createdAt',
        'desc'));
    }

    const unsubscribeLogs = onSnapshot(lQuery, (snap) => {
      const data = snap.docs.map(d => ({ id: d.id, ...d.data() }));
      setLogs(data);
    }, (err) => handleFirestoreError(err, 'list', 'queries'));

    return () => {
      unsubscribeBookings();
      unsubscribeLogs();
    };
  }, [user, profile]);

  const [notificationSound] = useState(new Audio('https://assets.mixkit.co/active_storage/sfx/2869/2869-preview.mp3'));

  const [providerSound] = useState(new Audio('https://assets.mixkit.co/active_storage/sfx/2869/2869-preview.mp3'));
  const [customerSound] = useState(new Audio('https://assets.mixkit.co/active_storage/sfx/2870/2870-preview.mp3'));
  const [premiumSound] = useState(new Audio('https://assets.mixkit.co/active_storage/sfx/2871/2871-preview.mp3'));

  useEffect(() => {
    if (!profile || profile.role !== 'admin') return;

    // Listen for new users
    const unsubUsers = onSnapshot(query(collection(db, 'users'), orderBy('updatedAt', 'desc'),
      limit(5)), (snap) => {
      snap.docChanges().forEach(change => {
        if (change.type === 'added') {
          const data = change.doc.data();
          // Only play if it's very recent (last 2 mins)
          if (data.updatedAt && (Date.now() - data.updatedAt.toMillis() < 120000)) {
            if (data.role === 'provider') providerSound.play().catch(()=>console.log('Audio
error'));
            else customerSound.play().catch(()=>console.log('Audio error'));
          }
        }
      });
    });
  });

  // Listen for admin notifications (like source code download)
  const unsubAdminNotifs = onSnapshot(query(collection(db, 'adminNotifications'),
    orderBy('timestamp', 'desc'), limit(1)), (snap) => {
    snap.docChanges().forEach(change => {

```

```

    if (change.type === 'added') {
      const data = change.doc.data();
      if (Date.now() - data.timestamp < 120000 && data.adminId !== user?.uid) {
        notificationSound.play().catch(()=>console.log('Audio error'));
        const newAlert = {
          id: `SYS-${Date.now()}-${Math.random().toString(36).substring(2, 9)}`,
          type: 'SYSTEM',
          details: data.message,
          timestamp: new Date().toLocaleTimeString(),
          acknowledged: false
        };
        setFinancialAlerts(prev => [newAlert, ...prev]);
      }
    }
  });
});

return () => {
  unsubUsers();
  unsubAdminNotifs();
};
}, [profile, user, notificationSound]);

const handleLogout = async () => {
  try {
    await signOut(auth);
    setIsLoggedIn(false);
    setIsLandingPage(true);
    setIsAdminDashboardOpen(false);
    setIsProviderDashboardOpen(false);
    setIsProfileOpen(false);
    setProfile(null);
    setUser(null);
  } catch (error) {
    console.error("Logout failed:", error);
  }
};

const playNotification = () => {
  notificationSound.currentTime = 0;
  notificationSound.play().catch(e => console.log("Sound blocked by browser:", e));
};

const handleSPAccept = (bookingId: string) => {
  setActiveBookings(prev => prev.map(b => b.id === bookingId ? { ...b, status: 'ACCEPTED_BY_SP' } :
b));
  playNotification(); // Notify Admin
  addLog({ action: `SP Accepted Booking ${bookingId}. Awaiting Admin Finalization.`, admin:
"System", time: new Date().toLocaleString(), type: 'system' });
};

const triggerFinancialAlert = (type: 'PAYMENT' | 'WALLET', details: string) => {
  const newAlert = {
    id: `FIN-${Date.now()}-${Math.random().toString(36).substring(2, 9)}`,
    type,
    details,
    timestamp: new Date().toLocaleTimeString(),
    acknowledged: false
  };
  setFinancialAlerts(prev => [newAlert, ...prev]);
  playNotification();
  addLog({ action: `Financial Event Intercepted: ${type} - ${details}`, admin: "Finance Bot", time:
new Date().toLocaleString(), type: 'financial' });
};

const handleProviderAction = (bookingId: string, action: string) => {
  setActiveBookings(prev => prev.map(b => {
    if (b.id === bookingId) {
      if (action === 'ACCEPT') return { ...b, status: 'ACCEPTED_BY_SP' };
    }
  }));
};

```

```

        if (action === 'DECLINE') return { ...b, status: 'DECLINED' };
        if (action === 'START_SERVICE') return { ...b, status: 'IN_PROGRESS' };
        if (action === 'END_SERVICE') return { ...b, status: 'COMPLETED' };
    }
    return b;
  }));

  addLog({
    action: `Provider ${action}ed Booking ${bookingId}`,
    admin: "System",
    time: new Date().toLocaleString(),
    type: 'system',
    details: `Action: ${action} triggered by Partner ID ${providerProfile.spId}`
  });

  if (action === 'ACCEPT' || action === 'START_SERVICE' || action === 'END_SERVICE') {
    playNotification();
  }
};

const handleConfirmBooking = (bookingId: string) => {
  setActiveBookings(prev => prev.map(b => b.id === bookingId ? { ...b, status: 'CONFIRMED', otp:
Math.floor(1000 + Math.random() * 9000).toString() } : b));
  addLog({ action: `Booking ${bookingId} finalized by Admin`, admin: "Ashvin", time: new
Date().toLocaleString(), type: 'admin' });
};

const [bankDetails, setBankDetails] = useState({
  accountHolder: 'CAREVIA SOLUTIONS PVT LTD',
  accountNumber: '923010045566778',
  ifsc: 'UTIB00000001',
  bankName: 'AXIS BANK',
  branch: 'MUMBAI MAIN'
});

const [logs, setLogs] = useState<any[]>([]);

const addLog = (log: any) => {
  setLogs(prev => [{ ...log, id: `${Date.now()}-${Math.random().toString(36).substring(2, 9)}
`, ...prev}]);
};

const [sharingLevel, setSharingLevel] = useState('Restricted');
const [teamAccess, setTeamAccess] = useState('Read-Only');
const aiSessionId = useMemo(() => `SID-${Math.random().toString(36).substring(2, 9).toUpperCase}`,
[]);

// AI Service Matching States
const [userLocation, setUserLocation] = useState('Nationwide');
const [activeServiceTab, setActiveServiceTab] = useState('elderly');
const [isAnalyzing, setIsAnalyzing] = useState(false);
const [analysisStep, setAnalysisStep] = useState(0);
const [selectedCategory, setSelectedCategory] = useState('');

const analysisSteps = [
  "Analyzing nature of concern...",
  "Cross-referencing provider database...",
  "Applying precision matching logic...",
  "Optimizing care coordinator assignment...",
  "Finalizing recommendations..."
];

const handleRequirementSubmit = () => {
  setIsAnalyzing(true);
  setAnalysisStep(0);

  // Simulate AI analysis steps
  const interval = setInterval(() => {
    setAnalysisStep(prev => {
      if (prev >= analysisSteps.length - 1) {
        clearInterval(interval);
        setTimeout(() => {

```

```

        setIsAnalyzing(false);
        // Map category to tab
        const mapping: Record<string, string> = {
            'Elderly Assistance': 'elderly',
            'Medical Support': 'elderly',
            'Child Development': 'child',
            'Pet Care': 'pet',
            'Domestic Help': 'helpers'
        };
        if (mapping[selectedCategory]) {
            setActiveServiceTab(mapping[selectedCategory]);
        }
        document.getElementById('services')?.scrollIntoView({ behavior: 'smooth' });
    }, 800);
    return prev;
}
return prev + 1;
});
}, 600);
};

return (
    <div className="min-h-screen overflow-x-hidden">
        {isLandingPage ? (
            <AuthLandingPage
                onEnter={() => setIsLandingPage(false)}
                onProviderRegister={() => {
                    setIsLandingPage(false);
                    setIsProviderModalOpen(true);
                }}
            />
        ) : (
            <>
                <Navbar
                    onAuthClick={() => setIsAuthOpen(true)}
                    onBotClick={() => setIsBotOpen(true)}
                    onProviderClick={() => setIsProviderModalOpen(true)}
                    isPremium={isPremium}
                    isLoggedIn={isLoggedIn}
                    onProfileClick={() => setIsProfileOpen(true)}
                    setActiveTab={setActiveServiceTab}
                    onLogout={handleLogout}
                />

                <MobileBottomNav
                    onAuthClick={() => setIsAuthOpen(true)}
                    onBotClick={() => setIsBotOpen(true)}
                    isLoggedIn={isLoggedIn}
                    onProfileClick={() => setIsProfileOpen(true)}
                />

                <main className="pb-24 lg:pb-0">
                    {/* Hero Overhaul */}
                    <section id="home" className="relative min-h-screen flex items-center pt-20 overflow-
hidden font-sans">
                        <div className="absolute inset-0 z-0">
                            <div className="absolute top-1/2 left-1/2 -translate-x-1/2 -translate-y-1/2 text-[450px]
font-black leading-none uppercase opacity-[0.03] select-none pointer-events-none tracking-tighter">
                                HEALTH
                            </div>
                            
                            <div className="absolute inset-0 bg-gradient-to-t from-surface via-surface/40 to-
transparent" />
                        </div>

                        <div className="max-w-7xl mx-auto px-6 relative z-10 grid lg:grid-cols-2 gap-16 items-
center">

```

```

<motion.div
  initial={{ opacity: 0, x: -50 }}
  animate={{ opacity: 1, x: 0 }}
  transition={{ duration: 0.8 }}
>
  <h1 className="text-[72px] md:text-[110px] leading-[0.85] font-black tracking-tighter
mb-8 uppercase">
    HEALTH. <br />
    <span className="text-primary">Wellness.</span><br />
    Compassion.
  </h1>
  <p className="text-lg text-white/50 mb-12 max-w-lg font-light leading-relaxed">
    Elite-tier healthcare and assistance management for your loved ones. Experience the
future of home-based support.
  </p>
  <div className="flex flex-wrap gap-6">
    <Button variant="primary" className="px-10 py-5 text-xs tracking-widest uppercase"
onClick={() => setIsAuthOpen(true)}>
      Get Started
    </Button>
    <Button variant="outline" className="px-10 py-5 text-xs tracking-widest uppercase"
onClick={() => document.getElementById('services')?.scrollIntoView({ behavior: 'smooth' })}>
      Our Packages
    </Button>
  </div>
</motion.div>

<div className="relative">
  <div className="glass-card p-4 rounded-[3rem] border-white/10">
    <div className="bg-neutral-900 rounded-[2.5rem] overflow-hidden aspect-video relative
group">
      
      <div className="absolute inset-0 bg-gradient-to-t from-black/80 to-transparent
flex items-end p-8">
        <div className="flex items-center gap-4">
          <div className="w-12 h-12 rounded-full bg-primary flex items-center justify-
center text-surface">
            <Phone className="w-5 h-5" />
          </div>
          <div>
            <p className="text-xs font-bold text-primary uppercase tracking-
widest">Connect Instantly</p>
            <p className="text-xl font-bold">Priority Medical Dispatch</p>
          </div>
        </div>
      </div>
    </div>
    <div className="mt-4 flex flex-col gap-4">
      <ActiveServiceTracker bookings={activeBookings} />
      <WalletSection onManage={() => setIsWalletOpen(true)} />
    </div>
  </div>
</div>
</div>
</section>

<HowToUse />

<AboutSection />

{/* Requirements Form Section - Moved here before Services */}
<section id="requirements" className="relative py-24 bg-surface monolith-grid font-sans
overflow-hidden scroll-mt-24">
  {isAnalyzing && (

```

```

<motion.div
  initial={{ opacity: 0 }}
  animate={{ opacity: 1 }}
  className="absolute inset-0 z-50 bg-surface/90 backdrop-blur-xl flex flex-col items-
center justify-center text-center p-6"
>
  <div className="w-24 h-24 mb-8 relative">
    <motion.div
      animate={{ rotate: 360 }}
      transition={{ duration: 4, repeat: Infinity, ease: "linear" }}
      className="absolute inset-0 rounded-full border-t-2 border-primary"
    />
    <motion.div
      animate={{ rotate: -360 }}
      transition={{ duration: 6, repeat: Infinity, ease: "linear" }}
      className="absolute inset-2 rounded-full border-b-2 border-primary/30"
    />
    <div className="absolute inset-0 flex items-center justify-center">
      <Bot className="w-8 h-8 text-primary animate-pulse" />
    </div>
  </div>
  <h3 className="text-xl font-black uppercase tracking-widest mb-2">Analyzing
Requirements</h3>
  <p className="text-primary font-mono text-[10px] uppercase tracking-[0.3em] h-4">
    {analysisSteps[analysisStep]}
  </p>
  <div className="mt-8 w-64 h-1 bg-white/5 rounded-full overflow-hidden">
    <motion.div
      initial={{ width: 0 }}
      animate={{ width: `${(analysisStep + 1) / analysisSteps.length * 100}%` }}
      className="h-full bg-primary"
    />
  </div>
</motion.div>
)}

<div className="max-w-5xl mx-auto px-6">
  <SectionHeading
    sub="Tailored For You"
    title="Describe Your Requirements."
    desc="Tell us about the problems you're facing. Our AI evaluates your needs to recommend
the ideal care strategy."
    centered
  />
  <motion.div
    whileHover={{ scale: 1.01 }}
    className="glass-card p-12 bg-white/[0.02]"
  >
    <div className="grid md:grid-cols-2 gap-8 mb-8">
      <div>
        <label className="label-bold mb-4 block">Nature of Concern</label>
        <select
          value={selectedCategory}
          onChange={(e) => setSelectedCategory(e.target.value)}
          className="w-full bg-white/5 border border-white/10 px-6 py-4 rounded-2xl text-sm
focus:border-primary outline-none transition-colors appearance-none text-white"
        >
          <option value="" className="bg-surface">Select Category</option>
          <option value="Elderly Assistance" className="bg-surface">Elderly Assistance</
option>
          <option value="Medical Support" className="bg-surface">Medical Support</option>
          <option value="Child Development" className="bg-surface">Child Development</option>
          <option value="Pet Care" className="bg-surface">Pet Care</option>
          <option value="Domestic Help" className="bg-surface">Domestic Help</option>
        </select>
      </div>
      <div>
        <label className="label-bold mb-4 block">Urgency Level</label>
        <div className="flex flex-wrap sm:flex-nowrap gap-4">
          {['Standard', 'Priority', 'Emergency'].map(level => (
            <button key={level} className="flex-1 min-w-[100px] py-4 border border-white/10

```

rounded-2xl text-xs font-bold uppercase tracking-widest hover:bg-primary/10 hover:border-primary/40 transition-all">

```
        {level}
      </button>
    )}}
  </div>
</div>
<div className="mb-8">
  <label className="label-bold mb-4 block">Brief Description</label>
  <textarea rows={4} className="w-full bg-white/5 border border-white/10 px-6 py-4
rounded-2xl text-sm focus:border-primary outline-none transition-colors resize-none"
placeholder="Provide details for our AI to analyze..." />
</div>
<Button
  variant="primary"
  className="w-full py-5 text-xs tracking-widest uppercase"
  onClick={handleRequirementSubmit}
  disabled={!selectedCategory || isAnalyzing}
>
  {isAnalyzing ? 'Studying Requirements...' : 'Analyze & Show Best Services'}
</Button>
</motion.div>
</div>
</section>

<ServiceCatalog
  activeTab={activeServiceTab}
  setActiveTab={setActiveServiceTab}
  userLocation={userLocation}
  setUserLocation={setUserLocation}
  onBook={(name) => {
    setSelectedBookingService(name);
    setIsBookingOpen(true);
  }}
/>

<SubscriptionPlans onUpgrade={(planName: string) => {
  setSelectedPlanName(planName);
  setIsPaymentOpen(true);
}} />

<section id="join-provider" className="py-24 bg-surface relative overflow-hidden font-sans">
  <div className="absolute inset-0 bg-primary/5 -skew-y-3 translate-y-12" />
  <div className="max-w-7xl mx-auto px-6 relative z-10">
    <div className="glass-card p-12 border-primary/20 bg-primary-container/10 flex flex-col
lg:flex-row items-center justify-between gap-12">
      <div className="lg:max-w-2xl">
        <div className="flex items-center gap-4 mb-6 text-primary">
          <Handshake className="w-10 h-10" />
          <h2 className="text-3xl font-black uppercase tracking-tight">Empower Lives With
Us.</h2>
        </div>
        <p className="text-lg text-white/60 leading-relaxed mb-8 font-light">
          Are you a specialized care provider? Join the CAREVIA ecosystem to connect with
          families seeking elite healthcare, child care, and domestic assistance. We offer fair commissions,
          flexible slots, and a platform built on trust.
        </p>
        <div className="grid grid-cols-2 gap-6 mb-10">
          <div className="flex items-center gap-3">
            <CheckCircle2 className="text-primary w-5 h-5 flex-shrink-0" />
            <span className="text-xs font-bold uppercase tracking-widest text-
white/40">Verified Onboarding</span>
          </div>
          <div className="flex items-center gap-3">
            <CheckCircle2 className="text-primary w-5 h-5 flex-shrink-0" />
            <span className="text-xs font-bold uppercase tracking-widest text-
white/40">Flexible Schedules</span>
          </div>
          <div className="flex items-center gap-3">
            <CheckCircle2 className="text-primary w-5 h-5 flex-shrink-0" />
```



```

                <span className="text-xs font-bold uppercase tracking-widest text-
white/40">Direct Payouts</span>
            </div>
            <div className="flex items-center gap-3">
                <CheckCircle2 className="text-primary w-5 h-5 flex-shrink-0" />
                <span className="text-xs font-bold uppercase tracking-widest text-
white/40">Premium Client Base</span>
            </div>
        </div>
        <Button
            variant="primary"
            className="px-10 py-5 uppercase tracking-[0.2em] text-xs"
            onClick={() => setIsProviderModalOpen(true)}
        >
            Join as Service Provider
        </Button>
    </div>
    <div className="w-full lg:w-96 flex flex-col gap-4">
        <div className="glass-card p-6 border-white/5 bg-white/[0.02]">
            <p className="text-[10px] font-bold text-primary uppercase tracking-widest
mb-4">Required Documents</p>
            <ul className="space-y-3">
                <li className="flex items-center gap-3 text-xs text-white/60">
                    <FileText className="w-4 h-4 text-white/20" /> Aadhaar Card
                </li>
                <li className="flex items-center gap-3 text-xs text-white/60">
                    <FileText className="w-4 h-4 text-white/20" /> PAN Card
                </li>
                <li className="flex items-center gap-3 text-xs text-white/60">
                    <GraduationCap className="w-4 h-4 text-white/20" /> Academic Certificates
                </li>
            </ul>
        </div>
        <div className="glass-card p-6 border-white/5 bg-white/[0.02] text-center">
            <p className="text-3xl font-bold text-primary mb-1">2.4k+</p>
            <p className="text-[10px] font-bold text-white/30 uppercase tracking-
widest">Active Partners</p>
        </div>
    </div>
</div>
</div>
</div>
</section>

<ReviewsSection />

<ContactSection />
</main>

<Footer onLegalClick={() => setIsLegalOpen(true)} />
<SOSButton user={user} />
<AuthModal
    isOpen={isOpen}
    onOpenAdmin={() => setIsAdminDashboardOpen(true)}
    onClose={() => setIsAuthOpen(false)}
    onLogin={() => setIsLoggedIn(true)}
    onProviderLogin={() => setIsProviderDashboardOpen(true)}
/>
{isAdminDashboardOpen && (
    <AdminDashboard
        onClose={() => setIsAdminDashboardOpen(false)}
        actions={logs}
        bankDetails={bankDetails}
        setBankDetails={setBankDetails}
        sharingLevel={sharingLevel}
        setSharingLevel={setSharingLevel}
        teamAccess={teamAccess}
        setTeamAccess={setTeamAccess}
        bookings={activeBookings}
        financialAlerts={financialAlerts}
        onConfirmBooking={handleConfirmBooking}
        onAction={handleProviderAction}
    >

```

```

        onSpectateProvider={(p: any) => {
            setSpectatedProvider(p);
            setIsAdminDashboardOpen(false);
        }}
        masterOtp={masterOtp}
        setMasterOtp={setMasterOtp}
        onLogout={handleLogout}
    />
)}
{spectatedProvider && (
    <ProviderDashboard
        providerData={spectatedProvider}
        isSpectator={true}
        onUpdateProvider={() => {}}
        onClose={() => setSpectatedProvider(null)}
        bookings={activeBookings.filter((b: any) => b.providerName === spectatedProvider.name)}
        onAction={() => {}}
        masterOtp={masterOtp}
    />
)}
{isProviderDashboardOpen && (
    <ProviderDashboard
        providerData={providerProfile}
        onUpdateProvider={(data: any) => setProviderProfile(data)}
        onClose={() => setIsProviderDashboardOpen(false)}
        bookings={activeBookings}
        onAction={handleProviderAction}
        masterOtp={masterOtp}
        onLogout={handleLogout}
    />
)}
<BookingModal
    isOpen={isBookingOpen}
    serviceName={selectedBookingService}
    onClose={() => setIsBookingOpen(false)}
/>
<ProviderRegistrationModal
    isOpen={isProviderModalOpen}
    onClose={() => setIsProviderModalOpen(false)}
/>
<ProfileModal isOpen={isProfileOpen} onClose={() => setIsProfileOpen(false)} />
<PaymentModal
    isOpen={isPaymentOpen}
    planName={selectedPlanName}
    onClose={() => setIsPaymentOpen(false)}
    onPaymentComplete={() => {
        setIsPaymentOpen(false);
        setIsPremium(true);
        triggerFinancialAlert('PAYMENT', `Customer completed payment for ${selectedPlanName} Pack`);
    }}
/>
<WalletModal isOpen={isWalletOpen} onClose={() => setIsWalletOpen(false)} />
<LegalModal isOpen={isLegalOpen} onClose={() => setIsLegalOpen(false)} />
<AIBotChat isOpen={isBotOpen} isPremium={isPremium} onClose={() => setIsBotOpen(false)}
sessionId={aiSessionId} onLog={addLog} />
<LiveAlarm
    bookings={activeBookings}
    financialAlerts={financialAlerts}
    isAdmin={isAdminDashboardOpen}
    isSP={isProviderDashboardOpen}
    onAcknowledge={() => {}}
/>
</>
)}
</div>
);
}

```

```

const MobileBottomNav = ({ onAuthClick, onBotClick, isLoggedIn, onProfileClick }: any) => {
    return (
        <div className="lg:hidden fixed bottom-0 left-0 right-0 z-[150] bg-surface/90 backdrop-blur-xl

```

```

border-t border-white/5 pb-safe font-sans">
  <div className="flex items-center justify-around p-4">
    <a href="#home" className="flex flex-col items-center gap-1 text-white/50 hover:text-primary
transition-colors">
      <Home className="w-5 h-5" />
      <span className="text-[8px] font-bold uppercase tracking-widest">Home</span>
    </a>
    <a href="#services" className="flex flex-col items-center gap-1 text-white/50 hover:text-
primary transition-colors">
      <Stethoscope className="w-5 h-5" />
      <span className="text-[8px] font-bold uppercase tracking-widest">Services</span>
    </a>
    <button onClick={onBotClick} className="flex flex-col items-center gap-1 text-primary -mt-6
relative">
      <div className="w-12 h-12 rounded-full bg-primary flex items-center justify-center shadow-
[0_0_20px_rgba(212,175,55,0.4)]">
        <Bot className="w-6 h-6 text-surface" />
      </div>
      <span className="text-[8px] font-bold uppercase tracking-widest mt-1">AI Concierge</span>
    </button>
    <a href="#pricing" className="flex flex-col items-center gap-1 text-white/50 hover:text-
primary transition-colors">
      <Star className="w-5 h-5" />
      <span className="text-[8px] font-bold uppercase tracking-widest">Premium</span>
    </a>
    <button onClick={isLoggedIn ? onProfileClick : onAuthClick} className="flex flex-col items-
center gap-1 text-white/50 hover:text-primary transition-colors">
      <User className="w-5 h-5" />
      <span className="text-[8px] font-bold uppercase tracking-widest">{isLoggedIn ? 'Profile' :
'Login'}</span>
    </button>
  </div>
</div>
);
};

```

```

const Navbar = ({ onAuthClick, onBotClick, isPremium, isLoggedIn, onProfileClick, setActiveTab,
onProviderClick, onLogout }: any) => {
  const [isScrolled, setIsScrolled] = useState(false);
  const [searchQuery, setSearchQuery] = useState('');
  const [searchResults, setSearchResults] = useState<any[]>([]);
  const [isMobileMenuOpen, setIsMobileMenuOpen] = useState(false);

```

```

  useEffect(() => {
    const handleScroll = () => setIsScrolled(window.scrollY > 20);
    window.addEventListener('scroll', handleScroll);
    return () => window.removeEventListener('scroll', handleScroll);
  }, []);

```

```

  useEffect(() => {
    if (!searchQuery.trim()) {
      setSearchResults([]);
      return;
    }
  }

```

```

  const query = searchQuery.toLowerCase();
  const results: any[] = [];

```

```

  CATEGORIES.forEach(cat => {
    cat.sections.forEach(sec => {
      sec.items.forEach(item => {
        if (item.toLowerCase().includes(query) || sec.name.toLowerCase().includes(query) ||
cat.name.toLowerCase().includes(query)) {
          // Avoid duplicates of the same item if it matches multiple things, though unlikely here
          if (!results.find(r => r.item === item)) {
            results.push({
              catId: cat.id,
              catName: cat.name,
              item: item,
              section: sec.name
            });
          }
        }
      });
    });
  });

```

```

    }
  }
});
});
});

setSearchResults(results.slice(0, 6)); // Limit results
}, [searchQuery]);

return (
  <nav className={`fixed top-0 left-0 right-0 z-[160] transition-all duration-300 font-sans border-b
border-primary/20 ${isScrolled ? 'bg-surface py-3 shadow-[0_4px_30px_rgba(0,0,0,0.5)]' : 'bg-surface
py-5'}`>
    <div className="max-w-7xl mx-auto px-6 flex justify-between items-center">
      <div className="flex items-center gap-4 flex-shrink-0">
        <Logo />
      </div>

      {/* Search Bar - Desktop */}
      <div className="hidden lg:flex flex-1 max-w-sm mx-12 relative">
        <div className="relative w-full group">
          <Search className="absolute left-4 top-1/2 -translate-y-1/2 w-4 h-4 text-white/30 group-
focus-within:text-primary transition-colors" />
          <input
            type="text"
            value={searchQuery}
            onChange={(e) => setSearchQuery(e.target.value)}
            placeholder="Search services..."
            className="w-full bg-white/5 border border-white/10 px-10 py-3 rounded-2xl text-xs
outline-none focus:border-primary/50 focus:bg-white/10 transition-all font-bold tracking-widest
placeholder:text-white/20"
          />
          <AnimatePresence>
            {searchResults.length > 0 && (
              <motion.div
                initial={{ opacity: 0, y: 10, scale: 0.95 }}
                animate={{ opacity: 1, y: 0, scale: 1 }}
                exit={{ opacity: 0, y: 10, scale: 0.95 }}
                className="absolute top-full left-0 right-0 mt-4 glass-card p-2 border-primary/20
shadow-2xl overflow-hidden"
              >
                {searchResults.map((res, i) => (
                  <button
                    key={i}
                    onClick={() => {
                      setActiveTab(res.catId);
                      setSearchQuery('');
                      setSearchResults([]);
                      document.getElementById('services')?.scrollIntoView({ behavior: 'smooth' });
                    }}
                    className="w-full text-left p-3 hover:bg-primary/10 rounded-xl transition-all
group"
                  >
                    <p className="text-[10px] font-bold text-primary uppercase tracking-widest
mb-0.5">{res.catName}</p>
                    <p className="text-xs font-bold text-white/80 group-hover:text-white">{res.item}
</p>
                    <p className="text-[8px] text-white/30 uppercase tracking-widest
mt-1">{res.section}</p>
                  </button>
                ))}
              </motion.div>
            )}
          </AnimatePresence>
        </div>

        <div className="flex items-center gap-3">
          {/* Join as Provider - Desktop */}
          <div className="hidden xl:flex gap-6 mr-4">
            {NAV_LINKS.map(link => (

```

```

        <a
            key={link.name}
            href={link.href}
            className="text-[9px] font-bold tracking-[0.2em] uppercase text-white/50 hover:text-
primary transition-all"
        >
            {link.name}
        </a>
    )}}
</div>

<button
    onClick={onBotClick}
    className={`p-3 rounded-xl border transition-all flex items-center gap-2 group relative
${isPremium ? 'bg-primary/20 border-primary/40 text-primary' : 'bg-white/5 border-white/10 text-
white/60 hover:bg-white/10'}`}
    >
        <Bot className="w-4 h-4" />
        <span className="text-[9px] uppercase font-bold tracking-widest hidden md:block">Elite AI</
span>
        {!isPremium && <Lock className="w-2.5 h-2.5 opacity-40" />}
        {isPremium && <Sparkles className="w-2.5 h-2.5 animate-pulse" />}
    </button>

    <button
        onClick={isLoggedIn ? onProfileClick : onAuthClick}
        className="btn-outline p-3 xs:px-5 xs:py-2.5 text-[9px] uppercase tracking-widest flex
items-center gap-2 bg-primary text-surface font-black border-transparent hover:opacity-90 transition-
all shadow-[0_0_20px_rgba(45,212,191,0.2)]"
    >
        <User className="w-3.5 h-3.5" />
        <span className="hidden xs:block">{isLoggedIn ? 'Logged In' : 'Login'}</span>
    </button>

    {isLoggedIn && (
        <button
            onClick={onLogout}
            className="p-3 xs:px-5 xs:py-2.5 bg-red-500/10 border border-red-500/20 text-red-500
rounded-xl hover:bg-red-500 hover:text-white transition-all flex items-center gap-2"
            title="Logout"
        >
            <LogOut className="w-3.5 h-3.5" />
            <span className="hidden xs:block text-[9px] uppercase tracking-widest font-black">Log
Out</span>
        </button>
    )}

    <button
        onClick={() => setIsMobileMenuOpen(!isMobileMenuOpen)}
        className="xl:hidden p-3 bg-white/5 rounded-xl text-white/50 hover:text-white transition-
all ml-1"
    >
        {isMobileMenuOpen ? <X className="w-5 h-5" /> : <Menu className="w-5 h-5" />}
    </button>
</div>
</div>

{/* Mobile Menu Overlay */}
<AnimatePresence>
    {isMobileMenuOpen && (
        <motion.div
            initial={{ opacity: 0, height: 0 }}
            animate={{ opacity: 1, height: 'auto' }}
            exit={{ opacity: 0, height: 0 }}
            className="xl:hidden bg-surface border-t border-white/5 overflow-hidden"
        >
            <div className="p-6 space-y-6">
                <div className="grid grid-cols-2 gap-4">
                    {NAV_LINKS.map(link => (
                        <a
                            key={link.name}

```

```

        href={link.href}
        onClick={() => setIsMobileMenuOpen(false)}
        className="block text-[10px] font-black uppercase tracking-[0.2em] text-white/60
hover:text-primary transition-all p-4 bg-white/5 rounded-2xl border border-white/5 hover:border-
primary/20"
      >
        {link.name}
      </a>
    )}}
  </div>
  <div className="pt-4 space-y-3">
    <button
      onClick={() => { onProviderClick(); setIsMobileMenuOpen(false); }}
      className="w-full py-4 bg-primary/10 border border-primary/20 rounded-2xl text-
[10px] font-bold uppercase tracking-widest text-primary flex items-center justify-center gap-3"
    >
      <Handshake className="w-4 h-4" /> Join as Provider
    </button>
    <button
      onClick={() => { isLoggedIn ? onProfileClick() : onAuthClick();
setIsMobileMenuOpen(false); }}
      className="w-full py-5 bg-primary text-surface rounded-2xl text-[10px] font-black
uppercase tracking-widest flex items-center justify-center gap-3"
    >
      <User className="w-4 h-4" /> {isLoggedIn ? 'Logged In' : 'Login'}
    </button>
    {isLoggedIn && (
      <button
        onClick={() => { onLogout(); setIsMobileMenuOpen(false); }}
        className="w-full py-4 bg-red-500/10 border border-red-500/20 rounded-2xl text-
[10px] font-bold uppercase tracking-widest text-red-500 flex items-center justify-center gap-3"
      >
        <LogOut className="w-4 h-4" /> Sign Out
      </button>
    )}
  </div>
</div>
</motion.div>
  </AnimatePresence>
</nav>
);
};

const Footer = ({ onLegalClick }: any) => {
  return (
    <footer className="py-24 border-t border-white/5 font-sans">
      <div className="max-w-7xl mx-auto px-6 grid md:grid-cols-2 lg:grid-cols-4 gap-16 mb-20">
        <div className="col-span-2">
          <Logo className="mb-8" />
          <p className="text-white/30 text-sm font-light leading-loose max-w-sm">
            The definitive destination for elite concierge healthcare and domestic management.
            Discretion, quality, and commitment.
          </p>
        </div>

        <div>
          <h5 className="text-[10px] uppercase font-bold tracking-[0.3em] text-primary
mb-8">Governance</h5>
          <ul className="space-y-4 text-xs font-bold text-white/40 uppercase tracking-widest">
            <li><button onClick={onLegalClick} className="hover:text-white transition-colors">Legal
Terms</button></li>
            <li><button onClick={onLegalClick} className="hover:text-white transition-colors">Privacy
Policy</button></li>
            <li><a href="#" className="hover:text-white transition-colors">User Agreement</a></li>
            <li><a href="#" className="hover:text-white transition-colors">Provider Vetting</a></li>
          </ul>
        </div>

        <div>
          <h5 className="text-[10px] uppercase font-bold tracking-[0.3em] text-primary

```

```

mb-8">Newsletter</h5>
    <div className="flex gap-2">
        <input type="email" placeholder="Email" className="flex-1 bg-white/5 border border-
white/10 rounded-xl px-4 py-3 text-xs outline-none focus:border-primary/50" />
        <button className="p-3 bg-white text-surface rounded-xl hover:bg-neutral-200 transition-
colors">
            <ArrowRight className="w-4 h-4" />
        </button>
    </div>
</div>
</div>

    <div className="max-w-7xl mx-auto px-6 pt-12 border-t border-white/5 flex flex-col sm:flex-row
justify-between items-center gap-6">
        <div className="flex items-center gap-4 text-[10px] font-bold uppercase tracking-widest text-
white/20">
            <span>© 2025 CAREVIA™</span>
            <span className="w-1 h-1 bg-white/20 rounded-full" />
            <span>Berlin // New York // Dubai</span>
        </div>
        <div className="flex gap-8 text-[10px] font-bold uppercase tracking-widest text-white/20">
            <a href="#" className="hover:text-white">Refunds</a>
            <a href="#" className="hover:text-white">SOS Feedback</a>
            <a href="#" className="hover:text-white">Investor Relations</a>
        </div>
    </div>
</footer>
);
};

```

File: src/index.css

```
@import url('https://fonts.googleapis.com/css2?family=Playfair+Display:ital,wght@0,400;0,600;0,700;1,400&family=Inter:wght@300;400;500;600&display=swap');
@import "tailwindcss";

@theme {
  --font-sans: "Inter", ui-sans-serif, system-ui, sans-serif;
  --font-serif: "Playfair Display", ui-serif, Georgia, serif;

  --color-surface: #151312; /* Deep Espresso */
  --color-card: #1D1A18; /* Warm Dark Brown */
  --color-primary: #D4AF37; /* Champagne Gold */
  --color-primary-container: #2A241D;
  --color-secondary: #E6D5B8; /* Light Champagne */
  --color-muted: #A39B93; /* Warm Gray */
  --color-glass: rgba(29, 26, 24, 0.7);
  --color-border-glass: rgba(212, 175, 55, 0.15);
  --color-border-secondary: #332D28;
}

@layer base {
  body {
    @apply bg-surface text-[#F0EBE1] font-sans antialiased selection:bg-primary selection:text-surface;
    background-image:
      radial-gradient(circle at 0% 0%, rgba(212, 175, 55, 0.05) 0%, transparent 50%),
      radial-gradient(circle at 100% 100%, rgba(230, 213, 184, 0.05) 0%, transparent 50%);
    min-height: 100vh;
  }

  h1, h2, h3, h4, h5, h6 {
    @apply font-serif font-semibold tracking-normal text-[#FDFCFB];
  }
}

@layer components {
  .glass {
    @apply bg-card/80 backdrop-blur-[12px] border border-border-glass;
  }

  .glass-card {
    @apply bg-card/60 backdrop-blur-[12px] border border-border-glass p-6 transition-all duration-300 rounded-3xl;
  }

  .btn-primary {
    @apply bg-primary text-surface px-6 py-3 rounded-full font-bold transition-all
    hover:brightness-110 active:scale-95 text-xs uppercase tracking-widest;
  }

  .btn-outline {
    @apply border border-border-secondary text-muted px-6 py-3 rounded-full font-semibold transition-all
    hover:bg-white/5;
  }

  .btn-gold {
    @apply bg-primary text-surface px-6 py-3 rounded-full font-bold transition-all
    hover:brightness-110 active:scale-95;
  }

  .label-bold {
    @apply text-[10px] uppercase tracking-[0.2em] font-bold text-muted;
  }

  .sos-button {
    @apply w-16 h-16 bg-red-600 rounded-full flex items-center justify-center shadow-[0_0_20px_rgba(220,38,38,0.5)] animate-pulse hover:scale-110 transition-transform cursor-pointer z-[100];
  }
}
```



```
.monolith-grid {
  background-image:
    linear-gradient(rgba(212, 175, 55, 0.03) 1px, transparent 1px),
    linear-gradient(90deg, rgba(212, 175, 55, 0.03) 1px, transparent 1px);
  background-size: 50px 50px;
}

.hide-scrollbar::-webkit-scrollbar {
  display: none;
}
.hide-scrollbar {
  -ms-overflow-style: none;
  scrollbar-width: none;
}
}
```

File: src/lib/firebase.ts

```
import { initializeApp } from 'firebase/app';
import { getAuth } from 'firebase/auth';
import { getFirestore, doc, getDocFromServer } from 'firebase/firestore';
import { getStorage } from 'firebase/storage';
import firebaseConfig from '../../../firebase-applet-config.json';

const app = initializeApp(firebaseConfig);
export const auth = getAuth(app);
// Use the firestoreDatabaseId from the config
export const db = getFirestore(app, (firebaseConfig as any).firestoreDatabaseId);
export const storage = getStorage(app);

/**
 * Validates connection to Firestore
 */
async function testConnection() {
  try {
    await getDocFromServer(doc(db, 'test', 'connection'));
    console.log("Firestore Connected successfully");
  } catch (error) {
    if (error instanceof Error && error.message.includes('the client is offline')) {
      console.error("Please check your Firebase configuration.");
    } else {
      console.warn("Initial connection test failed, but may succeed after auth:", error);
    }
  }
}

testConnection();

export interface FirestoreErrorInfo {
  error: string;
  operationType: 'create' | 'update' | 'delete' | 'list' | 'get' | 'write';
  path: string | null;
  authInfo: {
    userId: string;
    email: string;
    emailVerified: boolean;
    isAnonymous: boolean;
    providerInfo: { providerId: string; displayName: string; email: string; }[];
  }
}

export function handleFirestoreError(error: any, operationType: FirestoreErrorInfo['operationType'],
path: string | null = null) {
  if (error.code === 'permission-denied') {
    const errorInfo: FirestoreErrorInfo = {
      error: error.message,
      operationType,
      path,
      authInfo: {
        userId: auth.currentUser?.uid || 'anonymous',
        email: auth.currentUser?.email || '',
        emailVerified: auth.currentUser?.emailVerified || false,
        isAnonymous: auth.currentUser?.isAnonymous || true,
        providerInfo: auth.currentUser?.providerData.map(p => ({
          providerId: p.providerId,
          displayName: p.displayName || '',
          email: p.email || ''
        }))) || []
      }
    };
    throw new Error(JSON.stringify(errorInfo));
  }
  throw error;
}
```

File: src/lib/workspace.ts

```
declare const google: any;

const CLIENT_ID = import.meta.env.VITE_CLIENT_ID;

const SCOPES = [
  'openid',
  'email',
  'profile',
  'https://www.googleapis.com/auth/spreadsheets',
  'https://www.googleapis.com/auth/drive.file',
].join(' ');

let tokenResponse: any = null;

export const getAccessToken = (): Promise<string> => {
  return new Promise((resolve, reject) => {
    if (!CLIENT_ID) {
      reject(new Error('VITE_CLIENT_ID is not configured in .env'));
      return;
    }

    if (tokenResponse && Date.now() < tokenResponse.expires_at) {
      resolve(tokenResponse.access_token);
      return;
    }

    try {
      const client = google.accounts.oauth2.initTokenClient({
        client_id: CLIENT_ID,
        scope: SCOPES,
        callback: (response: any) => {
          if (response.access_token) {
            tokenResponse = {
              ...response,
              expires_at: Date.now() + (response.expires_in * 1000)
            };
            resolve(response.access_token);
          } else {
            reject(new Error('Failed to get access token: ' + (response.error || 'Unknown error')));
          }
        },
      });
      client.requestAccessToken();
    } catch (error) {
      reject(error);
    }
  });
};

/**
 * Uploads a file to Google Drive
 */
export const uploadToDrive = async (fileName: string, content: string, mimeType: string = 'text/plain') => {
  const token = await getAccessToken();

  const metadata = {
    name: fileName,
    mimeType: mimeType,
  };

  const form = new FormData();
  form.append('metadata', new Blob([JSON.stringify(metadata)], { type: 'application/json' }));
  form.append('file', new Blob([content], { type: mimeType }));

  const response = await fetch('https://www.googleapis.com/upload/drive/v3/files?uploadType=multipart', {
    method: 'POST',
  });
}
```

```

    headers: {
      Authorization: `Bearer ${token}`,
    },
    body: form,
  });

  if (!response.ok) {
    throw new Error('Failed to upload to Drive: ' + await response.text());
  }

  return response.json();
};

/**
 * Exports data to a new Google Sheet
 */
export const exportToSheets = async (title: string, headers: string[], rows: any[][]) => {
  const token = await getAccessToken();

  // 1. Create a new Spreadsheet
  const createRes = await fetch('https://sheets.googleapis.com/v4/spreadsheets', {
    method: 'POST',
    headers: {
      Authorization: `Bearer ${token}`,
      'Content-Type': 'application/json',
    },
    body: JSON.stringify({
      properties: { title }
    }),
  });

  if (!createRes.ok) {
    throw new Error('Failed to create spreadsheet: ' + await createRes.text());
  }

  const spreadsheet = await createRes.json();
  const spreadsheetId = spreadsheet.spreadsheetId;

  // 2. Add data
  const values = [headers, ...rows];
  const updateRes = await fetch(`https://sheets.googleapis.com/v4/spreadsheets/${spreadsheetId}/values/Sheet1!A1:append?valueInputOption=RAW`, {
    method: 'POST',
    headers: {
      Authorization: `Bearer ${token}`,
      'Content-Type': 'application/json',
    },
    body: JSON.stringify({
      values
    }),
  });

  if (!updateRes.ok) {
    throw new Error('Failed to update spreadsheet: ' + await updateRes.text());
  }

  return spreadsheet;
};

```

File: src/main.tsx

```
import {StrictMode} from 'react';
import {createRoot} from 'react-dom/client';
import App from './App.tsx';
import './index.css';

createRoot(document.getElementById('root')!).render(
  <StrictMode>
    <App />
  </StrictMode>,
);
```

File: src/vite-env.d.ts

```
/// <reference types="vite/client" />
```

File: tsconfig.json

```
{
  "compilerOptions": {
    "target": "ES2022",
    "experimentalDecorators": true,
    "useDefineForClassFields": false,
    "module": "ESNext",
    "lib": [
      "ES2022",
      "DOM",
      "DOM.Iterable"
    ],
    "skipLibCheck": true,
    "moduleResolution": "bundler",
    "isolatedModules": true,
    "moduleDetection": "force",
    "allowJs": true,
    "jsx": "react-jsx",
    "paths": {
      "@/*": [
        "./*"
      ]
    },
    "allowImportingTsExtensions": true,
    "noEmit": true
  }
}
```

File: vite.config.ts

```
import tailwindcss from '@tailwindcss/vite';
import react from '@vitejs/plugin-react';
import path from 'path';
import {defineConfig, loadEnv} from 'vite';

export default defineConfig(({mode}) => {
  const env = loadEnv(mode, '.', '');
  return {
    plugins: [react(), tailwindcss()],
    define: {
      'process.env.GEMINI_API_KEY': JSON.stringify(env.GEMINI_API_KEY),
    },
    resolve: {
      alias: {
        '@': path.resolve(__dirname, '.'),
      },
    },
    server: {
      // HMR is disabled in AI Studio via DISABLE_HMR env var.
      // Do not modify "file watching is disabled to prevent flickering during agent edits.
      hmr: process.env.DISABLE_HMR !== 'true',
    },
  };
});
```