

# The mention Package

Ashwani Anand

2026/05/11

## Abstract

The mention package adds targeted collaborative comments on top of phfcc. Comments remain visible inline in the source document, while only the addressed collaborator sees margin highlights and a header summary of unresolved comments for the active viewer.

## Contents

|           |                                      |          |
|-----------|--------------------------------------|----------|
| <b>1</b>  | <b>Introduction</b>                  | <b>2</b> |
| <b>2</b>  | <b>Installation</b>                  | <b>2</b> |
| <b>3</b>  | <b>Defining Authors</b>              | <b>2</b> |
| 3.1       | The author command factory . . . . . | 2        |
| <b>4</b>  | <b>Writing Comments</b>              | <b>3</b> |
| <b>5</b>  | <b>Viewer Selection</b>              | <b>3</b> |
| 5.1       | Direct handle selection . . . . .    | 3        |
| 5.2       | User-id selection . . . . .          | 3        |
| 5.3       | Explicit user-id mappings . . . . .  | 3        |
| 5.4       | Local Configuration . . . . .        | 4        |
| 5.5       | Automatic Detection . . . . .        | 4        |
| <b>6</b>  | <b>Header Summary</b>                | <b>4</b> |
| 6.1       | The standard header . . . . .        | 4        |
| <b>7</b>  | <b>Complete Example</b>              | <b>4</b> |
| <b>8</b>  | <b>Public Interface</b>              | <b>5</b> |
| <b>9</b>  | <b>Limitations</b>                   | <b>5</b> |
| <b>10</b> | <b>License</b>                       | <b>6</b> |

# 1 Introduction

Collaborative drafts often need comments that are visible in context but routed to a specific co-author. The `mention` package provides one command per author, a recipient list for each comment, optional important-comment styling, and a resolved flag that keeps old comments visible without counting them as open work.

The package is intentionally small. It depends on `phfcc` for the base commenting environment and on common LaTeX packages for colors, margin notes, and command parsing. Automatic viewer detection is best-effort; projects that need the most predictable behavior should use a local `mention-local.cfg` file.

# 2 Installation

Place `mention.sty` where TeX can find it. For a single project, putting the file next to the main `.tex` document is enough:

```
project/  
  paper.tex  
  mention.sty  
  mention-local.cfg.example
```

Then load the package with:

```
\usepackage{mention}
```

The package requires `phfcc`, `xparse`, `xcolor`, and `marginnote`. The optional automatic viewer detection path can use `catchfile` and `texosquery` when they are available.

# 3 Defining Authors

## 3.1 The author command factory

Define one author command per collaborator:

```
\phfMakeTargetedCommentCommand[  
  initials={AL},  
  color=blue,  
  handle=alice,  
  userid=alice-laptop  
{\Alice}
```

This defines a command named `\Alice`. Its comments are printed inline using the configured color. If a comment targets the active viewer, a margin note is also printed using the author's initials.

| Option                | Meaning                                                |
|-----------------------|--------------------------------------------------------|
| <code>initials</code> | Short text printed in margin notes.                    |
| <code>color</code>    | Any color expression accepted by <code>xcolor</code> . |
| <code>handle</code>   | Stable collaborator handle used in recipient lists.    |
| <code>userid</code>   | Optional system user id mapped to the handle.          |

If `initials` is omitted, the command name is used. If `handle` is omitted, the lower-cased command name is used. If `color` is omitted, the package chooses the next color from its built-in cycle.

## 4 Writing Comments

Comments use the optional argument for recipient handles:

```
\Alice[bob]{Please check this lemma.}
\Alice[bob, claire]{Please verify this proof.}
\Alice![bob]{Please add the missing citation.}
\Alice[bob, resolved]{This has already been handled.}
```

The form with `!` marks a comment as important. Important comments use a stronger filled margin label for the active viewer.

The special recipient-list item `resolved` makes a comment dormant. It still appears inline, but it is not routed to anyone, does not get a margin note, and does not contribute to unresolved counts.

Consecutive comments for the active viewer share one side-by-side margin note. This keeps co-authors who comment at the same spot from covering each other in the margin.

## 5 Viewer Selection

### 5.1 Direct handle selection

Set the active viewer directly by handle:

```
\phfSetViewer{bob}
```

### 5.2 User-id selection

Set the active viewer by user id. If the user id was registered through an author's `userid` option, it maps to that author's handle:

```
\phfSetViewerUser{bob-laptop}
```

### 5.3 Explicit user-id mappings

Register or override an explicit user-id mapping:

```
\phfRegisterViewerUser{bob-laptop}{bob}
```

Viewer selection is resolved in this order:

1. an explicit `\phfSetViewer{...}` call;
2. an explicit `\phfSetViewerUser{...}` call;
3. a local `mention-local.cfg` file, if present;
4. best-effort automatic detection.

## 5.4 Local Configuration

For shared Git repositories, the recommended workflow is to keep `mention-local.cfg` ignored and let each collaborator create their own copy from `mention-local.cfg.example`.

```
cp mention-local.cfg.example mention-local.cfg
```

A local config can select a handle:

```
\phfSetViewer{bob}
```

or a user id:

```
\phfSetViewerUser{bob-laptop}
```

The package loads `mention-local.cfg` automatically when the document starts.

## 5.5 Automatic Detection

When no explicit viewer is set, `mention` tries to infer the compiling user. With shell access, it first asks `kpsewhich` for common user variables: `USER`, `USERNAME`, and `LOGNAME`. If that does not work and `texosquery` is available, it tries to derive a user id from the home-directory path.

This detection path is best-effort. It may be unavailable on systems that disable shell escape or do not ship the optional helper packages. Manual viewer selection through `mention-local.cfg` does not require shell escape.

## 6 Header Summary

### 6.1 The standard header

Enable a centered page-header summary:

```
\phfUseTargetedCommentHeader
```

The summary reports unresolved comments for the active viewer, for example:

```
There are 2 unresolved comments for you.
```

The count is written through the `.aux` file. Compile twice after changing comments or viewer selection.

## 7 Complete Example

```
\documentclass{article}
\usepackage[margin=1in]{geometry}
\setlength{\marginparwidth}{3cm}
\usepackage{xcolor}
\usepackage{mention}

\phfMakeTargetedCommentCommand[
```

```

initials={AL},
color=blue,
handle=alice,
userid=alice-laptop
]{Alice}

\phfMakeTargetedCommentCommand[
initials={BO},
color=orange,
handle=bob,
userid=bob-laptop
]{Bob}

\phfUseTargetedCommentHeader

\begin{document}

We should revise this proof
\Alice[bob]{Please check the induction step.}
before submission.

\Alice![bob]{Please add the missing citation.}
\Alice[bob, resolved]{This earlier point is done.}

\end{document}

```

## 8 Public Interface

| Command                                     | Purpose                             |
|---------------------------------------------|-------------------------------------|
| <code>\phfMakeTargetedCommentCommand</code> | define an author command            |
| <code>\phfSetViewer</code>                  | select the active viewer by handle  |
| <code>\phfSetViewerUser</code>              | select the active viewer by user id |
| <code>\phfRegisterViewerUser</code>         | map a user id to a handle           |
| <code>\phfUseTargetedCommentHeader</code>   | install the standard header         |
| <code>\phfTargetedCommentSummary</code>     | typeset only the summary text       |

The author-command factory has the form:

```
\phfMakeTargetedCommentCommand[options]{CommandName}
```

The viewer commands have the forms:

```

\phfSetViewer{handle}
\phfSetViewerUser{userid}
\phfRegisterViewerUser{userid}{handle}

```

## 9 Limitations

The response-marker commands

```

\phfMarkCommentResponded
\phfccDeclareResponded

```

are retained only as compatibility stubs and emit a warning. Use the `resolved` flag in a comment recipient list instead.

The package does not hide inline comments from non-recipients. Targeting only controls margin notes and unresolved counts.

## 10 License

Copyright © 2026 Ashwani Anand.

This work may be distributed and/or modified under the conditions of the LaTeX Project Public License, either version 1.3c of this license or any later version.

This work has the LPPL maintenance status `maintained`.

The Current Maintainer of this work is Ashwani Anand.

This work consists of the files `README.md`, `mention.tex`, `mention.sty`, `mention-local.cfg.example`, and `targeted-comments-demo.tex`, and the derived file `mention.pdf`.