

[Open in app](#)Get unlimited access to all of Medium for less than \$1/week. [Become a member](#)

Supporting different screen sizes on Android with Jetpack Compose

In this post, we are going to discover the pitfalls of using hard-coded dimensions and a way to support different screen sizes.

**Rahul Sainani** · [Follow](#)Published in [ProAndroidDev](#)

4 min read · May 6, 2021






Listen



Share



More



[Rooms](#), an app built with Jetpack Compose — dimensions case study.


Since the early days of Android, it has been recommended to use Density-independent pixel (abbreviated dp or dip) instead of Pixels for creating layouts and UI elements. Dp helps in creating layouts on multiple screen sizes with different densities easier and more manageable.

. . .

“Dp is a virtual pixel unit that takes the same amount of space as 1 pixel on 160 dpi (mdpi) screen.” — Android Design Bytes, gift that keeps on giving ❤️

That means 50dp will take roughly the same amount of physical real world space on a Pixel 5 and on a Nexus One, roughly the size of a finger tip. But if you think about it, we have much less space on smaller devices (regardless of the density) as they are, as you guessed, smaller. Yet we use the same set of dimensions for those devices as our latest and biggest devices.

The Problem — Same dimensions on Nexus One and Pixel 5



Here's the same screen using the same dimensions on Nexus One (left) and Pixel 5 (right).

Here we can see that while the screen looks pretty neat on a Pixel 5, it looks quite bad on a smaller device. The padding takes a considerable proportion of the space, the text size is way too big, and there's not enough space left for the button so it gets cropped. Even though the screenshot on the post doesn't look too shabby, it leaves a lot to be desired when experienced on an actual device. Obviously we can make the screen scroll-able and that would be fine for most apps but we want to do better, don't we? 🤔

In the screenshot above, we had been using Dimensions by creating a *Dimens* object with all the app specific dimensions in one place.

```
1  /**
2   * An 8dp grid system. Smaller components can align to a 2dp 'sub' grid.
3   */
4   object Dimens {
5       val grid_0_25 = 2.dp
6       val grid_0_5 = 4.dp
```

```
7     val grid_1 = 8.dp
8     val grid_1_5 = 12.dp
9     val grid_2 = 16.dp
10    val grid_2_5 = 20.dp
11    val grid_3 = 24.dp
12    val grid_3_5 = 28.dp
13    val grid_4 = 32.dp
14    val grid_4_5 = 36.dp
15    val grid_5 = 40.dp
16    val grid_5_5 = 44.dp
17    val grid_6 = 48.dp
18 }
```

Dimens.kt hosted with ❤️ by GitHub

[view raw](#)

Initial dimensions approach

Although this allowed us to define dimensions in Kotlin, we did not take advantage of resource configurations as individual dimensions have the same values for all the screen sizes and configurations.

For instance, `Dimens.grid_1` will always be `8.dp` regardless of the screen size.

We can take inspiration from the way colors are set in the Theme that allows apps to support multiple themes with relative ease. The idea is to provide values based on a certain configuration, let's see how colors are setup and how do they update when the theme is updated.

We define two *Colors* objects *LightThemeColors* and *DarkThemeColors* and based on the *darkTheme* flag one of them is provided to the *CompositionLocal*.

```
1 // To simplify the example, we will use the defaults provided in the Material Theme
2 private val LightThemeColors = lightColors()
3
4 private val DarkThemeColors = darkColors()
5
6 @Composable
7 fun ProvideAppColors(
8     colors: Colors,
9     content: @Composable () -> Unit
10 ) {
11     val colorPalette = remember { colors }
12     CompositionLocalProvider(LocalAppColors provides colorPalette, content = content)
13 }
14
15 private val LocalAppColors = staticCompositionLocalOf {
```

```
16     LightThemeColors
17 }
18
19 @Composable
20 fun AppTheme(
21     darkTheme: Boolean = isSystemInDarkTheme(),
22     content: @Composable () -> Unit
23 ) {
24     val colors = if (darkTheme) DarkThemeColors else LightThemeColors
25
26     ProvideAppColors(colors = colors) {
27         MaterialTheme(
28             colors = colors,
29             shapes = Shapes,
30             typography = typography,
31             content = content
32         )
33     }
34 }
35
36 object Theme {
37     val colors: Colors
38     @Composable
39     get() = LocalAppColors.current
40 }
41
```

Theme.kt hosted with ❤ by GitHub

[view raw](#)

Colors provided to CompositionLocal based on darkTheme flag

To use colors in the composable screens reference them through the theme object.

```
1 @Composable
2 fun AppProgressBar() {
3     CircularProgressIndicator(color = Theme.colors.onBackground)
4 }
```

ReferencingColors.kt hosted with ❤ by GitHub

[view raw](#)

Color of the progress bar would be the one set as onBackground in the selected theme

Similarly, we can define dimensions for different configurations and take advantage of smallest width configurations. We can define a default set of dimensions and one for devices with shortest width of at least 360dp.

```
1  class Dimensions(  
2      val grid_0_25: Dp,  
3      val grid_0_5: Dp,  
4      val grid_1: Dp,  
5      val grid_1_5: Dp,  
6      val grid_2: Dp,  
7      val grid_2_5: Dp,  
8      val grid_3: Dp,  
9      val grid_3_5: Dp,  
10     val grid_4: Dp,  
11     val grid_4_5: Dp,  
12     val grid_5: Dp,  
13     val grid_5_5: Dp,  
14     val grid_6: Dp,  
15     val plane_0: Dp,  
16     val plane_1: Dp,  
17     val plane_2: Dp,  
18     val plane_3: Dp,  
19     val plane_4: Dp,  
20     val plane_5: Dp,  
21     val minimum_touch_target: Dp = 48.dp,  
22 )  
23  
24 val smallDimensions = Dimensions(  
25     grid_0_25 = 1.5f.dp,  
26     grid_0_5 = 3.dp,  
27     grid_1 = 6.dp,  
28     grid_1_5 = 9.dp,  
29     grid_2 = 12.dp,  
30     grid_2_5 = 15.dp,  
31     grid_3 = 18.dp,  
32     grid_3_5 = 21.dp,  
33     grid_4 = 24.dp,  
34     grid_4_5 = 27.dp,  
35     grid_5 = 30.dp,  
36     grid_5_5 = 33.dp,  
37     grid_6 = 36.dp,  
38     plane_0 = 0.dp,  
39     plane_1 = 1.dp,  
40     plane_2 = 2.dp,  
41     plane_3 = 3.dp,  
42     plane_4 = 6.dp,  
43     plane_5 = 12.dp,  
44 )  
45  
46 val sw360Dimensions = Dimensions(  
47     grid_0_25 = 2.dp,  
48     grid_0_5 = 4.dp,
```

```

49     grid_1 = 8.dp,
50     grid_1_5 = 12.dp,
51     grid_2 = 16.dp,
52     grid_2_5 = 20.dp,
53     grid_3 = 24.dp,
54     grid_3_5 = 28.dp,
55     grid_4 = 32.dp,
56     grid_4_5 = 36.dp,
57     grid_5 = 40.dp,
58     grid_5_5 = 44.dp,
59     grid_6 = 48.dp,
60     plane_0 = 0.dp,
61     plane_1 = 1.dp,
62     plane_2 = 2.dp,
63     plane_3 = 4.dp,
64     plane_4 = 8.dp,
65     plane_5 = 16.dp,
66 )

```

[view raw](#)

This is similar to defining two different **dimens.xml** files in **res/values** and **res-values-sw360dp**. This forces us to define all the non default dimensions for different configurations at compile time. With the xml approach, we do not get these checks, easily anyway.

Note that we can also define dimensions with a default value like
minimum_touch_target = 48.dp

Now, we have defined both sets of dimensions but how does the system know which one to use? We use [CompositionLocal](#) and provide dimensions based on the current configuration.

```

1  @Composable
2  fun ProvideDimens(
3      dimensions: Dimensions,
4      content: @Composable () -> Unit
5  ) {
6      val dimensionSet = remember { dimensions }
7      CompositionLocalProvider(LocalAppDimens provides dimensionSet, content = content)
8  }
9
10 private val LocalAppDimens = staticCompositionLocalOf {
11     smallDimensions
12 }
13
14 @Composable
15 fun AppTheme(
16     darkTheme: Boolean = isSystemInDarkTheme(),
17     content: @Composable () -> Unit
18 ) {
19     val colors = if (darkTheme) DarkThemeColors else LightThemeColors
20     val configuration = LocalConfiguration.current
21     val dimensions = if (configuration.screenWidthDp <= 360) smallDimensions else sw360
22     val typography = if (configuration.screenWidthDp <= 360) smallTypography else sw360
23
24     ProvideDimens(dimensions = dimensions) {
25         ProvideColors(colors = colors) {
26             MaterialTheme(
27                 colors = colors,
28                 shapes = Shapes,
29                 typography = typography,
30                 content = content,
31             )
32         }
33     }
34 }
35
36 object AppTheme {
37     val colors: Colors
38     @Composable
39     get() = LocalAppColors.current
40
41     val dims: Dimensions
42     @Composable
43     get() = LocalAppDimens.current
44 }
45
46 val Dimens: Dimensions
47 @Composable
48 get() = AppTheme.dimens

```


49

Theme-Dimens.kt hosted with ❤️ by GitHub

[view raw](#)

As you can see, we provide *smallDimensions* for small devices and *sw360Dimensions* for devices with *screenWidthDp* of at least 360. We can also define multiple typography objects with different font sizes in the same way. Dimensions can now be referenced through the theme object as shown below.

```


1 Row(
2     modifier = Modifier.padding(
3         horizontal = AppTheme.dimens.grid_2,
4         vertical = AppTheme.dimens.grid_3
5     ),
6 ) {
7     ...
8 }

```

ReferencingDimens.kt hosted with ❤️ by GitHub

[view raw](#)

And now our screen looks much better on a Nexus One!



A classic before and after screenshot for effect! 😎

If you are migrating the app from the Android View system to Jetpack Compose and don't want to redefine dimensions again, another approach would be to directly

reference the dimensions from xml (using `dimensionResource(id=R.dimen.grid_1)`) similar to how strings are used in Compose. You would have to define multiple sets of dimensions in `res/values` and `res/values-sw360dp` to have the desired result.

. . .

In most cases, we can rely on various modifiers like *fillMaxWidth*, *fillMaxHeight*, *wrapContent* or think of our layouts in percentages/fractions or aspect ratios but there are definitely cases where it's important to use dimensions. Following the same pattern, we can define dimensions or integers for `sw600dp` (7 inch Tablets) and `sw720dp` (10 inch Tablets) whenever they make a comeback on Android. 🤨 In many cases the layouts for tablets are different and “traditionally” have resided in `res/layout-sw600dp` or `res/layout-sw720dp` or other configuration for even larger devices, but we can still rely on common dimensions being defined for those configurations so we do not duplicate them in all the layout files/composable screens for larger screen sizes.

. . .

Migrating existing Dimens

In case you already have Dimens defined in the object like in the beginning of the post, you can use *replaceWith* param from the `Deprecated` annotation for IntelliJ to assist with the migration.

```

1  @Deprecated(
2      message = "Use AppTheme.dimens instead to support smaller screen sizes as well",
3      replaceWith = ReplaceWith(expression = "AppTheme.dimens", imports = ["_.ui.theme.AppTheme"])
4  )
5  object Dimens {
6      ...
7  }
8
9  class Dimensions(
10     ...
11 )
12
13 val defaultDimensions = Dimensions(
14     ...
15 )
16
17 val sw360Dimensions = Dimensions(
18     ...
19 )

```

ReplaceDimens.kt hosted with ❤️ by GitHub

[view raw](#)

• • •

References

- [DesignBytes: Density-independent Pixels](#)
- [Supporting different screen sizes](#)
- [CompositionLocal Documentation](#)
- [dimensionResource\(\)](#)
- [Deprecated Annotation Documentation](#)

• • •

That's all folks! Feel free to comment or message me if you have any questions.

[GitHub](#) | [LinkedIn](#) | [Twitter](#)

Android

Jetpack Compose

Android App Development

Kotlin

AndroidDev