PRACTICAL-06

AIM: Implementation of chain matrix multiplication using dynamic programming.

PROGRAM:

```
#include <iostream>
#include <climits>
using namespace std;

int main() {
    int n;
    cout << "Enter number of matrices: ";
   cin >> n;

    int p[n + 1];  cout << "Enter dimensions array (" << n + 1
   << " values): ";  for (int i = 0; i <= n; i++) {  cin >> p[i];
   }

    int dp[n][n];

    // Cost is 0 when multiplying one
   matrix  for (int i = 0; i < n; i++) {
   dp[i][i] = 0;
    }

    // chainLength is the number of matrices in a subchain  for
   (int chainLength = 2; chainLength <= n; chainLength++) {
   for (int i = 0; i <= n - chainLength; i++) {  int j = i +
   chainLength - 1;




          for (int k = i; k < j; k++) {  int
             cost = dp[i][k] + dp[k + 1][j]
```

```
        dp[i][j] = INT_MAX;

                + p[i] * p[k + 1] * p[j + 1];


            if (cost < dp[i][j]) {
               dp[i][j] = cost;
            }
         }
       }
  }
      cout << "Minimum number of scalar multiplications: "
       << dp[0][n - 1] << endl;
  return 0;
}
```

OUTPUT:



CONCLUSION:

Matrix Chain Multiplication uses dynamic programming to find the most efficient order for multiplying matrices. It does not change the final matrix result; it only minimizes the number of scalar multiplications required. The C++ program computes this minimum cost efficiently in $O(n^3)$ time and uses $O(n^2)$ memory.