RAJALAKSHMI ENGINEERING COLLEGE

Ashwanth M P 251801030-2025-AIDS

A2

| | |
|---|---|
| **Started on** | Thursday, 24 September 2026, 10:59 AM |
| **State** | Finished |
| **Completed on** | Thursday, 8 October 2026, 10:12 AM |
| **Time taken** | 13 days 23 hours |
| **Marks** | 1.00/1.00 |
| **Grade** | **10.00** out of 10.00 (**100**%) |

**Question 1** | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array

2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

**For example:**

| Input | Result |
|---|---|
| 1<br>3 10 17 57<br>6<br>2 7 10 15 57 246 | 10 57 |

**Answer:** (penalty regime: 0 %)

```
#include <stdio.h>
int main() {
int T;
scanf("%d", &T);
while (T--) {
int n1, n2;
scanf("%d", &n1);
int a[n1];
for (int i = 0; i < n1; i++) {
scanf("%d", &a[i]);
}
scanf("%d", &n2);
int b[n2];
for (int i = 0; i < n2; i++) {
```

```
15  scanf("%d", &b[i]);
16  }
17  int i = 0, j = 0;
18  while (i < n1 && j < n2) {
19  if (a[i] == b[j]) {
20  printf("%d ", a[i]);
21  i++;
22  j++;
23  }
24  else if (a[i] < b[j]) {
25  i++;
26  }else {
27  j++;
28  }}
29  printf("\n");
30  }
31  return 0;
32  }
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✔ | 1<br>3 10 17 57<br>6<br>2 7 10 15 57 246 | 10 57 | 10 57 | ✔ |
| ✔ | 1<br>6 1 2 3 4 5 6<br>2<br>1 6 | 1 6 | 1 6 | ✔ |

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course