

Logic

February 28, 2021

0.1 Notes

1. The notebooks are largely self-contained, i.e, if you see a symbol there will be an explanation about it at some point in the notebook.
 - Most often there will be links to the cell where the symbols are explained
 - If the symbols are not explained in this notebook, a reference to the appropriate notebook will be provided
2. **Github does a poor job of rendering this notebook.** The online render of this notebook is missing links, symbols, and notations are badly formatted. It is advised that you clone a local copy (or download the notebook) and open it locally.

1 Contents

1. Logic
 - Boolean operations
 - And
 - Or
 - Not
 - Exclusive Or
 - Nand
 - Proof symbols
 - Implies
 - Implied by
 - If and only if
 - Therefore
 - Because
 - Contradiction
 - End of Proof
 - Quantifiers
 - For all
 - There exists
 - There exists uniquely
 - Combining quantifiers

1.1 Importing Libraries

```
[1]: import random
import math
```

Boolean Operations

And

The Boolean And operation is denoted using \wedge

$$p \wedge q$$

```
[2]: p = bool()
q = bool()

p and q
```

```
[2]: False
```

Or

The Boolean Or operation is denoted using \vee

$$p \vee q$$

```
[3]: p = bool()
q = bool()

p or q
```

```
[3]: False
```

Not

The Boolean Not operation is denoted using \sim or \neg and sometimes just the text ‘not’ is used:

$$\sim p$$

or

$$\neg p$$

or

$$\text{not } p$$

```
[4]: p = bool()

not p
```

```
[4]: True
```

Exclusive Or

The Exclusive Or operation is denoted using $\underline{\vee}$ or \oplus or just XOR

$$p \underline{\vee} q$$

or

$$p \oplus q$$

or

$$p \text{ XOR } q$$

```
[5]: p = bool()
q = bool()

#Shorter code since bool Xor equivalent to bitwise Xor
XOR_short = p ^ q

#Longer code by definition
XOR_long = (not q and p) or (not p and q)

XOR_short, XOR_long
```

```
[5]: (False, False)
```

Nand

The Nand operation is denoted using $\bar{\wedge}$

$$p \bar{\wedge} q$$

The Nand operator can be expanded to: $p \bar{\wedge} q = \neg(p \vee q)$

```
[6]: p = bool()
q = bool()

not (p and q)
```

```
[6]: True
```

Proof Symbols

Implies

In mathematical proofs, the term ‘implies’ means ‘if a then b ’ or ‘ a implies b ’ and this is denoted using the symbol: \Rightarrow

$$a \Rightarrow b$$

Here a and b are any mathematical concepts (or *logical predicates*)

```
[7]: boo = [True, False]

for a in boo:
    for b in boo:
        print('a: ', a, 'b: ', b, ', a implies b :', b or (not a))
```

```
a: True b: True , a implies b : True
a: True b: False , a implies b : False
a: False b: True , a implies b : True
a: False b: False , a implies b : True
```

To prove a theorem of this form, you must prove that b is true whenever a is true. Example: if x is greater than or equal to 4, then $2^x \geq x^2$

$$\forall x \in \mathbb{R}, x \geq 4 \Rightarrow 2^x \geq x^2$$

i.e: if $(a = x \geq 4)$, then $(b = 2^x \geq x^2)$

Notice from the above truth table that a may be False when b is True. However, b **must** be True when a is True. Hence, if we can show that b is False when a is True, we have invalidated the $a \Rightarrow b$ statement.

(See: For all)

For more information on the real set and the belongs to notation see the [Collections notebook](#)

```
[8]: print('if a then b')

X = [-10.00,-2.20,0.00,2.00,3.10,4.00,5.5,6.00,7.8] #Subset of R used as an
↪example

for x in X:
    condition_a = x >= 4
    condition_b = 2**x >= x**2
    print('x :', x, ', x>=4, a: ', condition_a, ', 2^x>=x^2, b: ', condition_b)

print('\nCompared with the truth table above')
print('a implies b')
```

```
#Atleast for this subset of R
```

```
if a then b
x : -10.0 , x>=4, a:  False , 2^x>=x^2, b:  False
x : -2.2 , x>=4, a:  False , 2^x>=x^2, b:  False
x : 0.0 , x>=4, a:  False , 2^x>=x^2, b:  True
x : 2.0 , x>=4, a:  False , 2^x>=x^2, b:  True
x : 3.1 , x>=4, a:  False , 2^x>=x^2, b:  False
x : 4.0 , x>=4, a:  True  , 2^x>=x^2, b:  True
x : 5.5 , x>=4, a:  True  , 2^x>=x^2, b:  True
x : 6.0 , x>=4, a:  True  , 2^x>=x^2, b:  True
x : 7.8 , x>=4, a:  True  , 2^x>=x^2, b:  True
```

Compared with the truth table above
 a implies b

Implied by

In mathematical proofs, the term ‘implied by’ means ‘if b then a ’ or ‘ a is implied by b ’ and this is denoted using the symbol: \Leftarrow

$$a \Leftarrow b$$

Here a and b are any mathematical concepts (or *logical predicates*)

```
[9]: boo = [True, False]

for a in boo:
    for b in boo:
        print('a: ', a, 'b: ', b, ', a implied by b :', a or (not b))
```

```
a:  True b:  True , a implied by b : True
a:  True b:  False , a implied by b : True
a:  False b:  True , a implied by b : False
a:  False b:  False , a implied by b : True
```

To prove a theorem of this form, you must prove that a true whenever b is true. To explain the concept, let's expand on the previous example, but here let's assume that the opposite condition is true, i.e: $x \geq 4$ is implied by $2^x \geq x^2$

$$\forall x \in \mathbb{R}, x \geq 4 \Leftarrow 2^x \geq x^2$$

So based on our truth table above we have: $a = (x \geq 4)$, $b = (2^x \geq x^2)$. Interestingly, if this is true we would have proved that $x \geq 4$ if and only if $2^x \geq x^2$ (See: if and only if)

(See: For all)

For more information on the real set and the belongs to notation see the Collections notebook

Now based on the truth table above if we observe a is False when b is True we have essentially disproved the implied by assertion:

```
[10]: print('if b then a')

X = [0.00,2.00]

for x in X:
    condition_a = x >= 4
    condition_b = 2**x >= x**2
    print('x :', x, ', 2^x>=x^2, b: ', condition_b, ', x>=4, a: ', condition_a,)

print('a is NOT implied by b')
```

```
if b then a
x : 0.0 , 2^x>=x^2, b: True , x>=4, a: False
x : 2.0 , 2^x>=x^2, b: True , x>=4, a: False
a is NOT implied by b
```

If and only if

In mathematical proofs, the term ‘if and only if’ means ‘if a then b ’ as well as ‘if b then a ’ and this is denoted using the symbol: \iff but it is also sometimes abbreviated as: iff

$$a \iff b$$

or

$$a \text{ iff } b$$

The concept of iff is also logically equivalent to $(a \Rightarrow b) \wedge (b \Rightarrow a)$

(See: And and Implies)

Here a and b are any mathematical concepts (or *logical predicates*).

```
[11]: boo = [True, False]

for a in boo:
    for b in boo:
        print('a: ', a, 'b: ', b, ', a iff b :', (b or (not a)) and (a or (not b)))
```

```
a: True b: True , a iff b : True
a: True b: False , a iff b : False
a: False b: True , a iff b : False
a: False b: False , a iff b : True
```

To prove a theorem of this form, you must prove that a and b are equivalent. Not only is b true whenever a is true, but a is true whenever b is true. Example: The integer n is odd if and only if

n^2 is odd.

$$\forall n \in \mathbb{Z}, n \text{ is odd} \iff n^2 \text{ is odd}$$

i.e: ($a = n$ is odd) iff ($b = n^2$ is odd)

(See: For all)

For more information on the integer set and the belongs to notation see the Collections notebook

```
[12]: def is_odd(x):
      return not (x%2 == 0)

      print('if a then b')

      #Check if a then b
      N = [random.randint(-1000,1000) for i in range(5)]

      for n in N:
          print('n: ', n, ', odd(n), a:', is_odd(n),
                '\nn2: ', n**2, ', odd(n2), b:', is_odd(n**2), '\n')

      print('if b then a')
      #Check if b then a:
      N_new = [random.randint(-1000,1000)**2 for i in range(5)]

      for n_squared in N_new:
          n = int(math.sqrt(n_squared))
          print('n2: ', n_squared, ', odd(n2), a:', is_odd(n_squared),
                '\nn: ', n, ', odd(n): ', all([is_odd(n), is_odd(-n)]), '\n')
```

if a then b

n: 941 , odd(n), a: True

n2: 885481 , odd(n2), b: True

n: -608 , odd(n), a: False

n2: 369664 , odd(n2), b: False

n: 860 , odd(n), a: False

n2: 739600 , odd(n2), b: False

n: -503 , odd(n), a: True

n2: 253009 , odd(n2), b: True

n: -649 , odd(n), a: True

n2: 421201 , odd(n2), b: True

if b then a

n2: 5329 , odd(n2), a: True

```

n: 73 , odd(n): True

n2: 535824 , odd(n2), a: False
n: 732 , odd(n): False

n2: 175561 , odd(n2), a: True
n: 419 , odd(n): True

n2: 20736 , odd(n2), a: False
n: 144 , odd(n): False

n2: 654481 , odd(n2), a: True
n: 809 , odd(n): True

```

Therefore

The term therefore is denoted by:

$$r^2 + \lambda^2 c^2 = 0 \therefore r = \pm \lambda ci$$

Because

The term *because* is denoted by: \because

$$\because x + 1 = 10 \therefore x = 9$$

Contradiction

Contradiction in a proof is denoted by: $\Rightarrow \Leftarrow$

Used to show that the supposition was False

End of Proof

The end of a proof is show using the following notations or text:

Just a square box:



a filled square box:



or the text:

QED

Quantifiers

For all

Also called a universal quantifier. The ‘for all’ symbol is used simply to denote that a concept or relation (or *logical predicates*) is applied to every member of the domain. Denoted by \forall

For example: squares of all real numbers are positive or zero can be expressed through:

$$\forall x \in \mathbb{R}, x^2 \geq 0$$

Which can be read as, for all x belonging to the set of real numbers (essentially any real number), the square of x is always greater or equal to zero.

For more information on the real set and the belongs to notation see the Collections notebook

```
[13]: trials = 5

for i in range(trials):
    x = random.uniform(-100000, 100000)**2
    print(x >= 0)
```

True

True

True

True

True

The for all \forall notations can be extended to denote complex statements. For example the commutative property of addition can be denoted using:

$$\forall x \in \mathbb{R}, \forall y \in \mathbb{R}, x + y = y + x$$

There exists

Also called an existential quantifier. This symbol can be interpreted as ‘there exists’, ‘there is at least one’, or ‘for some’ and applied to a mathematical concept (or *logical predicates*); it is denoted by: \exists

For example: there exists at least one real number x whose square equals 2

$$\exists x \in \mathbb{R}, x^2 = 2$$

With this symbol, an assertion is being made about an object’s existence which fulfills a criteria, which is true in this case since both $x = +\sqrt{2}$ and $x = -\sqrt{2}$ satisfy this condition.

Sometimes for readability, some authors will use the abbreviation for **such that** (*s.t.*) :

$$\exists x \in \mathbb{R} \text{ s.t. } x^2 = 2$$

For more information on the real set and the belongs to notation see the Collections notebook

```
[14]: x_square = 2
      x_1 = math.sqrt(2)
      x_2 = -math.sqrt(2)

      type(x_1) == float, type(x_2) == float

      #There may be more x's but we've shown enough to prove this statement to be true
```

```
[14]: (True, True)
```

There exists uniquely

When the existential quantifier symbol is followed by an exclamation point, it means there exists a **unique** object that fulfills a given criteria: $\exists!$

For example: there exists a unique real number x whose square equals 0

$$\exists!x \in \mathbb{R}, x^2 = 0$$

which is true in this case since only $x = 0$ satisfies this condition.

For more information on the real set and the belongs to notation see the Collections notebook

```
[15]: #Shown as an example, in reality you would have to look at each element
      #in the infinite real set to prove uniqueness
      for x in range(-5,5):
          print('x: ',(x/10),', x2 == 0', (x/10)**2 == 0)
```

```
x: -0.5 , x2 == 0 False
x: -0.4 , x2 == 0 False
x: -0.3 , x2 == 0 False
x: -0.2 , x2 == 0 False
x: -0.1 , x2 == 0 False
x: 0.0 , x2 == 0 True
x: 0.1 , x2 == 0 False
x: 0.2 , x2 == 0 False
x: 0.3 , x2 == 0 False
x: 0.4 , x2 == 0 False
```

Combining quantifiers

The for all \forall and exists \exists notations can be combined to denote complex statements.

For example: For all x in the real number set, there exists at least one real number y such that $x + y = 0$

$$\forall x \in \mathbb{R}, \exists y \in \mathbb{R}, x + y = 0$$

This statement means that if we were to pick **any** real number x , we can find at least one number y so that we get $x + y = 0$. We know this to be a True statement since we can always find a number $y = -x$

For more information on the real set and the belongs to notation see the **Collections notebook**

```
[16]: R_sample = [random.random() for i in range(10)] #checking for a small subset of
↳the real number
#set as an example. In reality we would have to loop over the entire infinite
↳Real number set
#to check for all x

X = R_sample
Y = [-x for x in X]

all([ x + y == 0 for x,y in zip(X,Y)])
```

[16]: True

Note: The statement order is very important since it evolves logically and combines to form a logical assertion. The above example was well ordered but consider the following example:

$$\exists y \in \mathbb{R}, \forall x \in \mathbb{R}, x + y = 0$$

In this case we make an assertion that there exists a real number y which will have the property $x + y = 0$ for any real number x . Such a real number y does not exist and so this assertion is **False**.

```
[17]: R_sample = [random.random() for i in range(10)] #checking for a small subset of
↳the real number
#set as an example. In reality we would have to loop over the entire infinite
↳Real number set
#to check for all y

any([all([ x+y == 0 for x in R_sample]) for y in R_sample ])
```

[17]: False