

Specification Sheet – Unit Model 77

Manufacturer: Legacy Industrial Co.

Date: 1987-04-12

This document contains original factory specifications for Unit Model 77.

All measurements are in imperial units unless otherwise noted.

Refer to Appendix B for SI conversion factors.

Section 1 – Mechanical Specifications

Frame material: Carbon steel, ASTM A36

Overall dimensions: 24 in x 18 in x 12 in

Weight (unloaded): 185 lb

Mounting: Four 1/2-inch bolt holes on 16 in x 12 in pattern

Maximum static load: 2,500 lb

Dynamic load rating: 1,800 lb at 60 RPM

Journal of Management Education 37(1)

Journal of Management Education 37(1)

Journal of Management Education 37(1)

Journal of Management Education 37(1)

Journal of Management Education 37(1)

Journal of Management Education 37(1)

Journal of Management Education 37(1)

Section 3 – Operating Conditions

Ambient temperature: 32 F to 104 F (0 C to 40 C)

Relative humidity: 10% to 90% non-condensing

Altitude: Up to 3,300 ft (1,000 m) without derating

Enclosure class: NEMA 12 (IP54 equivalent)

Cooling: Forced air, internal fan

Section 4 – Maintenance Schedule

Monthly:

- Inspect all electrical connections for corrosion
- Check cooling fan operation
- Verify input voltage within +/-5% of rating

Annually:

- Replace cooling fan filter (Part No. LG-F001)
- Inspect and re-torque all bus connections
- Perform insulation resistance test (>1 MOhm at 500 V DC)

Section 5 – Fault Codes

Code F01: Overcurrent - reduce load or check motor winding

Code F02: Overvoltage - check supply voltage regulation

Code F03: Undervoltage - check supply breaker and wiring

Code F04: Overtemperature - check ambient conditions and cooling

Code F07: Ground fault - inspect wiring insulation

Code F09: Communication loss - check control wiring

Section 6 – Spare Parts List

Part No.	Description	Qty
LG-0041	Drive Belt Assembly	1
LG-0042	Bearing Set (4 per kit)	2
LG-0043	Seal Kit (input shaft)	1
LG-F001	Cooling Fan Filter	2
LG-C001	Control Board	1
LG-P001	Power Supply Module 24V	1

Section 7 – Wiring Diagram Notes

All field wiring must be copper conductor rated for 75 C minimum.

Use wire gauge per NEC Table 310.15(B)(16) based on calculated ampacity.

Maintain minimum 1-inch separation between power and control wiring.

Shield control cables and ground shield at one end only (drive end).

Maximum control cable run: 100 feet without signal repeater.

Section 8 – Warranty and Service

Warranty period: 24 months from date of shipment.

Warranty covers defects in materials and workmanship under normal use.

Warranty void if operated outside specified conditions or improperly installed.

For service, contact

Legacy Industrial Service Center

Phone: 1-800-555-0199

Hours: 8 AM to 5 PM Eastern, Monday to Friday

Appendix A – Agency Certifications

UL Listed: File No. E123456, Category QCZZ

CSA Certified: File No. 123456, Class 3211 06

CE Marked: Directive 2014/35/EU (LVD), 2014/30/EU (EMC)

RoHS Compliant: Directive 2011/65/EU

All certifications apply to standard configurations only.

Consult factory for modified or special configurations.

Appendix B-- SI Conversion Factors

1 inch = 25.4 mm

1 foot = 0.3048 m

1 pound (mass) = 0.4536 kg

1 pound-force = 4.448 N

1 ft-lb = 1.356 N-m

1 HP = 0.7457 kW

1 BTU/hr = 0.2931 W

F to C: $(F - 32) \times 5/9$

Appendix C – Ordering Information

Base model: LG-M77-460-3P

Options

- A1 Extended temperature (-20 C to 60 C)
- A2 NEMA 4X enclosure (IP66)
- B1 Modbus RTU communication card
- B2 Ethernet/IP adapter
- C1 Conformal coating (IEC 60721-3-3, Class 3C2)

Example: LG-M77-460-3P-A2-B1 = NEMA 4X with Modbus