```c
//************************************************
// BISECTION METHOD
//************************************************
#include<stdio.h>   // Inclusion of the input-output header file

#define eps 0.0005   //eps=EPSILON
#define N 20         //N= Maximum number of iterations

float func(float x);         //Function Prototype
float absolute(float y);     //Function Prototype

//*************STARTING MAIN FUNCTION*********
int main(void)
{
   float a,b,mid;            //Variable declaration
   int i;                    //Variable declaration

   // Defining the input and output files

   FILE *input, *out1, *out2;
   input=fopen("input/data.txt","r");
   out1=fopen("iterations/iteration.txt","w");
   out2=fopen("mid values/mid.txt","w");
   // End of input-output file definition

    // Reading inputs from the input file
   printf("Enter the brackets");
   fscanf(input,"%f\t%f",&a,&b);
   // End of reading the inputs from input file

   if(func(a)*func(b)<0)
    {
    printf("The required roots\n");
    printf("****************\n");
    for(i=0;i<N;i++)
        {
            mid=(a+b)/2.0;
            if(absolute(func(mid))<eps)
                break;
            else if(func(mid)*func(a)<0)b=mid;
            else if(func(mid)*func(b)<0)a=mid;

            // Writing the outputs in the output files
            fprintf(out1,"%d\n",i+1);
            fprintf(out2,"%f\n",mid);
        }
        fprintf(out1,"%d\n",i+1);
        fprintf(out2,"%f\n",mid);
            //  End of taking the outputs
    }
    else
    {
        printf("Please enter feasible values of brackets");
    }
    return 0;
}
//****************END OF MAIN FUNCTION**********

//*******EVALUATION OF THE FUNCTION
float func(float x)
{
    return (x*x*x-x-1);
}
//*******END OF FUNCTION EVALUATION

// FUNCTION FOR OBTAING THE ABSOLUTE
float absolute(float y)
```

```
68  {
69      if(y<0)
70          return -1*y;
71      else
72          return y;
73  }
74  // END OF THE FUNCTION: ABSOLUTE
75
```