```
/*Implementation of solution of system of linear equations by
Gauss-Jacobi's iteration method.
 Coded by Ashwini Kumar Singh on 10-Feb-2021*/
#include<stdio.h>
#include<math.h>
int main() {
   int i,j,m,n,itrn;
*************************\n");
   printf("\nImplementation of solution of system of linear equations
by Gauss-Jacobi's iteration method\n");
   printf("Coded by Ashwini Kumar Singh on 10-Feb-2021\n");
***********************
   FILE *fp in 1=fopen("a matrix.txt","r");
   FILE *fp in 2=fopen("b matrix.txt","r");
   FILE *output=fopen("outGaussSeidelItr.tsy", "w");
   printf("\nEnter the value of n :");
   scanf("%d",&n);
   printf("\nEnter the number of iterations : ");
   scanf("%d", &itrn);
   double a[n][n],b[n],x[n],c[n];
   for (i=0; i<n; i++)</pre>
       for (j=0; j<n; j++)
           fscanf(fp in 1, "%]f", &a[i][j]);
       fscanf(fp in 2, "%]f", &b[i]);
   }
   printf("\nThe matrices read from a matrix.txt and b matrix.txt
are:\n\n\t\tMatrix - A\t\t\tMatrix - B\n\n");
   for (i=0; i<n; i++)</pre>
    {
       for (j=0; j<n; j++)
           printf("%lf\t",a[i][j]);
       printf("\t%lf\n",b[i]);
   fprintf (output, "\nIteration");
   for (i=1; i<=n; i++)</pre>
           fprintf(output, "\tJx%d", i);
   m=1;
```

```
do{
for (i=0;i<n;i++) {</pre>
    c[i]=b[i];
     for(j=0;j<n;j++) {
         if(i!=j) {
              c[i]=c[i]-a[i][j]*x[j];
for (i=0;i<n;i++) {</pre>
    x[i]=c[i]/a[i][i];
printf("\n%d\t:\t",m);
fprintf(output, "\n%d\t", m);
for (i=0; i<n; i++)</pre>
     {
         printf("x(%d) = %f\t", i+1, x[i]);
         fprintf(output, "%f\t", x[i]);
m++;
}while (m<=itrn);</pre>
printf("\n\nThe Solution is : \n");
for (i=0; i<n; i++)</pre>
    {
         printf("\nx(%d) = %f", i, x[i]);
```

}