RAJALAKSHMI ENGINEERING COLLEGE

R Ashwin Kumar 251801033-2025-AIDS

R2

| | |
|---|---|
| **Started on** | Tuesday, 25 August 2026, 2:23 PM |
| **State** | Finished |
| **Completed on** | Tuesday, 25 August 2026, 2:44 PM |
| **Time taken** | 21 mins 8 secs |
| **Marks** | 1.00/1.00 |
| **Grade** | **10.00** out of 10.00 (**100**%) |

**Question 1** | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs( 1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

**For example:**

| Input | Result |
|---|---|
| 3<br>1<br>2<br>3<br>4<br>5<br>6 | 28 |

**Answer:** (penalty regime: 0 %)

```c
#include <stdio.h>

void sortAscending(int a[], int n)
{
    for (int i = 0; i < n - 1; i++)
    {
        for (int j = i + 1; j < n; j++)
        {
            if (a[i] > a[j])
            {
                int temp = a[i];
                a[i] = a[j];
                a[j] = temp;
            }
        }
    }
}

void sortDescending(int b[], int n)
{
    for (int i = 0; i < n - 1; i++)
    {
        for (int j = i + 1; j < n; j++)
        {
            if (b[i] < b[j])
            {
                int temp = b[i];
                b[i] = b[j];
                b[j] = temp;
            }
        }
    }
}

int main()
{
    int n;
    scanf("%d", &n);

    int a[n], b[n];

    for (int i = 0; i < n; i++)
        scanf("%d", &a[i]);

    for (int i = 0; i < n; i++)
        scanf("%d", &b[i]);

    sortAscending(a, n);
    sortDescending(b, n);

    int sum = 0;

```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✔ | 3<br>1<br>2<br>3<br>4<br>5<br>6 | 28 | 28 | ✔ |
| ✔ | 4<br>7<br>5<br>1<br>2<br>1<br>3<br>4<br>1 | 22 | 22 | ✔ |
| ✔ | 5<br>20<br>10<br>30<br>10<br>40<br>8<br>9<br>4<br>3<br>10 | 590 | 590 | ✔ |

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course