Enhancing Comprehension and Navigation in Jupyter Notebooks with Static Analysis

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit`; emboldening with the com-

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.

[*]Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[†]Dr. Trovato also works at...

Copyright is held by the IW3C2.

WWW2007, May 8–12, 2007, Banff, Canada.

Flowdroid: Precise context, flow, field, object-sensitive and lifecycle-aware taint analysis for android apps

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit`; emboldening with the com-

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.

[*]Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[†]Dr. Trovato also works at...

Copyright is held by the IW3C2.

WWW2007, May 8–12, 2007, Banff, Canada.

A qualitative analysis of android taint-analysis results

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit`; emboldening with the com-

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.

[*]Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[†]Dr. Trovato also works at...

Copyright is held by the IW3C2.

WWW2007, May 8–12, 2007, Banff, Canada.

Enhancing human-in-the-loop adaptive systems through digital twins and VR interfaces

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit`; emboldening with the com-

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.

[*]Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[†]Dr. Trovato also works at...

Copyright is held by the IW3C2.

WWW2007, May 8–12, 2007, Banff, Canada.

A large-scale study of usability criteria addressed by static analysis tools

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit`; emboldening with the com-

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.

[*]Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[†]Dr. Trovato also works at...

Copyright is held by the IW3C2.

WWW2007, May 8–12, 2007, Banff, Canada.

CrySL: An Extensible Approach to Validating the Correct Usage of Cryptographic APIs

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit`; emboldening with the com-

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.

[*]Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[†]Dr. Trovato also works at...

Copyright is held by the IW3C2.

WWW2007, May 8–12, 2007, Banff, Canada.

Boomerang: Demand-driven flow-and context-sensitive pointer analysis for java

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit`; emboldening with the com-

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.

[*]Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[†]Dr. Trovato also works at...

Copyright is held by the IW3C2.

WWW2007, May 8–12, 2007, Banff, Canada.

VREUD-an end-user development tool to simplify the creation of interactive VR scenes

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit`; emboldening with the com-

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.

[*]Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[†]Dr. Trovato also works at...

Copyright is held by the IW3C2.

WWW2007, May 8–12, 2007, Banff, Canada.

Automated cell header generator for Jupyter notebooks

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit`; emboldening with the com-

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.

[*]Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[†]Dr. Trovato also works at...

Copyright is held by the IW3C2.

WWW2007, May 8–12, 2007, Banff, Canada.

Iccta: Detecting inter-component privacy leaks in android apps

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit;` emboldening with the com-

*Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[1]Dr. Trovato also works at...

Copyright is held by the IW3C2.
WWW2007, May 8–12, 2007, Banff, Canada.

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.

Magpiebridge: A general approach to integrating static analyses into ides and editors (tool insights paper)

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit;` emboldening with the com-

*Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[1]Dr. Trovato also works at...

Copyright is held by the IW3C2.
WWW2007, May 8–12, 2007, Banff, Canada.

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.

Sootfx: A static code feature extraction tool for java and android

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit;` emboldening with the com-

*Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[1]Dr. Trovato also works at...

Copyright is held by the IW3C2.
WWW2007, May 8–12, 2007, Banff, Canada.

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.

Fully-featured anonymous credentials with reputation system

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit;` emboldening with the com-

*Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[1]Dr. Trovato also works at...

Copyright is held by the IW3C2.
WWW2007, May 8–12, 2007, Banff, Canada.

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.

Context-, flow-, and field-sensitive data-flow analysis using synchronized pushdown systems

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit;` emboldening with the com-

*Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[1]Dr. Trovato also works at...

Copyright is held by the IW3C2.
WWW2007, May 8–12, 2007, Banff, Canada.

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.

Just-in-time static analysis

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit;` emboldening with the com-

*Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[1]Dr. Trovato also works at...

Copyright is held by the IW3C2.
WWW2007, May 8–12, 2007, Banff, Canada.

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.

Forward-secure 0-RTT goes live: implementation and performance analysis in QUIC

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit;` emboldening with the com-

*Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[1]Dr. Trovato also works at...

Copyright is held by the IW3C2.
WWW2007, May 8–12, 2007, Banff, Canada.

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.

Security Implications Of Compiler Optimizations On Cryptography–A Review

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit;` emboldening with the com-

*Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[1]Dr. Trovato also works at...

Copyright is held by the IW3C2.
WWW2007, May 8–12, 2007, Banff, Canada.

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.

Effective Inter-Component communication mapping in android: An essential step towards holistic security analysis

ABSTRACT

This paper provides a sample of a LaTeX document which conforms, somewhat loosely, to the formatting guidelines for ACM SIG Proceedings. It is an *alternate* style which produces a *tighter-looking* paper and was designed in response to concerns expressed, by authors, over page-budgets. It complements the document *Author's (Alternate) Guide to Preparing ACM SIG Proceedings Using LaTeX2ε, and BibTeX*. This source file has been written with the intention of being compiled under LaTeX2ε, and BibTeX. The developers have tried to include every imaginable sort of "bells and whistles", such as a subtitle, footnotes on title, subtitle and authors, as well as in the text, and every optional component (e.g. Acknowledgments, Additional Authors, Appendices), not to mention examples of equations, theorems, tables and figures. To make best use of this sample document, run it through LaTeX and BibTeX, and compare this source code with the printed output produced by the dvi file. A compiled PDF version is available on the web page to help you with the 'look and feel'.

Categories and Subject Descriptors

H.4.m [**Information Systems**]: Miscellaneous; D.2 [**Software**]: Software Engineering; D.2.8 [**Software Engineering**]: Metrics—*complexity measures, performance measures*

General Terms

Delphi theory

Keywords

ACM proceedings, LaTeX, text tagging

1. INTRODUCTION

The *proceedings* are the records of a conference. ACM seeks to give these conference by-products a uniform, high-quality appearance. To do this, ACM has some rigid requirements for the format of the proceedings documents: there is a specified format (balanced double columns), a specified set of fonts (Arial or Helvetica and Times Roman) in certain specified sizes (for instance, 9 point for body copy), a specified live area (18 × 23.5 cm [7" × 9.25"]) centered on the page, specified size of margins (2.54cm [1"] top and bottom and 1.9cm [.75"] left and right; specified column width (8.45cm [3.33"]) and gutter size (.083cm [.33"]).

The good news is, with only a handful of manual settings[1], the LaTeX document class file handles all of this for you.

The remainder of this document is concerned with showing, in the context of an "actual" document, the LaTeX commands specifically available for denoting the structure of a proceedings paper, rather than with giving rigorous descriptions or explanations of such commands.

2. THE *BODY* OF THE PAPER

Typically, the body of a paper is organized into a hierarchical *structure*, with numbered or unnumbered headings for sections, subsections, sub-subsections, and even smaller sections. The command `\section` that precedes this paragraph is part of such a hierarchy.[2] LaTeX handles the numbering and placement of these headings for you, when you use the appropriate heading commands around the titles of the headings. If you want a sub-subsection or smaller part to be unnumbered in your output, simply append an asterisk to the command name. Examples of both numbered and unnumbered headings will appear throughout the balance of this sample document.

Because the entire article is contained in the **document** environment, you can indicate the start of a new paragraph with a blank line in your input file; that is why this sentence forms a separate paragraph.

2.1 Type Changes and *Special* Characters

We have already seen several typeface changes in this sample. You can indicate italicized words or phrases in your text with the command `\textit;` emboldening with the com-

*Produces the WWW2007-specific release, location and copyright information). For use with www2007-submission.cls V1.4. Supported by ACM.

[1]Dr. Trovato also works at...

Copyright is held by the IW3C2.
WWW2007, May 8–12, 2007, Banff, Canada.

[1]Two of these, the `\numberofauthors` and `\alignauthor` commands, you have already used; another, `\balancecolumns`, will be used in your very last run of LaTeX to ensure balanced column heights on the last page.

[2]This is the second footnote. It starts a series of three footnotes that add nothing informational, but just give an idea of how footnotes work and look. It is a wordy one, just so you see how a longish one plays out.