

Task 5: Create onCellEdit Client Script

Activity 1: Create Client Script

1. **Navigate to Client Scripts:**

Go to System UI → Client Scripts in your ServiceNow instance.

2. **Click New** to create a new Client Script.

3. **Fill in the details:**

- **Name:** Prevent state change via list edit – clearly indicates that the script prevents users from changing the State field directly in a list.
- **Table:** Incident – applies the script only to Incident records.
- **Type:** onCellEdit – runs whenever a field is edited directly in a list view.
- **Field name:** State – the script will monitor changes to the State field.
- **Active:** true – ensures the script is enforced immediately.

4. **Paste the script** into the script editor section. The script should prevent unauthorized changes to the State field when editing from the list view.

5. **Click Submit** to save the Client Script.

6. **Verify:** Open an Incident list and try to change the State field directly in the list. The script should block the change as intended.

7. In the Script field, paste the following code:

```
function onCellEdit(sysIDs, table, oldValues, newValue, callback) {
```

```
    alert('State cannot be updated using list editing. Please open the Incident.');
```

```
    callback(false);
```

}

8. Click Submit.

The screenshot shows the ServiceNow interface for configuring a Client Script. The left sidebar contains the navigation menu with 'Client Scripts' selected. The main area displays the configuration form for a Client Script named 'Prevent state change via list edit'. The form includes fields for Name, Table, UI Type, Type, and Field name, all of which are highlighted with red boxes. The 'Script' field is also highlighted with a red box and contains a JavaScript function that alerts the user and cancels the list edit. The 'Isolate script' checkbox is checked.

Client Script - Prevent state change via list edit

New client-scripts are run in strict mode, with direct DOM access disabled. Access to jQuery, prototype and the window object are likewise disabled. To disable this on a per-script basis, configure this form and add the "isolate script" field. To disable this feature for all new globally-scoped client-side scripts set the system property "glide.script.block.client.globals" to false.

Name: Prevent state change via list edit

Table: Incident [incident]

UI Type: Desktop

Type: onCellEdit

Field name: State

Application: Global

Active: ☒

Inherited: ☐

Global: ☒

Description:

Messages:

Script:

```
1 function onCellEdit(sysIDs, table, oldValues, newValue, callback) {  
2  
3     alert('State cannot be changed from the list. Please open the Incident.');
```

```
4  
5     // Cancel the list edit  
6     callback(false, oldValues);  
7 }  
8  
9
```

Isolate script: ☒