No.	Signature	Interpretation	Attack Labels	Individual Precision
1	Source port: ⟨0, 0⟩ ∧ Connection duration: ⟨1.0, 3.0⟩ ∧ Start time scalar: ⟨0.0, 14850.0⟩	Short-lived source-port-0 probing. The flow lasts 1–3 seconds and uses source port 0, an unusual pattern consistent with raw-socket reconnaissance when repeated across hosts or services. The start-time range provides dataset context rather than attack evidence. Operators can verify it using TCP flags, handshake completion, and host or port fan-out.	satan	82%
2	Connection duration: ⟨4.0, 60758.0⟩ ∧ Protocol code: ⟨1000, 1000⟩ ∧ Date scalar: ⟨8967e+05, 8969e+05⟩ ∧ Start time scalar: ⟨0.0, 14850.0⟩	Long protocol-specific sessions. Protocol code 1000 appears in connections lasting 4–60,758 seconds, while the date and start-time ranges only localize the records within the dataset. Long sessions may reflect warezclient-related retrieval. Operators can verify this by mapping the protocol code to its service and checking transfer direction, byte volume, and requested files.	warezclient	90%
3	Destination port: ⟨1000, 1000⟩ ∧ Protocol code: ⟨1005, 1005⟩ ∧ Date scalar: ⟨8967e+05, 8969e+05⟩ ∧ Connection duration: ⟨1.0, 3.0⟩	Short-lived service probes. Connections to port 1000 using protocol code 1005 last 1–3 seconds and are consistent with IP-sweep reconnaissance only when repeated across many destination hosts. The date range is contextual. Operators can verify the behavior through destination-host fan-out, incomplete handshakes, and repeated probe timing.	ipsweep	100%
4	∧ Date scalar: ⟨8967e+05, 8969e+05⟩ ∧ Connection duration: ⟨1.0, 3.0⟩ ∧ Start time scalar: ⟨0.0, 14850.0⟩	Short-lived traffic within a fixed collection interval. The 1–3 second duration is compatible with reconnaissance, but the temporal conditions alone do not uniquely identify Nmap. Operators must confirm destination-port or host fan-out, TCP flag patterns, incomplete handshakes, and repeated probe timing.	nmap	98%
5	Protocol code: ⟨1000, 1000⟩ ∧ Source port: ⟨10011, 10011⟩ ∧ Date scalar: ⟨8967e+05, 8969e+05⟩ ∧ Start time scalar: ⟨0.0, 14850.0⟩	Protocol-specific traffic from source port 10011. The flow uses protocol code 1000 during a fixed collection interval, but these conditions alone do not establish warezmaster activity. Operators should map the protocol code to its service and check upload direction, file-transfer commands, transferred payloads, and repeated server contact.	warezmaster	100%

Table 7: Five representative signatures from DARPA98. Those signatures are used to detect denial-of-service attacks, which accounts for most of the attacks in the dataset.

aggregating flow statistics in real-time and exposing them as rule-usable primitives - is portable and could be implemented in other NIDS engines (e.g., Suricata) through analogous plugin systems or feature hooks.