No.	Signature	Interpretation	Attack Labels	Individual Precision
1	Socket weight over 1 minute: $\langle 0.0, 0.0 \rangle$ ∧ Source IP variance over 1 minute: $\langle 0.0, 0.0 \rangle$ ∧ Minimum number of IP addresses claimed by source MAC within 500 ms: $\langle 1965e{+}2, 1967e{+}2 \rangle$	Short-lived MAC–IP packet variability. The source MAC–IP pair shows high variability over 500 ms, while the one-minute source and socket statistics are zero, indicating a brief burst with little longer-term history. This is consistent with ARP-based traffic redirection but does not imply that one MAC directly claimed many IP addresses. Operators can verify it through unsolicited ARP replies, IP-to-MAC binding changes, and traffic forwarding through the same MAC.	ARP-MitM	100%
2	Socket variance over 1.5 seconds: $\langle -5.09, 3.50 \rangle$ ∧ Source IP variance over 10 seconds: $\langle 7.13e{-}05, 1.17e{-}05 \rangle$	Short-term socket-direction inconsistency. The 1.5-second socket statistic spans negative and positive values, while the 10-second source-IP packet-size variance remains low. This difference can occur when traffic is relayed through an ARP-poisoning intermediary. Operators can verify it through altered IP-to-MAC bindings, duplicate or unsolicited ARP replies, and Ethernet MAC changes within the same IP conversation.	ARP-MitM	100%
3	Socket variance over 1.5 seconds: $\langle 309.09, 349.92 \rangle$ ∧ Socket weight over 1 minute: $\langle 0.0, 0.0 \rangle$	Transient socket-level packet variability. High packet-size variance over 1.5 seconds with zero one-minute socket weight indicates a brief heterogeneous burst with little recent socket history. This is consistent with a newly introduced or redirected path during ARP poisoning. Operators can check for new victim or gateway MAC mappings, preceding unsolicited ARP replies, and subsequent traffic forwarding.	ARP-MitM	98%
4	Maximum jitter over 1 minute: $\langle 0.0, 0.0 \rangle$ ∧ Maximum socket change over 1.5 seconds: $\langle 22.90e{-}04, 24.71e{-}04 \rangle$ ∧ Socket weight over 1 minute: $\langle 0.0, 0.0 \rangle$ ∧ Source MAC-to-IP mapping weight over 1 minute: $\langle 0.0, 0.0 \rangle$	Sparse long-term context with a short-term socket change. Zero one-minute jitter and packet weights indicate little measurable recent history rather than failed communication, while the small 1.5-second change may mark a new path or MAC–IP association. Operators can verify it through recent ARP updates, duplicate bindings, unsolicited replies, and Ethernet MAC changes.	ARP-MitM	97%

Table 9: Four representative signatures from `Kitsune`. Those signatures are used to detect denial-of-service attacks, which accounts for most of the attacks in the dataset.