No.	Signature	Interpretation	Attack Labels	Individual Precision
1	Maximum backward packet length: ⟨1460.0, 1460.0⟩ ∧ Maximum forward inter-arrival time: ⟨104930.0, 105146.0⟩	Large backward packet with intermittent forward activity. The flow contains a 1460-byte backward packet and a maximum forward gap of about 105 ms. These conditions co-occur but do not establish causality or maliciousness, although they match anomaly-labeled traffic. Operators can check the directional byte ratio, packet counts, protocol, service, endpoint baseline, and recurrence.	ANOMALY	100%
2	Average forward segment size: ⟨58.67, 58.67⟩ ∧ Minimum backward inter-arrival time: ⟨49.0, 49.0⟩ ∧ Maximum flow inter-arrival time: ⟨85198.0, 85198.0⟩	Small forward segments with mixed timing scales. Forward segments average 58.67 bytes, one backward packet pair is separated by 49 microseconds, and the longest flow gap is about 85 ms. This suggests burst-oriented communication but not a specific attack mechanism. Operators can inspect the full timing distribution, backward packet count, directional byte volume, protocol, and recurrence.	ANOMALY	100%
3	Mean backward packet length: ⟨630.33, 630.33⟩ ∧ Standard deviation of backward packet length: ⟨677.22, 677.22⟩ ∧ Mean flow inter-arrival time: ⟨23678.36, 23684.91⟩	Highly variable backward packet sizes. Backward packets have a mean length of 630.33 bytes and a standard deviation of 677.22 bytes, while the mean flow inter-arrival time of about 23.68 ms does not imply regular timing. This may reflect mixed control and data packets. Operators can inspect the packet-size distribution, protocol flags, directional byte volume, service, and endpoint baseline.	ANOMALY	100%
4	Destination port: ⟨443, 443⟩ ∧ Source port: ⟨49318, 49318⟩	Port-443 traffic using source port 49318. This port pair matches bot-labeled traffic but provides no timing, destination, payload, or recurrence evidence of command-and-control behavior and may be dataset-specific. Operators should check periodicity, destination identity, DNS and TLS metadata, certificates or SNI, and repeated byte or timing patterns.	BOT	100%

Table 12: Four representative signatures from `netML`. Those signatures are used to detect denial-of-service attacks, which accounts for most of the attacks in the dataset.