Table 1
System overhead measured on the same testbed.

Method	CPU, no attack	CPU added, no attack	CPU under attack	Peak memory (MB)	Memory added (MB)	Decision time per poll (ms)
None	48.2 %	-	92.9 %	216	-	30
FTMaster	48.6 %	+0.4 %	91.2 %	219	+2	72
DMS-BTT	52.4 %	+4.3 %	94.6 %	243	+27	65
FEVER	50.5 %	+2.4 %	92.8 %	303	+87	13

Controller process (Ryu), sampled every 1 s. No attack: 5 runs; under attack: A2, A4 and E9P x 5 runs. Under attack the controller saturates one core with or without a defense.

Table 2
System overhead reported by each method.

Method	CPU	Memory (MB)	Platform
SFTO-Guard	+1.64 %	-	Mininet + Ryu
FTMaster	+2.38 %	230	Mininet + Ryu
FTODefender	about +4 %	175	Mininet + Ryu
FTOP	about +18 %	129	Mininet + Ryu
FloRa	1.86 %	217	Mininet + Raspberry Pi
ALFO-Guard	+5.19 %	+206	Mininet + Ryu
DMS-BTT	+10 to 15 %	-	Mininet + Ryu
FEVER	+2.4 %	303 (+87)	Mininet + Ryu

Values as reported in each paper on its own setup; - : not reported. FEVER: CPU added with no attack and peak memory (added memory) from Table 1.