API Documentation of AamarSMS

SMS SENDING VIA API FOR BULK:

Connection protocol	НТТР
Link API	https://aamarsms.com/api
Transfer method	GET

Sample Request (For single message):

 $\frac{https://aamarsms.com/api?user=username\&password=yourpassword\&from=MaskingName\&too=88017XXXXXXXX\&text=yourmessage}{}$

Sample Request (For multiple message):

https://aamarsms.com/api?user=username&password=yourpassword&from= MaskingName&t o=88017XXXXXXXX,88018XXXXXXXX ,88019XXXXXXXX &text=yourmessage

DESCRIPTION OF INPUT PARAMETERS:

Parameter	Description	
user	Your AamarSMS username	
password	Your AamarSMS password	
from	Sender ID or your masking name. Eg: Ajra Tech	
to	MSISDN of the recipient that the message will be sent to. Eg: 8801711111111 (Do not use "+" before the country code)	
text	Your message body that you want to send. Eg: Hello Mr.X , how are you?	

Note: For promotional messages text should be "Bangla".

SAMPLE RESPONSE:

```
{
         "success": 1,
         "message": "SMS send successfully.",
         "response_code": 100,
         "campaign cost": 0.5,
         "delivery_status": [
                {
                        "MSISDN": "8801829673377",
                        "Status": 1,
                        "StatusText": "Sent"
                },
                {
                        "MSISDN": "8801730085980",
                        "Status": 0,
                        "StatusText": "Failed"
                }
        ]
}
```

Field	Description
success	1 = SMS sent. 0 = SMS sent failed.
message	Message from the system based on success or failure.
response_code	100 = SMS send successfully. 101 = Username empty. 102 = Password empty. 103 = Recipient number empty. 104 = Message text empty. 105 = Invalid credential. 106 = Your Balance is not sufficient. 107 = Reseller balance is not sufficient. 108 = Message text is too long.
campaign_cost	The expense for this message
delivery_status	{ "MSISDN": "8801829673377", // Mobile no "Status": 1, // sms sent "StatusText": "Sent" }, { "MSISDN": "8801730085980", // Mobile no "Status": 0, // sms sent failed "StatusText": "Failed" }

SMS SENDING VIA API FOR OTP:

Connection protocol	НТТР
Link API	https://aamarsms.com/otp
Transfer method	GET

Sample Request (For single message):

 $\frac{https://aamarsms.com/otp?user=username\&password=yourpassword\&from=MaskingName\&to=88017XXXXXXXXX&text=yourmessage}{}$

DESCRIPTION OF INPUT PARAMETERS:

Parameter	Description	
user	Your AamarSMS username	
password	Your AamarSMS password	
from	Sender ID or your masking name. Eg: Ajra Tech	
to	MSISDN of the recipient that the message will be sent to. Eg: 8801711111111 (Do not use "+" before the country code)	
text	Your message body that you want to send. Eg: Your OTP is 1234.	

SAMPLE RESPONSE:

```
{
  "success": 1,
  "message": "SMS send successfully.",
  "response_code": 100,
  "campaign_cost": 0.50,
  "status": "Delivered"
}
```

Field	Description
success	1 = SMS sent.
	0 = SMS sent failed.
message	Message from the system based on success or failure.
response_code	100 = SMS send successfully.
	101 = Username empty.
	102 = Password empty.
	103 = Recipient number empty.
	104 = Message text empty.
	105 = Invalid credential.
	106 = Your Balance is not sufficient.
	107 = Reseller balance is not sufficient.
	108 = Message text is too long.
campaign_cost	The expense for this message
status	Delivered or Failed

SMS STATUS VIA API:

Connection protocol	НТТР
Link API	https://aamarsms.com/smsstatus
Transfer method	GET

Sample Request (For single message):

 $\underline{\text{https://aamarsms.com/smsstatus?user=username\&password=yourpassword\&smsid=910-}} \underline{17XXXXXXXX}$

DESCRIPTION OF INPUT PARAMETERS:

Parameter	Description
user	Your AamarSMS username
password	Your AamarSMS password
smsid	Smsid is a unique key to track your sms status. Eg: 910-17XXXXXXXX

SAMPLE RESPONSE:

```
{
"success":1,
"response_code":100,
"message":"SMS send successfully",
"STATUS":"SENT"
}
```

Field	Description
success	1 = SMS sent. 0 = SMS sent failed.
message	Message from the system based on success or failure.
response_code	100 = SMS send successfully.
	101 = Username empty.
	102 = Password empty.
	109 = smsid empty
status	Sent or Failed

USER AVAILABLE BALANCE VIA API:

Connection protocol	НТТР
Link API	https://aamarsms.com/balance
Transfer method	GET

Sample Request (For single message):

https://aamarsms.com/balance?user=username&password=yourpassword

DESCRIPTION OF INPUT PARAMETERS:

Parameter	Description	
user	Your AamarSMS username	
password	Your AamarSMS password	

SAMPLE RESPONSE:

```
{
"message":"Active Balance Available",
"response_code":110,
"AVAILABLE BALANCE =":"502.56559"
}
```

Field	Description
message	Message from the system based on success or failure.
response_code	101 = Username empty.
	102 = Password empty.
	105 = Invalid credential.
	106 = No Credits available
	110 = Available balance
Available balance	Current balance