

Programming Paradigms

LECTURE 1

Ms. FARZEEN ASHFAQ

Programming Paradigms

- Procedural
- Functional
- Logic
- Object-Oriented

Specifying the WHAT

- Describe the Inputs
 - Specific values
 - Properties
- Describe the Outputs (as above)
- Describe the Relationships Between I x O
 - As a possibly infinite table
 - Equations and other predicates between input and output expressions
 - For a given input, output may not be unique

Specifying the HOW

- Describe the Inputs
 - Specific values
 - Properties
- Describe HOW the Outputs are produced
- Models of existing computers
 - Program State
 - Control Flow
- A Few Abstractions
 - Block Structure
 - Recursion via a Stack

Procedural programming

- Describes the details of *HOW* the results are to be obtained, in terms of the underlying machine model.
- Describes computation in terms of
 - Statements that change a program state
 - Explicit control flow
- Synonyms
 - Imperative programming
 - Operational
- Fortran, C, ...
 - Abstractions of typical machines
 - Control Flow Encapsulation
 - Control Structures
 - Procedures
 - No return values
 - Functions
 - Return one or more values
 - Recursion via stack

Procedural Programming: State

- Program State
 - Collection of Variables and their values
 - Contents of variables change
- Expressions
 - Not expected to change Program State
- Assignment Statements
- Other Statements
- Side Effects

C, C++, C#, Java

- Abstractions of typical machines
- Control Flow Encapsulation
 - Control Structures
 - Procedures
 - No return values
 - Functions
 - Return one or more values
 - Recursion via stack
- Better Data Type support

Illustrative Example

- Expression (to be computed) : $a + b + c$
- Recipe for Computation
 - Account for machine limitations
 - Intermediate Location
 - $T := a + b;$ $T := T + c;$
 - Accumulator Machine
 - Load a ; Add b ; Add c
 - Stack Machine
 - Push a ; Push b ; Add; Push c ; Add

Declarative Programming

- Specifies *WHAT* is to be computed abstractly
- Expresses the logic of a computation without describing its control flow
- Declarative languages include
 - logic programming, and
 - functional programming.
- often defined as any style of programming that is not imperative.

Imperative vs Non-Imperative

- Functional/Logic style clearly separates WHAT aspects of a program (programmers' responsibility) from the HOW aspects (implementation decisions).
- An Imperative program contains both the specification and the implementation details, inseparably inter-twined.

Procedural vs Functional

- Program: a sequence of instructions for a von Neumann m/c.
- Computation by instruction execution.
- Iteration.
- Modifiable or updatable variables..
- Program: a collection of function definitions (m/c independent).
- Computation by term rewriting.
- Recursion.
- Assign-only-once variables.

Functional Style : Illustration

- Definition: Equations

$$\text{sumto}(0) = 0$$

$$\text{sumto}(n) = n + \text{sumto}(n-1)$$

- Computation: Substitution and Replacement

$$\text{sumto}(2) = 2 + \text{sumto}(2-1)$$

$$= 2 + \text{sumto}(1)$$

$$= 2 + 1 + \text{sumto}(1-1) = 2 + 1 + \text{sumto}(0)$$

$$= 2 + 1 + 0 = \dots$$

$$= 3$$

Paradigm vs Language

Imperative Style

```
tsum := 0;  
i := 0;  
while (i < n) do  
    i := i + 1;  
    tsum := tsum + i  
od
```

Storage efficient

Functional Style

```
func sumto(n: int): int;  
    if n = 0  
        then 0  
        else n + sumto(n-1)  
    fi  
endfunc;
```

No Side-effect

Bridging the Gap

- Imperative is not always faster, or more memory efficient than functional.
- E.g., tail recursive programs can be automatically translated into equivalent while-loops.

```
func xyz(n : int, r : int) : int;  
    if n = 0  
        then r  
        else xyz(n-1, n+r)  
    fi  
endfunc
```

Logic Programming Paradigm

1. `edge(a,b).`
2. `edge(a,c).`
3. `edge(c,a).`
4. `path(X,X).`
5. `path(X,Y) :- edge(X,Y).`
6. `path(X,Y) :- edge(X,Z), path(Z,Y).`

Logic Programming

- A logic program defines a set of relations.
- This “knowledge” can be used in various ways by the interpreter to solve different “queries”.
- In contrast, the programs in other languages
- Make explicit HOW the “declarative knowledge” is used to solve the query.

Append in Prolog

- `append([], L, L).`
- `append([H | T], X, [H | Y]) :-`
 - `append(T, X, Y).`
- True statements about append relation.
- Uses pattern matching.
 - “[]” and “|” stand for empty list and cons operation.

Different Kinds of Queries

- Verification
 - append: list x list x list
 - `append([1], [2,3], [1,2,3]).`
- Concatenation
 - append: list x list -> list
 - `append([1], [2,3], R).`

More Queries

- Constraint solving
 - append: list x list \rightarrow list
 - append(R, [2,3], [1,2,3]).
 - append: list \rightarrow list x list
 - append(A, B, [1,2,3]).
- Generation
 - append: \rightarrow list x list x list
 - append(X, Y, Z).

Object-Oriented Style

- Programming with Abstract Data Types
 - ADTs specify/describe behaviors.
- Basic Program Unit: Class
 - Implementation of an ADT.
 - Abstraction enforced by encapsulation..
- Basic Run-time Unit: Object
 - Instance of a class.
 - Has an associated state.

Procedural vs Object-Oriented

- Emphasis on procedural abstraction.
- Top-down design; Step-wise refinement.
- Suited for programming in the small.
- Emphasis on data abstraction.
- Bottom-up design; Reusable libraries.
- Suited for programming in the large.

Integrating Heterogeneous Data

- In C, Pascal, etc., use
 - Union Type / Switch Statement
 - Variant Record Type / Case Statement
- In C++, Java, Eiffel, etc., use
 - Abstract Classes / Virtual Functions
 - Interfaces and Classes / Dynamic Binding

Procedural vs Object-Oriented

- New operations cause additive changes in procedural style, but require modifications to all existing “class modules” in object-oriented style.
- New data representations cause additive changes in object-oriented style, but require modifications to all “procedure modules”.

Object-Oriented Concepts

- Data Abstraction (specifies behavior)
- Encapsulation (controls visibility of names)
- Polymorphism (accommodates various implementations)
- Inheritance (facilitates code reuse)
- Modularity (relates to unit of compilation)