

① ②

A single qubit is in the form $a|0\rangle + b|1\rangle$

$$\text{and } a|0\rangle + b|1\rangle = a \begin{pmatrix} 1 \\ 0 \end{pmatrix} + b \begin{pmatrix} 0 \\ 1 \end{pmatrix} = \begin{pmatrix} a \\ b \end{pmatrix},$$

$$\text{where } |a|^2 + |b|^2 = 1.$$

~~Example:~~

Example:

$$\begin{aligned} \textcircled{1} \quad \frac{1}{\sqrt{2}} |00\rangle + \frac{1}{\sqrt{2}} |11\rangle &= \frac{1}{\sqrt{2}} (|0\rangle \otimes |0\rangle) + \frac{1}{\sqrt{2}} (|1\rangle \otimes |1\rangle) \\ &= \frac{1}{\sqrt{2}} \left\{ \begin{pmatrix} 1 \\ 0 \end{pmatrix} \otimes \begin{pmatrix} 1 \\ 0 \end{pmatrix} \right\} + \frac{1}{\sqrt{2}} \left\{ \begin{pmatrix} 0 \\ 1 \end{pmatrix} \otimes \begin{pmatrix} 0 \\ 1 \end{pmatrix} \right\} \\ &= \frac{1}{\sqrt{2}} \begin{pmatrix} 1 \\ 0 \\ 0 \\ 0 \end{pmatrix} + \frac{1}{\sqrt{2}} \begin{pmatrix} 0 \\ 0 \\ 0 \\ 1 \end{pmatrix} \\ &= \begin{pmatrix} \frac{1}{\sqrt{2}} \\ 0 \\ 0 \\ \frac{1}{\sqrt{2}} \end{pmatrix} \end{aligned}$$

$$\begin{aligned} \textcircled{2} \quad |10\rangle &= |1\rangle \otimes |0\rangle \\ &= \begin{pmatrix} 0 \\ 1 \end{pmatrix} \otimes \begin{pmatrix} 1 \\ 0 \end{pmatrix} = \begin{pmatrix} 0 \\ 0 \\ 1 \\ 0 \end{pmatrix} \end{aligned}$$


①

$$\textcircled{b} \quad (i) \quad \begin{pmatrix} 1 & 0 & 0 & 0 & \dots & 0 \\ 0 & 1 & 0 & 0 & \dots & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & 0 & 0 & \dots & 1 \end{pmatrix}_{2^n \times 2^n}$$

for input $\begin{pmatrix} a_1 \\ a_2 \\ \vdots \\ a_{2^n} \end{pmatrix}$, the output will be $\begin{pmatrix} a_1 \\ a_2 \\ \vdots \\ a_{2^n} \end{pmatrix}$

$$\begin{aligned} (ii) \quad &\begin{pmatrix} 0 & 0 & \dots & 1 \\ 0 & 0 & \dots & 1 & 0 \\ 1 & 0 & 0 & 0 \end{pmatrix} \text{ for input } \begin{pmatrix} a_1 \\ a_2 \\ \vdots \\ a_{2^n} \end{pmatrix} \text{ and output} \\ &\rightarrow \begin{pmatrix} a_{2^n} \\ a_{2^n-1} \\ a_1 \end{pmatrix} \end{aligned}$$

② Teleportation:



Here, $|\Psi_0\rangle = |\psi\rangle |\Phi_{00}\rangle = (\alpha|0\rangle + \beta|1\rangle) \frac{(|00\rangle + |11\rangle)}{\sqrt{2}}$

and $|\Psi_1\rangle = \alpha|0\rangle \frac{(|00\rangle + |11\rangle)}{\sqrt{2}} + \beta|1\rangle \frac{(|10\rangle + |01\rangle)}{\sqrt{2}}$

$$|\Psi_2\rangle = \alpha \left(\frac{|0\rangle + |1\rangle}{\sqrt{2}} \right) \left(\frac{(|00\rangle + |11\rangle)}{\sqrt{2}} \right)$$

$$+ \beta \left(\frac{|0\rangle - |1\rangle}{\sqrt{2}} \right) \left(\frac{(|0\rangle + |01\rangle)}{\sqrt{2}} \right)$$

$$= \frac{1}{2} |00\rangle (\alpha|0\rangle + \beta|1\rangle) \quad (\text{Nothing to do})$$

$$+ \frac{1}{2} |01\rangle (\beta|0\rangle + \alpha|1\rangle) \quad (\text{Apply X gate})$$

$$+ \frac{1}{2} |10\rangle (\alpha|0\rangle - \beta|1\rangle) \quad (\text{Apply Z gate})$$

$$- \frac{1}{2} |11\rangle (\beta|0\rangle - \alpha|1\rangle) \quad (\text{Apply both X and Z gates})$$

Now, (i) if Bob gets 00, then he will do nothing.

(ii) if Bob gets 01 then he will apply X gate

(iii) if Bob gets 10 then Bob will apply Z gate

(iv) if Bob gets 11 then Bob will apply X and Z both then back $|\psi\rangle$.

③ ② let us consider a boolean function ~~$f: \{0,1\}^n$~~
 $f: \{0,1\}^n \rightarrow \{0,1\}$. Deutsch-Jozsa algorithm
finds the function is balanced or constant
The function is ~~balanced~~ constant if it gives 0's or all 1's.
and balanced if it gives half inputs 0's and
half inputs are 1's.

(b) Deutsch-Jozsa Algorithm?

At first two quantum registers, the first one is an n -qubit quantum register with all the qubits are initialized to $|0\rangle$, and the 2nd one is a 1 qubit register, initialized to $|1\rangle$.

$$|\psi_0\rangle = |0\rangle^{\otimes n} |1\rangle.$$

Then apply Hadamard gate to each qubit.

$$|\psi_1\rangle = \frac{1}{\sqrt{2^{n+1}}} \sum_{x \in \{0,1\}^n} |x\rangle (|0\rangle - |1\rangle).$$

Apply the quantum oracle $U_f : |x\rangle|y\rangle \rightarrow |x\rangle|y \oplus f(x)\rangle$ on $|\psi_1\rangle$:

$$|\psi_2\rangle = \frac{1}{\sqrt{2^{n+1}}} \sum_{x \in \{0,1\}^n} |x\rangle (|0 \oplus f(x)\rangle - |1 \oplus f(x)\rangle)$$

$$\Rightarrow |\psi_2\rangle = \frac{1}{\sqrt{2^{n+1}}} \sum_{x \in \{0,1\}^n} (-1)^{f(x)} |x\rangle (|0\rangle - |1\rangle)$$

Ignore the last qubit from the 2nd register and apply Hadamard gate to all n qubits from the last register

$$H^{\otimes n} \left(\frac{1}{\sqrt{2^n}} \sum_{x \in \{0,1\}^n} (-1)^{f(x)} |x\rangle \right)$$

$$= \frac{1}{\sqrt{2^n}} \sum_{x \in \{0,1\}^n} (-1)^{f(x)} \left[\frac{1}{\sqrt{2^n}} \sum_{y \in \{0,1\}^n} (-1)^{x \cdot y} |y\rangle \right]$$

$$= \frac{1}{\sqrt{2^n}} \sum_{x \in \{0,1\}^n} \left[\sum_{y \in \{0,1\}^n} (-1)^{f(x)} (-1)^{x \cdot y} \right] |y\rangle.$$

Then measure all the n qubits from the first register:

if $f(x)$ is constant, then check that the above prob is 1 if $f(x)$ is balanced the probability is 0.

Hence after measurement if we get $|0\rangle^{\otimes n}$ we can conclude that $f(x)$ is constant function then $f(x)$ is balanced.

⑤ Correctness of Algorithm:

If f is constant: Then, there is no effect on input qubits. It states before and after querying the oracle are same. ~~Since H-gate is~~

~~self inverse~~ $H^{\otimes n} \begin{pmatrix} 1 \\ 0 \\ \vdots \\ 0 \end{pmatrix} = \frac{1}{\sqrt{2^n}} \begin{pmatrix} 1 \\ 1 \\ \vdots \\ 1 \end{pmatrix} \xrightarrow{\text{apply } U_f} H^{\otimes n} \frac{1}{\sqrt{2^n}} \begin{pmatrix} 1 \\ 1 \\ \vdots \\ 1 \end{pmatrix}$

$$= \begin{pmatrix} 1 \\ 0 \\ \vdots \\ 0 \end{pmatrix}$$

In Case if f is balanced:

The input register would be an equal superposition of all states. then, for exactly half of these states,

$$U_f \frac{1}{\sqrt{2^n}} [1, \dots, 1]^T = \frac{1}{\sqrt{2^n}} [-1, 1, \dots, 1]^T, \text{ so the}$$

Kickback phase add negative phase. Hence, the in the last part, after applying Hadamard gate the gate we receive is orthogonal to $|00\dots 0\rangle$. Hence, that cannot measure in the all 0-state.

③ In deterministic ~~or~~ classical algorithm
the worst case we might have to check
 $2^{n-1} + 1$ queries. It is required in the
worst case. and in probabilistic
classical algo a constant is many queries
can generate the answer with $5/12$
prob. $\leq \frac{1}{2^n}$. But Deutsch-Jozsa algo
can conclude the result deterministically
with just a single query.

③ ④

Given boolean function

$$f(x_1, x_2, x_3) = x_1 x_2 x_3$$

Now, $| \psi_0 \rangle = | 000 \rangle \otimes | 1 \rangle$

Then

$$| \psi_1 \rangle = \frac{1}{\sqrt{2}} \{ | 000 \rangle + | 010 \rangle + | 011 \rangle + | 100 \rangle + | 101 \rangle + | 110 \rangle + | 111 \rangle \} \otimes \frac{1}{\sqrt{2}} (| 0 \rangle - | 1 \rangle)$$

$$\Rightarrow | \psi_2 \rangle = \frac{1}{\sqrt{2}} \{ (-1)^0 | 000 \rangle + (-1)^0 | 001 \rangle + (-1)^0 | 010 \rangle + (-1)^0 | 011 \rangle + (-1)^0 | 100 \rangle + (-1)^0 | 101 \rangle + (-1)^0 | 110 \rangle + (-1)^1 | 111 \rangle \} \otimes \frac{1}{\sqrt{2}} (| 0 \rangle - | 1 \rangle)$$

$$= \frac{1}{\sqrt{2}} \{ | 000 \rangle + | 001 \rangle + | 010 \rangle + | 011 \rangle + | 100 \rangle + | 101 \rangle + | 110 \rangle - | 111 \rangle \} \otimes \frac{1}{\sqrt{2}} (| 0 \rangle - | 1 \rangle)$$

Now we ignore the last q-bit from the 2nd register

$$| \psi_2 \rangle = \frac{1}{\sqrt{2}} \{ | 000 \rangle + | 001 \rangle + | 010 \rangle + | 011 \rangle + | 100 \rangle + | 101 \rangle + | 110 \rangle - | 111 \rangle \}$$

Now $| \psi_3 \rangle = H^{\otimes 3} [| \psi_2 \rangle]$

Finally we calculate the prob. of getting $| 0 \rangle^{\otimes 3}$

$$= \frac{1}{2^6} \left[\sum_{x \in \{0,1\}^3} (-1)^{f(x)} \right]^2$$

Here $f(1,1,1) = 1$ & for all other cases of outputs 0. Hence the probability of getting $| 0 \rangle^{\otimes 3}$ is

$$\begin{aligned} & \frac{1}{2^6} \left[(-1)^0 + (-1)^0 + (-1)^0 + (-1)^0 + (-1)^0 + (-1)^0 + (-1)^0 + (-1)^1 \right]^2 \\ &= \frac{1}{2^6} \{ 1+1+1+1+1+1+1-1 \}^2 \\ &= \frac{1}{36} \cdot 6^2 = \frac{36}{36} = 0.5625 \end{aligned}$$

Hence for JS algo, if it is assumed to be either balance or constant. The given output 1 in one case and 0 in others. Hence it is neither ~~constant~~ balanced nor constant. So ~~assuming the given algo~~, we cannot get any information

④ ②

Given a function $f: \{0,1\}^n \rightarrow \{0,1\}$.
The goal is to find $x \in \{0,1\}^n$ such that $f(x)=1$, or to conclude that no such x exists i.e. $f=0$, a constant function.

Let, $A = \{x \in \{0,1\}^n : f(x)=1\}$

$B = \{x \in \{0,1\}^n : f(x)=0\}$

Also let, $|A|=a$, $|B|=b$, then $N=2^n$, $a+b=N$.

Begin with a state: $|\psi_0\rangle = |0\rangle^{\otimes n}$

Matrix Representation $|\psi_0\rangle = \begin{pmatrix} 1 \\ 0 \end{pmatrix}^{\otimes n}$

• Apply the Hadamard gate to each of these qubits $|\psi_1\rangle = (H|0\rangle)^{\otimes n}$

$$|\psi_1\rangle = \left(\frac{1}{\sqrt{2}} \begin{pmatrix} 1 & 1 \\ 1 & -1 \end{pmatrix} \begin{pmatrix} 1 \\ 0 \end{pmatrix} \right)^{\otimes n} = \left(\frac{1}{\sqrt{2}} \begin{pmatrix} 1 \\ 1 \end{pmatrix} \right)^{\otimes n}$$

$$= \frac{1}{\sqrt{2^n}} \sum_{x \in \{0,1\}^n} |x\rangle = \frac{1}{\sqrt{N}} \sum_{x \in \{0,1\}^n} |x\rangle$$

consider the states: $|A\rangle = \frac{1}{\sqrt{a}} \sum_{x \in A} |x\rangle$ & $|B\rangle = \frac{1}{\sqrt{b}} \sum_{x \in B} |x\rangle$

Note that $|A\rangle$ & $|B\rangle$ are orthogonal. Consider the space spanned by $|A\rangle$ & $|B\rangle$.

$$\text{Then } |\psi_1\rangle = \frac{1}{\sqrt{N}} \sum_{x \in \{0,1\}^n} |x\rangle = \frac{1}{\sqrt{N}} \left(\sum_{x \in A} |x\rangle + \sum_{x \in B} |x\rangle \right)$$

$$= \frac{1}{\sqrt{N}} \left(\sqrt{a} \times \frac{1}{\sqrt{a}} \sum_{x \in A} |x\rangle + \sqrt{b} \times \frac{1}{\sqrt{b}} \sum_{x \in B} |x\rangle \right)$$

$$\Rightarrow |\psi_1\rangle = \sqrt{\frac{a}{N}} |A\rangle + \sqrt{\frac{b}{N}} |B\rangle$$

$$|\psi_1\rangle = \sqrt{\frac{a}{N}} |A\rangle + \sqrt{\frac{b}{N}} |B\rangle$$

Assuming $\sqrt{\frac{a}{N}} = \sin \theta$ & $\sqrt{\frac{b}{N}} = \cos \theta$ geomet

we can think of $|\psi_1\rangle$ is making an angle θ with the state $|B\rangle$. This implies $\theta = \sin^{-1} \sqrt{\frac{a}{N}}$.

$$Z_1|x\rangle = (-1)^{f(x)}|x\rangle, \text{ then } Z_0|x\rangle = \begin{cases} -|x\rangle & \text{if } x=0^n \\ |x\rangle & \text{if } x \neq 0^n \end{cases}$$

Matrix Represent, $Z_0 = I - 2|0^n\rangle\langle 0^n|$

$$\text{for } n=2, Z_0 = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} - 2 \begin{pmatrix} 1 \\ 0 \\ 0 \\ 0 \end{pmatrix} \begin{pmatrix} 1 & 0 & 0 & 0 \end{pmatrix}$$

$$= \begin{pmatrix} -1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

Define the unitary operator $G = -H^{\otimes n} Z_0 H^{\otimes n} Z_f$

$$\begin{aligned} H^{\otimes n} Z_0 H^{\otimes n} &= H^{\otimes n} (I - 2|0^n\rangle\langle 0^n|) H^{\otimes n} \\ &= (H^{\otimes n} - 2H^{\otimes n}|0^n\rangle\langle 0^n|) H^{\otimes n} \\ &= I - 2H^{\otimes n}|0^n\rangle\langle 0^n|H^{\otimes n} \\ &= I - 2|\psi_1\rangle\langle\psi_1| \end{aligned}$$

Thus $G = (I - 2|\psi_1\rangle\langle\psi_1|)(-Z_f)$

Same derivation for $n=2$

$$\begin{aligned} H^{\otimes 2} Z_0 H^{\otimes 2} &= \frac{1}{2} \begin{pmatrix} 1 & 1 & 1 & 1 \\ 1 & -1 & 1 & -1 \\ 1 & 1 & -1 & -1 \\ 1 & -1 & -1 & 1 \end{pmatrix} \begin{pmatrix} -1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \frac{1}{2} \begin{pmatrix} 1 & 1 & 1 & 1 \\ 1 & -1 & 1 & -1 \\ 1 & 1 & -1 & -1 \\ 1 & -1 & -1 & 1 \end{pmatrix} \\ &= \frac{1}{2} \begin{pmatrix} 1 & -1 & -1 & -1 \\ -1 & 1 & -1 & -1 \\ -1 & -1 & 1 & -1 \\ -1 & -1 & -1 & 1 \end{pmatrix} \end{aligned}$$

similar $I - 2|\psi_1\rangle\langle\psi_1| =$

$$\begin{aligned} &= \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} - 2 \cdot \frac{1}{2} \begin{pmatrix} 1 \\ 1 \\ 1 \\ 1 \end{pmatrix} \frac{1}{2} \begin{pmatrix} 1 & 1 & 1 & 1 \end{pmatrix} \\ &= \frac{1}{2} \begin{pmatrix} 1 & -1 & -1 & -1 \\ -1 & 1 & -1 & -1 \\ -1 & -1 & 1 & -1 \\ -1 & -1 & -1 & 1 \end{pmatrix} \end{aligned}$$

$$\text{Hence } H^{\otimes n} Z_0 H^{\otimes n} = I - 2|\psi_1\rangle\langle\psi_1|$$

Q. 3.12

Note that

$$\begin{aligned}
 G|A\rangle &= [I - 2|\psi_1\rangle\langle\psi_1|](-2)|A\rangle \\
 &= [I - 2|\psi_1\rangle\langle\psi_1|] \cdot |A\rangle \\
 &= |A\rangle - 2\langle\psi_1|A\rangle|\psi_1\rangle \\
 &= |A\rangle - 2\sqrt{\frac{a}{N}} \left(\sqrt{\frac{b}{N}}|A\rangle + \sqrt{\frac{b}{N}}|B\rangle \right) \\
 &= \left(1 - \frac{2a}{N}\right)|A\rangle - \frac{2\sqrt{ab}}{N}|B\rangle
 \end{aligned}$$

Similarly $G|B\rangle = \frac{2\sqrt{ab}}{N}|A\rangle - \left(1 - \frac{2b}{N}\right)|B\rangle$

Thus G can be considered as a matrix


$$\begin{pmatrix} -\left(1 - \frac{2b}{N}\right) & -\frac{2\sqrt{ab}}{N} \\ \frac{2\sqrt{ab}}{N} & \left(1 - \frac{2b}{N}\right) \end{pmatrix}$$

Now using $N = a + b$, we get:

$$\begin{pmatrix} \frac{b-a}{N} & -\frac{2\sqrt{ab}}{N} \\ \frac{2\sqrt{ab}}{N} & \frac{b-a}{N} \end{pmatrix} = \begin{pmatrix} \sqrt{\frac{b}{N}} & -\sqrt{\frac{a}{N}} \\ \sqrt{\frac{a}{N}} & \sqrt{\frac{b}{N}} \end{pmatrix}^2 = \begin{pmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{pmatrix}^2$$

Thus G can be considered as a rotation matrix which on application to a state increases its angle by 2θ . & our goal is to increase the prob. of getting $|A\rangle$ i.e. $\sin^2 \approx 1$

Each application of G or G^2 amplifies the angle from θ to 3θ .



After k applications of amplified amplification operator

G^k of the resulting state is of the following form

$$|\psi_k\rangle = \sin(2k+1)\theta|x_0\rangle + \cos(2k+1)\theta|p\rangle$$

prob. of observing x_0 from $|\psi_k\rangle$ is $\sin^2(2k+1)\theta$

calculating the number of iterations $0 \rightarrow \theta$

The success prob. is $\sin^2(2k+1)\theta$

To make the success prob. $\frac{1}{2}$ we need

$$\sin^2(2k+1)\theta = \frac{1}{2}$$

$$\Rightarrow (2k+1)\theta = \arcsin \frac{1}{\sqrt{2}}$$

$$\Rightarrow (2k+1)\theta = \frac{\pi}{4} \Rightarrow k \approx \frac{\pi}{8\theta}$$

$$= \frac{\pi}{8} \sqrt{2^n}$$

prepare the initial state.

$$| \psi_0 \rangle = \frac{1}{\sqrt{2^n}} \sum_{x \in \{0,1\}^n} | x \rangle$$

$$\text{Apply } U = -H^{\otimes n} Z_0 H^{\otimes n} Z_f$$

$$= (I - 2| \psi_1 \rangle \langle \psi_1 |) (-Z_f) \text{ on the}$$

state $| \psi_0 \rangle$ for approx $\frac{\pi \sqrt{N}}{4}$ many times

Measure the state in computation basis.


check $| x' \rangle \xrightarrow{Z_f} (-1)^{f(x')} | x' \rangle = -| x' \rangle$ or not.

If yes then we got the correct result
otherwise incorrect

④ ⑤ Grover algorithm performs a search over an unordered set of $N = 2^m$ items to find a unique element that satisfies some condition, while the best classical algo for a ~~search~~ search ^{over} unordered data requires $O(N)$ times quantum computers is only $O(\sqrt{N})$ operation an quadratic speed up.

⑤ a) Alice randomly generates two strings of bits $x, y \in \{0,1\}^m$
 Define $|\psi_{00}\rangle = |0\rangle$, $|\psi_{10}\rangle = |1\rangle$, $|\psi_{01}\rangle = |+\rangle$
 & $|\psi_{11}\rangle = |-\rangle$

We have these 4 states as



Alice prepares m qubits

in the state $|\psi_{x,y}\rangle = |\psi_{x_i y_i}\rangle \dots |\psi_{x_m y_m}\rangle$.

and sends these m q-bits over quantum channel to Bob. Bob receives m q-bits, although they may not longer be a state $|\psi_{x,y}\rangle$ because Eve may have tampered with them or possibly the channel is noisy.

Bob randomly chooses $y' \in \{0,1\}^m$ & measures each q-bit received from Alice to follow.

• If $y'_i = 0$, Bob measures qubit i .

• If $y'_i = 1$, Bob performs a Hadamard transform to q-bit i , then measures it with respect to the standard basis.

Let $x' \in \{0,1\}^m$ be the string corresponding to the results of Bob's measurements. The important thing to note at this point is that if $y_i = y'_i$ for some i & there was no noise or eavesdropping, then it is certain $x_i = x'_i$.

Finally, Alice & Bob publicly compare y and y' . They discard bits x_i & x'_i for which $y_i \neq y'_i$. The remaining bits of x & x' represent a 'semi private' key that will go into the next stage of the protocol.

2nd stage of protocol:

Alice & Bob now need to estimate how much Eve might know about x and x' . They do this by some of bits x and x' .

Comparing these bits publicly, they can estimate the error rate with high accuracy and if it is too large they abort. The maximum error rate can be tolerated is about 11%. If they have acceptable error rate Alice & Bob will have two strings x and x' that agree in a high percentage of positions with high prob. They have some bound on the amount of information Eve possesses about the given strings.