

# Tensor Omics (TOX)

Analyze gene expression data and evolutionary relationships between genes

## User's Guide

Vivian Bass<sup>1</sup>, Anna Beketova<sup>1</sup>, Luka Faensen<sup>1</sup>, Asis Hallab<sup>1</sup>, Aaron Schröder<sup>1</sup>, Franz-Eric Sill<sup>1</sup>

<sup>1</sup>University of Applied Sciences Bingen, Germany

Last revised November 4, 2025

# Contents

|          |                                                              |          |
|----------|--------------------------------------------------------------|----------|
| <b>1</b> | <b>Tensor Omics Method and Theory</b>                        | <b>3</b> |
| 1.1      | The TOX Data Table . . . . .                                 | 3        |
| 1.2      | From Raw Data to Expression Vectors . . . . .                | 3        |
| 1.3      | Normalization of Expression Values . . . . .                 | 4        |
| 1.4      | Calculation of family Centroids . . . . .                    | 4        |
| 1.5      | Euclidean Distance Between Expression Vectors . . . . .      | 4        |
| 1.6      | Outlier Detection Based on Family-Scaled Distances . . . . . | 5        |
| 1.7      | Tissue Versatility and Specificity . . . . .                 | 5        |
| <b>2</b> | <b>Error Handling</b>                                        | <b>6</b> |
| <b>3</b> | <b>Implementation Notes</b>                                  | <b>7</b> |
| 3.1      | Fortran Pipeline . . . . .                                   | 7        |
| 3.2      | Python Pipeline . . . . .                                    | 40       |
| 3.3      | R Pipeline . . . . .                                         | 59       |

# 1 Tensor Omics Method and Theory

The Tensor Omics (TOX) tool implements a streamlined pipeline for analyzing gene expression data and evolutionary relationships between genes. The pipeline integrates tools for data normalization, and geometric analysis of gene expression vectors. This document outlines the current implementation details and provides the mathematical formulation of the algorithms used in the prototype.

## 1.1 The TOX Data Table

The foundational data structure in Tensor Omics is the **Data Table**. Unlike a simple spreadsheet, a Data Table is a conceptual grouping of multiple, type-specific 2D arrays that represent datasets read from a source like a CSV file. Because Fortran is a strongly-typed language, data of different types (e.g., integers, reals, characters) cannot be stored in a single matrix. The TOX library solves this by parsing the source data into a collection of distinct, column-major arrays that share the same number of rows.

The process begins by reading the entire CSV file into a single, general-purpose 2D array of strings. This string array acts as an in-memory staging area. From this staging array, users can then extract specific columns into strongly-typed arrays, creating the components of the Data Table:

- `integer_data(:, :)`: An array for integer columns (e.g., gene IDs).
- `real_data(:, :)`: An array for real-valued columns (e.g., expression levels, scores).
- `logical_data(:, :)`: An array for boolean columns (e.g., status flags).
- `character_data(:, :)`: An array for string columns (e.g., gene names).
- `complex_data(:, :)`: An array for complex number columns.

All downstream analyses in TOX operate on these strongly-typed arrays.

## 1.2 From Raw Data to Expression Vectors

The starting point for all downstream analyses is a table of gene-wise expression measurements across a set of biological samples, such as tissues, developmental stages, or experimental conditions. These measurements may originate from transcriptomic, proteomic, or metabolomic experiments, typically normalized to account for sequencing depth and technical variation.

**What is Gene Expression Data?** For each gene, a real-valued quantity is recorded that reflects its biological activity in a given sample. In the case of transcriptomics, this is often the abundance of messenger RNA (mRNA) molecules transcribed from that gene, estimated via sequencing and mapped back to the gene’s known sequence. The result is a non-negative real number proportional to the gene’s transcriptional activity in that sample. After normalization and transformation, these values can be treated as coordinates in a real vector space.

Thus, each gene is represented as a vector  $\vec{v} \in \mathbb{R}^n$ , where  $n$  is the number of biological samples (e.g., tissues or time points), and each component  $v_i \geq 0$  corresponds to the expression level in sample  $i$ . These vectors encode the distribution of gene activity across conditions and form the geometric basis for all downstream analyses.

**Note on Stress Responses.** In certain studies, a subset of the samples may correspond to stress conditions. Here, “stress” refers to any external or internal perturbation—such as mechanical damage, heat shock, pathogen infection, or nutrient deprivation—that triggers measurable changes in gene expression. These are often analyzed relative to baseline conditions using log fold-change transformations, such that the resulting vectors reflect differential expression patterns, including up- and downregulation across dimensions.

### 1.3 Normalization of Expression Values

Raw gene expression data is normalized in the following steps:

1. Division by gene-wise standard deviation for scale normalization.
2. Quantile normalization across samples to reduce global expression biases.
3. Log-transformation:  $x \mapsto \log(1 + x)$  to stabilize variance and suppress outliers.
4. For stress response studies, log fold-changes are computed:

$$\Delta_{\text{stress}} = \log(1 + x_{\text{stress}}) - \log(1 + x_{\text{control}})$$

This effectively makes each stress related axis show the fold change in gene expression under stress, e.g. “drought in root divided by control root”.

### 1.4 Calculation of family Centroids

To summarize the expression profile of each family, Tensor Omics computes a centroid vector for every group. The centroid represents the average expression pattern of all genes assigned to the family across all conditions or tissues.

There are two modes for selecting the set of genes to include in the centroid:

- **Full mode:** All genes assigned to the family are used to compute the centroid (mean vector).
- **Orthologs-only mode:** Only genes explicitly marked as orthologs are included in the centroid calculation. This mode is useful for focusing on conserved gene relationships across species.

### 1.5 Euclidean Distance Between Expression Vectors

The Euclidean distance is used throughout Tensor Omics to quantify the geometric difference between two gene expression vectors, or between a gene and its family centroid. Given two vectors  $\vec{v}_1, \vec{v}_2 \in \mathbb{R}^n$ , the Euclidean distance is defined as:

$$d(\vec{v}_1, \vec{v}_2) = \sqrt{\sum_{i=1}^n (v_{1,i} - v_{2,i})^2}$$

This metric measures the straight-line distance between two points in  $n$ -dimensional space. In the context of gene expression, it reflects the overall magnitude of difference in expression profiles across all samples or conditions.

For example, the distance between a paralog’s expression vector and the centroid of its gene family is used to detect outlier genes and to quantify the degree of divergence.

## 1.6 Outlier Detection Based on Family-Scaled Distances

To robustly identify genes with divergent expression profiles within their families, Tensor Omics implements an outlier detection procedure based on family-scaled Euclidean distances. The process consists of the following steps:

1. **Compute Euclidean Distances:** For each gene, calculate the Euclidean distance  $d_i$  between its expression vector and the centroid of its assigned family (see Section 1.5).
2. **Estimate Family-Specific Scaling Factors:** For each family  $f$ , we compute a family-specific scaling factor. This can be the maximum distance between any ortholog and the ortholog centroid. For families lacking sufficient orthologs, a LOESS smoothing strategy is used to estimate an appropriate scaling factor based on the family’s median intra-member distance.
3. **Relative Distance Index (RDI):** For each gene  $i$  in family  $f$ , compute the Relative Distance Index (RDI):

$$\text{RDI}_i = \frac{d_i}{d_{scale}}$$

This normalizes the gene’s distance by the expected intra-family variability, making the metric comparable across families of different sizes and variances.

4. **Outlier Detection:** Genes are flagged as outliers if their RDI exceeds a chosen percentile threshold (typically the 95th percentile) of the empirical RDI distribution. That is, gene  $i$  is an outlier if  $\text{RDI}_i \geq T$ , where  $T$  is the threshold value corresponding to the desired percentile.

This approach ensures that outlier detection is adaptive to the structure and variability of each gene family, and is robust to differences in family size and dispersion. The LOESS-based scaling is particularly important for families with few members.

## 1.7 Tissue Versatility and Specificity

**Tissue Versatility** quantifies how uniformly a gene is expressed across all tissues (or, more generally, axes of the expression space). It is defined as the cosine of the angle between a gene’s expression vector  $\vec{v}$  and the space diagonal  $\vec{d} = (1, 1, \dots, 1)$ . The smaller this angle (the larger the cosine), the greater the tissue (axis) versatility of the gene’s expression.

### Interpretation:

- A lower angle (cosine closer to 1) means the gene is more evenly expressed across all tissues (high versatility).
- A larger angle (cosine closer to 0) means the gene is active in only a few tissues (high specificity).

### Dimensionality Dependence

The maximum possible angle to the diagonal depends on the number of tissues  $n$ . The cosine of this angle is minimal when a gene is expressed in only one tissue:

$$\cos(\varphi_{\max\_angle}) = \frac{1}{\sqrt{n}}$$

## Normalized Tissue Versatility

To make versatility comparable across datasets with different numbers of tissues, we define a normalized version that scales values into the interval  $[0, 1]$ :

$$\text{Tissue Versatility} = \frac{\cos(\varphi) - \frac{1}{\sqrt{n}}}{1 - \frac{1}{\sqrt{n}}}$$

This maps the cosine values into the interval  $[0, 1]$ :

- 1: perfectly uniform expression (maximum versatility)
- 0: expression in only one tissue (minimum versatility)

## Tissue Specificity

Tissue specificity is defined as the complement of normalized tissue versatility:

$$\text{Tissue Specificity} = 1 - \text{Tissue Versatility}$$

Values close to 1 indicate high tissue-specificity; values close to 0 indicate broad, uniform expression.

## 2 Error Handling

In case you encounter errors while using TOX, the following error codes may help you identify the issue. The error codes are grouped into categories based on their nature, such as I/O errors, format validation errors, memory errors, and internal errors.

Table 1: TOX Error Codes Reference

| Error Code                                   | Description                                                       |
|----------------------------------------------|-------------------------------------------------------------------|
| 0                                            | Success                                                           |
| <b>1xx: I/O / File Reading Errors</b>        |                                                                   |
| 101                                          | Could not open file.                                              |
| 102                                          | Could not read magic number.                                      |
| 103                                          | Could not read array type code.                                   |
| 104                                          | Could not read number of dimensions.                              |
| 105                                          | Could not read array dimensions.                                  |
| 106                                          | Could not read character length.                                  |
| 107                                          | Could not read array data.                                        |
| 112                                          | Could not write magic number                                      |
| 113                                          | Could not write array type code                                   |
| 114                                          | Could not write number of dimensions                              |
| 115                                          | Could not write dimensions                                        |
| 116                                          | Could not write character length                                  |
| 117                                          | Could not write array data                                        |
| <b>2xx: Format / Input Validation Errors</b> |                                                                   |
| 200                                          | Invalid format detected (e.g., magic mismatch or corrupt format). |

Continued on next page

**Table 1 – continued from previous page**

| Error Code                                       | Description                                              |
|--------------------------------------------------|----------------------------------------------------------|
| 201                                              | Invalid input provided.                                  |
| 202                                              | Empty input arrays provided (e.g., zero-length arrays).  |
| 203                                              | Dimension mismatch detected (shape inconsistencies).     |
| 204                                              | NaN or Inf found in input data where not allowed.        |
| 205                                              | Unsupported data type encountered (e.g., complex types). |
| 206                                              | Array size mismatch                                      |
| 208                                              | Array index out of bounds                                |
| 209                                              | Division by zero detected                                |
| <b>3xx: Memory Errors</b>                        |                                                          |
| 301                                              | Memory allocation failed.                                |
| 302                                              | Null pointer reference encountered.                      |
| <b>5xxx: Fortran Runtime / Unit State Errors</b> |                                                          |
| 5002                                             | Fortran runtime error: unit not open or not connected.   |
| <b>9xxx: Internal / Unknown Errors</b>           |                                                          |
| 9001                                             | Internal error: unexpected state or invariant violated.  |
| 9999                                             | Unknown error (fallback for unexpected errors).          |

### 3 Implementation Notes

This section details the practical pipeline for using the TOX library to read and process tabular data. The workflow is consistent across Fortran, Python, and R, starting with reading a CSV file into a staging area of strings and then converting columns to their proper data types.

#### 3.1 Fortran Pipeline

##### 1. Data Reading and Processing

All arrays read have dependencies to each other. The gene ids array stores the ids, column number seven of the expression vectors belongs to entry number seven in the gene ids. Entry number nine in the gene to family mapping array, belongs to entry nine in the gene ids. These dependencies must be given at any time, therefore, only the provided functions shall be used to modify arrays in any form. For error code details please check error handling section.

##### (a) Reading Data

##### • Read Gene IDs from TSV File

Reads gene identifiers from a TSV file containing expression data. Typically reads from the first column after skipping header rows. Call the `read_gene_ids_from_tsv_file` subroutine with the following arguments:

##### Input arguments:

- `filename` `character(len=*)`: Path to the TSV file
- `n_header_rows` `integer(int32)`: Number of header rows to skip (typically 1)
- `gene_col` `integer(int32)`: Column index containing gene IDs (typically 1)

##### Output arguments:

- `gene_ids` `character(len=*)`: Pre-allocated array for gene identifiers

- `ierr` integer(int32): Error code

Listing 1: Read Gene IDs from TSV File

```
character(len=256) :: gene_ids(n_genes) ! Pre-allocate with
expected size
integer(int32) :: ierr

call read_gene_ids_from_tsv_file('expression_data.tsv',
gene_ids, 1, 1, ierr)
```

- **Read Expression Vectors**

Reads expression data from one or more TSV/CSV files and populates a pre-allocated 2D array (samples x genes). Uses hashmap for efficient gene ID matching and validates for finite values. Call the `read_expression_vectors` subroutine with the following arguments:

**Input arguments:**

- `file_list` character(len=\*): Array of file paths to read from
- `gene_ids` character(len=\*): Reference gene IDs for validation and matching
- `expression_vectors` real(real64): Pre-allocated 2D array for expression data
- `n_header_rows` integer(int32): Number of header rows to skip
- `gene_col` integer(int32): Column index containing gene IDs
- `value_cols` integer(int32): Array of column indices containing expression values
- `start_row` integer(int32): Starting row index in `expression_vectors` array
- `delimiter` character(len=1), optional: Column delimiter (default: tab)

**Output arguments:**

- `expression_vectors` real(real64): Pre-allocated 2D array for expression data populated with data
- `ierr` integer(int32): Error code

Listing 2: Read Expression Vectors

```
! Pre-allocate arrays
real(real64) :: expr_data(n_samples, n_genes)

! Read TSV file with tab delimiter (default)
call read_expression_vectors(files, gene_ids, expr_data, 1, 1,
value_cols, 1, ierr)

! Read CSV file with comma delimiter
call read_expression_vectors(files, gene_ids, expr_data, 1, 1,
value_cols, 1, ierr, ',')
```

- **Read OrthoFinder Family Mapping**

Reads gene family assignments from OrthoFinder output TSV file and creates mapping arrays between genes and families. The `gene_to_fam` array contains for each gene the index of its family. Uses hashmap for efficient gene lookup. Call the `read_orthofinder_file` subroutine with the following arguments:

**Input arguments:**



- filename character(len=\*): Path to OrthoFinder TSV file
- gene\_ids character(len=\*): Pre-allocated array of gene IDs to match

**Output arguments:**

- family\_ids character(len=\*): Pre-allocated array for family identifiers
- gene\_to\_fam integer(int32): Pre-allocated array for gene to family mapping
- ierr integer(int32): Error code

Listing 3: Read OrthoFinder Family Mapping

```
character(len=256) :: family_ids(n_families) ! Pre-allocate
with expected family count
integer(int32) :: gene_to_fam(n_genes) ! Pre-allocate with
gene count
integer(int32) :: ierr

call read_orthofinder_file('Orthogroups.tsv', gene_ids,
family_ids, gene_to_fam, ierr)
```

**Important Implementation Details:**

- All output arrays must be pre-allocated with the correct dimensions and sizes
- Uses hashmap data structure for O(1) gene ID lookups
- Validates for finite values (rejects NaN and Inf) in expression data
- Handles both TSV (tab-separated) and CSV (comma-separated) formats, gene\_to\_fam array uses 1-based indexing for family assignments (0 indicates unassigned)

**Typical Data Reading Workflow:**

Listing 4: Complete Data Reading Workflow

```
! 1. Pre-allocate arrays

! 2. Read gene IDs from expression file
call read_gene_ids_from_tsv_file('expression.tsv', gene_ids, 1,
1, ierr)

! 3. Read expression data (columns 2-68 contain sample data)
character(len=256) :: files(1) = ['expression.tsv']

call read_expression_vectors(files, gene_ids, expr_data, 1, 1,
samples, 1, ierr)

! 4. Read family mapping from OrthoFinder
call read_orthofinder_file('Orthogroups.tsv', gene_ids,
family_ids, gene_to_fam, ierr)
```

**(b) Data Filtering and Validation**

• **Get Unassigned Genes Mask**

Creates a logical mask identifying genes that have no family assignment (gene\_to\_fam value = 0). Call the `get_unassigned_mask` subroutine with the following arguments:

**Input arguments:**

- gene\_to\_fam integer(int32): Gene to family mapping array

**Output arguments:**

- mask logical: Logical mask array (same size as gene\_to\_fam)
- n\_genes\_kept integer(int32): Number of genes with family assignments
- ierr integer(int32): Error code

Listing 5: Create Unassigned Genes Mask

```
logical :: unassigned_mask(n_genes)
integer(int32) :: n_kept, ierr

call get_unassigned_mask(gene_to_fam, unassigned_mask, n_kept)
! unassigned_mask(i) = .true. if gene i has family assignment
! n_kept = count of genes with family assignments
```

#### • Apply Unassigned Mask

Filters out genes without family assignments from all data arrays (gene\_ids, expression\_vectors, gene\_to\_fam). Arrays are reallocated to the filtered size. Call the apply\_unassigned\_mask subroutine with the following arguments:

##### Input arguments:

- mask logical: Logical mask from get\_unassigned\_mask
- n\_genes\_kept integer(int32): Number of genes to keep (from get\_unassigned\_mask)

##### Input/Output arguments:

- gene\_ids character(len=\*), allocatable: Gene IDs array (reallocated)
- expression\_vectors real(real64), allocatable: Expression data matrix (reallocated)
- gene\_to\_fam integer(int32), allocatable: Gene to family mapping (relocated)
- ierr integer(int32): Error code

Listing 6: Filter Unassigned Genes

```
character(len=256), allocatable :: gene_ids(n_genes)
real(real64), allocatable :: expr_data(n_samples, n_genes)
integer(int32), allocatable :: gene_to_fam(n_genes)
logical :: unassigned_mask(n_genes)
integer(int32) :: n_kept, ierr

! First create the mask
call get_unassigned_mask(gene_to_fam, unassigned_mask, n_kept)

! Then apply it to filter all arrays
call apply_unassigned_mask(gene_ids, expr_data, gene_to_fam, &
                           unassigned_mask, n_kept, ierr)
! Arrays are now reallocated to size n_kept
```

#### • Validate Data Structure

Performs comprehensive validation of data dimensions and consistency across all arrays. Call the validate\_data\_structure subroutine with the following arguments:

##### Input arguments:

- n\_genes integer(int32): Number of genes
- n\_families integer(int32): Number of gene families
- n\_samples integer(int32): Number of samples

- `gene_ids` `character(len=*)`: Gene identifier array
- `family_ids` `character(len=*)`: Family identifier array
- `gene_to_family` `integer(int32)`: Gene to family mapping
- `expression` `real(real64)`: Expression data matrix
- `centroids` `real(real64)`: Family centroids matrix
- `shift_vectors` `real(real64)`: Shift vectors matrix
- `ierr` `integer(int32)`: Error code

Listing 7: Validate Data Structure

```
call validate_data_structure(n_genes, n_families, n_samples,
    gene_ids, &
                                family_ids, gene_to_fam, expr_data,
                                &
                                centroids, shift_vectors, ierr)
```

- **Validate Expression Data**

Validates expression data matrix for NaN, Inf, and optionally negative values. Call the `validate_expression_data` subroutine with the following arguments:

**Input arguments:**

- `expression` `real(real64)`: Expression data matrix to validate
- `allow_negative` `logical`: Whether to allow negative expression values
- `ierr` `integer(int32)`: Error code

Listing 8: Validate Expression Data

```
! Validate expression data (disallow negative values)
call validate_expression_data(expr_data, .false., ierr)

! Validate allowing negative values (e.g., for log-fold changes
)
call validate_expression_data(expr_data, .true., ierr)
```

- **Validate Empty Strings**

Validates that a string array contains no empty or whitespace-only entries. Call the `validate_empty_strings` subroutine with the following arguments:

**Input arguments:**

- `string_array` `character(len=*)`: String array to validate
- `array_name` `character(len=*)`: Name for error messages

**Output arguments:**

- `ierr` `integer(int32)`: Error code

Listing 9: Validate String Array

```
call validate_empty_strings(gene_ids, "Gene IDs", ierr)
call validate_empty_strings(family_ids, "Family IDs", ierr)
```

- **Validate Gene to Family Mapping**

Validates that all gene to family indices are within valid range (1 to `n_families`). Call the `validate_gene_to_family_mapping` subroutine with the following arguments:

**Input arguments:**

- `gene_to_family integer(int32)`: Gene to family mapping array
- `n_families integer(int32)`: Number of valid families

**Output arguments:**

- `ierr integer(int32)`: Error code

Listing 10: Validate Gene-Family Mapping

```
call validate_gene_to_family_mapping(gene_to_fam, n_families,
                                     ierr)
```

- **Validate String Array Uniqueness**

Validates that all entries in a string array are unique (no duplicates). Uses a hashset implementation internally for O(n) runtime. Call the `validate_string_array_uniqueness` subroutine with the following arguments:

**Input arguments:**

- `string_array character(len=*)`: String array to check for duplicates

**Output arguments:**

- `ierr integer(int32)`: Error code

Listing 11: Validate Unique Strings

```
call validate_string_array_uniqueness(gene_ids, ierr)
call validate_string_array_uniqueness(family_ids, ierr)
```

(c) **Data Accessors**

- **Get Gene Index**

Finds the array index for a given gene identifier. Call the `get_gene_index` function with the following arguments:

**Input arguments:**

- `gene_ids character(len=*)`: Array of gene identifiers
- `gene_id character(len=*)`: Gene ID to find

**Return value:**

- `index integer(int32)`: Array index (1-based) or 0 if not found

Listing 12: Find Gene Index

```
integer(int32) :: gene_idx

gene_idx = get_gene_index(gene_ids, 'NP_001000001.1')
if (gene_idx > 0) then
    ! Gene found at position gene_idx
else
    ! Gene not found
end if
```

- **Get Family Index**

Finds the array index for a given family identifier. Call the `get_family_index` function with the following arguments:

**Input arguments:**

- `family_ids character(len=*)`: Array of family identifiers
- `family_id character(len=*)`: Family ID to find

**Return value:**

- `index integer(int32)`: Array index (1-based) or 0 if not found

Listing 13: Find Family Index

```
integer(int32) :: fam_idx

fam_idx = get_family_index(family_ids, 'OG0000001')
```

- **Get Family for Gene Index**

Retrieves the family index for a given gene index. Call the `get_family_for_gene_index` subroutine with the following arguments:

**Input arguments:**

- `gene_index integer(int32)`: Gene array index (1-based)
- `gene_to_family integer(int32)`: Gene to family mapping array

**Output arguments:**

- `family_index integer(int32)`: Family array index (1-based)
- `ierr integer(int32)`: Error code

Listing 14: Get Family for Gene

```
integer(int32) :: gene_idx, fam_idx, ierr

gene_idx = get_gene_index(gene_ids, 'NP_001000001.1')
call get_family_for_gene_index(gene_idx, gene_to_fam, fam_idx,
                               ierr)
```

- **Get Family Centroid**

Retrieves the centroid expression profile for a given family. Call the `get_family_centroid` subroutine with the following arguments:

**Input arguments:**

- `family_index integer(int32)`: Family array index (1-based)
- `family_centroids real(real64)`: Family centroids matrix

**Output arguments:**

- `ierr integer(int32)`: Error code
- `centroid_vector real(real64)`: Centroid expression profile

Listing 15: Get Family Centroid

```
real(real64) :: centroid_vector(n_samples)
integer(int32) :: fam_idx, ierr

fam_idx = get_family_index(family_ids, 'OG0000001')
call get_family_centroid(fam_idx, centroids, centroid_vector,
                          ierr)
```

**Complete Validation Workflow:**

Listing 16: Complete Data Validation Workflow

```
integer(int32) :: ierr

! 1. Filter unassigned genes
```

```

logical :: unassigned_mask(n_genes)
integer(int32) :: n_kept
call get_unassigned_mask(gene_to_fam, unassigned_mask, n_kept)
call apply_unassigned_mask(gene_ids, expr_data, gene_to_fam, &
                           unassigned_mask, n_kept, ierr)

! 2. Validate individual components
call validate_empty_strings(gene_ids, "Gene IDs", ierr)
call validate_empty_strings(family_ids, "Family IDs", ierr)
call validate_string_array_uniqueness(gene_ids, ierr)
call validate_string_array_uniqueness(family_ids, ierr)
call validate_gene_to_family_mapping(gene_to_fam, n_families,
                                     ierr)
call validate_expression_data(expr_data, .false., ierr)

! 3. Comprehensive structure validation
call validate_data_structure(n_genes, n_families, n_samples,
                             gene_ids, &
                             family_ids, gene_to_fam, expr_data,
                             &
                             centroids, shift_vectors, ierr)

! 4. Use accessors for data retrieval
integer(int32) :: gene_idx, fam_idx
real(real64) :: centroid(n_samples)

gene_idx = get_gene_index(gene_ids, 'NP_001000001.1')
call get_family_for_gene_index(gene_idx, gene_to_fam, fam_idx,
                               ierr)
call get_family_centroid(fam_idx, centroids, centroid, ierr)

```

#### (d) Standard Archive Operations

- **Save Tox Data Archive**

Saves multiple data arrays to a ZIP archive with automatic manifest creation and temporary file management. Handles any combination of available standard data arrays. This function can only be used with standard gene expression data. If other data needs to be saved, see section "Non-standard archive operations". Call the `save_tox_data` subroutine with the following arguments:

**Input arguments:**

- `zip_filename` character(len=\*): Output ZIP file name
- `ierr` integer(int32): Error code

**Optional input arguments (provide both array and filename for each data type):**

- `gene_ids` character(len=\*): Gene IDs array
- `gene_ids_file` character(len=\*): Internal filename for gene IDs
- `expression` real(real64): Expression data matrix
- `expression_file` character(len=\*): Internal filename for expression data
- `gene_to_family` integer(int32): Gene to family mapping
- `gene_to_family_file` character(len=\*): Internal filename for mapping
- `family_ids` character(len=\*): Family IDs array

- family\_ids\_file character(len=\*): Internal filename for family IDs
- family\_centroids real(real64): Family centroids matrix
- family\_centroids\_file character(len=\*): Internal filename for centroids
- shift\_vectors real(real64): Shift vectors matrix
- shift\_vectors\_file character(len=\*): Internal filename for shift vectors

Listing 17: Save Complete Data Archive

```
integer(int32) :: ierr

! Save all available data arrays
call save_tox_data("complete_data.zip", ierr, &
    gene_ids=gene_ids, gene_ids_file="genes.bin",
    &
    expression=expr_data, expression_file="
    expression.bin", &
    gene_to_family=gene_to_fam,
    gene_to_family_file="mapping.bin", &
    family_ids=family_ids, family_ids_file="
    families.bin", &
    family_centroids=centroids,
    family_centroids_file="centroids.bin", &
    shift_vectors=shift_vecs, shift_vectors_file="
    shifts.bin")
```

Listing 18: Save Partial Data Archive

```
! Save only gene IDs and expression data
call save_tox_data("expression_only.zip", ierr, &
    gene_ids=gene_ids, gene_ids_file="genes.bin",
    &
    expression=expr_data, expression_file="
    expression.bin")

! Save only family-related data
call save_tox_data("families_only.zip", ierr, &
    family_ids=family_ids, family_ids_file="
    families.bin", &
    family_centroids=centroids,
    family_centroids_file="centroids.bin")
```

#### • Read Tox Data Archive

Reads data arrays from a ZIP archive created with `save_tox_data`. Automatically handles array allocation based on archive contents. The function will try to read all requested arrays (optional arguments that are provided) from the given archive. If an array can not be found in the archive, the output arrays won't be allocated or returned. Call the `read_tox_data` subroutine with the following arguments:

##### Input arguments:

- zip\_filename character(len=\*): Input ZIP file name
- ierr integer(int32): Error code

##### Optional output arguments:

- gene\_ids character(len=:), allocatable: Gene IDs array

- expression real(real64), allocatable: Expression data matrix
- gene\_to\_family integer(int32), allocatable: Gene to family mapping
- family\_ids character(len=:), allocatable: Family IDs array
- family\_centroids real(real64), allocatable: Family centroids matrix
- shift\_vectors real(real64), allocatable: Shift vectors matrix

**Optional filename output arguments:**

- gene\_ids\_file character(len=:), allocatable: Internal filename used
- expression\_file character(len=:), allocatable: Internal filename used
- gene\_to\_family\_file character(len=:), allocatable: Internal filename used
- family\_ids\_file character(len=:), allocatable: Internal filename used
- family\_centroids\_file character(len=:), allocatable: Internal filename used
- shift\_vectors\_file character(len=:), allocatable: Internal filename used

Listing 19: Read Complete Data Archive

```
character(len=:), allocatable :: loaded_gene_ids(:),
    loaded_family_ids(:)
real(real64), allocatable :: loaded_expr(:, :), loaded_centroids
    (:, :)
real(real64), allocatable :: loaded_shifts(:, :)
integer(int32), allocatable :: loaded_gene_to_fam(:)
integer(int32) :: ierr

! Read all available data from archive
call read_tox_data("complete_data.zip", ierr, &
    gene_ids=loaded_gene_ids, &
    expression=loaded_expr, &
    gene_to_family=loaded_gene_to_fam, &
    family_ids=loaded_family_ids, &
    family_centroids=loaded_centroids, &
    shift_vectors=loaded_shifts)
```

Listing 20: Read Partial Data Archive

```
! Read only specific arrays (others remain unallocated)
call read_tox_data("expression_only.zip", ierr, &
    gene_ids=loaded_gene_ids, &
    expression=loaded_expr)
```

Listing 21: Read with Filename Retrieval

```
character(len=:), allocatable :: actual_gene_file,
    actual_expr_file
integer(int32) :: ierr

! Get both data and internal filenames
call read_tox_data("complete_data.zip", ierr, &
    gene_ids=loaded_gene_ids, gene_ids_file=
        actual_gene_file, &
    expression=loaded_expr, expression_file=
        actual_expr_file)
```



### (e) Non-Standard Archive Operations

- **Create Custom ZIP Archive**

Creates a ZIP archive from arbitrary files with key-based manifest for non-standard data. Call the `create_zip_archive` subroutine with the following arguments:

**Input arguments:**

- `zip_filename` character(len=\*): Output ZIP file name
- `keys` character(len=\*): Array of keys for manifest entries
- `filenames` character(len=\*): Array of file paths to include
- `ierr` integer(int32): Error code

Listing 22: Create Custom Archive

```
character(len=32) :: keys(3) = ['test_data_1', 'test_data_2', 'test_data_3']
character(len=256) :: files(3) = ['test_data_1.bin', 'test_2.bin', 'test_3.bin']
integer(int32) :: ierr

call create_zip_archive("custom_data.zip", keys, files, ierr)
```

- **Extract ZIP Archive**

Extracts all files from a ZIP archive to the disk in the current directory and returns key-value pairs from the manifest. Call the `extract_zip_archive` subroutine with the following arguments:

**Input arguments:**

- `zip_filename` character(len=\*): Input ZIP file name
- `ierr` integer(int32): Error code

**Output arguments:**

- `keys` character(len=:), allocatable: Array of keys from manifest
- `filenames` character(len=:), allocatable: Array of extracted filenames

Listing 23: Extract Custom Archive

```
character(len=:), allocatable :: archive_keys(:), archive_files(:)
integer(int32) :: ierr

call extract_zip_archive("custom_data.zip", archive_keys, archive_files, ierr)
```

### Complete Archive Workflow:

Listing 24: Complete Archive Management Workflow

```
integer(int32) :: ierr

! 1. Save processed data
call save_tox_data("analysis_results.zip", ierr, &
                  gene_ids=gene_ids, gene_ids_file="genes.bin", &
                  expression=expr_data, expression_file="expression.bin", &
```

```

        family_centroids=centroids,
        family_centroids_file="centroids.bin")

! 2. Later, read the data back
character(len=:), allocatable :: loaded_genes(:)
real(real64), allocatable :: loaded_expr(:, :), loaded_centroids
    (:, :)
call read_tox_data("analysis_results.zip", ierr, &
    gene_ids=loaded_genes, &
    expression=loaded_expr, &
    family_centroids=loaded_centroids)

! 3. Create custom archive with additional results
character(len=32) :: custom_keys(2) = ['data_1', 'data_2']
character(len=256) :: custom_files(2) = ['data_1_v2.bin', '
    data_2_v1.bin']
call create_zip_archive("full_analysis.zip", custom_keys,
    custom_files, ierr)

! 4. Extract and verify custom archive
character(len=:), allocatable :: extracted_keys(:),
    extracted_files(:)
call extract_zip_archive("full_analysis.zip", extracted_keys,
    extracted_files, ierr)

```

### Key Features of Archive Operations:

- **Automatic Memory Management:** Arrays automatically allocated to correct sizes
- **Flexible Data Selection:** Save/read any combination of data arrays
- **Cross-Platform Compatibility:** Archives work across R, Python, and Fortran implementations
- **Manifest-Based:** Automatic tracking of file contents and relationships
- **Temporary File Handling:** Automatic cleanup of intermediate files
- **Error Recovery:** Comprehensive error checking and reporting

### Archive Structure:

```

archive.zip
|- manifest.txt           (key=filename mappings)
|- genes.bin              (gene IDs, if provided)
|- expression.bin         (expression data, if provided)
|- mapping.bin            (gene to family, if provided)
|- families.bin           (family IDs, if provided)
|- centroids.bin          (family centroids, if provided)
|- shifts.bin             (shift vectors, if provided)

```

### (f) Individual Array Save/Load Operations

#### • Save Gene IDs

Saves a gene IDs array to a binary file with automatic character length preservation. Call the `save_gene_ids` subroutine with the following arguments:

#### Input arguments:

- `gene_ids` `character(len=*)`: Array of gene identifiers

- filename character(len=\*): Output binary file name
- ierr integer(int32): Error code

Listing 25: Save Gene IDs Array

```
character(len=256) :: gene_ids(10000)
integer(int32) :: ierr

call save_gene_ids(gene_ids, 'gene_ids.bin', ierr)
```

#### • Load Gene IDs

Loads a gene IDs array from a binary file with automatic allocation and character length detection. Call the `load_gene_ids` subroutine with the following arguments:

##### Input arguments:

- filename character(len=\*): Input binary file name
- ierr integer(int32): Error code

##### Output arguments:

- gene\_ids character(len=:), allocatable: Loaded gene IDs array

Listing 26: Load Gene IDs Array

```
character(len=:), allocatable :: loaded_gene_ids(:)
integer(int32) :: ierr

call load_gene_ids(loaded_gene_ids, 'gene_ids.bin', ierr)
! loaded_gene_ids automatically allocated with correct size and
  character length
```

#### • Save Expression Vectors

Saves an expression data matrix to a binary file. Call the `save_expression_vectors` subroutine with the following arguments:

##### Input arguments:

- expression real(real64): 2D expression data matrix
- filename character(len=\*): Output binary file name
- ierr integer(int32): Error code

Listing 27: Save Expression Data

```
real(real64) :: expr_data(n_samples, n_genes)
integer(int32) :: ierr

call save_expression_vectors(expr_data, 'expression.bin', ierr)
```

#### • Load Expression Vectors

Loads an expression data matrix from a binary file with automatic allocation. Call the `load_expression_vectors` subroutine with the following arguments:

##### Input arguments:

- filename character(len=\*): Input binary file name
- ierr integer(int32): Error code

##### Output arguments:

- expression real(real64), allocatable: Loaded expression data matrix

Listing 28: Load Expression Data

```
real(real64), allocatable :: loaded_expr(:, :)
integer(int32) :: ierr

call load_expression_vectors(loaded_expr, 'expression.bin',
    ierr)
! loaded_expr automatically allocated as (samples x genes)
```

- **Save Gene to Family Mapping**

Saves a gene to family mapping array to a binary file. Call the `save_gene_to_family` subroutine with the following arguments:

**Input arguments:**

- `gene_to_family` integer(int32): Gene to family mapping array
- `filename` character(len=\*): Output binary file name
- `ierr` integer(int32): Error code

Listing 29: Save Gene-Family Mapping

```
integer(int32) :: gene_to_fam(n_genes)
integer(int32) :: ierr

call save_gene_to_family(gene_to_fam, 'gene_to_fam.bin', ierr)
```

- **Load Gene to Family Mapping**

Loads a gene to family mapping array from a binary file with automatic allocation. Call the `load_gene_to_family` subroutine with the following arguments:

**Input arguments:**

- `filename` character(len=\*): Input binary file name
- `ierr` integer(int32): Error code

**Output arguments:**

- `gene_to_family` integer(int32), allocatable: Loaded gene to family mapping

Listing 30: Load Gene-Family Mapping

```
integer(int32), allocatable :: loaded_gene_to_fam(:)
integer(int32) :: ierr

call load_gene_to_family(loaded_gene_to_fam, 'gene_to_fam.bin',
    ierr)
```

- **Save Family IDs**

Saves a family IDs array to a binary file with automatic character length preservation. Call the `save_family_ids` subroutine with the following arguments:

**Input arguments:**

- `family_ids` character(len=\*): Array of family identifiers
- `filename` character(len=\*): Output binary file name
- `ierr` integer(int32): Error code

Listing 31: Save Family IDs

```

character(len=256) :: family_ids(n_families)
integer(int32) :: ierr

call save_family_ids(family_ids, 'family_ids.bin', ierr)

```

- **Load Family IDs**

Loads a family IDs array from a binary file with automatic allocation and character length detection. Call the `load_family_ids` subroutine with the following arguments:

**Input arguments:**

- filename character(len=\*): Input binary file name
- ierr integer(int32): Error code

**Output arguments:**

- family\_ids character(len=:), allocatable: Loaded family IDs array

Listing 32: Load Family IDs

```

character(len=:), allocatable :: loaded_family_ids(:)
integer(int32) :: ierr

call load_family_ids(loaded_family_ids, 'family_ids.bin', ierr)

```

- **Save Family Centroids**

Saves a family centroids matrix to a binary file. Call the `save_family_centroids` subroutine with the following arguments:

**Input arguments:**

- family\_centroids real(real64): 2D family centroids matrix
- filename character(len=\*): Output binary file name
- ierr integer(int32): Error code

Listing 33: Save Family Centroids

```

real(real64) :: centroids(67, 15512)
integer(int32) :: ierr

call save_family_centroids(centroids, 'centroids.bin', ierr)

```

- **Load Family Centroids**

Loads a family centroids matrix from a binary file with automatic allocation. Call the `load_family_centroids` subroutine with the following arguments:

**Input arguments:**

- filename character(len=\*): Input binary file name
- ierr integer(int32): Error code

**Output arguments:**

- family\_centroids real(real64), allocatable: Loaded family centroids matrix

Listing 34: Load Family Centroids

```

real(real64), allocatable :: loaded_centroids(:, :)
integer(int32) :: ierr

```

```
call load_family_centroids(loaded_centroids, 'centroids.bin',
    ierr)
```

- **Save Shift Vectors**

Saves a shift vectors matrix to a binary file. Call the `save_shift_vectors` subroutine with the following arguments:

**Input arguments:**

- `shift_vectors` `real(real64)`: 2D shift vectors matrix
- `filename` `character(len=*)`: Output binary file name
- `ierr` `integer(int32)`: Error code

Listing 35: Save Shift Vectors

```
real(real64) :: shift_vecs(134, 88327) ! 2xsamples x genes
integer(int32) :: ierr

call save_shift_vectors(shift_vecs, 'shift_vectors.bin', ierr)
```

- **Load Shift Vectors**

Loads a shift vectors matrix from a binary file with automatic allocation. Call the `load_shift_vectors` subroutine with the following arguments:

**Input arguments:**

- `filename` `character(len=*)`: Input binary file name
- `ierr` `integer(int32)`: Error code

**Output arguments:**

- `shift_vectors` `real(real64)`, `allocatable`: Loaded shift vectors matrix

Listing 36: Load Shift Vectors

```
real(real64), allocatable :: loaded_shifts(:, :)
integer(int32) :: ierr

call load_shift_vectors(loaded_shifts, 'shift_vectors.bin',
    ierr)
```

- **Get Array Metadata**

Retrieves metadata (dimensions, character length) from a binary file without loading the entire array. Call the `get_array_metadata` subroutine with the following arguments:

**Input arguments:**

- `filename` `character(len=*)`: Binary file name to inspect
- `max_dims` `integer(int32)`: Maximum number of dimensions to return
- `ierr` `integer(int32)`: Error code

**Output arguments:**

- `dims` `integer(int32)`: Array dimensions
- `ndims` `integer(int32)`: Number of dimensions
- `char_len` `integer(int32)`, `optional`: Character length for string arrays

### Listing 37: Inspect Array File Metadata

```
integer(int32) :: dims(5), ndims, char_len, ierr

! Get metadata for gene IDs file
call get_array_metadata('gene_ids.bin', dims, 5, ndims, ierr,
    char_len)
if (is_ok(ierr)) then
    print *, "Dimensions:", dims(1:ndims)
    print *, "Character length:", char_len
end if

! Get metadata for expression data file
call get_array_metadata('expression.bin', dims, 5, ndims, ierr)
if (is_ok(ierr)) then
    print *, "Expression data shape:", dims(1), "x", dims(2)
end if
```

### Complete Individual Array Workflow:

#### Listing 38: Individual Array Save/Load Workflow

```
integer(int32) :: ierr

! 1. Save individual arrays
call save_gene_ids(gene_ids, 'gene_ids.bin', ierr)
call save_expression_vectors(expr_data, 'expression.bin', ierr)
call save_gene_to_family(gene_to_fam, 'mapping.bin', ierr)
call save_family_ids(family_ids, 'families.bin', ierr)
call save_family_centroids(centroids, 'centroids.bin', ierr)
call save_shift_vectors(shift_vecs, 'shifts.bin', ierr)

! 2. Check file metadata before loading
integer(int32) :: dims(5), ndims, char_len
call get_array_metadata('expression.bin', dims, 5, ndims, ierr)
if (is_ok(ierr) .and. ndims == 2) then
    print *, "Will load expression data:", dims(1), "samples x",
        , dims(2), "genes"
end if

! 3. Load arrays (automatic allocation)
character(len=:), allocatable :: loaded_genes(:)
real(real64), allocatable :: loaded_expr(:, :)
integer(int32), allocatable :: loaded_mapping(:)
character(len=:), allocatable :: loaded_families(:)
real(real64), allocatable :: loaded_centroids(:, :)
real(real64), allocatable :: loaded_shifts(:, :)

call load_gene_ids(loaded_genes, 'gene_ids.bin', ierr)
call load_expression_vectors(loaded_expr, 'expression.bin',
    ierr)
call load_gene_to_family(loaded_mapping, 'mapping.bin', ierr)
call load_family_ids(loaded_families, 'families.bin', ierr)
call load_family_centroids(loaded_centroids, 'centroids.bin',
    ierr)
call load_shift_vectors(loaded_shifts, 'shifts.bin', ierr)
```

```

! 4. Verify loaded data
print *, "Loaded", size(loaded_genes), "genes"
print *, "Loaded expression data:", size(loaded_expr, 1), "x",
      size(loaded_expr, 2)
print *, "Loaded", size(loaded_families), "families"

```

### Manual Archive Creation with Individual Arrays:

Listing 39: Manual Archive Creation

```

integer(int32) :: ierr

! 1. Save arrays to individual files
call save_gene_ids(gene_ids, 'temp_genes.bin', ierr)
call save_expression_vectors(expr_data, 'temp_expr.bin', ierr)

! 2. Create custom archive with specific keys
character(len=32) :: keys(2) = ['gene_data', 'expression_data']
character(len=256) :: files(2) = ['temp_genes.bin', 'temp_expr.
      bin']
call create_zip_archive('manual_archive.zip', keys, files, ierr
)

! 3. Clean up temporary files (optional)
call delete_file('temp_genes.bin', ierr)
call delete_file('temp_expr.bin', ierr)

```

### Key Features of Individual Array Operations:

- **Automatic Allocation:** Output arrays automatically allocated to correct sizes
- **Character Length Preservation:** String arrays maintain original character lengths
- **Metadata Inspection:** Check array properties without loading data
- **Binary Format:** Efficient storage for large datasets
- **Error Handling:** Comprehensive error checking for file operations
- **Memory Efficient:** Can process arrays larger than available memory

### Performance Considerations:

- Binary format provides fast I/O for large arrays
- Automatic dimension detection eliminates manual size tracking
- Character length preservation avoids fixed-width string limitations
- Suitable for datasets with millions of genes and thousands of samples

In a pure Fortran application, the user follows a two-step process to construct the Data Table.

2. **Read CSV to Strings:** First, call the `read_csv_to_strings` subroutine. This reads the entire CSV file into a 2D allocatable array of characters, which serves as the in-memory source for all subsequent operations.
3. **Extract Typed Columns:** Next, call the specific `read*_columns` subroutines (e.g., `read_integer_columns`, `read_real_columns`) to parse columns from the string array into new, strongly-typed 2D arrays.



Listing 40: Fortran Data Loading Workflow

```

PROGRAM tox_fortran_example
  USE csv_file_reader_module, ONLY: read_csv_to_strings
  USE csv_read_int_module, ONLY: read_integer_columns
  USE csv_read_real_module, ONLY: read_real_columns
  USE csv_parser_module, ONLY: MAX_FIELD_LEN
  IMPLICIT NONE

  CHARACTER(LEN=MAX_FIELD_LEN), ALLOCATABLE :: data_str(:,:),
    header_str(:)
  INTEGER, ALLOCATABLE :: data_int(:,:)
  REAL(8), ALLOCATABLE :: data_real(:,:)
  INTEGER :: status

  CHARACTER(LEN=*), PARAMETER :: FILENAME = 'my_data.csv'

  ! 1. Read entire CSV into a 2D string array
  CALL read_csv_to_strings(FILENAME, .TRUE., ', ', header_str,
    data_str, status)
  IF (status /= 0) STOP 'Error reading CSV'

  ! 2. Extract specific columns into typed arrays
  !   Let's say column 1 is Integer IDs, column 3 is Real scores
  CALL read_integer_columns(data_str, [1], data_int, status)
  IF (status /= 0) STOP 'Error reading integer columns'

  CALL read_real_columns(data_str, [3], data_real, status)
  IF (status /= 0) STOP 'Error reading real columns'

  ! The typed arrays data_int and data_real are now ready for
  ! analysis.
  PRINT *, 'Successfully processed data.'

END PROGRAM tox_fortran_example

```

#### 4. TODO Functions relating section 1.2

#### 5. Normalization of Expression Values

The subroutine runs a complete normalization pipeline on gene expression data. It first applies standard deviation normalization, then quantile normalization, followed by replicate averaging, and finally a log2 transformation. The result is returned in the `buf_log` array, which contains the fully normalized expression values. Additionally intermediate results of the performed calculations are available in output buffer arrays. Call the `normalization_pipeline` subroutine with the following arguments:

##### Input arguments:

- `n_genes` integer(int32): Total number of genes
- `n_tissues` integer(int32): Number of axes (tissues / dimensions)
- `input_matrix` real(real64): Expression vector matrix with size `n_genes` × `n_tissues`
- `max_stack` integer(int32): Stack size for quicksort

- `group_s` integer(int32): Start column index for each replicate group (`n_grps`)
- `group_c` integer(int32): Number of columns per replicate group (`n_grps`)
- `n_grps` integer(int32): Number of replicate groups

**Output arguments:**

- `buf_stddev` real(real64): Buffer for std dev normalization (`n_genes * n_tissues`)
- `buf_quant` real(real64): Buffer for quantile normalization (`n_genes * n_tissues`)
- `buf_avg` real(real64): Buffer for replicate averaging (`n_genes * n_grps`)
- `buf_log` real(real64): Buffer for  $\log_2(x+1)$  transformation (`n_genes * n_grps`)
- `temp_col` real(real64): Temporary column vector for sorting (`n_genes`)
- `rank_means` real(real64): Buffer for rank means (`n_genes`)
- `perm` integer(int32): Permutation vector for sorting (`n_genes`)
- `stack_left` integer(int32): Left stack for quicksort (`max_stack`)
- `stack_right` integer(int32): Right stack for quicksort (`max_stack`)
- `ierr` integer(int32): Error code (for error details please check error handling section )

Listing 41: Normalization Pipeline

```
call normalization_pipeline(n_genes, n_tissues, input_matrix,
    buf_stddev, buf_quant, buf_avg, buf_log, temp_col, rank_means, perm,
    stack_left, stack_right, max_stack, group_s, group_c, n_grps,
    ierr)
```

Alternatively you can calculate each step of the normalization pipeline manually by calling the following subroutines in sequence:

(a) **Normalize by Standard Deviation**

The subroutine normalizes each gene's expression vector using `sqrt(mean(x2))` across tissues (not classical standard deviation). Call the `normalize_by_std_dev` subroutine with the following arguments:

**Input arguments:**

- `n_genes` integer(int32): Number of genes (rows)
- `n_tissues` integer(int32): Number of tissues (columns)
- `input_matrix` real(real64): Flattened input matrix of gene expression values (column-major)

**Output arguments:**

- `output_matrix` real(real64): Output normalized matrix (same shape as input)
- `ierr` integer(int32): Error code (for error details please check error handling section )

Listing 42: Standard Deviation Normalization

```
call normalize_by_std_dev(n_genes, n_tissues, input_matrix,
    output_matrix, ierr)
```

### (b) Quantile Normalization

The subroutine performs quantile normalization of a gene expression matrix (F42-compliant) and computes average expression per rank across tissues. Call the `quantile_normalization` subroutine with the following arguments:

#### Input arguments:

- `n_genes` `integer(int32)`: Number of genes (rows)
- `n_tissues` `integer(int32)`: Number of tissues (columns)
- `input_matrix` `real(real64)`: Flattened input matrix (column-major)
- `max_stack` `integer(int32)`: Stack size passed from R

#### Output arguments:

- `output_matrix` `real(real64)`: Output normalized matrix (same shape as input)
- `temp_col` `real(real64)`: Temporary vector for column sorting (size `n_genes`)
- `rank_means` `real(real64)`: Preallocated vector to store rank means (size `n_genes`)
- `perm` `integer(int32)`: Permutation vector (size `n_genes`)
- `stack_left` `integer(int32)`: Manual quicksort stack ( $\geq \log_2(n\_genes) + 10$ )
- `stack_right` `integer(int32)`: Manual quicksort stack (same size as `stack_left`)
- `ierr` `integer(int32)`: Error code (for error details please check error handling section )

Listing 43: Quantile Normalization

```
call quantile_normalization(n_genes, n_tissues, input_matrix,
    output_matrix, temp_col, rank_means, perm, stack_left,
    stack_right, max_stack, ierr)
```

### (c) Calculate Tissue Averages

The subroutine calculates tissue averages by averaging replicates within each group. For each group of tissue replicates, it computes the average expression per gene. The input matrix is column-major, flattened as a 1D array. Call the `calc_tiss_avg` subroutine with the following arguments:

#### Input arguments:

- `n_gene` `integer(int32)`: Number of genes (rows)
- `n_grps` `integer(int32)`: Number of tissue groups
- `group_s` `integer(int32)`: Start column index for each group (length: `n_grps`)
- `group_c` `integer(int32)`: Number of columns per group (length: `n_grps`)
- `input_matrix` `real(real64)`: Flattened input matrix (length: `n_gene * sum(group_c)`)

#### Output arguments:

- `output_matrix` `real(real64)`: Flattened output matrix (length: `n_gene * n_grps`)
- `ierr` `integer(int32)`: Error code (for error details please check error handling section )

Listing 44: Tissue Averages Calculation

```
call calc_tiss_avg(n_gene, n_grps, group_s, group_c, input_matrix,
    output_matrix, ierr)
```

#### (d) Log2 Transformation

The subroutine applies  $\log_2(x + 1)$  transformation to each element of the input matrix. This is computed via  $\log(x + 1) / \log(2)$  for compatibility with WebAssembly (WASM). Call the `log2_transformation` subroutine with the following arguments:

##### Input arguments:

- `n_genes` integer(int32): Number of genes (rows)
- `n_tissues` integer(int32): Number of tissues (columns)
- `input_matrix` real(real64): Flattened input matrix (size: `n_genes` \* `n_tissues`)

##### Output arguments:

- `output_matrix` real(real64): Output matrix (same size as input)
- `ierr` integer(int32): Error code (for error details please check error handling section )

Listing 45: Log2 Transformation

```
call log2_transformation(n_genes, n_tissues, input_matrix,
                        output_matrix, ierr)
```

## 6. Calculate Fold Change

If fold change calculation is needed, this subroutine can be used after normalization. The subroutine calculates  $\log_2$  fold changes between condition and control columns. For each control-condition pair, this subroutine computes the  $\log_2$  fold change by subtracting the expression value in the control column from the corresponding value in the condition column, for all genes. Call the `calc_fchange` subroutine with the following arguments:

##### Input arguments:

- `n_genes` integer(int32): Total number of genes
- `n_cols` integer(int32): Number of columns in the input matrix
- `n_pairs` integer(int32): Number of control-condition pairs
- `control_cols` integer(int32): Control column indices (length `n_pairs`)
- `cond_cols` integer(int32): Condition column indices (length `n_pairs`)
- `i_matrix` real(real64): Input matrix, flattened (length: `n_genes` × `n_cols`)

##### Output arguments:

- `o_matrix` real(real64): Output matrix for fold changes (length: `n_genes` × `n_pairs`)
- `ierr` integer(int32): Error code (for error details please check error handling section )

Listing 46: Fold Change Calculation

```
call calc_fchange(n_genes, n_cols, n_pairs, control_cols, cond_cols,
                 i_matrix, o_matrix, ierr)
```

## 7. Calculation of family Centroids

The subroutine computes the centroid (mean expression vector) for each gene family in a gene expression dataset. It iterates over all families, selects the relevant genes for each family and calculates the mean vector for each family. There are two possible modes to use. To use all genes for calculation, select `all` mode. If you want to specify relevant genes for calculation, select `orthologs` mode. It is important that you provide a logical `ortholog_set` array when using `orthologs` mode. Call the `group_centroid` subroutine with the following arguments:

### Input arguments:

- `expression_vectors` `real(real64)`: Expression vector matrix with size `n_axes` × `n_genes`
- `n_axes` `integer(int32)`: Number of axes (tissues / dimensions)
- `n_genes` `integer(int32)`: Total number of genes
- `gene_to_family` `integer(int32)`: Gene-to-family mapping array with the length of `n_genes` (1-based indexing)
- `n_families` `integer(int32)`: Total number of gene families
- `mode` `character(len=*)`: Calculation mode ("all" or "orthologs")
- (Optional) `ortholog_set` `logical`: Logical array indicating if a gene is part of the calculation subset (only used in `orthologs` mode)

### Output arguments:

- `centroid_matrix` `real(real64)`: Matrix of calculated family centroid vectors with size `n_axes` × `n_families`
- `selected_indices` `integer(int32)`: Array of gene indices used for the calculation with length of `n_genes`
- `ierr` `integer(int32)`: Error code (for error details please check error handling section)

Listing 47: Calculation of Family Centroids

```
call group_centroid(expression_vectors, n_axes, n_genes,
                    gene_to_family, n_families, centroid_matrix, mode, selected_indices,
                    ierr, ortholog_set)
```

### (a) Calculate Mean Vector

Alternatively you can calculate a single mean vector for a given set of vectors by calling the `mean_vector` subroutine directly with the following arguments:

#### Input arguments:

- `expression_vectors` `real(real64)`: Expression vector matrix with size `n_axes` × `n_genes`
- `n_axes` `integer(int32)`: Number of axes (tissues / dimensions)
- `n_genes` `integer(int32)`: Total number of genes
- `gene_indices` `integer(int32)`: An array containing the column indices of the selected genes in `expression_vectors`
- `n_selected_genes` `integer(int32)`: Total number of genes in the current family to be calculated

**Output arguments:**

- `centroid real(real64)`: Calculated mean vector (centroid) with length of `n_axes`
- `ierr integer(int32)`: Error code (for error details please check error handling section )

Listing 48: Mean Vector Calculation

```
call mean_vector(expression_vectors, n_axes, n_genes, gene_indices
, n_selected_genes, centroid, ierr)
```

**8. Calculate Distance to Centroid**

For each gene in the expression vector matrix, the subroutine computes the Euclidean distance to its corresponding family centroid and returns a distances array containing the distance value for each expression vector to its family centroid. Call the `distance_to_centroid` subroutine with the following arguments:

**Input arguments:**

- `n_genes integer(int32)`: Total number of genes
- `n_families integer(int32)`: Total number of gene families
- `genes real(real64)`: Gene expression matrix ( $d \times n\_genes$ )
- `centroids real(real64)`: Family centroid matrix ( $d \times n\_genes$ )
- `gene_to_fam integer(int32)`: Gene-to-family mapping array with the length of `n_genes` (1-based indexing)
- `d integer(int32)`: Expression vector dimension

**Output arguments:**

- `distances real(real64)`: Array of distances for each gene with length of `n_genes`

Listing 49: Distance to Centroid Calculation

```
call distance_to_centroid(n_genes, n_families, genes, centroids,
gene_to_fam, distances, d)
```

**(a) Calculate Euclidean Distance**

Alternatively you can calculate a single Euclidean distance between two vectors manually by calling `euclidean_distance` subroutine with the following arguments:

**Input arguments:**

- `vec1 real(real64)`: First expression vector as array with length of dimension `d`
- `vec2 real(real64)`: Second expression vector as array with length of dimension `d`
- `d integer(int32)`: Dimension value

**Output arguments:**

- `result real(real64)`: Euclidean distance value between `vec1` and `vec2`

Listing 50: Euclidean distance calculation

```
call euclidean_distance(vec1, vec2, d, result)
```

## 9. Detect Gene Outliers

The subroutine first computes family scaling, then calculates relative distance indices (RDI) and identifies outliers based on the specified percentile threshold. It returns a boolean array indicating whether each gene is an outlier. Call the `detect_outliers` subroutine with the following arguments:

### Input arguments:

- `n_genes` `integer(int32)`: Total number of genes
- `n_families` `integer(int32)`: Total number of gene families
- `distances` `real(real64)`: Array of distances for each gene to its centroid with length of `n_genes`
- `gene_to_fam` `integer(int32)`: Gene-to-family mapping array with the length of `n_genes` (1-based indexing)
- **(Optional)** `percentile` `real(real64)`: Percentile threshold value for outlier detection (default is 95)

### Input / Output arguments:

- `work_array` `real(real64)`: Work array for sorting with length of `n_genes`
- `perm` `integer(int32)`: Permutation array for sorting with length of `n_genes`
- `stack_left` `integer(int32)`: Stack array for left indices during sorting with length of `n_genes`
- `stack_right` `integer(int32)`: Stack array for right indices during sorting with length of `n_genes`
- `loess_x` `real(real64)`: Reference x-coordinates for loess smoothing with length of `n_families`
- `loess_y` `real(real64)`: Reference y-coordinates for loess smoothing with length of `n_families`
- `loess_n` `integer(int32)`: Indices of reference points used for smoothing with length of `n_families`

### Output arguments:

- `is_outlier` `logical`: Boolean array with length of `n_genes` indicating whether each gene is an outlier
- `ierr` `integer(int32)`: Error code (for error details please check error handling section)

Listing 51: Gene Outlier Calculation

```
call detect_outliers(n_genes, n_families, distances, gene_to_fam,  
    work_array, perm, stack_left, stack_right, is_outlier, loess_x,  
    loess_y, loess_n, ierr, percentile)
```

Alternatively you can calculate each step of `detect_outliers` manually with the following subroutine:

(a) **Compute Family Scaling**

The subroutine calculates a scaling factor for each gene family by computing the median and standard deviation of gene-to-centroid distances within each family, then applies LOESS smoothing to these values. Call the `compute_family_scaling` subroutine with the following arguments:

**Input arguments:**

- `n_genes` integer(int32): Total number of genes
- `n_families` integer(int32): Total number of gene families
- `distances` real(real64): Array of distances for each gene to its centroid with length of `n_genes`
- `gene_to_fam` integer(int32): Gene-to-family mapping array with the length of `n_genes` (1-based indexing)

**Input / Output arguments:**

- `loess_x` real(real64): Reference x-coordinates for loess smoothing with length of `n_families`
- `loess_y` real(real64): Reference y-coordinates for loess smoothing with length of `n_families`
- `indices_used` integer(int32): Indices of reference points used for smoothing with length of `n_families`
- `perm_tmp` integer(int32): Permutation array for sorting with length of `n_genes`

**Output arguments:**

- `dscale` real(real64): Array of scaling factors per family with length of `n_families`
- `family_distances` real(real64): Temporary work array with length of `n_genes` to store distances of genes within each family during calculation
- `ierr` integer(int32): Error code (for error details please check error handling section )

Listing 52: Compute Family Scaling

```
call compute_family_scaling(n_genes, n_families, distances,
    gene_to_fam, dscale, loess_x, loess_y, indices_used, perm_tmp,
    stack_left_tmp, stack_right_tmp, family_distances, ierr)
```

(b) **Compute Family Scaling Helper**

This helper subroutine allocates internal arrays for easier usage and calls `compute_family_scaling`. Call the `compute_family_scaling_alloc` subroutine with the following arguments:

**Input arguments:**

- `n_genes` integer(int32): Total number of genes
- `n_families` integer(int32): Total number of gene families
- `distances` real(real64): Array of distances for each gene to its centroid with length of `n_genes`
- `gene_to_fam` integer(int32): Gene-to-family mapping array with the length of `n_genes` (1-based indexing)

**Input / Output arguments:**



- `loess_x` `real(real64)`: Reference x-coordinates for loess smoothing with length of `n_families`
- `loess_y` `real(real64)`: Reference y-coordinates for loess smoothing with length of `n_families`
- `indices_used` `integer(int32)`: Indices of reference points used for smoothing with length of `n_families`

**Output arguments:**

- `dscale` `real(real64)`: Array of scaling factors per family with length of `n_families`
- `ierr` `integer(int32)`: Error code (for error details please check error handling section )

Listing 53: Compute Family Scaling

```
call compute_family_scaling_alloc(n_genes, n_families, distances,
    gene_to_fam, dscale, loess_x, loess_y, indices_used, ierr)
```

(c) **Compute Relative Distance Index (RDI)**

The subroutine calculates the Relative Distance Index (RDI) for each gene by dividing its Eculidean distance to the family centroid by the scaling factor of its family. Call the `compute_rdi` subroutine with the following arguments:

**Input arguments:**

- `n_genes` `integer(int32)`: Total number of genes
- `distances` `real(real64)`: Array of distances for each gene to its centroid with length of `n_genes`
- `gene_to_fam` `integer(int32)`: Gene-to-family mapping array with the length of `n_genes` (1-based indexing)
- `dscale` `real(real64)`: Array of scaling factors per family with length of `n_families`

**Input / Output arguments:**

- `sorted_rdi` `real(real64)`: Work array for sorting with length of `n_genes`
- `perm` `integer(int32)`: Pre-initialized (1: `n_genes`) permutation array for sorting with length of `n_genes`
- `stack_left` `integer(int32)`: Stack array for sorting with length of `n_genes`
- `stack_right` `integer(int32)`: Stack array for sorting with length of `n_genes`

**Output arguments:**

- `rdi` `real(real64)`: Array of RDI values for each gene with length of `n_genes`

Listing 54: Compute Relative Distance Index (RDI)

```
call compute_rdi(n_genes, distances, gene_to_fam, dscale, rdi,
    sorted_rdi, perm, stack_left, stack_right)
```

(d) **Identify Outliers**

The subroutine identifies outliers based on the top percentile of RDI values. Call the `identify_outliers` subroutine with the following arguments:

**Input arguments:**

- `n_genes` `integer(int32)`: Total number of genes

- `rdi` `real(real64)`: Array of RDI values for each gene with length of `n_genes`
- `sorted_rdi` `real(real64)`: Array of sorted RDI values for each gene with length of `n_genes` - **this array must be filtered to remove negatives and be sorted in ascending order!**
- **(Optional)** `percentile` `real(real64)`: Percentile threshold value for outlier detection (default is 95)

**Output arguments:**

- `is_outlier` `logical`: Boolean array with length of `n_genes` indicating whether each gene is an outlier
- `threshold`: Actual threshold value used for outlier detection

Listing 55: Identify Outliers

```
call identify_outliers(n_genes, rdi, sorted_rdi, is_outlier,
                      threshold, percentile)
```

## 10. Compute Normalized Tissue Versatility

The subroutine calculates a normalized tissue versatility score for selected gene expression vectors. It is based on the angle between each gene expression vector and the space diagonal. Versatility is normalized to  $[0, 1]$ , where 0 means uniform expression 1 means expression in only one axis. Call the `compute_tissue_versatility` subroutine with the following parameters:

**Input arguments:**

- `n_genes` `integer(int32)`: Total number of genes
- `n_vectors` `integer(int32)`: Total number of expression vectors
- `n_selected_axes` `integer(int32)`: Total number of selected axes
- `n_selected_vectors` `integer(int32)`: Total number of selected vectors
- `expression_vectors` `real(real64)`: Expression vector matrix with size `n_axes`  $\times$  `n_vectors`
- `exp_vecs_selection_index` `logical`: Logical array with length of `n_vectors` to specify which vectors should be included in the calculation
- `axes_selection` `logical`: Logical array with length of `n_axes` to specify which axes should be included in the calculation

**Output arguments:**

- `tissue_versilities` `real(real64)`: Array with the length of `n_selected_vectors` containing the calculated tissue versilities
- `tissue_angles_deg` `real(real64)`: Array with the length of `n_selected_vectors` containing the calculated angles in degrees
- `ierr` `integer(int32)`: Error code (for error details please check error handling section)

Listing 56: Tissue Versatility Calculation

```
call compute_tissue_versatility(n_axes, n_vectors, expression_vectors,
                               exp_vecs_selection_index, n_selected_vectors, axes_selection,
                               n_selected_axes, tissue_versilities, tissue_angles_deg, ierr)
```

## 11. Binary Search Trees for 1D Range Queries

Binary Search Trees provide efficient indexing and range query capabilities for one-dimensional data using flat array implementations for optimal memory performance.

### Fortran BST Implementation

#### (a) Build BST Index

Constructs a Binary Search Tree index by sorting the input values and storing permutation indices. Uses an efficient stack-based sorting algorithm.

##### Input:

- `values` `real(real64)`: 1D array of values to index
- `num_values` `integer(int32)`: Number of elements

##### Output:

- `sorted_indices` `integer(int32)`: Permutation indices after sorting (1-based)
- `left_stack, right_stack` `integer(int32)`: Sorting workspace
- `ierr` `integer(int32)`: Error code

```
call build_bst_index(values, num_values, sorted_indices,  
    left_stack, right_stack, ierr)
```

#### (b) Get Sorted Value

Retrieves the value at a specific position in the sorted order defined by the BST index.

##### Input:

- `values` `real(real64)`: Original values array
- `sorted_indices` `integer(int32)`: BST index array (1-based)
- `position` `integer(int32)`: Position in sorted order (1-based)

##### Output:

- `sorted_value` `real(real64)`: Value at specified position
- `ierr` `integer(int32)`: Error code

```
sorted_value = get_sorted_value(values, sorted_indices, position,  
    ierr)
```

#### (c) BST Range Query

Efficiently finds all values within a specified range using the precomputed BST index.

##### Input:

- `values` `real(real64)`: Original values array
- `sorted_indices` `integer(int32)`: BST index array (1-based)
- `num_values` `integer(int32)`: Number of elements
- `lower_bound, upper_bound` `real(real64)`: Range boundaries

##### Output:

- `output_indices` `integer(int32)`: Indices of matching values (1-based)
- `num_matches` `integer(int32)`: Number of matches found
- `ierr` `integer(int32)`: Error code

```
call bst_range_query(values, sorted_indices, num_values,
    lower_bound, upper_bound, &
    output_indices, num_matches, ierr)
```

## 12. k-d Trees for Multi-Dimensional Indexing

k-d trees provide efficient space partitioning for multi-dimensional data with support for both Euclidean and spherical geometries.

### Fortran k-d Tree Implementation

#### (a) Build k-d Tree Index

Constructs a k-d tree index using stack-based non-recursive partitioning along specified dimensions.

##### Input:

- `points` `real(real64)`: Data points matrix (dimensions  $\times$  points)
- `num_dimensions` `integer(int32)`: Number of dimensions
- `num_points` `integer(int32)`: Number of points
- `dimension_order` `integer(int32)`: Dimension ordering for splitting (1-based)

##### Output:

- `kd_indices` `integer(int32)`: Output index array (1-based)
- `workspace` `integer(int32)`: Workspace array
- `value_buffer` `real(real64)`: Value buffer for sorting
- `permutation` `integer(int32)`: Permutation array
- `left_stack`, `right_stack` `integer(int32)`: Sorting stacks
- `recursion_stack` `integer(int32)`: Recursion stack
- `ierr` `integer(int32)`: Error code

```
call build_kd_index(points, num_dimensions, num_points, kd_indices,
    dimension_order, &
    workspace, value_buffer, permutation, left_stack,
    right_stack, recursion_stack, ierr)
```

#### (b) Build Spherical k-d Tree

Specialized k-d tree construction optimized for unit vectors on hyperspheres.

##### Input:

- `vectors` `real(real64)`: Unit vectors matrix (dimensions  $\times$  vectors)
- `num_dimensions` `integer(int32)`: Number of dimensions
- `num_vectors` `integer(int32)`: Number of vectors
- `dimension_order` `integer(int32)`: Dimension ordering for splitting (1-based)

##### Output:

- `sphere_indices` `integer(int32)`: Output index array (1-based)
- Various workspace arrays (same as `build_kd_index`)
- `ierr` `integer(int32)`: Error code

```
call build_spherical_kd(vectors, num_dimensions, num_vectors,
    sphere_indices, dimension_order, &
    workspace, value_buffer, permutation,
    left_stack, right_stack, recursion_stack,
    ierr)
```

### (c) Get Point from k-d Index

Retrieves point coordinates from specified position in k-d tree ordering.

#### Input:

- `points` `real(real64)`: Original points matrix
- `kd_indices` `integer(int32)`: k-d tree index array (1-based)
- `position` `integer(int32)`: Position in index (1-based)

#### Output:

- `point_values` `real(real64)`: Retrieved point values
- `ierr` `integer(int32)`: Error code

```
call get_kd_point(points, kd_indices, position, point_values, ierr
)
```

## 13. Array Serialization and Deserialization Module

The array serialization and deserialization module provides comprehensive routines for efficiently storing and retrieving multi-dimensional arrays of various data types.

### (a) General Architecture

The module supports five data types (integer, real, character, logical and complex) across dimensions 1 through 5. All routines follow a consistent naming convention and parameter structure for ease of use.

### (b) Supported Functions

- `serialize_int_Nd(arr, filename, ierr)` - Serialize N-dimensional integer arrays.
- `deserialize_int_Nd(arr, filename, ierr)` - Deserialize N-dimensional integer arrays.
- `serialize_real_Nd(arr, filename, ierr)` - Serialize N-dimensional real arrays.
- `deserialize_real_Nd(arr, filename, ierr)` - Deserialize N-dimensional real arrays.
- `serialize_char_Nd(arr, filename, ierr)` - Serialize N-dimensional character arrays.
- `deserialize_char_Nd(arr, filename, ierr)` - Deserialize N-dimensional character arrays.
- `serialize_logical_Nd(arr, filename, ierr)` - Serialize N-dimensional logical arrays.
- `deserialize_logical_Nd(arr, filename, ierr)` - Deserialize N-dimensional logical arrays.
- `serialize_complex_Nd(arr, filename, ierr)` - Serialize N-dimensional complex arrays.

- `deserialize_complex_Nd(arr, filename, ierr)` - Deserialize N-dimensional complex arrays.
- `get_array_metadata(filename, dims, max_dims, ndims, ierr, [clen])` - Retrieve array metadata from files

Where N represents the array dimension (1-5).

#### (c) Detailed Parameter Specifications

##### Serialization Functions Parameters:

- `arr` (input): The array to be serialized.  
**Type:** Allocatable array of type `integer(int32)`, `real(real64)`, `character(len=clen)`, (logical) or `complex`  
**Dimensions:** 1D to 5D  
**Intent:** in  
**Note:** `clen` has to be the size of the arrays elements
- `filename` (input): The name of the binary file to create.  
**Type:** `character(len=*)`  
**Intent:** in
- `ierr` (output): Error code indicating operation status.  
**Type:** `integer(int32)`  
**Intent:** out  
**Values:** 0 indicates success, non-zero values indicate specific error conditions

Listing 57: Example usage of a serialize function

```
call serialize_int_2d(array, "test_file.bin", ierr)
```

#### (d) Metadata Retrieval Function Parameters:

- `filename` (input): The name of the binary file to read metadata from.  
**Type:** `character(len=*)`  
**Intent:** in
- `dims` (output): Array containing the dimensions of the stored array.  
**Type:** `integer(int32)`, `dimension(max_dims)`  
**Intent:** out **Note:** Must be preallocated, recommended with size 5
- `max_dims` (input): Size of the `dims` array (typically 5 for maximum supported dimensions).  
**Type:** `integer(int32)`  
**Intent:** in
- `ndims` (output): Number of dimensions actually used by the array.  
**Type:** `integer(int32)`  
**Intent:** out
- `ierr` (output): Error code indicating operation status.  
**Type:** `integer(int32)`  
**Intent:** out  
**Values:** 0 indicates success, non-zero values indicate specific error conditions
- `clen` (output, optional): For character arrays, the length of character elements.  
**Type:** `integer(int32)`  
**Intent:** out  
**Note:** This parameter is only used and required for character arrays

Listing 58: Usage of metadata retrieval

```
call get_array_metadata(filename, dims, max_dims, ndims, ierr,
    clen)
```

#### Deserialization Functions Parameters:

- **arr** (output): The array to be populated with deserialized data.  
**Type:** Allocatable array of type `integer(int32)`, `real(real64)`, `character(len=clen)`, `logical`, or `complex`  
**Dimensions:** 1D to 5D  
**Intent:** out  
**Note:** The array must be allocated with correct dimensions and correct element length before calling deserialization routines
- **filename** (input): The name of the binary file to read.  
**Type:** `character(len=*)`  
**Intent:** in
- **ierr** (output): Error code indicating operation status.  
**Type:** `integer(int32)`  
**Intent:** out  
**Values:** 0 indicates success, non-zero values indicate specific error conditions

Listing 59: Example usage of a deserialize function

```
call deserialize_int_2d(array, "test_file.bin", ierr)
```

Listing 60: Full example

```
integer(int32), allocatable :: kallisto_expression(:, :),
    kallisto_expression_2(:, :)
integer(int32) :: dims(5)
integer(int32) :: ndims, ierr, max_dims
character(len=64) :: fname

!Assume array is filled with data

call serialize_real_2d(kallisto_expression, "kallisto_data_v1.bin",
    , ierr)
if(.not. is_ok(ierr)) error stop ierr

!Reading the data again
call get_array_metadata("kallisto_data_v1.bin", dims, max_dims,
    ndims, ierr)
if(.not. is_ok(ierr)) error stop ierr
allocate(kallisto_expression_2(dims(1), dims(2)))

call deserialize_real_2d(kallisto_expression_2, "kallisto_data_v1.
    bin", ierr)
if(.not. is_ok(ierr)) error stop ierr
```

#### (e) Error Handling

All functions return an error code through the `ierr` parameter. The error handling utility `tox errors` provides functions to check and interpret these codes.

(f) **Implementation Notes**

- All routines are implemented in standard Fortran for interoperability
- The module uses allocatable arrays for flexible memory management
- File operations use Fortran’s native unformatted I/O for efficiency
- Error handling is consistent across all functions for predictable behavior

## 3.2 Python Pipeline

The Python workflow is exposed through the `tensoromics_functions.py` module. The functions provide a high-level interface that mirrors the Fortran pipeline.

### 1. Read Gene IDs from TSV File

The function reads gene identifiers from a tab-separated value (TSV) file, extracting specific gene IDs from a designated column while skipping header rows. This function is typically used as the first step in processing gene expression data to obtain the complete list of gene identifiers. Call the `read_gene_ids_from_tsv_file` function with the following arguments:

- `filename`: Path to the TSV file containing gene IDs (string or list with single file)
- `n_genes`: Total number of genes in the file
- `gene_ids_len`: Maximum character length for each gene ID
- `n_header_rows`: Number of header rows to skip at the beginning of the file
- `gene_col`: Column index (1-based) where gene IDs are located

**Returns:**

- `gene_ids`: Numpy array of shape (`n_genes`) containing gene ID strings

Listing 61: Python Read Gene IDs from TSV File

```
gene_ids = read_gene_ids_from_tsv_file(filename, n_genes, gene_ids_len,
                                     n_header_rows, gene_col)
```

### 2. Read Expression Vectors

The function reads gene expression data from multiple tabular files (CSV/TSV format), extracting expression values for specified genes across multiple samples. This function consolidates expression data from multiple files into a single 2D array. Call the `read_expression_vectors` function with the following arguments:

- `file_list`: List of file paths containing expression data
- `gene_ids`: Array of gene IDs to extract expression values for
- `n_samples`: Number of samples
- `n_header_rows`: Number of header rows to skip in each file
- `gene_col`: Column index (1-based) containing gene identifiers
- `value_cols`: List of column indices (1-based) containing expression values
- **(Optional)** `delimiter`: Delimiter used in the files (default: tab)



#### Returns:

- **expression\_vectors**: 2D numpy array of shape (**n\_samples**, **n\_genes**) containing expression values as 64-bit floats

Listing 62: Python Read Expression Vectors

```
expression_vectors = read_expression_vectors(file_list, gene_ids,
                                             n_samples, n_header_rows, gene_col, value_cols, delimiter='\t')
```

### 3. Read OrthoFinder File

The function processes an OrthoFinder output file to map genes to their respective orthologous families. This function establishes the gene-family relationships essential for downstream orthology-based analyses. Call the `read_orthofinder_file` function with the following arguments:

- **filename**: Path to the OrthoFinder TSV file (string or list with single file)
- **gene\_ids**: Complete list of gene identifiers to map
- **family\_ids\_len**: Maximum character length for family IDs
- **n\_families**: Total number of gene families expected

#### Return dictionary:

- **family\_ids**: Numpy array of shape (**n\_families**,) containing family ID strings
- **gene\_to\_fam**: Numpy array of shape (**n\_genes**,) containing family indices for each gene (0 = unassigned)

Listing 63: Python Read OrthoFinder File

```
family_result = read_orthofinder_file(filename, gene_ids,
                                       family_ids_len, n_families)
```

### Complete Data Loading Workflow Example:

Listing 64: Python Complete Data Loading Workflow

```
# Step 1: Load gene identifiers
gene_ids = read_gene_ids_from_tsv_file(
    filename="data/expression_data.tsv",
    n_genes=50000,
    gene_ids_len=32,
    n_header_rows=1,
    gene_col=1
)

# Step 2: Load expression data from multiple samples
samples = ["sample1.tsv", "sample2.tsv", "sample3.tsv", "sample4.tsv"]
expression_vectors = read_expression_vectors(
    file_list=samples,
    gene_ids=gene_ids,
    n_samples=12, # assuming 3 samples per file
    n_header_rows=1,
```

```

        gene_col=1,
        value_cols=[2, 3]
    )

# Step 3: Load orthology information
orthology_data = read_orthofinder_file(
    filename="data/Orthogroups.tsv",
    gene_ids=gene_ids,
    family_ids_len=32,
    n_families=15000
)

```

#### 4. Filter Unassigned Genes

The function filters out genes that are not assigned to any family (where `gene_to_fam = 0`). This is essential for cleaning data before orthology-based analyses, ensuring only genes with valid family assignments are processed. Call the `filter_unassigned_genes` function with the following arguments:

- `gene_to_fam`: Family assignment array where 0 indicates unassigned genes

**Return dictionary:**

- `mask`: Boolean array indicating which genes to keep (1 = assigned to family, 0 = unassigned)
- `n_genes_kept`: Number of genes kept after filtering

Listing 65: Python Filter Unassigned Genes

```

filtered_genes = filter_unassigned_genes(gene_to_fam)

```

#### 5. Validate Gene to Family Mapping

The function validates the gene-to-family mapping array, ensuring all family indices are within valid range and properly assigned. This prevents downstream errors from invalid family indices. Call the `validate_gene_to_family_mapping` function with the following arguments:

- `gene_to_fam`: Array mapping each gene to a family index (0 = unassigned)
- `n_families`: Total number of families

Listing 66: Python Validate Gene to Family Mapping

```

validate_gene_to_family_mapping(gene_to_fam, n_families)

```

#### 6. Validate Expression Data

The function validates expression data, checking for NaN/Inf values and optionally verifying non-negative values. This ensures data quality before computational analyses. Call the `validate_expression_data` function with the following arguments:

- `expression_vectors`: 2D array of expression data ( $n_{samples} \times n_{genes}$ ) (**Optional**) `check_non_negative`: Whether to check for non-negative values (default: True)

#### Listing 67: Python Validate Expression Data

```
validate_expression_data(expression_vectors, check_non_negative=True)
```

### 7. Validate Family Centroids

The function validates family centroids data, checking for NaN/Inf values and proper data structure. Centroids represent the central tendency of each gene family's expression profile. Call the `validate_family_centroids` function with the following arguments:

- `family_centroids`: 2D array of family centroids (samples  $\times$  families)

#### Listing 68: Python Validate Family Centroids

```
validate_family_centroids(family_centroids)
```

### 8. Validate Shift Vectors

The function validates shift vectors, ensuring data types are correct and structure matches expected patterns. Shift vectors represent the deviation of each gene from its family centroid. Call the `validate_shift_vectors` function with the following arguments:

- `shift_vectors`: 2D array of shift vectors (genes  $\times$  samples)
- `expression_vectors`: 2D array of expression data (genes  $\times$  samples)
- `family_centroids`: 2D array of family centroids (samples  $\times$  families)
- `gene_to_fam`: Array mapping each gene to a family index
- `n_genes`: Number of genes
- `n_samples`: Number of samples
- `n_families`: Number of families

#### Listing 69: Python Validate Shift Vectors

```
validate_shift_vectors(shift_vectors, expression_vectors,  
                      family_centroids, gene_to_fam, n_genes, n_samples, n_families)
```

### 9. Validate String Array Uniqueness

The function validates that all strings in an array are unique, using a hashset internally. Note: This may increase memory usage temporarily for large datasets. Call the `validate_string_array_uniqueness` function with the following arguments:

- `strings`: Array of strings to validate (typically gene IDs or family IDs)

#### Listing 70: Python Validate String Array Uniqueness

```
validate_string_array_uniqueness(strings)
```

### 10. Validate Data Structure

The function performs comprehensive validation of the overall data structure consistency, confirming sizes and dependencies between different data components as far as possible. Call the `validate_data_structure` function with the following arguments:

- `n_genes`: Number of genes
- `n_families`: Number of families
- `n_samples`: Number of samples
- `gene_ids`: Array of gene IDs
- `gene_family_ids`: Array of family IDs
- `gene_to_fam`: Array mapping each gene to a family index
- `expression_vectors`: 2D array of expression data (genes  $\times$  samples)
- `family_centroids`: 2D array of family centroids (samples  $\times$  families)
- `shift_vectors`: 2D array of shift vectors (genes  $\times$  samples)

Listing 71: Python Validate Data Structure

```
validate_data_structure(n_genes, n_families, n_samples, gene_ids,
                        gene_family_ids, gene_to_fam, expression_vectors, family_centroids,
                        shift_vectors)
```

## 11. Validate All Data

The function performs comprehensive validation of all data components in one call. This function executes all individual validations sequentially for complete data quality assurance. Call the `validate_all_data` function with the following arguments:

- `n_genes`: Number of genes
- `n_families`: Number of families
- `n_samples`: Number of samples
- `gene_ids`: Array of gene IDs
- `gene_family_ids`: Array of family IDs
- `gene_to_fam`: Array mapping each gene to a family index
- `expression_vectors`: 2D array of expression data (genes  $\times$  samples)
- `family_centroids`: 2D array of family centroids (samples  $\times$  families)
- `shift_vectors`: 2D array of shift vectors (genes  $\times$  samples)

Listing 72: Python Validate All Data

```
validate_all_data(n_genes, n_families, n_samples, gene_ids,
                  gene_family_ids, gene_to_fam, expression_vectors, family_centroids,
                  shift_vectors)
```

## Data Filtering and Validation Workflow Example:

Listing 73: Python Data Filtering and Validation Workflow

```
# After loading data, filter unassigned genes
filter_result = filter_unassigned_genes(gene_to_fam)
mask = np.array(filter_result['mask'], dtype=bool)
n_genes_kept = filter_result['n_genes_kept']
```

```

print(f"Filtered from {len(gene_to_fam)} to {n_genes_kept} genes")

# Apply filter to all gene-based arrays
filtered_gene_ids = gene_ids[mask]
filtered_expression = expression_vectors[:, mask]
filtered_gene_to_fam = gene_to_fam[mask]

# Run comprehensive validations
validate_string_array_uniqueness(filtered_gene_ids)
validate_string_array_uniqueness(family_ids)
validate_expression_data(filtered_expression, check_non_negative=True)
validate_gene_to_family_mapping(filtered_gene_to_fam, n_families)

# For complete analysis with centroids and shift vectors
validate_data_structure(
    n_genes_kept, n_families, n_samples,
    filtered_gene_ids, family_ids, filtered_gene_to_fam,
    filtered_expression, family_centroids, shift_vectors
)

# Or use the comprehensive validation
validate_all_data(
    n_genes_kept, n_families, n_samples,
    filtered_gene_ids, family_ids, filtered_gene_to_fam,
    filtered_expression, family_centroids, shift_vectors
)

print("All data validations passed successfully")

```

## 12. Create Zip Archive (Low-Level)

The low-level function creates a zip archive from keys and filenames, directly calling the Fortran backend. Use this function for custom data serialization scenarios or when you need fine-grained control over archive creation. Call the `create_zip_archive` function with the following arguments:

- `zip_filename`: Name of the zip file to create
- `keys`: List of keys for the manifest (identifiers for each file)
- `filenames`: List of filenames to include in archive

Listing 74: Python Create Zip Archive (Low-Level)

```
create_zip_archive(zip_filename, keys, filenames)
```

## 13. Extract Zip Archive

The function extracts a zip archive created by `create_zip_archive` and returns a dictionary mapping data keys to extracted filenames. This is useful for accessing individual files from custom archives. Call the `extract_zip_archive` function with the following arguments:

- `zip_filename`: Path to the zip file to extract

**Returns:**

- Dictionary mapping data keys to extracted temporary filenames

Listing 75: Python Extract Zip Archive

```
extract_zip_archive(zip_filename)
```

#### 14. Save TOX Data (High-Level)

The high-level function saves TOX data to a zip archive, handling validation, serialization, and archive creation for standard-conform tox gene data. This function automatically manages temporary files and cleanup. Call the `save_tox_data` function with the following arguments:

- `zip_filename`: Name of the zip file to create
- **(Optional)** `gene_ids`: Array of gene IDs
- **(Optional)** `expression_vectors`: 2D array of expression data
- **(Optional)** `gene_to_fam`: Array mapping genes to families
- **(Optional)** `family_ids`: Array of family IDs
- **(Optional)** `family_centroids`: 2D array of family centroids
- **(Optional)** `shift_vectors`: 2D array of shift vectors
- Corresponding `*_name` parameters for temporary filenames (e.g., `gene_ids_name`, `expression_vectors_name`, etc.)

Listing 76: Python Save TOX Data

```
save_tox_data(zip_filename, gene_ids=None, expression_vectors=None,
              gene_to_fam=None, family_ids=None, family_centroids=None,
              shift_vectors=None, gene_ids_name=None, expression_vectors_name=
              None, gene_to_fam_name=None, family_ids_name=None,
              family_centroids_name=None, shift_vectors_name=None)
```

#### 15. Read TOX Data

The function reads data from a zip archive created by `save_tox_data`, extracting and deserializing the requested data components for standard-conform tox gene data. This function automatically handles file extraction and cleanup. Call the `read_tox_data` function with the following arguments:

- `zip_filename`: Name of the zip file to read
- **(Optional)** `load_gene_ids`: Whether to load gene IDs (default: False)
- **(Optional)** `load_expression_vectors`: Whether to load expression vectors (default: False)
- **(Optional)** `load_gene_to_fam`: Whether to load gene-to-family mapping (default: False)
- **(Optional)** `load_family_ids`: Whether to load family IDs (default: False)
- **(Optional)** `load_family_centroids`: Whether to load family centroids (default: False)
- **(Optional)** `load_shift_vectors`: Whether to load shift vectors (default: False)

**Return dictionary:**

- **gene\_ids**: Loaded gene IDs array (if requested)
- **expression\_vectors**: Loaded expression vectors array (if requested)
- **gene\_to\_fam**: Loaded gene-to-family mapping array (if requested)
- **family\_ids**: Loaded family IDs array (if requested)
- **family\_centroids**: Loaded family centroids array (if requested)
- **shift\_vectors**: Loaded shift vectors array (if requested)

Listing 77: Python Read TOX Data

```
read_tox_data(zip_filename, load_gene_ids=False,
              load_expression_vectors=False, load_gene_to_fam=False,
              load_family_ids=False, load_family_centroids=False,
              load_shift_vectors=False)
```

## Data Archiving Workflow Examples:

Listing 78: Python Standard TOX Data Archiving

```
# Save complete TOX dataset
save_tox_data(
    zip_filename="complete_tox_dataset.zip",
    gene_ids=filtered_gene_ids,
    gene_ids_name="gene_ids.bin",
    expression_vectors=filtered_expression,
    expression_vectors_name="expression.bin",
    gene_to_fam=filtered_gene_to_fam,
    gene_to_fam_name="gene_to_fam.bin",
    family_ids=family_ids,
    family_ids_name="family_ids.bin",
    family_centroids=family_centroids,
    family_centroids_name="centroids.bin",
    shift_vectors=shift_vectors,
    shift_vectors_name="shift_vectors.bin"
)

# Save partial dataset
save_tox_data(
    zip_filename="basic_data.zip",
    gene_ids=filtered_gene_ids,
    gene_ids_name="gene_ids.bin",
    expression_vectors=filtered_expression,
    expression_vectors_name="expression.bin"
)

# Read data back with selective loading
loaded_data = read_tox_data(
    zip_filename="complete_tox_dataset.zip",
    load_gene_ids=True,
    load_expression_vectors=True,
    load_gene_to_fam=True
)

# Access loaded data
```

```
print(f"Loaded {len(loaded_data['gene_ids'])} genes")
print(f"Expression matrix: {loaded_data['expression_vectors'].shape}")
```

Listing 79: Python Custom Archive Creation and Extraction

```
# Create custom archive with non-standard data
create_zip_archive(
    zip_filename="custom_data.zip",
    keys=["3d_tensor", "metadata", "results"],
    filenames=["tensor_data.bin", "meta.txt", "analysis_results.bin"]
)

# Extract and access custom archive
file_mapping = extract_zip_archive("custom_data.zip")
print("Files in archive:", file_mapping)
# Output: {'3d_tensor': 'tensor_data.bin', 'metadata': 'meta.txt', '
        results': 'analysis_results.bin'}

# Access specific files
if 'metadata' in file_mapping:
    with open(file_mapping['metadata'], 'r') as f:
        metadata = f.read()
        print("Metadata:", metadata)
```

Listing 80: Python Mixed Standard and Custom Data Archiving

```
# Serialize custom arrays
tox_serialize_real_nd(custom_array, "custom_data.bin")
tox_serialize_int_nd(another_array, "another_data.bin")

# Create mixed archive with both standard and custom data
create_zip_archive(
    zip_filename="mixed_archive.zip",
    keys=["standard_expression", "custom_feature", "analysis_results"
    ],
    filenames=["expression.bin", "custom_data.bin", "another_data.bin"
    ]
)

# Later, extract and process
mapping = extract_zip_archive("mixed_archive.zip")
expression_data = tox_deserialize_real_nd(mapping["standard_expression
"])
custom_features = tox_deserialize_real_nd(mapping["custom_feature"])
results = tox_deserialize_int_nd(mapping["analysis_results"])
```

16. **Read CSV to Strings:** Call the `read_csv_as_strings` function. It takes the file path and returns the header and a 2D NumPy array of strings.
17. **Extract Typed Columns:** Pass the string NumPy array to the desired conversion functions, such as `read_integer_columns` or `read_real_columns`, along with a list of 1-based column indices to extract. All returned NumPy arrays are read-only for data safety.



Listing 81: Python Data Loading Workflow

```
import numpy as np
from tensoromics_functions import (
    read_csv_as_strings,
    read_integer_columns,
    read_real_columns
)

# Define the path to the data file
filename = 'my_data.csv'

try:
    # 1. Read the entire CSV into a NumPy array of strings
    header, data_str = read_csv_as_strings(filename)

    print("CSV data read successfully as strings:")
    print(data_str)

    # 2. Extract specific columns into new, typed NumPy arrays
    #     Column 1: Integer IDs
    #     Column 3: Real scores

    integer_data = read_integer_columns(data_str, columns=[1])
    real_data = read_real_columns(data_str, columns=[3])

    print("\nInteger data (column 1):")
    print(integer_data)

    print("\nReal data (column 3):")
    print(real_data)

    # The typed arrays are now ready for analysis (e.g., with SciPy,
    # pandas)

except (FileNotFoundError, ValueError) as e:
    print(f"An error occurred: {e}")
```

## 18. TODO Functions relating section 1.2

## 19. Normalization of Expression Values

The function runs a complete normalization pipeline on gene expression data. It first applies standard deviation normalization, then quantile normalization, followed by replicate averaging, and finally a log2 transformation. The result is returned in an array, which contains the fully normalized expression values. Call the `tox_normalization_pipeline` function with the following arguments:

- `input_matrix`: Numeric expression vector matrix with size `genes × tissues`
- `group_starts`: Integer array, start column index for each replicate group (1-based)
- `group_counts`: Integer array, number of columns per replicate group

**Return:**

- Numpy array with  $\log_2(x+1)$  normalized expression with size (genes  $\times$  groups)

Listing 82: Python Normalization Pipeline

```
tox_normalization_pipeline(input_matrix, group_starts, group_counts)
```

**Alternatively you can calculate each step of the normalization pipeline manually by calling the following functions in sequence:**

(a) **Normalize by Standard Deviation**

The function normalizes each gene's expression vector using `sqrt(mean(x2))` across tissues (not classical standard deviation). Call the `tox_normalize_by_std_dev` function with the following arguments:

- `input_matrix`: A numeric matrix with genes as rows and tissues as columns

**Returns:**

- Numpy array: Contains a normalized matrix with same dimensions as input

Listing 83: Python Standard Deviation Normalization

```
tox_normalize_by_std_dev(input_matrix)
```

(b) **Quantile Normalization**

The function performs quantile normalization of a gene expression matrix (F42-compliant) and computes average expression per rank across tissues. Call the `tox_quantile_normalization` function with the following arguments:

- `input_matrix`: A numeric matrix with genes as rows and tissues as columns

**Returns:**

- Numpy array: Quantile-normalized matrix with same dimensions as input

Listing 84: Python Quantile Normalization

```
tox_quantile_normalization(input_matrix)
```

(c) **Calculate Tissue Averages**

The function calculates tissue averages by averaging replicates within each group. For each group of tissue replicates, it computes the average expression per gene. The input matrix is column-major, flattened as a 1D array. Call the `tox_calculate_tissue_averages` function with the following arguments:

- `input_matrix`: A numeric matrix with genes as rows and tissue replicates as columns
- `group_starts`: Array of starting column indices for each group (1-based for Fortran)
- `group_counts`: Array of counts for each group

**Returns:**

- Numpy array: Matrix with genes as rows and averaged tissues as columns

Listing 85: Python Tissue Averages Calculation

```
tox_calculate_tissue_averages(input_matrix, group_starts,
                               group_counts)
```

#### (d) **Log2 Transformation**

The function applies  $\log_2(x + 1)$  transformation to each element of the input matrix. This is computed via  $\log(x + 1) / \log(2)$  for compatibility with WebAssembly (WASM). Call the `tox_log2_transformation` function with the following arguments:

- `input_matrix`: A numeric matrix with genes as rows and tissues as columns

#### **Returns:**

- Numpy array: Log2-transformed matrix with same dimensions as input

Listing 86: Python Log2 Transformation

```
tox_log2_transformation(input_matrix)
```

### 20. **Calculate Fold Change**

If fold change calculation is needed, this function can be used after normalization. The function calculates  $\log_2$  fold changes between condition and control columns. For each control-condition pair, this function computes the  $\log_2$  fold change by subtracting the expression value in the control column from the corresponding value in the condition column, for all genes. Call the `tox_calculate_fold_changes` function with the following arguments:

- `input_matrix`: A numeric matrix with genes as rows and tissues/conditions as columns
- `control_cols`: Array of control column indices (1-based for Fortran)
- `condition_cols`: Array of condition column indices (1-based for Fortran)

#### **Returns:**

- Numpy array: Matrix with genes as rows and fold change values as columns

Listing 87: Python Fold Change Calculation

```
tox_calculate_fold_changes(input_matrix, control_cols, condition_cols)
```

### 21. **Calculation of family Centroids**

The function computes the centroid (mean expression vector) for each gene family in a gene expression dataset. It iterates over all families, selects the relevant genes for each family and calculates the mean vector for each family. There are two possible modes to use. To use all genes for calculation, select `all` mode. If you want to specify relevant genes for calculation, select `orthologs` mode. It is important that you provide a logical `ortholog_set` array when using `orthologs` mode. Call the `tox_group_centroid` function with the following arguments:

- `expression_vectors`: Expression vector matrix with size `n_axes × n_genes`
- `gene_to_family`: Gene-to-family mapping array with the length of `n_genes` (1-based indexing)
- `n_families`: Total number of gene families
- `mode`: Calculation mode ("all" or "orthologs")
- (Optional) `ortholog_set`: Logical array indicating if a gene is part of the calculation subset (only used in `orthologs` mode)

**Return:**

- **centroids\_out**: Matrix of calculated family centroid vectors with size **n\_axes** × **n\_families** (read-only)

Listing 88: Python Calculation of Family Centroids

```
tox_group_centroid(expression_vectors, gene_to_family, n_families,
                    mode, ortholog_set)
```

**(a) Calculate Mean Vector**

Alternatively you can calculate a single mean vector for a given set of vectors by calling the **mean\_vector** function directly with the following arguments:

- **expression\_vectors** **real(real64)**: Expression vector matrix with size **n\_axes** × **n\_genes**
- **gene\_indices** **integer(int32)**: An array containing the column indices of the selected genes in **expression\_vectors**

**Return:**

- **centroid**: Calculated mean vector (centroid) with length of **n\_axes** (read-only)

Listing 89: Python Mean Vector Calculation

```
tox_mean_vector(expression_vectors, gene_indices)
```

**22. Calculate Distance to Centroid**

For each gene in the gene expression matrix, the function computes the Euclidean distance to its corresponding family centroid and returns a read-only distances array containing the distance value for each expression vector to its family centroid. Call the **tox\_distance\_to\_centroid** function with the following arguments:

- **genes**: Gene expression matrix array with size of (**n\_genes** × **d**)
- **centroids**: Family centroid matrix array with size of (**n\_families** × **d**)
- **gene\_to\_fam**: Gene-to-family mapping array with the length of **n\_genes** (0 = no family, >0 = family index)
- **d**: Gene expression matrix dimension as number

Listing 90: Python Distance to Centroid Calculation

```
tox_distance_to_centroid(genes, centroids, gene_to_fam, d)
```

**(a) Calculate Euclidean Distance**

Alternatively you can calculate a single Euclidean distance between two vectors manually by calling **tox\_euclidean\_distance** function with the following arguments:

- **vec1**: First vector as array
- **vec2**: Second vector as array

**Both vectors must have same length!**

Listing 91: Python Euclidean distance calculation

```
tox_euclidean_distance(vec1, vec2)
```

## 23. Detect Gene Outliers

The function first computes family scaling, then calculates relative distance indices (RDI) and identifies outliers based on the specified percentile threshold. It returns a read-only dictionary containing the outlier boolean values and intermediate results. Call the `tox_detect_outliers` function with the following arguments:

- **distances:** Array of distances for each gene to its centroid
- **gene\_to\_fam:** Gene-to-family mapping array with the same length as the distances array (0 = no family, >0 = family index)
- **(Optional) percentile:** Percentile threshold value for outlier detection (default is 95)

### Return dictionary:

- **outliers:** Boolean array indicating whether each gene is an outlier
- **loess\_x:** Array of x coordinates used as reference points for LOESS smoothing (median distance)
- **loess\_y:** Array of y coordinates used as reference points for LOESS smoothing (standard deviation)
- **loess\_n:** Array with numbers of genes in each family used to compute the corresponding median and standard deviation

Listing 92: Python Gene Outlier Calculation

```
tox_detect_outliers(distances, gene_to_fam, percentile=95.0)
```

Alternatively you can calculate each step of `tox_detect_outliers` manually with the following functions:

### (a) Compute Family Scaling

The function calculates a scaling factor for each gene family by computing the median and standard deviation of gene-to-centroid distances within each family, then applies LOESS smoothing to these values. Call the `tox_compute_family_scaling` function with the following arguments:

- **distances:** Array of distances for each gene to its centroid
- **gene\_to\_fam:** Gene-to-family mapping array with the same length as the distances array (0 = no family, >0 = family index)

### Return dictionary:

- **dscale:** Array of scaling factors per family
- **loess\_x:** Array of x coordinates used as reference points for LOESS smoothing (median distance)
- **loess\_y:** Array of y coordinates used as reference points for LOESS smoothing (standard deviation)
- **indices\_used:** Array of indices of families that have been included in the calculation

Listing 93: Python Compute Family Scaling

```
tox_compute_family_scaling(distances, gene_to_fam)
```

(b) **Compute Family Scaling (Expert Version)**

This function is the expert version of `tox_detect_outliers` and requires pre-allocated work arrays for maximum performance and control. It can be used when you need fine-grained control over memory allocation or you are calling this function many times in a tight loop. Call the `tox_compute_family_scaling_expert` function with the following arguments:

- **distances**: Array of distances for each gene to its centroid
- **gene\_to\_fam**: Gene-to-family mapping array with the same length as the distances array (0 = no family, >0 = family index)
- **perm\_tmp**: Permutation array for sorting with the same length as the distances array
- **stack\_left\_tmp**: Stack array for sorting with the same length as the distances array
- **stack\_right\_tmp**: Stack array for sorting with the same length as the distances array
- **family\_distances**: Work array for sorting with the same length as the distances array

**Return dictionary:**

- **dscale**: Array of scaling factors per family
- **loess\_x**: Array of x coordinates used as reference points for LOESS smoothing (median distance)
- **loess\_y**: Array of y coordinates used as reference points for LOESS smoothing (standard deviation)
- **indices\_used**: Array of indices of families that have been included in the calculation
- **perm\_tmp**: Permutation array for sorting
- **stack\_left\_tmp**: Stack array for sorting
- **stack\_right\_tmp**: Stack array for sorting
- **family\_distances**: Work array for sorting

Listing 94: Python Compute Family Scaling (Expert Version)

```
tox_compute_family_scaling_expert(distances, gene_to_fam, perm_tmp,
                                  stack_left_tmp, stack_right_tmp, family_distances)
```

(c) **Compute Relative Distance Index (RDI)**

The function calculates the Relative Distance Index (RDI) for each gene by dividing its Euclidean distance to the family centroid by the scaling factor of its family. The function returns a numpy array with RDI values for each gene. Call the `tox_compute_rdi` function with the following arguments:

- **distances**: Array of distances for each gene to its centroid
- **gene\_to\_fam**: Gene-to-family mapping array with the same length as the distances array (0 = no family, >0 = family index)
- **dscale**: Array of scaling factors per family

Listing 95: Python Compute Relative Distance Index (RDI)

```
tox_compute_rdi(distances, gene_to_fam, dscale)
```

(d) **Identify Outliers**

The function identifies outliers based on the top percentile of RDI values. Call the `tox_identify_outliers` function with the following arguments:

- `rdi`: Array of RDI values for each gene
- **(Optional) threshold**: Fixed RDI threshold number (if None, percentile value is used)
- **(Optional) percentile**: Percentile threshold number for outlier detection (default is 95)

**Return dictionary:**

- `outliers`: Boolean array indicating whether each gene is an outlier
- `threshold`: Actual threshold value used for outlier detection

Listing 96: Python Identify Outliers

```
tox_identify_outliers(rdi, threshold=None, percentile=95.0)
```

24. **Compute Normalized Tissue Versatility:**

The function calculates a normalized tissue versatility score for selected gene expression vectors. It is based on the angle between each gene expression vector and the space diagonal. Versatility is normalized to  $[0, 1]$ , where 0 means uniform expression 1 means expression in only one axis. Call the `tox_compute_tissue_versatility` function with the following parameters:

- `expression_vectors`: Expression vector matrix array with size `n_axes × n_vectors`
- `vector_selection`: Logical array with length of `n_vectors` to specify which vectors should be included in the calculation
- `axes_selection`: Logical array with length of `n_axes` to specify which axes should be included in the calculation

**Return dictionary:**

- `tissue_versilities`: Array containing the calculated tissue versilities for selected vectors
- `tissue_angles_deg`: Array containing the calculated angles in degrees for selected vectors
- `n_selected_vectors`: Number of vectors processed
- `n_selected_axes`: Number of axes used in calculation

Listing 97: Python Tissue Versatility Calculation

```
tox_calculate_tissue_versatility(expression_vectors, vector_selection,
                                axis_selection)
```

## 25. Python BST Interface

### (a) Build BST Index

Python wrapper for building BST index from NumPy arrays. Note that indices are 1-based and need to be converted for correct usage in python.

**Input:**

- `values` `numpy.ndarray`: 1D array of float64 values

**Output:**

- `np.array`: Permutation indices (1-based Fortran indices)

```
# - 1 at the end converts from fortrons 1-based indexing to  
#     pythons 0-based  
indices = build_bst_index(values) - 1
```

### (b) BST Range Query

Performs range queries on BST index. Accepts and returns Fortran 1-based indices.

**Input:**

- `values` `numpy.ndarray`: Original values array
- `indices` `numpy.ndarray`: BST index array from `build_bst_index` (1-based)
- `lower_bound` `float`: Lower bound of range (inclusive)
- `upper_bound` `float`: Upper bound of range (inclusive)

**Output:**

- Dictionary: (`matching_indices`, `count`) where indices are 1-based

```
# + 1 is added because of 0-based indexing. If the indices are  
#     already 1 based, this is not necessary  
res = bst_range_query(values, indices + 1, lower_bound,  
                      upper_bound)
```

### (c) Get Sorted Value

**Note:** This function is not implemented as a separate Python function. Use direct array indexing instead:

```
value = values[indices[position]] # position is 1-based
```

## 26. Python k-d Tree Interface

### (a) Build k-d Tree Index

Python interface for constructing k-d trees. Requires Fortran-ordered arrays and returns 1-based indices.

**Input:**

- `points` `numpy.ndarray`: 2D array of points (`dimensions × n.points`) in Fortran order
- `dimension_order` `numpy.ndarray`: Dimension ordering (1-based Fortran indices, optional)

**Output:**



- `np.array`: Permutation indices (1-based Python indices)

```
kd_indices = build_kd_index(points, dimension_order)
```

(b) **Build Spherical k-d Tree**

Alias for `build_kd_index` with the same parameters and behavior.

**Input:** Same as `build_kd_index` **Output:** Same as `build_kd_index`

```
sphere_indices = build_spherical_kd(vectors, dimension_order)
```

(c) **Get Point from k-d Index**

**Note:** This function is not implemented as a separate Python function. Use direct array indexing instead:

```
point = points[:, kd_indices[position - 1]] # position is 1-based
```

## 27. Python Interface for Array Serialization and Deserialization

The Python interface provides bindings to the Fortran serialization and deserialization routines, enabling efficient handling of multi-dimensional arrays. This interface supports NumPy arrays with native data type compatibility and Fortran-style column-major memory layout.

(a) **General Architecture**

The Python module `tensoromics_functions` provides ten main functions for array handling:

- `tox_serialize_int_nd(array, filename)` - Serialize N-dimensional integer arrays.
- `tox_deserialize_int_nd(filename)` - Deserialize N-dimensional integer arrays.
- `tox_serialize_real_nd(array, filename)` - Serialize N-dimensional real arrays.
- `tox_deserialize_real_nd(filename)` - Deserialize N-dimensional real arrays.
- `tox_serialize_char_nd(array, filename)` - Serialize N-dimensional character arrays.
- `tox_deserialize_char_nd(filename)` - Deserialize N-dimensional character arrays.
- `tox_serialize_logical_nd(array, filename)` - Serialize N-dimensional logical arrays.
- `tox_deserialize_logical_nd(filename)` - Deserialize N-dimensional logical arrays.
- `tox_serialize_complex_nd(array, filename)` - Serialize N-dimensional complex arrays.
- `tox_deserialize_complex_nd(filename)` - Deserialize N-dimensional complex arrays.
- `get_array_metadata(filename)` - Retrieve array dimensions and metadata

(b) **Array Functions**

**Serialization Functions:**

- **array (input):** NumPy array to be serialized  
**Type:** `numpy.ndarray` with dtype:
  - `np.int32` for integer
  - `np.float64` for float values

- U5 for characters
- `boolean` for logical
- `np.complex128` for complex numbers

**Layout:** Column-major (Fortran) order (`order='F'`)

**Dimensions:** Since the array is being passed flat, theoretically all dimensions are supported, but practical use cases are typically 1D to 5D

- **filename** (input): Name of the binary file to create

**Type:** `str`

Listing 98: Example usage of serialization function

```
tox_serialize_int_nd(int_array, filename)
tox_serialize_real_nd(real_array, filename)
```

#### Deserialization Functions:

- **filename** (input): Name of the binary file to read

**Type:** `str`

- **Return Value:** Deserialized NumPy array

**Type:** `numpy.ndarray` with original dtype and dimensions

**Layout:** Column-major (Fortran) order

Listing 99: Example usage of deserialization function

```
restored_int = tox_deserialize_int_nd(filename)
restored_real = tox_deserialize_real_nd(filename)
```

#### (c) Implementation Details

- The Python interface uses Fortran-style column-major array ordering for optimal compatibility
- All arrays are converted to the appropriate Fortran data types before serialization
- The interface automatically handles metadata including dimensions and data types
- Error handling is implemented through Python exceptions

#### (d) Usage Example

Listing 100: Full example of serialization and deserialization

```
# Real array example
real_array = np.array([1.5, 2.3, 3.2, 4.0, 5.0], dtype=np.float64,
                      order='F')
tox_serialize_real_nd(real_array, "test_real_1d.bin")
restored_real = tox_deserialize_real_nd("test_real_1d.bin")

# Character array example with metadata
char_array = np.asfortranarray(["hello", "world"], dtype='U5')
tox_serialize_char_nd(char_array, "test_char_1d.bin")

restored_char = tox_deserialize_char_nd("test_char_1d.bin")

# Multi-dimensional examples
int_2d = np.array([[1, 2, 3], [4, 5, 6]], dtype=np.int32, order='F')
')
```

```
tox_serialize_int_nd(int_2d, "test_int_2d.bin")

restored_2d = tox_deserialize_int_nd("test_int_2d.bin")
```

#### (e) Compatibility Notes

- Requires NumPy installation
- Arrays must use Fortran-style column-major ordering
- Character arrays must use fixed-length string data types
- The interface supports N dimensions, but practical use cases are typically 1D to 5D
- Data types are restricted to int32, float64, and U5 for characters

### 3.3 R Pipeline

The R pipeline first reads the file into a raw, memory-efficient format (an integer array of ASCII codes) and then performs conversions from that raw format.

1. **Read CSV to Raw ASCII:** Call `tox.read_csv_raw`. This function reads the file and returns a list containing the data as a 3D integer array of ASCII codes. This intermediate format is efficient for passing between functions.
2. **Extract Typed Columns:** Pass the raw data array (`$data`) from the previous step to conversion functions like `tox.read_integer_columns` to get typed matrices.
3. **(Optional) Convert to Strings:** For inspection, you can convert the raw ASCII data to a human-readable character matrix using `tox.convert_ascii_to_strings`.

Listing 101: R Data Loading Workflow

```
# Load the TOX API functions
source("R/tensoromics_functions.R")

filename <- "my_data.csv"

# 1. Read the CSV file into a raw ASCII integer array format
raw_data_list <- tox.read_csv_raw(filename)

# For user inspection, convert the raw data to a character matrix
string_matrix <- tox.convert_ascii_to_strings(raw_data_list$data)
cat("Data as character matrix:\n")
print(string_matrix)

# 2. Use the raw_data_list$data to extract typed columns
#   Column 1: Integer IDs
#   Column 3: Real scores
integer_matrix <- tox.read_integer_columns(raw_data_list$data, columns
    = 1)
real_matrix <- tox.read_real_columns(raw_data_list$data, columns = 3)

cat("\nExtracted integer data (column 1):\n")
print(integer_matrix)

cat("\nExtracted real data (column 3):\n")
print(real_matrix)
```

#### 4. TODO Functions relating section 1.2

#### 5. Normalization of Expression Values

The function runs a complete normalization pipeline on gene expression data. It first applies standard deviation normalization, then quantile normalization, followed by replicate averaging, and finally a log2 transformation. The result is returned in an array, which contains the fully normalized expression values. Call the `tox_normalization_pipeline` function with the following arguments:

- `input_matrix`: Numeric expression vector matrix with size `genes × tissues`
- `group_s`: Integer vector: start column index for each replicate group (1-based)
- `group_c`: Integer vector: number of columns per replicate group

##### Return:

- Numeric matrix:  $\log_2(x+1)$  normalized expression

Listing 102: R Normalization Pipeline

```
tox_normalization_pipeline(input_matrix, group_s, group_c)
```

**Alternatively you can calculate each step of the normalization pipeline manually by calling the following functions in sequence:**

##### (a) Normalize by Standard Deviation

The function normalizes each gene's expression vector using `sqrt(mean(x^2))` across tissues (not classical standard deviation). Call the `tox_normalize_by_std_dev` function with the following arguments:

- `input_matrix`: A numeric matrix with genes as rows and tissues as columns

##### Returns:

- A normalized numeric matrix with the same dimensions and names as the input

Listing 103: R Standard Deviation Normalization

```
tox_normalize_by_std_dev(input_matrix)
```

##### (b) Quantile Normalization

The function performs quantile normalization of a gene expression matrix (F42-compliant) and computes average expression per rank across tissues. Call the `tox_quantile_normalization` function with the following arguments:

- `input_matrix`: A numeric matrix with genes as rows and tissues as columns

##### Returns:

- A quantile-normalized numeric matrix with the same dimensions and names as the input

Listing 104: R Quantile Normalization

```
tox_quantile_normalization(input_matrix)
```

(c) **Calculate Tissue Averages**

The function calculates tissue averages by averaging replicates within each group. For each group of tissue replicates, it computes the average expression per gene. The input matrix is column-major, flattened as a 1D array. Call the `tox_calculate_tissue_averages` function with the following arguments:

- `df`: A data frame or matrix with genes as rows and tissue replicates as columns

**Returns:**

- A data frame with genes as rows and averaged tissues as columns

Listing 105: R Tissue Averages Calculation

```
tox_calculate_tissue_averages(df)
```

(d) **Log2 Transformation**

The function applies  $\log_2(x + 1)$  transformation to each element of the input matrix. This is computed via  $\log(x + 1) / \log(2)$  for compatibility with WebAssembly (WASM). Call the `tox_log2_transformation` function with the following arguments:

- `input_matrix`: A numeric matrix with genes as rows and tissues as columns

**Returns:**

- A numeric matrix with log2-transformed expression values, preserving the same dimensions and names as the input.

Listing 106: R Log2 Transformation

```
tox_log2_transformation(input_matrix)
```

**Additionally there are two helper functions to improve the data quality and prevent calculation errors:**

(a) **Diagnose Data Quality**

The function checks your gene expression matrix for common data quality issues, such as missing values (NA), infinite values, NaNs, zeros, and negative values. It provides a summary of these problems, lists affected genes, and reports basic statistics like minimum, maximum, and mean values. Use this function to quickly assess the quality of your data before running normalization or analysis steps. Call the `tox_diagnose_data_quality` function with the following arguments:

- `input_matrix`: A numeric matrix with genes as rows and tissues as columns
- (Optional) `show_details`: Logical indicating whether to show detailed information (default is TRUE)

**Returns:**

- A list with diagnostic information about the data quality

Listing 107: R Diagnose Data Quality

```
tox_diagnose_data_quality(input_matrix, show_details)
```

## (b) Clean Data for Normalization

The function prepares your gene expression matrix for normalization by handling problematic values. It can remove or impute NA, NaN, and Inf values, filter out genes with all zero values, and optionally convert very small values to zero. You can choose different strategies for dealing with missing data, ensuring your matrix is clean and ready for downstream analysis. Call the `tox_clean_data_for_normalization` function with the following arguments:

- `df_matrix`: A numeric matrix with genes as rows and tissues as columns
- (Optional) `remove_all_zero_genes`: Logical, whether to remove genes that are all zeros (default = TRUE)
- (Optional) `na_strategy`: Strategy for handling NA values: "remove\_genes", "remove\_samples", "impute\_zero", "impute\_mean" (default = "remove\_genes")
- (Optional) `min_expression_threshold`: Minimum expression value to consider (values below this become 0 and default is 0)
- (Optional) `convert_small_to_zero`: Logical, whether very small numbers should be converted to zero (default = FALSE)

### Returns:

- A cleaned matrix ready for normalization

Listing 108: R Clean Data for Normalization

```
tox_clean_data_for_normalization(df_matrix, remove_all_zero_genes,
                                na_strategy, min_expression_threshold, convert_small_to_zero)
```

## 6. Calculate Fold Change

If fold change calculation is needed, this function can be used after normalization. The function calculates  $\log_2$  fold changes between condition and control columns. For each control-condition pair, this function computes the  $\log_2$  fold change by subtracting the expression value in the control column from the corresponding value in the condition column, for all genes. Call the `tox_calculate_fold_changes` function with the following arguments:

- `df`: A data frame with genes as rows and tissues/conditions as columns
- `control_pattern`: A string pattern to detect control columns
- `condition_patterns`: A character vector with patterns to detect condition columns

### Returns:

- A data frame with genes as rows and  $\log_2$  fold change values as columns

Listing 109: R Fold Change Calculation

```
tox_calculate_fc_by_patterns(df, control_pattern, condition_patterns)
```

## 7. Calculation of family Centroids

The function computes the centroid (mean expression vector) for each gene family in a gene expression dataset. It iterates over all families, selects the relevant genes for each family and calculates the mean vector for each family. There are two possible modes to use. To use all

genes for calculation, select `all` mode. If you want to specify relevant genes for calculation, select `orthologs` mode. It is important that you provide a logical `ortholog_set` array when using `orthologs` mode. Call the `tox_group_centroid` function with the following arguments:

- `expression_vectors`: Expression vector matrix with size `n_axes × n_genes`
- `gene_to_family`: Gene-to-family mapping array with the length of `n_genes` (1-based indexing)
- `n_families`: Total number of gene families
- `mode`: Calculation mode ("all" or "orthologs")
- (Optional) `ortholog_set`: Logical array indicating if a gene is part of the calculation subset (only used in `orthologs` mode)

**Return:**

- `centroid_matrix`: Matrix of calculated family centroid vectors with size `n_axes × n_families`

Listing 110: R Calculation of Family Centroids

```
tox_group_centroid(expression_vectors, gene_to_family, n_families,
                    mode, ortholog_set)
```

**(a) Calculate Mean Vector**

Alternatively you can calculate a single mean vector for a given set of vectors by calling the `mean_vector` function directly with the following arguments:

- `expression_vectors` `real(real64)`: Expression vector matrix with size `n_axes × n_genes`
- `gene_indices` `integer(int32)`: An array containing the column indices of the selected genes in `expression_vectors`

**Return:**

- `centroid`: Calculated mean vector (centroid) with length of `n_axes`

Listing 111: R Mean Vector Calculation

```
tox_mean_vector(expression_vectors, gene_indices)
```

## 8. Calculate Distance to Centroid

For each gene in the gene expression matrix, the function computes the Euclidean distance to its corresponding family centroid and returns a numeric vector of distances from each gene to its family centroid. Call the `tox_distance_to_centroid` function with the following arguments:

- `genes`: Gene expression matrix with size of `(n_genes × d)`
- `centroids`: Family centroid matrix with size of `(n_families × d)`
- `gene_to_fam`: Gene-to-family mapping integer vector with the length of `n_genes` (0 = no family, >0 = family index)

- **d**: Gene expression matrix dimension as integer

Listing 112: R Distance to Centroid Calculation

```
tox_distance_to_centroid(genes, centroids, gene_to_fam, d)
```

(a) **Calculate Euclidean Distance**

Alternatively you can calculate a single Euclidean distance between two vectors manually by calling `tox.euclidean_distance` function with the following arguments:

- **vec1**: First vector
- **vec2**: Second vector

**Both vectors must have same length!**

Listing 113: R Euclidean distance calculation

```
tox_euclidean_distance(vec1, vec2)
```

## 9. Detect Gene Outliers

The function first computes family scaling, then calculates relative distance indices (RDI) and identifies outliers based on the specified percentile threshold. It returns a list of components containing the outlier boolean values and intermediate results. Call the `tox_detect_outliers` function with the following arguments:

- **distances**: Numeric vector of distances for each gene to its centroid
- **gene\_to\_fam**: Gene-to-family mapping integer vector mapping with the same length as the distances vector (0 = no family, >0 = family index)
- **n\_families**: Integer number of families
- **(Optional) percentile**: Percentile threshold value for outlier detection (default is 95.0)

**Return list:**

- **is\_outlier**: Logical vector indicating whether each gene is an outlier
- **loess\_x**: Numeric vector of x coordinates used as reference points for LOESS smoothing (median distance)
- **loess\_y**: Numeric vector of y coordinates used as reference points for LOESS smoothing (standard deviation)
- **loess\_n**: Integer vector with numbers of genes in each family used to compute the corresponding median and standard deviation

Listing 114: R Gene Outlier Calculation

```
tox_detect_outliers(distances, gene_to_fam, n_families, percentile)
```

**Alternatively you can calculate each step of `tox_detect_outliers` manually with the following functions:**



(a) **Compute Family Scaling**

The function calculates a scaling factor for each gene family by computing the median and standard deviation of gene-to-centroid distances within each family, then applies LOESS smoothing to these values. Call the `tox_compute_family_scaling` function with the following arguments:

- **distances**: Numeric vector of distances for each gene to its centroid
- **gene\_to\_fam**: Gene-to-family mapping integer vector mapping with the same length as the distances vector (0 = no family, >0 = family index)
- **n\_families**: Integer number of families

**Return dictionary:**

- **dscale**: Numeric vector of scaling factors per family
- **loess\_x**: Numeric vector of x coordinates used as reference points for LOESS smoothing (median distance)
- **loess\_y**: Numeric vector of y coordinates used as reference points for LOESS smoothing (standard deviation)
- **indices\_used**: Integer vector of indices of families that have been included in the calculation

Listing 115: R Compute Family Scaling

```
tox_compute_family_scaling(distances, gene_to_fam, n_families)
```

(b) **Compute Family Scaling (Expert Version)**

This function is the expert version of `tox_detect_outliers` and requires pre-allocated work arrays for maximum performance and control. It can be used when you need fine-grained control over memory allocation or you are calling this function many times in a tight loop. Call the `tox_compute_family_scaling_expert` function with the following arguments:

- **distances**: Numeric vector of distances for each gene to its centroid
- **gene\_to\_fam**: Gene-to-family mapping integer vector mapping with the same length as the distances vector (0 = no family, >0 = family index)
- **n\_families**: Integer number of families
- **perm\_tmp**: Permutation integer vector for sorting with the same length as distances
- **stack\_left\_tmp**: Stack integer vector for sorting with the same length as distances
- **stack\_right\_tmp**: Stack integer vector for sorting with the same length as distances
- **family\_distances**: Work integer vector for sorting with the same length as distances

**Return list:**

- **dscale**: Numeric vector of scaling factors per family
- **loess\_x**: Numeric vector of x coordinates used as reference points for LOESS smoothing (median distance)
- **loess\_y**: Numeric vector of y coordinates used as reference points for LOESS smoothing (standard deviation)
- **indices\_used**: Integer vector of indices of families that have been included in the calculation

- **perm\_tmp**: Permutation vector for sorting
- **stack\_left\_tmp**: Stack vector for sorting
- **stack\_right\_tmp**: Stack vector for sorting
- **family\_distances**: Work vector for sorting

Listing 116: R Compute Family Scaling (Expert Version)

```
tox_compute_family_scaling_expert(distances, gene_to_fam, n_
    families, perm_tmp, stack_left_tmp, stack_right_tmp, family_
    distances)
```

### (c) Compute Relative Distance Index (RDI)

The function calculates the Relative Distance Index (RDI) for each gene by dividing its Euclidean distance to the family centroid by the scaling factor of its family. Call the `tox_compute_rdi` function with the following arguments:

- **distances**: Numeric vector of distances for each gene to its centroid
- **gene\_to\_fam**: Gene-to-family mapping integer vector mapping with the same length as the distances vector (0 = no family, >0 = family index)
- **dscale**: Numeric vector of scaling factors per family

#### Return list:

- **rdi**: Numeric vector containing the RDI value for each gene
- **sorted\_rdi**: Numeric vector containing the RDI values sorted in ascending order

Listing 117: R Compute Relative Distance Index (RDI)

```
tox_compute_rdi(distances, gene_to_fam, dscale)
```

### (d) Identify Outliers

The function identifies outliers based on the top percentile of RDI values. Call the `tox_identify_outliers` function with the following arguments:

- **rdi**: Numeric vector containing the RDI value for each gene
- **(Optional) percentile**: Percentile threshold number for outlier detection (default is 95.0)

#### Return list:

- **is\_outlier**: Logical vector indicating whether each gene is an outlier
- **threshold**: Actual threshold value used for outlier detection

Listing 118: R Identify Outliers

```
tox_identify_outliers(rdi, percentile)
```

## 10. Compute Normalized Tissue Versatility:

The function calculates a normalized tissue versatility score for selected gene expression vectors. It is based on the angle between each gene expression vector and the space diagonal. Versatility is normalized to [0, 1], where 0 means uniform expression 1 means expression in only one axis. Call the `tox_compute_tissue_versatility` function with the following parameters:

- **expression\_vectors**: Numeric matrix array with size **n\_axes** × **n\_vectors**
- **vector\_selection**: Logical vector with length of **n\_vectors** to specify which vectors should be included in the calculation
- **axes\_selection**: Logical vector with length of **n\_axes** to specify which axes should be included in the calculation

**Return list:**

- **tissue\_versatilities**: Numeric vector containing the calculated tissue versatilities for selected vectors
- **tissue\_angles\_deg**: Numeric vector containing the calculated angles in degrees for selected vectors
- **n\_selected\_vectors**: Integer number of vectors processed
- **n\_selected\_axes**: Integer number of axes used in calculation

Listing 119: R Tissue Versatility Calculation

```
tox_calculate_tissue_versatility(expression_vectors, vector_selection,
                                axis_selection)
```

## 11. R BST Interface

### (a) Build BST Index

R interface for building BST index. Uses R's native 1-based indexing.

**Input:**

- **x numeric**: Vector of real values

**Output:**

- **integer**: Permutation indices (1-based R indices)

```
ix <- build_bst_index(x)
```

### (b) BST Range Query

Performs range queries on BST index. Returns a list with components.

**Input:**

- **x numeric**: Original values vector
- **ix integer**: BST index vector from `build_bst_index` (1-based)
- **lo numeric**: Lower bound of range (inclusive)
- **hi numeric**: Upper bound of range (inclusive)

**Output:**

- **list**: Contains indices and count components

```
result <- bst_range_query(x, ix, lo, hi)
indices <- result$indices # 1-based indices
count <- result$count
```

(c) **Get Sorted Value**

Retrieves value from sorted position using R 1-based indexing.

**Input:**

- **x numeric:** Original values vector
- **ix integer:** BST index vector (1-based)
- **position integer:** Position in sorted order (1-based)

**Output:**

- **numeric:** Value at specified position

```
value <- get_sorted_value(x, ix, position)
```

## 12. R k-d Tree Interface

(a) **Build k-d Tree Index**

R interface for k-d tree construction. Input matrix dimensions are rows=dimensions, columns=points.

**Input:**

- **X matrix:** Matrix of points (nrow = dimensions, ncol = n\_points)
- **dim\_order integer:** Dimension ordering (1-based, optional)

**Output:**

- **integer:** Permutation indices (1-based R indices)

```
kd_ix <- build_kd_index(X, dim_order)
```

(b) **Build Spherical k-d Tree**

R interface for spherical k-d tree construction with separate implementation.

**Input:**

- **V matrix:** Matrix of vectors (nrow = dimensions, ncol = n\_vectors)
- **dim\_order integer:** Dimension ordering (1-based, optional)

**Output:**

- **integer:** Permutation indices (1-based R indices)

```
sphere_ix <- build_spherical_kd(V, dim_order)
```

(c) **Get Point from k-d Index**

Retrieves point from k-d tree using R matrix indexing.

**Input:**

- **X matrix:** Original points matrix
- **kd\_ix integer:** k-d tree index vector (1-based)
- **position integer:** Position in k-d tree order (1-based)

**Output:**

- **numeric:** Point values as vector

```
point <- get_kd_point(X, kd_ix, position)
```

### 13. R Interface for Array Serialization and Deserialization

The R interface provides bindings to the Fortran serialization and deserialization routines, enabling efficient handling of multi-dimensional arrays. This interface supports R arrays, matrices, and vectors with automatic type conversion to compatible Fortran data types.

#### (a) General Architecture

The R package provides ten main functions for array handling:

- `tox_serialize_int_array(array, filename)` - Serialize N-dimensional integer arrays
- `tox_deserialize_int_array(filename)` - Deserialize N-dimensional integer arrays
- `tox_serialize_real_array(array, filename)` - Serialize N-dimensional real arrays
- `tox_deserialize_real_array(filename)` - Deserialize N-dimensional real arrays
- `tox_serialize_char_array(array, filename)` - Serialize N-dimensional character arrays
- `tox_deserialize_char_array(filename)` - Deserialize N-dimensional character arrays
- `tox_serialize_logical_array(array, filename)` - Serialize N-dimensional logical array
- `tox_deserialize_logical_array(filename)` - Deserialize N-dimensional logical array
- `tox_serialize_complex_array(array, filename)` - Serialize N-dimensional complex array
- `tox_deserialize_complex_array(filename)` - Deserialize N-dimensional complex array

#### (b) Array Functions

##### Serialization Functions:

- **array** (input): R array, matrix, or vector to be serialized

##### Type:

- Integer
- Numeric (double precision)
- Characters
- Logical
- Complex

**Dimensions:** Theoretically are N dimensions supported, but typical use cases should not exceed 5 dimensions

- **filename** (input): Name of the binary file to create

##### Type: character

#### Listing 120: R Array Serialization Example

```
tox_serialize_int_array(array, filename)
tox_serialize_real_array(array, filename)
tox_serialize_char_array(array, filename)
```

### Deserialization Functions:

- **filename** (input): Name of the binary file to read  
**Type:** character
- **Return Value:** Deserialized R array with original dimensions  
**Type:** array, matrix, or vector  
**Data Type:** Same as original

Listing 121: R Array Deserialization Example

```
restored_int <- tox_deserialize_int_array(filename)
restored_real <- tox_deserialize_real_array(filename)
restored_char <- tox_deserialize_char_array(filename)
```

### (c) Implementation Details

- The R interface automatically converts between R data types and Fortran-compatible formats
- Integer vectors are converted to 32-bit integers
- Numeric vectors are converted to 64-bit floating point
- Character arrays handle variable-length strings with automatic padding
- All array dimensions are preserved during serialization/deserialization
- The interface handles both regular arrays and matrices seamlessly

### Usage Example

Listing 122: Full example of serialization and deserialization in R

```
tox_serialize_int_array(arr1, fn("int1d.bin"))
restored <- tox_deserialize_int_array(fn("int1d.bin"))

# Real array example
arr2 <- matrix(runif(12), nrow = 3, ncol = 4)
tox_serialize_real_array(arr2, fn("real2d.bin"))
restored <- tox_deserialize_real_array(fn("real2d.bin"))

# Character array example
arr3 <- c("GENE1", "BRCA1", "TP53", "EGFR")
tox_serialize_char_array(arr3, fn("char1d.bin"))
restored <- tox_deserialize_char_array(fn("char1d.bin"))
```

### Performance Characteristics

- Efficient memory mapping between R arrays and Fortran memory structures
- Minimal data copying between R and Fortran layers
- Optimized binary format for large scientific datasets
- Support for arrays exceeding available memory through file-based storage

### (d) Compatibility Notes

- Requires R with appropriate Fortran bindings
- Supports standard R data types (integer, numeric, character, logical, complex)

- Preserves array attributes and dimensions during serialization
- Character arrays maintain content but may have padding removed upon deserialization