

```

CAPS10_B9TB1710(1).m CAPS10_B9TB1710(2).m
1 R1=dlmread("rating1.txt"," ",5,1);
2 R1=R1(1:5,:);
3
4 #decomposition into R1=P1*S1
5 [U1,W1,V1]=svd(R1,'econ');
6 P1=U1(:,1:3);
7 S1=W1(1:3,1:3)*V1'(1:3,:);
8
9 r6=[4,2,3]; #known ratings of 6th person
10 X1=[S1(:,1)';S1(:,3)';S1(:,7)'];
11 p6=r6*inv(X1);
12
13 #complementing data of 6th person
14 R1(6,1)=4;
15 R1(6,3)=2;
16 R1(6,7)=3;
17
18 for i=1:20
19     if i!=1,3,7
20         R1(6,i)=p6*S1(:,i);
21     endif
22 endfor
23
24 Ra=[4,3,2,2,3,3,3,2,3,1,2,3,2,2,3,4,3,3,3,3];
25 result1=[R1(6,:);Ra;abs(R1(6,:)-Ra)];
26
27 estim1=[result1(2,3)',result1(4:6,3)', result1(8:20,3)'];
28 mean1=mean(estim1);
29 med1=median(estim1);
30
31 printf("Median of differences between estimations \nand actual data is %f, and mean is %f.",med1,mean1);

```

I start from loading ratings data into matrix $R1$ (data of 5 persons) using function **dlmread** (I had problems with function **load**). Then I decompose $R1$ into $U1$, $W1$, $V1$ using singular value decomposition. I include function 'econ' in order to eliminate rows of zeros in matrix $W1$. Then, I cut matrices $U1, W1, V1$ so that they are all of rank 3 but are still factors of $R1$. I create matrix $P1$ (size 5×3) from the shortened matrix $U1$, and matrix $S1$ (size 3×20) from the sum of shortened matrices $W1$ and $V1^T$.

Next, I want to predict unknown ratings of the new person. In order to do that, I want to find p_6 (size 1×3) in the following equation:

$$[R1(6,1) \quad R1(6,3) \quad R1(6,7)] = p_6 \times \begin{bmatrix} S1(1,1) & S1(2,1) & S1(3,1) \\ S1(1,3) & S1(2,3) & S1(3,3) \\ S1(1,7) & S1(2,7) & S1(3,7) \end{bmatrix}^T$$

I create matrix r_6 (size 1×3) which has only values of three known ratings, and matrix $X1$ which has columns 1,3,7 of matrix $S1$. Then, the above equation is equivalent to:

$$r_6 = p_6 \times X_1$$

By taking an inverse of $X1$ I get the value of p_6 .

$$r_6 \times X_1^{-1} = p_6$$

Now, I can estimate ratings of any song by $R1(6, i) = p_6 \times S1(:, i)$.

I complete R1 with estimations. I repeat all the steps with data from rating2.txt. The only difference I need to adjust is the different size of matrix R2 (storing data from the file), which is 15x20.

```

CAPS10_B9TB1710(1).m CAPS10_B9TB1710(2).m
1 R2=dlmread("rating2.txt", " ", 5, 1);
2 R2=R2(1:15, :);
3
4 #decomposition into R2=P2*S2
5 [U2,W2,V2]=svd(R2, 'econ');
6 P2=U2(:, 1:3);
7 S2=W2(1:3, 1:3)*V2'(1:3, :);
8
9 r16=[4,2,3]; #known ratings of 16th person
10 X2=[S2(:, 1)'; S2(:, 3)'; S2(:, 7)']';
11 p16=r16*inv(X2);
12
13 #complementing data of 16th person into R2
14 R2(16, 1)=4;
15 R2(16, 3)=2;
16 R2(16, 7)=3;
17
18 for i=1:20
19     if i!=1, 3, 7
20         R2(16, i)=p16*S2(:, i);
21     endif
22 endfor
23
24 Ra=[4, 3, 2, 2, 3, 3, 3, 2, 3, 1, 2, 3, 2, 2, 3, 4, 3, 3, 3, 3];
25 result2=[R2(16, :); Ra; abs(R2(16, :)-Ra)]';
26
27 estim2=[result2(2, 3)', result2(4:6, 3)', result2(8:20, 3)'];
28 mean2=mean(estim2);
29 med2=median(estim2);
30
31 printf("Median of differences between estimations \nand actual data is %f, and mean is %f.", med2, mean2);

```

Lastly, I compare my estimations with actual ratings of the new person in both cases. The results are as below.

コマンドウィンドウ	コマンドウィンドウ
>> result1 =	>> result2 =
4.00000 4.00000 0.00000	4.00000 4.00000 0.00000
4.23347 3.00000 1.23347	3.26521 3.00000 0.26521
2.00000 2.00000 0.00000	2.00000 2.00000 0.00000
4.43954 2.00000 2.43954	1.43091 2.00000 0.56909
4.38326 3.00000 1.38326	2.49526 3.00000 0.50474
4.17720 3.00000 1.17720	2.06190 3.00000 0.93810
3.00000 3.00000 0.00000	3.00000 3.00000 0.00000
3.43954 2.00000 1.43954	0.69249 2.00000 1.30751
3.14979 3.00000 0.14979	3.29798 3.00000 0.29798
3.20607 1.00000 2.20607	0.22492 1.00000 0.77508
3.20607 2.00000 1.20607	1.12459 2.00000 0.87541
3.00000 3.00000 0.00000	3.26909 3.00000 0.26909
1.91632 2.00000 0.08368	1.43751 2.00000 0.56249
1.71025 2.00000 0.28975	1.49979 2.00000 0.50021
3.14979 3.00000 0.14979	2.31549 3.00000 0.68451
3.09352 4.00000 0.90648	3.34886 4.00000 0.65114
4.00000 3.00000 1.00000	4.21450 3.00000 1.21450
4.28975 3.00000 1.28975	3.73124 3.00000 0.73124
3.00000 3.00000 0.00000	2.60018 3.00000 0.39982
3.38326 3.00000 0.38326	3.03495 3.00000 0.03495
Median of differences between estimations and actual data is 1.000000, and mean is 0.902214.	Median of differences between estimations and actual data is 0.569087, and mean is 0.622415.

1st column consists of estimated ratings of songs, where the number of a row stands for the number of a song. 2nd column is the actual rating of the corresponding song, and 3rd column has absolute values of differences between the actual and estimated rating. In rows where the 3rd column has zeros, the rating of a song was known prior to the estimation. Mean and median are calculated based only on estimated data.

I can see that when I had more data of people's ratings (result2), the mean and median of mistakes were smaller which means that my estimations were better in case 2.