

Command line arguments

\$

Command line arguments

```
$ ./a.out Deepanjan Kesh ↵
```

Command line arguments

```
$ ./a.out Deepanjan Kesh ↵  
Deepanjan Kesh  
$
```

Command line arguments

```
$ ./a.out Deepanjan Kesh ↵  
Deepanjan Kesh  
$ ./a.out hello, world! ↵
```

Command line arguments

```
$ ./a.out Deepanjan Kesh ↵  
Deepanjan Kesh  
$ ./a.out hello, world! ↵  
hello, world!  
$
```

Command line arguments

Command line arguments

```
#include <stdio.h>
```

```
int main(                                )
```

```
{
```

```
    return 0;
```

```
}
```

Command line arguments

```
#include <stdio.h>

int main(int argc          )
{

    return 0;
}
```


Command line arguments

```
#include <stdio.h>

int main(int argc                ) /* no.  of args */
{

    return 0;
}
```

Command line arguments

```
#include <stdio.h>

int main(int argc, char *argv[])
{

    return 0;
}
```

Command line arguments

```
#include <stdio.h>

int main(int argc, char *argv[]) /* arg list */
{

    return 0;
}
```

Command line arguments

```
#include <stdio.h>

int main(int argc, char *argv[])
{

    printf("No.  of args.  :  %d\n", argc);

    return 0;
}
```

Command line arguments

```
#include <stdio.h>

int main(int argc, char *argv[])
{

    printf("No. of args. : %d\n", argc);
    for (i = 0; i < argc; i++)

    return 0;
}
```

Command line arguments

```
#include <stdio.h>

int main(int argc, char *argv[])
{
    int i;

    printf("No. of args. : %d\n", argc);
    for (i = 0; i < argc; i++)

    return 0;
}
```

Command line arguments

```
#include <stdio.h>

int main(int argc, char *argv[])
{
    int i;

    printf("No. of args. : %d\n", argc);
    for (i = 0; i < argc; i++)
        printf("%s\n", argv[i]);
    return 0;
}
```

Command line arguments

```
#include <stdio.h>

int main(int argc, char *argv[])
{
    int i;

    printf("No. of args. : %d\n", argc);
    for (i = 0; i < argc; i++)
        printf("%s\n", argv[i]);
    return 0;
}
```

\$

Command line arguments

```
#include <stdio.h>

int main(int argc, char *argv[])
{
    int i;

    printf("No. of args. : %d\n", argc);
    for (i = 0; i < argc; i++)
        printf("%s\n", argv[i]);
    return 0;
}
```

```
$ ./a.out Deepanjan Kesh ↵
```

Command line arguments

```
#include <stdio.h>

int main(int argc, char *argv[])
{
    int i;

    printf("No. of args. : %d\n", argc);
    for (i = 0; i < argc; i++)
        printf("%s\n", argv[i]);
    return 0;
}
```

```
$ ./a.out Deepanjan Kesh ↵
No. of args. : 3
```

Command line arguments

```
#include <stdio.h>

int main(int argc, char *argv[])
{
    int i;

    printf("No. of args. : %d\n", argc);
    for (i = 0; i < argc; i++)
        printf("%s\n", argv[i]);
    return 0;
}
```

```
$ ./a.out Deepanjan Kesh ↵
No. of args. : 3
./a.out
```

Command line arguments

```
#include <stdio.h>

int main(int argc, char *argv[])
{
    int i;

    printf("No. of args. : %d\n", argc);
    for (i = 0; i < argc; i++)
        printf("%s\n", argv[i]);
    return 0;
}
```

```
$ ./a.out Deepanjan Kesh ↵
No. of args. : 3
./a.out
Deepanjan
Kesh
```

Command line arguments

```
#include <stdio.h>

int main(int argc, char *argv[])
{
    int i;

    printf("No. of args. : %d\n", argc);
    for (i = 0; i < argc; i++)
        printf("%s\n", argv[i]);
    return 0;
}
```

Remarks

argv[0] is the name of the program.