CS528

Workload Prediction in Cloud System

A Sahu

Dept of CSE, IIT Guwahati

A Sahu


Outline

- Work load Prediction
 - -EWMA, FUSD
- Dynamic Resource Management
 - —Scale up and Scale Down
- SLAV

Reference

Zhen Xiao, Weijia Song, and Qi Chen "Dynamic Resource Allocation Using Virtual Machines for Cloud Computing Environment", IEEE Trans. on Parallel & Dist. Computing., JUNE 2013

Clouds offer Subscription-Oriented IT Services: {compute, apps, data,...} as a Service (..aaS)



Basic Approaches

- Cloud computing allows business customers
 - To scale up and scale down
 - Their resource usage based on needs
- Allocate data center resources dynamically
 - based on application demands
- Supporting green computing
 - by optimizing the number of servers in use
- "skewness" to measure
 - unevenness in the multidimensional resource utilization of a server

Service Level Agreement

- Service Level Agreement
 - Agreement between user and provider
 - Cost, resources, QoS, timely manner
- Agreement in Cloud User and Provider
 - Want to execute a task with time deadline D for E time and require C cpu, M memory unit
 - Cost Payable to Cloud provider by User
 - If Violate, provider needs to penalty

Service Level Agreement

- Real life Example : SLA is every where
- Giving Party Food contract to Caterer
 - Caterer A is good one, what ever he say he do
 - Caterer B is not good: he say some thing but do not provide what he says, always he provide less.
- Transport service : Taking pickup/drop/tour service from Travel agent/Airlines
 - Travel agent TA1: Gives proper services, always service in times, no late, all service are excellent
 - Travel agent TA2: Don't gives proper services, always service in, late, service are bellow expectation based on price.

Service Level Agreement

- Agreement between user and provider
- Cost, resources, QoS, timely manner

Overload Avoidance

- Capacity of a PM should be sufficient
- to satisfy the resource needs of all VMs running on it.
- Otherwise, the PM is overloaded and can lead to degraded performance of its VMs.
- Hot threshold: Utilization of a host $U_h < U_{hotthrehold}$

- Green Computing
 - Number of PMs used should be minimized
 - as long as they can still satisfy the needs of all VMs.
 - Idle PMs can be turned off to save energy.
- Term used to do
 - Cold Threshold: Under utilized Server
 - Green Computing Threshold : Average Utilization of all active PM is bellow this → Some server are under utilized

- Assume 10 servers are there
- Average utilization is 40%
- Can we say some server are underutilized U_h < 25%
 - Yes, may be some server have
- If a server H have U_h<25%
 - Migrate VMs of H to other servers
 - Switch off **H** to save power
- Migrate to VMs of H to other server S
 - where Us < 90% after migration</p>
 - Should not be overloaded

Resource Prediction

- Given Catering to Caterer A: 100 Plates of food
 - Caterer will estimates 80% of guest will come
 - Average amount food (F_{avg}) per person consumes A knows in general
 - He (A) will prepare : $80*F_{avg}$ food for the party.
- Train services
 - During holiday period people go for travels
 - During Holi/Diwali/Dushehara require special train
- Customer at shop
 - Night time customer will be less
 - Evening time is peak time ==>prepare for that

Resource Prediction

- General prediction of online series
- May be more complex
- Most people use based on history, last one/n time slots
- Re Call: CPU burst time prediction by OS for an application
 - Application have series Compute and I/O requests




 OS schedule task on processor by estimating the CPU time of task for next CPU burst

Resource Prediction

Exponential Weighted Moving Average (EWMA)

$$E(t) = \alpha^* E(t-1) + (1-\alpha)^* O(t)$$

E(t) and O(t): Estimated and Observed load at time t



Resource Prediction Approaches

- If E(t) < O(t), estimated is less than observed
 - Party meals: Estimated 80 but came 90: 10 will not get any thing
 - Safe side: Estimate should be a bit higher to maintain the agreement (SLA)
- When observed usage is going down
 - be conservative in reducing our estimation
- Solution to Problem of EWMA

$$E(t) = -|\alpha| E(t-1) + (1+|\alpha|)O(t)$$

= O(t) + |\alpha| (O(t) - E(t-1))

- When O(t) > E(t) use α^u
- When O(t) < E(t) use α^d


Resource prediction Approaches

- FUSD: Fast Up-Slow Down
 - Up direction resource increment aggressive
 - Down direction : be conservative

if (
$$O(t-1) > E(t-1)$$
) // FU $\alpha^u = -0.2$
 $E(t) = \alpha^u * E(t-1) + (1-\alpha^u) * O(t)$
else //SD $\alpha^d = 0.7$
 $E(t) = \alpha^d * E(t-1) + (1-\alpha^d) * O(t)$

- FU : E(t) = 0.2E(t-1) + 1.2 O(t)
 - high weigh to $O(t) \rightarrow$ increase aggressively
- SD : E(t) = 0.7E(t-1) + 0.3 O(t)
 - high weight to E(t) \rightarrow decrease conservatively

- FUSD Example $\alpha^u = -0.2$ $\alpha^d = 0.7$
- E(t) > O(t) : No SLA Violation



Skewness

 Quantify unevenness in the utilization of multiple resources on a server

• Skewness (p) =
$$\sqrt{\sum_{i=1}^{n} (\frac{r_i}{\bar{r}} - 1)^2}$$

- $-\bar{r}$ is AVG utilization of the resources for server p
- -r_i is utilization of i_{th} resource
- Resources are CPU, memory, disk BW, net BW
- Skewed : CPU Util 90%, memory Util 10%

Hot and Cold Spots

- Hot spot: Utilization of any of the resources of a server above hot threshold
 - Hot threshold say 90% and CPU/mem of server is>90% utilized
- Cold Spot: Utilization of all of the resources of a server bellow cold threshold
- The term Temp of a server

Temp (p) =
$$\sum_{r \in R} (r - r_t)^2$$

 R is set of overloaded Resources, r_t is hot threshold of r

Hot and Cold Spots


- Green computing threshold: say 40%
 - Average Utilization of active server are bellow this
 - Have option is Consolidate
- Warm threshold : say 65%
 - Average Utilization above need to start another PM
- Consolidation limit: Max Num of cold server can be eliminated in each run (say 5%)
 - Consolidation takes time
 - Consolidation reduce the performance a bit

Typical Values

- Number of Active Physical Machine (APM) to server the work load depend on these values
 - The value of h, g, c, w, l
- Hot Threshold h = 0.9
- Cold Threshold c = 0.25
- Warm threshold w = 0.65
- Green computing threshold g = 0.4
- Consolidation limit I = 0.05

Impact of threshold on APM

Lower is better (h0.95, g0.5,c0.35)



Live Migration

- VM live migration technology
 - makes it possible to change the mapping between VMs and PMs
 - while applications are running
- Service of the VM is undisrupted during migration (in case of web/db/file server)
- At the time of migration: service continues at both Source and Target
- Same as Grace full Migration
 - Suppose you want to shift your shop from IITG CORE I to CORE V,
 - First get Space at CORE V, Start Service from CORE V, after some time Stop Service at CORE I