

Fortcoders Code Library

askd, yangster67, Nea1

April 29th 2022

Contents

Intro	2
Main template	2
Fast IO	2
Data Structures	2
Segment Tree	2
Recursive	2
Iterating	2
Union Find	3
Fenwick Tree	4
Fenwick2D Tree	4
PBDS	4
Treap	4
Implicit treap	5
Persistent implicit treap	6
2D Sparse Table	6
K-D Tree	6
Link/Cut Tree	7
Geometry	7
Basic stuff	7
Transformation	8
Relation	8
Area	9
Convex	10
Basic 3D	11
Miscellaneous	11
Graph Theory	12
Max Flow	12
PushRelabel Max-Flow (faster)	12
Min-Cost Max-Flow	13
Max Cost Feasible Flow	13
Heavy-Light Decomposition	13
General Unweight Graph Matching	14
Maximum Bipartite Matching	14
2-SAT and Strongly Connected Components	14
Enumerating Triangles	15
Tarjan	15
Kruskal reconstruct tree	15
Math	16
Inverse	16
Mod Class	16
Cancer mod class	17
NTT, FFT, FWT	17
Polynomial Class	17
Sieve	19
Gaussian Elimination	19
is_prime	20
Radix Sort	20
lucas	21
parity of n choose m	21
sosdp	21
String	21
AC Automaton	21
KMP	21
Z function	21

General Suffix Automaton	21
Manacher	22
Lyndon	22
minimal representation	22

Intro

Main template

```
1 #include <bits/stdc++.h>
2 using namespace std;
3
4 #define FOR(x,n) for(int x=0;x<n;x++)
5 #define forn(i, n) for (int i = 0; i < int(n); i++)
6 #define all(v) v.begin(),v.end()
7 using ll = long long;
8 using ld = long double;
9 using pii = pair<int, int>;
10 const char nl = '\n';
11
12 int main() {
13     cin.tie(nullptr)->sync_with_stdio(false);
14     cout << fixed << setprecision(20);
15     // mt19937
16     ↪ rng(chrono::steady_clock::now().time_since_epoch().count());
17 }
```

Fast IO

```
1 namespace io {
2     constexpr int SIZE = 1 << 16;
3     char buf[SIZE], *head, *tail;
4     char get_char() {
5         if (head == tail) tail = (head = buf) + fread(buf, 1, SIZE,
6             ↪ stdin);
7         return *head++;
8     }
9     ll read() {
10         ll x = 0, f = 1;
11         char c = get_char();
12         for (; !isdigit(c); c = get_char()) (c == '-') && (f = -1);
13         for (; isdigit(c); c = get_char()) x = x * 10 + c - '0';
14         return x * f;
15     }
16     string read_s() {
17         string str;
18         char c = get_char();
19         while (c == ' ' || c == '\n' || c == '\r') c = get_char();
20         while (c != ' ' && c != '\n' && c != '\r') str += c, c =
21             ↪ get_char();
22         return str;
23     }
24     void print(int x) {
25         if (x > 9) print(x / 10);
26         putchar(x % 10 | '0');
27     }
28     void println(int x) { print(x), putchar('\n'); }
29     struct Read {
30         Read& operator>>(ll& x) { return x = read(), *this; }
31         Read& operator>>(long double& x) { return x =
32             ↪ stold(read_s()), *this; }
33     } in;
34 } // namespace io
```

Data Structures

Segment Tree

Recursive

- Implicit segment tree, range query + point update

```
1 struct Node {
2     int lc, rc, p;
3 };
4
5 struct SegTree {
6     vector<Node> t = {{}};
7     SegTree(int n) { t.reserve(n * 40); }
8     int modify(int p, int l, int r, int x, int v) {
```

```
9         int u = p;
10        if (p == 0) {
11            t.push_back(t[p]);
12            u = (int)t.size() - 1;
13        }
14        if (r - l == 1) {
15            t[u].p = t[p].p + v;
16        } else {
17            int m = (l + r) / 2;
18            if (x < m) {
19                t[u].lc = modify(t[p].lc, l, m, x, v);
20            } else {
21                t[u].rc = modify(t[p].rc, m, r, x, v);
22            }
23            t[u].p = t[t[u].lc].p + t[t[u].rc].p;
24        }
25        return u;
26    }
27    int query(int p, int l, int r, int x, int y) {
28        if (x <= l && r <= y) return t[p].p;
29        int m = (l + r) / 2, res = 0;
30        if (x < m) res += query(t[p].lc, l, m, x, y);
31        if (y > m) res += query(t[p].rc, m, r, x, y);
32        return res;
33    }
34 };
```

- Persistent implicit, range query + point update

```
1 struct Node {
2     int lc = 0, rc = 0, p = 0;
3 };
4
5 struct SegTree {
6     vector<Node> t = {{}}; // init all
7     SegTree() = default;
8     SegTree(int n) { t.reserve(n * 20); }
9     int modify(int p, int l, int r, int x, int v) {
10         // p: original node, update a[x] -> v
11         t.push_back(t[p]);
12         int u = (int)t.size() - 1;
13         if (r - l == 1) {
14             t[u].p = v;
15         } else {
16             int m = (l + r) / 2;
17             if (x < m) {
18                 t[u].lc = modify(t[p].lc, l, m, x, v);
19                 t[u].rc = t[p].rc;
20             } else {
21                 t[u].lc = t[p].lc;
22                 t[u].rc = modify(t[p].rc, m, r, x, v);
23             }
24             t[u].p = t[t[u].lc].p + t[t[u].rc].p;
25         }
26         return u;
27     }
28     int query(int p, int l, int r, int x, int y) {
29         // query sum a[x]...a[y-1] rooted at p
30         // t[p] holds the info of [l, r)
31         if (x <= l && r <= y) return t[p].p;
32         int m = (l + r) / 2, res = 0;
33         if (x < m) res += query(t[p].lc, l, m, x, y);
34         if (y > m) res += query(t[p].rc, m, r, x, y);
35         return res;
36     }
37 };
```

Iterating

- Iterating, range query + point update

```
1 struct Node {
2     ll v = 0, init = 0;
3 };
4
5 Node pull(const Node &a, const Node &b) {
6     if (!a.init) return b;
```

```

7   if (!b.init) return a;
8   Node c;
9   return c;
10  }
11
12  struct SegTree {
13      ll n;
14      vector<Node> t;
15      SegTree(ll _n) : n(_n), t(2 * n){};
16      void modify(ll p, const Node &v) {
17          t[p += n] = v;
18          for (p /= 2; p; p /= 2) t[p] = pull(t[p * 2], t[p * 2 +
↵ 1]);
19      }
20      Node query(ll l, ll r) {
21          Node left, right;
22          for (l += n, r += n; l < r; l /= 2, r /= 2) {
23              if (l & 1) left = pull(left, t[l++]);
24              if (r & 1) right = pull(t[--r], right);
25          }
26          return pull(left, right);
27      }
28  };

```

• Iterating, range query + range update

```

1  struct Node {
2      ll v = 0;
3  };
4  struct Tag {
5      ll v = 0;
6  };
7  Node pull(const Node& a, const Node& b) { return {max(a.v,
↵ b.v)}; }
8  Tag pull(const Tag& a, const Tag& b) { return {a.v + b.v}; }
9  Node apply_tag(const Node& a, const Tag& b) { return {a.v +
↵ b.v}; }
10
11  struct SegTree {
12      ll n, h;
13      vector<Node> t;
14      vector<Tag> lazy;
15      SegTree(ll _n) : n(_n), h((ll)log2(n)), t(2 * _n), lazy(2 *
↵ _n) {}
16      void apply(ll x, const Tag& tag) {
17          t[x] = apply_tag(t[x], tag);
18          lazy[x] = pull(lazy[x], tag);
19      }
20      void build(ll l) {
21          for (l = (l + n) / 2; l > 0; l /= 2) {
22              if (!lazy[l].v) t[l] = pull(t[l * 2], t[2 * l + 1]);
23          }
24      }
25      void push(ll l) {
26          l += n;
27          for (ll s = h; s > 0; s--) {
28              ll i = l >> s;
29              if (lazy[i].v) {
30                  apply(2 * i, lazy[i]);
31                  apply(2 * i + 1, lazy[i]);
32              }
33              lazy[i] = Tag();
34          }
35      }
36      void modify(ll l, ll r, const Tag& v) {
37          push(l), push(r - 1);
38          ll l0 = l, r0 = r;
39          for (l += n, r += n; l < r; l /= 2, r /= 2) {
40              if (l & 1) apply(l++, v);
41              if (r & 1) apply(--r, v);
42          }
43          build(l0), build(r0 - 1);
44      }
45      Node query(ll l, ll r) {
46          push(l), push(r - 1);
47          Node left, right;
48          for (l += n, r += n; l < r; l /= 2, r /= 2) {
49              if (l & 1) left = pull(left, t[l++]);

```

```

50          if (r & 1) right = pull(t[--r], right);
51      }
52      return pull(left, right);
53  }
54  };

```

• AtCoder Segment Tree (recursive structure but iterative)

```

1  template <class T> struct PointSegmentTree {
2      int size = 1;
3      vector<T> tree;
4      PointSegmentTree(int n) : PointSegmentTree(vector<T>(n)) {}
5      PointSegmentTree(vector<T>& arr) {
6          while(size < (int)arr.size())
7              size <<= 1;
8          tree = vector<T>(size << 1);
9          for(int i = size + arr.size() - 1; i >= 1; i--)
10             if(i >= size) tree[i] = arr[i - size];
11             else consume(i);
12      }
13      void set(int i, T val) {
14          tree[i += size] = val;
15          for(i >>= 1; i >= 1; i >>= 1)
16              consume(i);
17      }
18      T get(int i) { return tree[i + size]; }
19      T query(int l, int r) {
20          T resl, resr;
21          for(l += size, r += size + 1; l < r; l >>= 1, r >>= 1) {
22              if(l & 1) resl = resl * tree[l++];
23              if(r & 1) resr = tree[--r] * resr;
24          }
25          return resl * resr;
26      }
27      T query_all() { return tree[1]; }
28      void consume(int i) { tree[i] = tree[i << 1] * tree[i << 1 |
↵ 1]; }
29  };
30
31  struct SegInfo {
32      ll v;
33      SegInfo() : SegInfo(0) {}
34      SegInfo(ll val) : v(val) {}
35      SegInfo operator*(SegInfo b) {
36          return SegInfo(v + b.v);
37      }
38  };
39  };

```

Union Find

```

1  vector<int> p(n);
2  iota(p.begin(), p.end(), 0);
3  function<int(int)> find = [&](int x) { return p[x] == x ? x :
↵ (p[x] = find(p[x])); };
4  auto merge = [&](int x, int y) { p[find(x)] = find(y); };

```

• Persistent version

```

1  struct Node {
2      int lc, rc, p;
3  };
4
5  struct SegTree {
6      vector<Node> t = {{0, 0, -1}}; // init all
7      SegTree() = default;
8      SegTree(int n) { t.reserve(n * 20); }
9      int modify(int p, int l, int r, int x, int v) {
10         // p: original node, update a[x] -> v
11         t.push_back(t[p]);
12         int u = (int)t.size() - 1;
13         if (r - l == 1) {
14             t[u].p = v;
15         } else {
16             int m = (l + r) / 2;
17             if (x < m) {
18                 t[u].lc = modify(t[p].lc, l, m, x, v);
19                 t[u].rc = t[p].rc;

```

```

20     } else {
21         t[u].lc = t[p].lc;
22         t[u].rc = modify(t[p].rc, m, r, x, v);
23     }
24     t[u].p = t[t[u].lc].p + t[t[u].rc].p;
25 }
26 return u;
27 }
28 int query(int p, int l, int r, int x, int y) {
29     // query sum a[x]...a[y-1] rooted at p
30     // t[p] holds the info of [l, r)
31     if (x <= l && r <= y) return t[p].p;
32     int m = (l + r) / 2, res = 0;
33     if (x < m) res += query(t[p].lc, l, m, x, y);
34     if (y > m) res += query(t[p].rc, m, r, x, y);
35     return res;
36 }
37 };
38
39 struct DSU {
40     int n;
41     SegTree seg;
42     DSU(int _n) : n(_n), seg(n) {}
43     int get(int p, int x) { return seg.query(p, 0, n, x, x + 1); }
44     int set(int p, int x, int v) { return seg.modify(p, 0, n, x,
45     v); }
46     int find(int p, int x) {
47         int parent = get(p, x);
48         if (parent < 0) return x;
49         return find(p, parent);
50     }
51     int is_same(int p, int x, int y) { return find(p, x) ==
52     find(p, y); }
53     int merge(int p, int x, int y) {
54         int rx = find(p, x), ry = find(p, y);
55         if (rx == ry) return -1;
56         int rank_x = -get(p, rx), rank_y = -get(p, ry);
57         if (rank_x < rank_y) {
58             p = set(p, rx, ry);
59         } else if (rank_x > rank_y) {
60             p = set(p, ry, rx);
61         } else {
62             p = set(p, rx, -rx - 1);
63         }
64         return p;
65     }
66 };

```

Fenwick Tree

```

1 template <typename T> struct FenwickTree {
2     int size = 1, high_bit = 1;
3     vector<T> tree;
4     FenwickTree(int _size) : size(_size) {
5         tree.resize(size + 1);
6         while((high_bit << 1) <= size) high_bit <<= 1;
7     }
8     FenwickTree(vector<T>& arr) : FenwickTree(arr.size()) {
9         for(int i = 0; i < size; i++) update(i, arr[i]);
10    }
11    int lower_bound(T x) {
12        int res = 0; T cur = 0;
13        for(int bit = high_bit; bit > 0; bit >>= 1) {
14            if((res|bit) <= size && cur + tree[res|bit] < x) {
15                res |= bit; cur += tree[res];
16            }
17        }
18        return res;
19    }
20    T prefix_sum(int i) {
21        T ret = 0;
22        for(i++; i > 0; i -= (i & -i)) ret += tree[i];
23        return ret;
24    }

```

```

25    T range_sum(int l, int r) { return (l > r) ? 0 :
26    prefix_sum(r) - prefix_sum(l - 1); }
27    void update(int i, T delta) { for(i++; i <= size; i += (i &
28    -i)) tree[i] += delta; }

```

Fenwick2D Tree

```

1 struct Fenwick2D {
2     ll n, m;
3     vector<vector<ll>> a;
4     Fenwick2D(ll _n, ll _m) : n(_n), m(_m), a(n, vector<ll>(m))
5     {}
6     void add(ll x, ll y, ll v) {
7         for (int i = x + 1; i <= n; i += i & -i) {
8             for (int j = y + 1; j <= m; j += j & -j) {
9                 (a[i - 1][j - 1] += v) %= MOD;
10            }
11        }
12    }
13    void add(ll x1, ll x2, ll y1, ll y2, ll v) {
14        // [(x1, y1), (x2, y2))
15        add(x1, y1, v);
16        add(x1, y2, MOD - v), add(x2, y1, MOD - v);
17        add(x2, y2, v);
18    }
19    ll sum(ll x, ll y) { // [(0, 0), (x, y))
20        ll ans = 0;
21        for (int i = x; i > 0; i -= i & -i) {
22            for (int j = y; j > 0; j -= j & -j) {
23                (ans += a[i - 1][j - 1]) %= MOD;
24            }
25        }
26        return ans;
27    }

```

PBDS

```

1 #include <bits/stdc++.h>
2 #include <ext/pb_ds/assoc_container.hpp>
3 using namespace std;
4 using namespace __gnu_pbds;
5 template<typename T>
6 using ordered_set = tree<T, null_type, less<T>, rb_tree_tag,
7 tree_order_statistics_node_update>;
8 using ordered_map = tree<T, X, less<T>, rb_tree_tag,
9 tree_order_statistics_node_update>;
10 template<typename T, typename X>
11 using fast_map = cc_hash_table<T, X>;
12 template<typename T, typename X>
13 using ht = gp_hash_table<T, X>;
14 mt19937_64
15 rng(chrono::steady_clock::now().time_since_epoch().count());
16
17 struct splitmix64 {
18     size_t operator()(size_t x) const {
19         static const size_t fixed =
20         chrono::steady_clock::now().time_since_epoch().count();
21         x += 0x9e3779b97f4a7c15 + fixed;
22         x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
23         x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
24         return x ^ (x >> 31);
25     }

```

Treap

- (No rotation version)

```

1 struct Node {
2     Node *l, *r;
3     int s, sz;
4     // int t = 0, a = 0, g = 0; // for lazy propagation

```

```

5     ll w;
6
7     Node(int _s) : l(nullptr), r(nullptr), s(_s), sz(1),
    ↪ w(rng()) {}
8     void apply(int vt, int vg) {
9         // for lazy propagation
10        // s -= vt;
11        // t += vt, a += vg, g += vg;
12    }
13    void push() {
14        // for lazy propagation
15        // if (l != nullptr) l->apply(t, g);
16        // if (r != nullptr) r->apply(t, g);
17        // t = g = 0;
18    }
19    void pull() { sz = 1 + (l ? l->sz : 0) + (r ? r->sz : 0); }
20 };
21
22 std::pair<Node *, Node *> split(Node *t, int v) {
23     if (t == nullptr) return {nullptr, nullptr};
24     t->push();
25     if (t->s < v) {
26         auto [x, y] = split(t->r, v);
27         t->r = x;
28         t->pull();
29         return {t, y};
30     } else {
31         auto [x, y] = split(t->l, v);
32         t->l = y;
33         t->pull();
34         return {x, t};
35     }
36 }
37
38 Node *merge(Node *p, Node *q) {
39     if (p == nullptr) return q;
40     if (q == nullptr) return p;
41     if (p->w < q->w) swap(p, q);
42     auto [x, y] = split(q, p->s + rng() % 2);
43     p->push();
44     p->l = merge(p->l, x);
45     p->r = merge(p->r, y);
46     p->pull();
47     return p;
48 }
49
50 Node *insert(Node *t, int v) {
51     auto [x, y] = split(t, v);
52     return merge(merge(x, new Node(v)), y);
53 }
54
55 Node *erase(Node *t, int v) {
56     auto [x, y] = split(t, v);
57     auto [p, q] = split(y, v + 1);
58     return merge(merge(x, merge(p->l, p->r)), q);
59 }
60
61 int get_rank(Node *t, int v) {
62     auto [x, y] = split(t, v);
63     int res = (x ? x->sz : 0) + 1;
64     t = merge(x, y);
65     return res;
66 }
67
68 Node *kth(Node *t, int k) {
69     k--;
70     while (true) {
71         int left_sz = t->l ? t->l->sz : 0;
72         if (k < left_sz) {
73             t = t->l;
74         } else if (k == left_sz) {
75             return t;
76         } else {
77             k -= left_sz + 1, t = t->r;
78         }
79     }
80 }

```

```

81
82 Node *get_prev(Node *t, int v) {
83     auto [x, y] = split(t, v);
84     Node *res = kth(x, x->sz);
85     t = merge(x, y);
86     return res;
87 }
88
89 Node *get_next(Node *t, int v) {
90     auto [x, y] = split(t, v + 1);
91     Node *res = kth(y, 1);
92     t = merge(x, y);
93     return res;
94 }

```

• USAGE

```

1  int main() {
2      cin.tie(nullptr)->sync_with_stdio(false);
3      int n;
4      cin >> n;
5      Node *t = nullptr;
6      for (int op, x; n--;) {
7          cin >> op >> x;
8          if (op == 1) {
9              t = insert(t, x);
10         } else if (op == 2) {
11             t = erase(t, x);
12         } else if (op == 3) {
13             cout << get_rank(t, x) << "\n";
14         } else if (op == 4) {
15             cout << kth(t, x)->s << "\n";
16         } else if (op == 5) {
17             cout << get_prev(t, x)->s << "\n";
18         } else {
19             cout << get_next(t, x)->s << "\n";
20         }
21     }
22 }

```

Implicit treap

• Split by size

```

1  struct Node {
2      Node *l, *r;
3      int s, sz;
4      // int lazy = 0;
5      ll w;
6
7      Node(int _s) : l(nullptr), r(nullptr), s(_s), sz(1),
    ↪ w(rnd()) {}
8      void apply() {
9          // for lazy propagation
10         // lazy ^= 1;
11     }
12     void push() {
13         // for lazy propagation
14         // if (lazy) {
15             // swap(l, r);
16             // if (l != nullptr) l->apply();
17             // if (r != nullptr) r->apply();
18             // lazy = 0;
19         // }
20     }
21     void pull() { sz = 1 + (l ? l->sz : 0) + (r ? r->sz : 0); }
22 };
23
24 std::pair<Node *, Node *> split(Node *t, int v) {
25     // first->sz == v
26     if (t == nullptr) return {nullptr, nullptr};
27     t->push();
28     int left_sz = t->l ? t->l->sz : 0;
29     if (left_sz < v) {
30         auto [x, y] = split(t->r, v - left_sz - 1);
31         t->r = x;
32         t->pull();

```

```

33     return {t, y};
34 } else {
35     auto [x, y] = split(t->l, v);
36     t->l = y;
37     t->pull();
38     return {x, t};
39 }
40 }
41
42 Node *merge(Node *p, Node *q) {
43     if (p == nullptr) return q;
44     if (q == nullptr) return p;
45     if (p->w < q->w) {
46         p->push();
47         p->r = merge(p->r, q);
48         p->pull();
49         return p;
50     } else {
51         q->push();
52         q->l = merge(p, q->l);
53         q->pull();
54         return q;
55     }
56 }

```

Persistent implicit treap

```

1 pair<Node *, Node *> split(Node *t, int v) {
2     // first->sz == v
3     if (t == nullptr) return {nullptr, nullptr};
4     t->push();
5     int left_sz = t->l ? t->l->sz : 0;
6     t = new Node(*t);
7     if (left_sz < v) {
8         auto [x, y] = split(t->r, v - left_sz - 1);
9         t->r = x;
10        t->pull();
11        return {t, y};
12    } else {
13        auto [x, y] = split(t->l, v);
14        t->l = y;
15        t->pull();
16        return {x, t};
17    }
18 }
19
20 Node *merge(Node *p, Node *q) {
21     if (p == nullptr) return new Node(*q);
22     if (q == nullptr) return new Node(*p);
23     if (p->w < q->w) {
24         p = new Node(*p);
25         p->push();
26         p->r = merge(p->r, q);
27         p->pull();
28         return p;
29     } else {
30         q = new Node(*q);
31         q->push();
32         q->l = merge(p, q->l);
33         q->pull();
34         return q;
35     }
36 }

```

2D Sparse Table

- Sorry that this sucks - askd

```

1 template <class T, class Compare = less<T>>
2 struct SparseTable2d {
3     int n = 0, m = 0;
4     T**** table;
5     int* log;
6     inline T choose(T x, T y) {
7         return Compare()(x, y) ? x : y;
8     }

```

```

9     SparseTable2d(vector<vector<T>>& grid) {
10         if(grid.empty() || grid[0].empty()) return;
11         n = grid.size(); m = grid[0].size();
12         log = new int[max(n, m) + 1];
13         log[1] = 0;
14         for(int i = 2; i <= max(n, m); i++)
15             log[i] = log[i - 1] + ((i ^ (i - 1)) > i);
16         table = new T***[n];
17         for(int i = n - 1; i >= 0; i--) {
18             table[i] = new T**[m];
19             for(int j = m - 1; j >= 0; j--) {
20                 table[i][j] = new T*[log[n - i] + 1];
21                 for(int k = 0; k <= log[n - i]; k++) {
22                     table[i][j][k] = new T[log[m - j] + 1];
23                     if(!k) table[i][j][k][0] = grid[i][j];
24                     else table[i][j][k][0] = choose(table[i][j][k-1][0],
25 ↪ table[i+(1<<(k-1))][j][k-1][0]);
26                     for(int l = 1; l <= log[m - j]; l++)
27                         table[i][j][k][l] = choose(table[i][j][k][l-1],
28 ↪ table[i][j+(1<<(l-1))][k][l-1]);
29                 }
30             }
31         }
32         T query(int r1, int r2, int c1, int c2) {
33             assert(r1 >= 0 && r2 < n && r1 <= r2);
34             assert(c1 >= 0 && c2 < m && c1 <= c2);
35             int r1 = log[r2 - r1 + 1], c1 = log[c2 - c1 + 1];
36             T ca1 = choose(table[r1][c1][r1][c1],
37 ↪ table[r2-(1<<r1)+1][c1][r1][c1]);
38             T ca2 = choose(table[r1][c2-(1<<c1)+1][r1][c1],
39 ↪ table[r2-(1<<r1)+1][c2-(1<<c1)+1][r1][c1]);
40             return choose(ca1, ca2);
41         }
42     };
43 };

```

• USAGE

```

1 vector<vector<int>> test = {
2     {1, 2, 3, 4}, {2, 3, 4, 5}, {9, 9, 9, 9}, {-1, -1, -1, -1}
3 };
4
5 SparseTable2d<int> st(test); // Range min query
6 SparseTable2d<int, greater<int>> st2(test); // Range max query

```

K-D Tree

```

1 struct Point {
2     int x, y;
3 };
4 struct Rectangle {
5     int lx, rx, ly, ry;
6 };
7
8 bool is_in(const Point &p, const Rectangle &rg) {
9     return (p.x >= rg.lx && (p.x <= rg.rx) && (p.y >= rg.ly) &&
10 ↪ (p.y <= rg.ry));
11 }
12
13 struct KDTree {
14     vector<Point> points;
15     struct Node {
16         int lc, rc;
17         Point point;
18         Rectangle range;
19         int num;
20     };
21     vector<Node> nodes;
22     int root = -1;
23     KDTree(const vector<Point> &points_) {
24         points = points_;
25         Rectangle range = {-1e9, 1e9, -1e9, 1e9};
26         root = tree_construct(0, (int)points.size(), range, 0);
27     }
28     int tree_construct(int l, int r, Rectangle range, int depth)
29     {
30         if (l == r) return -1;

```

```

29     if (l > r) throw;
30     int mid = (l + r) / 2;
31     auto comp = (depth % 2) ? [](Point &a, Point &b) { return
↪ a.x < b.x; }
32       : [](Point &a, Point &b) { return
↪ a.y < b.y; };
33     nth_element(points.begin() + l, points.begin() + mid,
↪ points.begin() + r, comp);
34     Rectangle l_range(range), r_range(range);
35     if (depth % 2) {
36         l_range.rx = points[mid].x;
37         r_range.lx = points[mid].x;
38     } else {
39         l_range.ry = points[mid].y;
40         r_range.ly = points[mid].y;
41     }
42     Node node = {tree_construct(l, mid, l_range, depth + 1),
43                 tree_construct(mid + 1, r, r_range, depth +
↪ 1), points[mid], range, r - l};
44     nodes.push_back(node);
45     return (int)nodes.size() - 1;
46 }
47
48 int inner_query(int id, const Rectangle &rec, int depth) {
49     if (id == -1) return 0;
50     Rectangle rg = nodes[id].range;
51     if (rg.lx >= rec.lx && rg.rx <= rec.rx && rg.ly >= rec.ly
↪ && rg.ry <= rec.ry) {
52         return nodes[id].num;
53     }
54     int ans = 0;
55     if (depth % 2) { // pruning
56         if (rec.lx <= nodes[id].point.x) ans +=
↪ inner_query(nodes[id].lc, rec, depth + 1);
57         if (rec.rx >= nodes[id].point.x) ans +=
↪ inner_query(nodes[id].rc, rec, depth + 1);
58     } else {
59         if (rec.ly <= nodes[id].point.y) ans +=
↪ inner_query(nodes[id].lc, rec, depth + 1);
60         if (rec.ry >= nodes[id].point.y) ans +=
↪ inner_query(nodes[id].rc, rec, depth + 1);
61     }
62     if (is_in(nodes[id].point, rec)) ans += 1;
63     return ans;
64 }
65 int query(const Rectangle &rec) { return inner_query(root,
↪ rec, 0); }
66 };

```

Link/Cut Tree

```

1 struct Node {
2     Node *ch[2], *p;
3     int id;
4     bool rev;
5     Node(int id) : ch{nullptr, nullptr}, p(nullptr), id(id),
↪ rev(false) {}
6     friend void reverse(Node *p) {
7         if (p != nullptr) {
8             swap(p->ch[0], p->ch[1]);
9             p->rev ^= 1;
10        }
11    }
12    void push() {
13        if (rev) {
14            reverse(ch[0]);
15            reverse(ch[1]);
16            rev = false;
17        }
18    }
19    void pull() {}
20    bool is_root() { return p == nullptr || p->ch[0] != this &&
↪ p->ch[1] != this; }
21    bool pos() { return p->ch[1] == this; }
22    void rotate() {
23        Node *q = p;

```

```

24        bool x = !pos();
25        q->ch[!x] = ch[x];
26        if (ch[x] != nullptr) ch[x]->p = q;
27        p = q->p;
28        if (!q->is_root()) q->p->ch[q->pos()] = this;
29        ch[x] = q;
30        q->p = this;
31        pull();
32        q->pull();
33    }
34    void splay() {
35        vector<Node *> s;
36        for (Node *i = this; !i->is_root(); i = i->p)
↪ s.push_back(i->p);
37        while (!s.empty()) s.back()->push(), s.pop_back();
38        push();
39        while (!is_root()) {
40            if (!p->is_root()) {
41                if (pos() == p->pos()) {
42                    p->rotate();
43                } else {
44                    rotate();
45                }
46            }
47            rotate();
48        }
49        pull();
50    }
51    void access() {
52        for (Node *i = this, *q = nullptr; i != nullptr; q = i, i
↪ = i->p) {
53            i->splay();
54            i->ch[1] = q;
55            i->pull();
56        }
57        splay();
58    }
59    void makeroot() {
60        access();
61        reverse(this);
62    }
63 };
64 void link(Node *x, Node *y) {
65     x->makeroot();
66     x->p = y;
67 }
68 void split(Node *x, Node *y) {
69     x->makeroot();
70     y->access();
71 }
72 void cut(Node *x, Node *y) {
73     split(x, y);
74     x->p = y->ch[0] = nullptr;
75     y->pull();
76 }
77 bool connected(Node *p, Node *q) {
78     p->access();
79     q->access();
80     return p->p != nullptr;
81 }

```

Geometry

Basic stuff

```

1 using ll = long long;
2 using ld = long double;
3
4 constexpr auto eps = 1e-8;
5 const auto PI = acos(-1);
6 int sgn(ld x) { return (abs(x) <= eps) ? 0 : (x < 0 ? -1 : 1);
↪ }
7
8 struct Point {
9     ld x = 0, y = 0;
10    Point() = default;

```



```

11 Point(ld_x, ld_y) : x(_x), y(_y) {}
12 bool operator<(const Point &p) const { return !sgn(p.x - x)
↪ ? sgn(y - p.y) < 0 : x < p.x; }
13 bool operator==(const Point &p) const { return !sgn(p.x - x)
↪ && !sgn(p.y - y); }
14 Point operator+(const Point &p) const { return {x + p.x, y +
↪ p.y}; }
15 Point operator-(const Point &p) const { return {x - p.x, y -
↪ p.y}; }
16 Point operator*(ld a) const { return {x * a, y * a}; }
17 Point operator/(ld a) const { return {x / a, y / a}; }
18 auto operator*(const Point &p) const { return x * p.x + y *
↪ p.y; } // dot
19 auto operator^(const Point &p) const { return x * p.y - y *
↪ p.x; } // cross
20 friend auto &operator>>(istream &i, Point &p) { return i >>
↪ p.x >> p.y; }
21 friend auto &operator<<(ostream &o, Point p) { return o <<
↪ p.x << ' ' << p.y; }
22 };
23
24 struct Line {
25     Point s = {0, 0}, e = {0, 0};
26     Line() = default;
27     Line(Point _s, Point _e) : s(_s), e(_e) {}
28     friend auto &operator>>(istream &i, Line &l) { return i >>
↪ l.s >> l.e; } // (x1, y1), (x2, y2)
29 };
30
31 struct Segment : Line {
32     using Line::Line;
33 };
34
35 struct Circle {
36     Point o = {0, 0};
37     ld r = 0;
38     Circle() = default;
39     Circle(Point _o, ld _r) : o(_o), r(_r) {}
40 };
41
42 auto dist2(const Point &a) { return a * a; }
43 auto dist2(const Point &a, const Point &b) { return dist2(a -
↪ b); }
44 auto dist(const Point &a) { return sqrt(dist2(a)); }
45 auto dist(const Point &a, const Point &b) { return
↪ sqrt(dist2(a - b)); }
46 auto dist(const Point &a, const Line &l) { return abs((a -
↪ l.s) ^ (l.e - l.s)) / dist(l.s, l.e); }
47 auto dist(const Point &p, const Segment &l) {
48     if (l.s == l.e) return dist(p, l.s);
49     auto d = dist2(l.s, l.e), t = min(d, max((ld)0, (p - l.s) *
↪ (l.e - l.s)));
50     return dist((p - l.s) * d, (l.e - l.s) * t) / d;
51 }
52
53 /* Needs is_intersect
54 auto dist(const Segment &l1, const Segment &l2) {
55     if (is_intersect(l1, l2)) return (ld)0;
56     return min({dist(l1.s, l2), dist(l1.e, l2), dist(l2.s, l1),
↪ dist(l2.e, l1)});
57 } */
58
59 Point perp(const Point &p) { return Point(-p.y, p.x); }
60
61 auto rad(const Point &p) { return atan2(p.y, p.x); }

```

Transformation

```

1 Point project(const Point &p, const Line &l) {
2     return l.s + ((l.e - l.s) * ((l.e - l.s) * (p - l.s))) /
↪ dist2(l.e - l.s);
3 }
4
5 Point reflect(const Point &p, const Line &l) {
6     return project(p, l) * 2 - p;
7 }
8

```

```

9 Point dilate(const Point &p, ld scale_x = 1, ld scale_y = 1) {
↪ return Point(p.x * scale_x, p.y * scale_y); }
10 Line dilate(const Line &l, ld scale_x = 1, ld scale_y = 1) {
↪ return Line(dilate(l.s, scale_x, scale_y), dilate(l.e,
↪ scale_x, scale_y)); }
11 Segment dilate(const Segment &l, ld scale_x = 1, ld scale_y =
↪ 1) { return Segment(dilate(l.s, scale_x, scale_y),
↪ dilate(l.e, scale_x, scale_y)); }
12 vector<Point> dilate(const vector<Point> &p, ld scale_x = 1,
↪ ld scale_y = 1) {
13     int n = p.size();
14     vector<Point> res(n);
15     for (int i = 0; i < n; i++)
16         res[i] = dilate(p[i], scale_x, scale_y);
17     return res;
18 }
19
20 Point rotate(const Point &p, ld a) { return Point(p.x * cos(a)
↪ - p.y * sin(a), p.x * sin(a) + p.y * cos(a)); }
21 Line rotate(const Line &l, ld a) { return Line(rotate(l.s, a),
↪ rotate(l.e, a)); }
22 Segment rotate(const Segment &l, ld a) { return
↪ Segment(rotate(l.s, a), rotate(l.e, a)); }
23 Circle rotate(const Circle &c, ld a) { return
↪ Circle(rotate(c.o, a), c.r); }
24 vector<Point> rotate(const vector<Point> &p, ld a) {
25     int n = p.size();
26     vector<Point> res(n);
27     for (int i = 0; i < n; i++)
28         res[i] = rotate(p[i], a);
29     return res;
30 }
31
32 Point translate(const Point &p, ld dx = 0, ld dy = 0) { return
↪ Point(p.x + dx, p.y + dy); }
33 Line translate(const Line &l, ld dx = 0, ld dy = 0) { return
↪ Line(translate(l.s, dx, dy), translate(l.e, dx, dy)); }
34 Segment translate(const Segment &l, ld dx = 0, ld dy = 0) {
↪ return Segment(translate(l.s, dx, dy), translate(l.e, dx,
↪ dy)); }
35 Circle translate(const Circle &c, ld dx = 0, ld dy = 0) {
↪ return Circle(translate(c.o, dx, dy), c.r); }
36 vector<Point> translate(const vector<Point> &p, ld dx = 0, ld
↪ dy = 0) {
37     int n = p.size();
38     vector<Point> res(n);
39     for (int i = 0; i < n; i++)
40         res[i] = translate(p[i], dx, dy);
41     return res;
42 }

```

Relation

```

1 enum class Relation { SEPARATE, EX_TOUCH, OVERLAP, IN_TOUCH,
↪ INSIDE };
2 Relation get_relation(const Circle &a, const Circle &b) {
3     auto c1c2 = dist(a.o, b.o);
4     auto r1r2 = a.r + b.r, diff = abs(a.r - b.r);
5     if (sgn(c1c2 - r1r2) > 0) return Relation::SEPARATE;
6     if (sgn(c1c2 - r1r2) == 0) return Relation::EX_TOUCH;
7     if (sgn(c1c2 - diff) > 0) return Relation::OVERLAP;
8     if (sgn(c1c2 - diff) == 0) return Relation::IN_TOUCH;
9     return Relation::INSIDE;
10 }
11
12 auto get_cos_from_triangle(ld a, ld b, ld c) { return (a * a +
↪ b * b - c * c) / (2.0 * a * b); }
13
14 bool on_line(const Line &l, const Point &p) { return !sgn((l.s
↪ - p) ^ (l.e - p)); }
15
16 bool on_segment(const Segment &l, const Point &p) {
17     return !sgn((l.s - p) ^ (l.e - p)) && sgn((l.s - p) * (l.e -
↪ p)) <= 0;
18 }
19

```

```

20 bool on_segment2(const Segment &l, const Point &p) { // assume
    ↪ p on Line l
    if (l.s == p || l.e == p) return true;
    if (min(l.s, l.e) < p && p < max(l.s, l.e)) return true;
    return false;
24 }
25
26 bool is_parallel(const Line &a, const Line &b) { return
    ↪ !sgn((a.s - a.e) ^ (b.s - b.e)); }
27 bool is_orthogonal(const Line &a, const Line &b) { return
    ↪ !sgn((a.s - a.e) * (b.s - b.e)); }
28
29 int is_intersect(const Segment &a, const Segment &b) {
30     auto d1 = sgn((a.e - a.s) ^ (b.s - a.s)), d2 = sgn((a.e -
    ↪ a.s) ^ (b.e - a.s));
31     auto d3 = sgn((b.e - b.s) ^ (a.s - b.s)), d4 = sgn((b.e -
    ↪ b.s) ^ (a.e - b.s));
32     if (d1 * d2 < 0 && d3 * d4 < 0) return 2; // intersect at
    ↪ non-end point
33     return (d1 == 0 && sgn((b.s - a.s) * (b.s - a.e)) <= 0) ||
34            (d2 == 0 && sgn((b.e - a.s) * (b.e - a.e)) <= 0) ||
35            (d3 == 0 && sgn((a.s - b.s) * (a.s - b.e)) <= 0) ||
36            (d4 == 0 && sgn((a.e - b.s) * (a.e - b.e)) <= 0);
37 }
38
39 int is_intersect(const Line &a, const Segment &b) {
40     auto d1 = sgn((a.e - a.s) ^ (b.s - a.s)), d2 = sgn((a.e -
    ↪ a.s) ^ (b.e - a.s));
41     if (d1 * d2 < 0) return 2; // intersect at non-end point
42     return d1 == 0 || d2 == 0;
43 }
44
45 Point intersect(const Line &a, const Line &b) {
46     auto u = a.e - a.s, v = b.e - b.s;
47     auto t = ((b.s - a.s) ^ v) / (u ^ v);
48     return a.s + u * t;
49 }
50
51 int is_intersect(const Circle &c, const Line &l) {
52     auto d = dist(c.o, l);
53     return sgn(d - c.r) < 0 ? 2 : !sgn(d - c.r);
54 }
55
56 vector<Point> intersect(const Circle &a, const Circle &b) {
57     vector relation = get_relation(a, b);
58     if (relation == Relation::INSIDE || relation ==
    ↪ Relation::SEPARATE) return {};
59     auto vec = b.o - a.o;
60     auto d2 = dist2(vec);
61     auto p = (d2 + a.r * a.r - b.r * b.r) / ((long double)2 *
    ↪ d2), h2 = a.r * a.r - p * p * d2;
62     auto mid = a.o + vec * p, per = perp(vec) * sqrt(max((long
    ↪ double)0, h2) / d2);
63     if (relation == Relation::OVERLAP)
64         return {mid + per, mid - per};
65     else
66         return {mid};
67 }
68
69 vector<Point> intersect(const Circle &c, const Line &l) {
70     if (!is_intersect(c, l)) return {};
71     auto v = l.e - l.s, t = v / dist(v);
72     Point a = l.s + t * ((c.o - l.s) * t);
73     auto d = sqrt(max((ld)0, c.r * c.r - dist2(c.o, a)));
74     if (!sgn(d)) return {a};
75     return {a - t * d, a + t * d};
76 }
77
78 int in_poly(const vector<Point> &p, const Point &a) {
79     int cnt = 0, n = (int)p.size();
80     for (int i = 0; i < n; i++) {
81         auto q = p[(i + 1) % n];
82         if (on_segment(Segment(p[i], q), a)) return 1; // on the
    ↪ edge of the polygon
83         cnt ^= ((a.y < p[i].y) - (a.y < q.y)) * ((p[i] - a) ^ (q -
    ↪ a)) > 0;
84     }
85     return cnt ? 2 : 0;
86 }
87
88 int is_intersect(const vector<Point> &p, const Line &a) {
89     // 1: touching, >=2: intersect count
90     int cnt = 0, edge_cnt = 0, n = (int)p.size();
91     for (int i = 0; i < n; i++) {
92         auto q = p[(i + 1) % n];
93         if (on_line(a, p[i]) && on_line(a, q)) return -1; //
    ↪ infinity
94         auto t = is_intersect(a, Segment(p[i], q));
95         (t == 1) && edge_cnt++, (t == 2) && cnt++;
96     }
97     return cnt + edge_cnt / 2;
98 }
99
100 vector<Point> tangent(const Circle &c, const Point &p) {
101     auto d = dist(c.o, p), l = c.r * c.r / d, h = sqrt(c.r * c.r
    ↪ - l * l);
102     auto v = (p - c.o) / d;
103     return {c.o + v * l + perp(v) * h, c.o + v * l - perp(v) *
    ↪ h};
104 }
105
106 Circle get_circumscribed(const Point &a, const Point &b, const
    ↪ Point &c) {
107     Line u((a + b) / 2, ((a + b) / 2) + perp(b - a));
108     Line v((b + c) / 2, ((b + c) / 2) + perp(c - b));
109     auto o = intersect(u, v);
110     return Circle(o, dist(o, a));
111 }
112
113 Circle get_inscribed(const Point &a, const Point &b, const
    ↪ Point &c) {
114     auto l1 = dist(b - c), l2 = dist(c - a), l3 = dist(a - b);
115     Point o = (a * l1 + b * l2 + c * l3) / (l1 + l2 + l3);
116     return Circle(o, dist(o, Line(a, b)));
117 }
118
119 pair<ld, ld> get_centroid(const vector<Point> &p) {
120     int n = (int)p.size();
121     ld x = 0, y = 0, sum = 0;
122     auto a = p[0], b = p[1];
123     for (int i = 2; i < n; i++) {
124         auto c = p[i];
125         auto s = area({a, b, c});
126         sum += s;
127         x += s * (a.x + b.x + c.x);
128         y += s * (a.y + b.y + c.y);
129         swap(b, c);
130     }
131     return {x / (3 * sum), y / (3 * sum)};
132 }
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955

```

Area

```

1 auto area(const vector<Point> &p) {
2     int n = (int)p.size();
3     long double area = 0;
4     for (int i = 0; i < n; i++) area += p[i] ^ p[(i + 1) % n];
5     return area / 2.0;
6 }
7
8 auto area(const Point &a, const Point &b, const Point &c) {
9     return ((long double)((b - a) ^ (c - a))) / 2.0;
10 }
11
12 auto area2(const Point &a, const Point &b, const Point &c) {
13     ↪ return (b - a) ^ (c - a); }
14
15 auto area_intersect(const Circle &c, const vector<Point> &ps)
    ↪ {
16     int n = (int)ps.size();
17     auto arg = [&](const Point &p, const Point &q) { return
    ↪ atan2(p ^ q, p * q); };
18     auto tri = [&](const Point &p, const Point &q) {
19         auto r2 = c.r * c.r / (long double)2;
20     }
21 }

```

```

19     auto d = q - p;
20     auto a = d * p / dist2(d), b = (dist2(p) - c.r * c.r) /
↳ dist2(d);
21     long double det = a * a - b;
22     if (sgn(det) <= 0) return arg(p, q) * r2;
23     auto s = max((long double)0, -a - sqrt(det)), t =
↳ min((long double)1, -a + sqrt(det));
24     if (sgn(t) < 0 || sgn(1 - s) <= 0) return arg(p, q) * r2;
25     auto u = p + d * s, v = p + d * t;
26     return arg(p, u) * r2 + (u ^ v) / 2 + arg(v, q) * r2;
27 };
28 long double sum = 0;
29 for (int i = 0; i < n; i++) sum += tri(ps[i] - c.o, ps[(i +
↳ 1) % n] - c.o);
30 return sum;
31 }
32
33 auto adaptive_simpson(ld _l, ld _r, function<ld(ld)> f) {
34     auto simpson = [&](ld l, ld r) { return (r - l) * (f(l) + 4
↳ * f((l + r) / 2) + f(r)) / 6; };
35     function<ld(ld, ld, ld)> asr = [&](ld l, ld r, ld s) {
36         auto mid = (l + r) / 2;
37         auto left = simpson(l, mid), right = simpson(mid, r);
38         if (!sgn(left + right - s)) return left + right;
39         return asr(l, mid, left) + asr(mid, r, right);
40     };
41     return asr(_l, _r, simpson(_l, _r));
42 }
43
44 vector<Point> half_plane_intersect(vector<Line> &L) {
45     int n = (int)L.size(), l = 0, r = 0; // [left, right]
46     sort(L.begin(), L.end());
47     [(const Line &a, const Line &b) { return rad(a.s -
↳ a.e) < rad(b.s - b.e); }];
48     vector<Point> p(n), res;
49     vector<Line> q(n);
50     q[0] = L[0];
51     for (int i = 1; i < n; i++) {
52         while (l < r && sgn((L[i].e - L[i].s) ^ (p[r - 1] -
↳ L[i].s)) <= 0) r--;
53         while (l < r && sgn((L[i].e - L[i].s) ^ (p[l] - L[i].s))
↳ <= 0) l++;
54         q[++r] = L[i];
55         if (sgn((q[r].e - q[r].s) ^ (q[r - 1].e - q[r - 1].s)) ==
↳ 0) {
56             r--;
57             if (sgn((q[r].e - q[r].s) ^ (L[i].s - q[r].s)) > 0) q[r]
↳ = L[i];
58         }
59         if (l < r) p[r - 1] = intersect(q[r - 1], q[r]);
60     }
61     while (l < r && sgn((q[l].e - q[l].s) ^ (p[r - 1] - q[l].s))
↳ <= 0) r--;
62     if (r - l <= 1) return {};
63     p[r] = intersect(q[r], q[l]);
64     return vector<Point>(p.begin() + 1, p.begin() + r + 1);
65 }

```

Convex

```

1 vector<Point> get_convex(vector<Point> &points, bool
↳ allow_collinear = false) {
2     // strict, no repeat, two pass
3     sort(points.begin(), points.end());
4     points.erase(unique(points.begin(), points.end()),
↳ points.end());
5     vector<Point> L, U;
6     for (auto &t : points) {
7         for (ll sz = L.size(); sz > 1 && (sgn((t - L[sz - 2]) ^
↳ (L[sz - 1] - L[sz - 2])) >= 0);
8             L.pop_back(), sz = L.size()) {
9         }
10        L.push_back(t);
11    }
12    for (auto &t : points) {
13        for (ll sz = U.size(); sz > 1 && (sgn((t - U[sz - 2]) ^
↳ (U[sz - 1] - U[sz - 2])) <= 0);

```

```

14        U.pop_back(), sz = U.size()) {
15        }
16        U.push_back(t);
17    }
18    // contain repeats if all collinear, use a set to remove
↳ repeats
19    if (allow_collinear) {
20        for (int i = (int)U.size() - 2; i >= 1; i--)
↳ L.push_back(U[i]);
21    } else {
22        set<Point> st(L.begin(), L.end());
23        for (int i = (int)U.size() - 2; i >= 1; i--) {
24            if (st.count(U[i]) == 0) L.push_back(U[i]),
↳ st.insert(U[i]);
25        }
26    }
27    return L;
28 }
29
30 vector<Point> get_convex2(vector<Point> &points, bool
↳ allow_collinear = false) { // strict, no repeat, one pass
31     nth_element(points.begin(), points.begin(), points.end());
32     sort(points.begin() + 1, points.end(), [&](const Point &a,
↳ const Point &b) {
33         int rad_diff = sgn((a - points[0]) ^ (b - points[0]));
34         return !rad_diff ? (dist2(a - points[0]) < dist2(b -
↳ points[0])) : (rad_diff > 0);
35     });
36     if (allow_collinear) {
37         int i = (int)points.size() - 1;
38         while (i >= 0 && !sgn((points[i] - points[0]) ^ (points[i]
↳ - points.back()))) i--;
39         reverse(points.begin() + i + 1, points.end());
40     }
41     vector<Point> hull;
42     for (auto &t : points) {
43         for (ll sz = hull.size();
44             sz > 1 && (sgn((t - hull[sz - 2]) ^ (hull[sz - 1] -
↳ hull[sz - 2])) >= allow_collinear);
45             hull.pop_back(), sz = hull.size()) {
46         }
47         hull.push_back(t);
48     }
49     return hull;
50 }
51
52 vector<Point> get_convex_safe(vector<Point> points, bool
↳ allow_collinear = false) {
53     return get_convex(points, allow_collinear);
54 }
55
56 vector<Point> get_convex2_safe(vector<Point> points, bool
↳ allow_collinear = false) {
57     return get_convex2(points, allow_collinear);
58 }
59
60 bool is_convex(const vector<Point> &p, bool allow_collinear =
↳ false) {
61     int n = p.size();
62     int lo = 1, hi = -1;
63     for (int i = 0; i < n; i++) {
64         int cur = sgn((p[(i + 2) % n] - p[(i + 1) % n]) ^ (p[(i +
↳ 1) % n] - p[i]));
65         lo = min(lo, cur); hi = max(hi, cur);
66     }
67     return allow_collinear ? (hi - lo) < 2 : (lo == hi && lo);
68 }
69
70 auto rotating_calipers(const vector<Point> &hull) {
71     // use get_convex2
72     int n = (int)hull.size(); // return the square of longest
↳ dist
73     assert(n > 1);
74     if (n <= 2) return dist2(hull[0], hull[1]);
75     ld res = 0;
76     for (int i = 0, j = 2; i < n; i++) {
77         auto d = hull[i], e = hull[(i + 1) % n];

```

```

78     while (area2(d, e, hull[j]) < area2(d, e, hull[(j + 1) %
↪ n])) j = (j + 1) % n;
79     res = max(res, max(dist2(d, hull[j]), dist2(e, hull[j])));
80 }
81 return res;
82 }
83
84 // Find polygon cut to the left of l
85 vector<Point> convex_cut(const vector<Point> &p, const Line
↪ &l) {
86     int n = p.size();
87     vector<Point> cut;
88     for (int i = 0; i < n; i++) {
89         auto a = p[i], b = p[(i + 1) % n];
90         if (sgn((l.e - l.s) ^ (a - l.s)) >= 0)
91             cut.push_back(a);
92         if (sgn((l.e - l.s) ^ (a - l.s)) * sgn((l.e - l.s) ^ (b -
↪ l.s)) == -1)
93             cut.push_back(intersect(Line(a, b), l));
94     }
95     return cut;
96 }
97
98 // Sort by angle in range [0, 2pi)
99 template <class RandomIt>
100 void polar_sort(RandomIt first, RandomIt last, Point origin =
↪ Point(0, 0)) {
101     auto get_quad = [&](const Point& p) {
102         Point diff = p - origin;
103         if (diff.x > 0 && diff.y >= 0) return 1;
104         if (diff.x <= 0 && diff.y > 0) return 2;
105         if (diff.x < 0 && diff.y <= 0) return 3;
106         return 4;
107     };
108     auto polar_cmp = [&](const Point& p1, const Point& p2) {
109         int q1 = get_quad(p1), q2 = get_quad(p2);
110         if (q1 != q2) return q1 < q2;
111         return ((p1 - origin) ^ (p2 - origin)) > 0;
112     };
113     sort(first, last, polar_cmp);
114 }

```

Basic 3D

```

1 using ll = long long;
2 using ld = long double;
3
4 constexpr auto eps = 1e-8;
5 const auto PI = acos(-1);
6 int sgn(ld x) { return (abs(x) <= eps) ? 0 : (x < 0 ? -1 : 1);
↪ }
7
8 struct Point3D {
9     ld x = 0, y = 0, z = 0;
10     Point3D() = default;
11     Point3D(ld _x, ld _y, ld _z) : x(_x), y(_y), z(_z) {}
12     bool operator<(const Point3D &p) const { return !sgn(p.x -
↪ x) ? (!sgn(p.y - y) ? sgn(p.z - z) < 0 : y < p.y) : x <
↪ p.x; }
13     bool operator==(const Point3D &p) const { return !sgn(p.x -
↪ x) && !sgn(p.y - y) && !sgn(p.z - z); }
14     Point3D operator+(const Point3D &p) const { return {x + p.x,
↪ y + p.y, z + p.z}; }
15     Point3D operator-(const Point3D &p) const { return {x - p.x,
↪ y - p.y, z - p.z}; }
16     Point3D operator*(ld a) const { return {x * a, y * a, z *
↪ a}; }
17     Point3D operator/(ld a) const { return {x / a, y / a, z /
↪ a}; }
18     auto operator*(const Point3D &p) const { return x * p.x + y
↪ * p.y + z * p.z; } // dot
19     Point3D operator^(const Point3D &p) const { return {y * p.z
↪ - z * p.y, z * p.x - x * p.z, x * p.y - y * p.x}; } //
↪ cross
20     friend auto &operator>>(istream &i, Point3D &p) { return i
↪ >> p.x >> p.y >> p.z; }
21 };

```

```

22 struct Line3D {
23     Point3D s = {0, 0, 0}, e = {0, 0, 0};
24     Line3D() = default;
25     Line3D(Point3D _s, Point3D _e) : s(_s), e(_e) {}
26 };
27
28 struct Segment3D : Line3D {
29     using Line3D::Line3D;
30 };
31
32 auto dist2(const Point3D &a) { return a * a; }
33 auto dist2(const Point3D &a, const Point3D &b) { return
↪ dist2(a - b); }
34 auto dist(const Point3D &a) { return sqrt(dist2(a)); }
35 auto dist(const Point3D &a, const Point3D &b) { return
↪ sqrt(dist2(a - b)); }
36 auto dist(const Point3D &a, const Line3D &l) { return dist((a
↪ - l.s) ^ (l.e - l.s)) / dist(l.s, l.e); }
37 auto dist(const Point3D &p, const Segment3D &l) {
38     if (l.s == l.e) return dist(p, l.s);
39     auto d = dist2(l.s, l.e), t = min(d, max((ld)0, (p - l.s) *
↪ (l.e - l.s)));
40     return dist((p - l.s) * d, (l.e - l.s) * t) / d;
41 }
42

```

Miscellaneous

```

1 tuple<int,int,ld> closest_pair(vector<Point> &p) {
2     using Pt = pair<Point,int>;
3     int n = p.size();
4     assert(n > 1);
5     vector<Pt> pts(n), buf;
6     for (int i = 0; i < n; i++) pts[i] = {p[i], i};
7     sort(pts.begin(), pts.end());
8     buf.reserve(n);
9     auto cmp_y = [&](const Pt& p1, const Pt& p2) { return
↪ p1.first.y < p2.first.y; };
10     function<tuple<int,int,ld>(int, int)> recurse = [&](int l,
↪ int r) -> tuple<int,int,ld> {
11         int i = pts[l].second, j = pts[l + 1].second;
12         ld d = dist(pts[l].first, pts[l + 1].first);
13         if (r - l < 5) {
14             for (int a = l; a < r; a++) for (int b = a + 1; b < r;
↪ b++) {
15                 ld cur = dist(pts[a].first, pts[b].first);
16                 if (cur < d) { i = pts[a].second; j = pts[b].second; d
↪ = cur; }
17             }
18             sort(pts.begin() + l, pts.begin() + r, cmp_y);
19         }
20         else {
21             int mid = (l + r) / 2;
22             ld x = pts[mid].first.x;
23             auto [li, lj, ldist] = recurse(l, mid);
24             auto [ri, rj, rdist] = recurse(mid, r);
25             if (ldist < rdist) { i = li; j = lj; d = ldist; }
26             else { i = ri; j = rj; d = rdist; }
27             inplace_merge(pts.begin() + l, pts.begin() + mid,
↪ pts.begin() + r, cmp_y);
28             buf.clear();
29             for (int a = l; a < r; a++) {
30                 if (abs(x - pts[a].first.x) >= d) continue;
31                 for (int b = buf.size() - 1; b >= 0; b--) {
32                     if (pts[a].first.y - buf[b].first.y >= d) break;
33                     ld cur = dist(pts[a].first, buf[b].first);
34                     if (cur < d) { i = pts[a].second; j = buf[b].second;
↪ d = cur; }
35                 }
36                 buf.push_back(pts[a]);
37             }
38             return {i, j, d};
39         }
40     };
41     return recurse(0, n);
42 }
43

```

```

44 Line abc_to_line(ld a, ld b, ld c) {
45     assert(!sgn(a) || !sgn(b));
46     if(a == 0) return Line(Point(0, -c/b), Point(1, -c/b));
47     if(b == 0) return Line(Point(-c/a, 0), Point(-c/a, 1));
48     Point s(0, -c/b), e(1, (-c - a)/b), diff = e - s;
49     return Line(s, s + diff/dist(diff));
50 }
51
52 tuple<ld,ld,ld> line_to_abc(const Line& l) {
53     Point diff = l.e - l.s;
54     return {-diff.y, diff.x, -(diff ^ l.s)};
55 }

```

Graph Theory

Max Flow

```

1 struct Edge {
2     int from, to, cap, remain;
3 };
4
5 struct Dinic {
6     int n;
7     vector<Edge> e;
8     vector<vector<int>> g;
9     vector<int> d, cur;
10    Dinic(int _n) : n(_n), g(n), d(n), cur(n) {}
11    void add_edge(int u, int v, int c) {
12        g[u].push_back((int)e.size());
13        e.push_back({u, v, c, c});
14        g[v].push_back((int)e.size());
15        e.push_back({v, u, 0, 0});
16    }
17    ll max_flow(int s, int t) {
18        int inf = 1e9;
19        auto bfs = [&]() {
20            fill(d.begin(), d.end(), inf), fill(cur.begin(),
21                cur.end(), 0);
22            d[s] = 0;
23            vector<int> q{s}, nq;
24            for (int step = 1; q.size(); swap(q, nq), nq.clear(),
25                step++) {
26                for (auto& node : q) {
27                    for (auto& edge : g[node]) {
28                        int ne = e[edge].to;
29                        if (!e[edge].remain || d[ne] <= step) continue;
30                        d[ne] = step, nq.push_back(ne);
31                        if (ne == t) return true;
32                    }
33                }
34            }
35            return false;
36        };
37        function<int(int, int)> find = [&](int node, int limit) {
38            if (node == t || !limit) return limit;
39            int flow = 0;
40            for (int i = cur[node]; i < g[node].size(); i++) {
41                cur[node] = i;
42                int edge = g[node][i], oe = edge ^ 1, ne = e[edge].to;
43                if (!e[edge].remain || d[ne] != d[node] + 1) continue;
44                if (int temp = find(ne, min(limit - flow,
45                    e[edge].remain))) {
46                    e[edge].remain -= temp, e[oe].remain += temp, flow
47                    += temp;
48                } else {
49                    d[ne] = -1;
50                }
51                if (flow == limit) break;
52            }
53            return flow;
54        };
55        ll res = 0;
56        while (bfs())
57            while (int flow = find(s, inf)) res += flow;
58        return res;
59    }

```

```

56 };
57
58 • USAGE
59
60 1 int main() {
61     int n, m, s, t;
62     cin >> n >> m >> s >> t;
63     Dinic dinic(n);
64     for (int i = 0, u, v, c; i < m; i++) {
65         cin >> u >> v >> c;
66         dinic.add_edge(u - 1, v - 1, c);
67     }
68     cout << dinic.max_flow(s - 1, t - 1) << '\n';
69 }

```

PushRelabel Max-Flow (faster)

```

1 //
2 ↪ https://github.com/kth-competitive-programming/kactl/blob/main/contest/flow/pushrelabel.cpp
3 #define rep(i, a, b) for (int i = a; i < (b); ++i)
4 #define all(x) begin(x), end(x)
5 #define sz(x) (int)(x).size()
6 typedef long long ll;
7 typedef pair<int, int> pii;
8 typedef vector<int> vi;
9
10 struct PushRelabel {
11     struct Edge {
12         int dest, back;
13         ll f, c;
14     };
15     vector<vector<Edge>> g;
16     vector<ll> ec;
17     vector<Edge*> cur;
18     vector<vi> hs;
19     vi H;
20     PushRelabel(int n) : g(n), ec(n), cur(n), hs(2 * n), H(n) {}
21
22     void addEdge(int s, int t, ll cap, ll rcap = 0) {
23         if (s == t) return;
24         g[s].push_back({t, sz(g[t]), 0, cap});
25         g[t].push_back({s, sz(g[s]) - 1, 0, rcap});
26     }
27
28     void addFlow(Edge& e, ll f) {
29         Edge& back = g[e.dest][e.back];
30         if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.dest);
31         e.f += f;
32         e.c -= f;
33         ec[e.dest] += f;
34         back.f -= f;
35         back.c += f;
36         ec[back.dest] -= f;
37     }
38
39     ll calc(int s, int t) {
40         int v = sz(g);
41         H[s] = v;
42         ec[t] = 1;
43         vi co(2 * v);
44         co[0] = v - 1;
45         rep(i, 0, v) cur[i] = g[i].data();
46         for (Edge& e : g[s]) addFlow(e, e.c);
47
48         for (int hi = 0;;) {
49             while (hs[hi].empty())
50                 if (!hi--) return -ec[s];
51             int u = hs[hi].back();
52             hs[hi].pop_back();
53             while (ec[u] > 0) // discharge u
54                 if (cur[u] == g[u].data() + sz(g[u])) {
55                     H[u] = 1e9;
56                     for (Edge& e : g[u])
57                         if (e.c && H[u] > H[e.dest] + 1) H[u] = H[e.dest]
58                         + 1, cur[u] = &e;
59                     if (++co[H[u]], !--co[hi] && hi < v)
60                         rep(i, 0, v) if (hi < H[i] && H[i] < v)--
61                         co[H[i]], H[i] = v + 1;
62                 }
63         }
64     }

```



```

58         hi = H[u];
59     } else if (cur[u]->c && H[u] == H[cur[u]->dest] + 1)
60         addFlow(*cur[u], min(ec[u], cur[u]->c));
61     else
62         ++cur[u];
63 }
64 }
65 bool leftOfMinCut(int a) { return H[a] >= sz(g); }
66 };

```

Min-Cost Max-Flow

```

1 class MCMF {
2 public:
3     static constexpr int INF = 1e9;
4     const int n;
5     vector<tuple<int, int, int>> e;
6     vector<vector<int>> g;
7     vector<int> h, dis, pre;
8     bool dijkstra(int s, int t) {
9         dis.assign(n, INF);
10        pre.assign(n, -1);
11        priority_queue<pair<int, int>, vector<pair<int, int>>,
12        ⇨ greater<>> que;
13        dis[s] = 0;
14        que.emplace(0, s);
15        while (!que.empty()) {
16            auto [d, u] = que.top();
17            que.pop();
18            if (dis[u] != d) continue;
19            for (int i : g[u]) {
20                auto [v, f, c] = e[i];
21                if (c > 0 && dis[v] > d + h[u] - h[v] + f) {
22                    dis[v] = d + h[u] - h[v] + f;
23                    pre[v] = i;
24                    que.emplace(dis[v], v);
25                }
26            }
27            return dis[t] != INF;
28        }
29        MCMF(int n) : n(n), g(n) {}
30        void add_edge(int u, int v, int fee, int c) {
31            g[u].push_back(e.size());
32            e.emplace_back(v, fee, c);
33            g[v].push_back(e.size());
34            e.emplace_back(u, -fee, 0);
35        }
36        pair<ll, ll> max_flow(const int s, const int t) {
37            int flow = 0, cost = 0;
38            h.assign(n, 0);
39            while (dijkstra(s, t)) {
40                for (int i = 0; i < n; ++i) h[i] += dis[i];
41                for (int i = t; i != s; i = get<0>(e[pre[i] ^ 1])) {
42                    --get<2>(e[pre[i]]);
43                    ++get<2>(e[pre[i] ^ 1]);
44                }
45                ++flow;
46                cost += h[t];
47            }
48            return {flow, cost};
49        }
50    };

```

Max Cost Feasible Flow

```

1 struct Edge {
2     int from, to, cap, remain, cost;
3 };
4
5 struct MCMF {
6     int n;
7     vector<Edge> e;
8     vector<vector<int>> g;
9     vector<ll> d, pre;
10    MCMF(int _n) : n(_n), g(n), d(n), pre(n) {}

```

```

11    void add_edge(int u, int v, int c, int w) {
12        g[u].push_back((int)e.size());
13        e.push_back({u, v, c, w});
14        g[v].push_back((int)e.size());
15        e.push_back({v, u, 0, -w});
16    }
17    pair<ll, ll> max_flow(int s, int t) {
18        ll inf = 1e18;
19        auto spfa = [&]() {
20            fill(d.begin(), d.end(), -inf); // important!
21            vector<int> f(n), seen(n);
22            d[s] = 0, f[s] = 1e9;
23            vector<int> q{s}, nq;
24            for (; q.size(); swap(q, nq), nq.clear()) {
25                for (auto& node : q) {
26                    seen[node] = false;
27                    for (auto& edge : g[node]) {
28                        int ne = e[edge].to, cost = e[edge].cost;
29                        if (!e[edge].remain || d[ne] >= d[node] + cost)
⇨ continue;
30                        d[ne] = d[node] + cost, pre[ne] = edge;
31                        f[ne] = min(e[edge].remain, f[node]);
32                        if (!seen[ne]) seen[ne] = true, nq.push_back(ne);
33                    }
34                }
35            }
36            return f[t];
37        };
38        ll flow = 0, cost = 0;
39        while (int temp = spfa()) {
40            if (d[t] < 0) break; // important!
41            flow += temp, cost += temp * d[t];
42            for (ll i = t; i != s; i = e[pre[i]].from) {
43                e[pre[i]].remain -= temp, e[pre[i] ^ 1].remain +=
⇨ temp;
44            }
45        }
46        return {flow, cost};
47    }
48 };

```

Heavy-Light Decomposition

```

1 int root = 0, cur = 0;
2 vector<int> parent(n), deep(n), hson(n, -1), top(n), sz(n),
⇨ dfn(n, -1);
3 function<int(int, int, int)> dfs = [&](int node, int fa, int
⇨ dep) {
4     deep[node] = dep, sz[node] = 1, parent[node] = fa;
5     for (auto &ne : g[node]) {
6         if (ne == fa) continue;
7         sz[node] += dfs(ne, node, dep + 1);
8         if (hson[node] == -1 || sz[ne] > sz[hson[node]]) hson[node]
⇨ = ne;
9     }
10    return sz[node];
11 };
12 function<void(int, int)> dfs2 = [&](int node, int t) {
13     top[node] = t, dfn[node] = cur++;
14     if (hson[node] == -1) return;
15     dfs2(hson[node], t);
16     for (auto &ne : g[node]) {
17         if (ne == parent[node] || ne == hson[node]) continue;
18         dfs2(ne, ne);
19     }
20 };
21 // read in graph as vector<vector<int>> g(n)
22 dfs(root, -1, 0), dfs2(root, root);

```

• USAGE: get LCA

```

1 function<int(int, int)> lca = [&](int x, int y) {
2     while (top[x] != top[y]) {
3         if (deep[top[x]] < deep[top[y]]) swap(x, y);
4         x = parent[top[x]];
5     }
6     return deep[x] < deep[y] ? x : y;

```

```

7 };

1 vector<ll> light(n);
2 SegTree heavy(n), form_parent(n);
3 // cin >> x >> y, x--, y--;
4 int z = lca(x, y);
5 while (x != z) {
6     if (dfn[top[x]] <= dfn[top[z]]) {
7         // [dfn[z], dfn[x]], from heavy
8         heavy.modify(dfn[z], dfn[x], 1);
9         break;
10    }
11    // x -> top[x];
12    heavy.modify(dfn[top[x]], dfn[x], 1);
13    light[parent[top[x]]] += a[top[x]];
14    x = parent[top[x]];
15 }
16 while (y != z) {
17     if (dfn[top[y]] <= dfn[top[z]]) {
18         // [dfn[z], dfn[y]], from heavy
19         form_parent.modify(dfn[z] + 1, dfn[y] + 1, 1);
20         break;
21     }
22     // y -> top[y];
23     form_parent.modify(dfn[top[y]], dfn[y] + 1, 1);
24     y = parent[top[y]];
25 }

```

General Unweight Graph Matching

- Complexity: $O(n^3)$ (?)

```

1 struct BlossomMatch {
2     int n;
3     vector<vector<int>> e;
4     BlossomMatch(int _n) : n(_n), e(_n) {}
5     void add_edge(int u, int v) { e[u].push_back(v),
6     e[v].push_back(u); }
7     vector<int> find_matching() {
8         vector<int> match(n, -1), vis(n), link(n), f(n), dep(n);
9         function<int(int)> find = [&](int x) { return f[x] == x ?
10         x : (f[x] = find(f[x])); };
11         auto lca = [&](int u, int v) {
12             u = find(u), v = find(v);
13             while (u != v) {
14                 if (dep[u] < dep[v]) swap(u, v);
15                 u = find(link[match[u]]);
16             }
17             return u;
18         };
19         queue<int> que;
20         auto blossom = [&](int u, int v, int p) {
21             while (find(u) != p) {
22                 link[u] = v, v = match[u];
23                 if (vis[v] == 0) vis[v] = 1, que.push(v);
24                 f[u] = f[v] = p, u = link[v];
25             }
26         };
27         // find an augmenting path starting from u and augment (if
28         exist)
29         auto augment = [&](int node) {
30             while (!que.empty()) que.pop();
31             iota(f.begin(), f.end(), 0);
32             // vis = 0 corresponds to inner vertices, vis = 1
33             corresponds to outer vertices
34             fill(vis.begin(), vis.end(), -1);
35             que.push(node);
36             vis[node] = 1, dep[node] = 0;
37             while (!que.empty()) {
38                 int u = que.front();
39                 que.pop();
40                 for (auto v : e[u]) {
41                     if (vis[v] == -1) {
42                         vis[v] = 0, link[v] = u, dep[v] = dep[u] + 1;
43                         // found an augmenting path
44                         if (match[v] == -1) {

```

```

45                 for (int x = v, y = u, temp; y != -1; x = temp,
46                 y = x == -1 ? -1 : link[x]) {
47                     temp = match[y], match[x] = y, match[y] = x;
48                 }
49                 return;
50             }
51             vis[match[v]] = 1, dep[match[v]] = dep[u] + 2;
52             que.push(match[v]);
53         } else if (vis[v] == 1 && find(v) != find(u)) {
54             // found a blossom
55             int p = lca(u, v);
56             blossom(u, v, p), blossom(v, u, p);
57         }
58     }
59 }
60 };
61 // find a maximal matching greedily (decrease constant)
62 auto greedy = [&]() {
63     for (int u = 0; u < n; ++u) {
64         if (match[u] != -1) continue;
65         for (auto v : e[u]) {
66             if (match[v] == -1) {
67                 match[u] = v, match[v] = u;
68                 break;
69             }
70         }
71     }
72     greedy();
73     for (int u = 0; u < n; ++u)
74         if (match[u] == -1) augment(u);
75     return match;
76 }
77 };

```

Maximum Bipartite Matching

- Needs dinic, complexity $\approx O(n + m\sqrt{n})$

```

1 struct BipartiteMatch {
2     int l, r;
3     Dinic dinic = Dinic(0);
4     BipartiteMatch(int _l, int _r) : l(_l), r(_r) {
5         dinic = Dinic(l + r + 2);
6         for (int i = 1; i <= l; i++) dinic.add_edge(0, i, 1);
7         for (int i = 1; i <= r; i++) dinic.add_edge(l + i, l + r +
8         1, 1);
9     }
10    void add_edge(int u, int v) { dinic.add_edge(u + 1, l + v +
11    1, 1); }
12    ll max_matching() { return dinic.max_flow(0, l + r + 1); }
13 };

```

2-SAT and Strongly Connected Components

```

1 void scc(vector<vector<int>>& g, int* idx) {
2     int n = g.size(), ct = 0;
3     int out[n];
4     vector<int> ginv[n];
5     memset(out, -1, sizeof out);
6     memset(idx, -1, n * sizeof(int));
7     function<void(int)> dfs = [&](int cur) {
8         out[cur] = INT_MAX;
9         for (int v : g[cur]) {
10             ginv[v].push_back(cur);
11             if (out[v] == -1) dfs(v);
12         }
13         ct++; out[cur] = ct;
14     };
15     vector<int> order;
16     for (int i = 0; i < n; i++) {
17         order.push_back(i);
18         if (out[i] == -1) dfs(i);
19     }
20     sort(order.begin(), order.end(), [&](int& u, int& v) {
21         return out[u] > out[v];
22     });
23 }

```

```

22     });
23     ct = 0;
24     stack<int> s;
25     auto dfs2 = [&](int start) {
26         s.push(start);
27         while(!s.empty()) {
28             int cur = s.top();
29             s.pop();
30             idx[cur] = ct;
31             for(int v : ginv[cur])
32                 if(idx[v] == -1) s.push(v);
33         }
34     };
35     for(int v : order) {
36         if(idx[v] == -1) {
37             dfs2(v);
38             ct++;
39         }
40     }
41 }
42
43 // 0 => impossible, 1 => possible
44 pair<int, vector<int>> sat2(int n, vector<pair<int, int>>&
45     ↪ clauses) {
46     vector<int> ans(n);
47     vector<vector<int>> g(2*n + 1);
48     for(auto [x, y] : clauses) {
49         x = x < 0 ? -x + n : x;
50         y = y < 0 ? -y + n : y;
51         int nx = x <= n ? x + n : x - n;
52         int ny = y <= n ? y + n : y - n;
53         g[nx].push_back(y);
54         g[ny].push_back(x);
55     }
56     int idx[2*n + 1];
57     scc(g, idx);
58     for(int i = 1; i <= n; i++) {
59         if(idx[i] == idx[i + n]) return {0, {}};
60         ans[i - 1] = idx[i + n] < idx[i];
61     }
62     return {1, ans};
63 }

```

Enumerating Triangles

- Complexity: $O(n + m\sqrt{m})$

```

1 void enumerate_triangles(vector<pair<int, int>>& edges,
2     ↪ function<void(int, int, int)> f) {
3     int n = 0;
4     for(auto [u, v] : edges) n = max({n, u + 1, v + 1});
5     vector<int> deg(n);
6     vector<int> g[n];
7     for(auto [u, v] : edges) {
8         deg[u]++;
9         deg[v]++;
10    }
11    for(auto [u, v] : edges) {
12        if(u == v) continue;
13        if(deg[u] > deg[v] || (deg[u] == deg[v] && u > v))
14            swap(u, v);
15        g[u].push_back(v);
16    }
17    vector<int> flag(n);
18    for(int i = 0; i < n; i++) {
19        for(int v : g[i]) flag[v] = 1;
20        for(int v : g[i]) for(int u : g[v]) {
21            if(flag[u]) f(i, v, u);
22        }
23        for(int v : g[i]) flag[v] = 0;
24    }
25 }

```

Tarjan

- shrink all circles into points (2-edge-connected-component)

```

1 int cnt = 0, now = 0;
2 vector<ll> dfn(n, -1), low(n), belong(n, -1), stk;
3 function<void(ll, ll)> tarjan = [&](ll node, ll fa) {
4     dfn[node] = low[node] = now++; stk.push_back(node);
5     for (auto& ne : g[node]) {
6         if (ne == fa) continue;
7         if (dfn[ne] == -1) {
8             tarjan(ne, node);
9             low[node] = min(low[node], low[ne]);
10        } else if (belong[ne] == -1) {
11            low[node] = min(low[node], dfn[ne]);
12        }
13    }
14    if (dfn[node] == low[node]) {
15        while (true) {
16            auto v = stk.back();
17            belong[v] = cnt;
18            stk.pop_back();
19            if (v == node) break;
20        }
21        ++cnt;
22    }
23 };

```

- 2-vertex-connected-component / Block forest

```

1 int cnt = 0, now = 0;
2 vector<vector<ll>> e1(n);
3 vector<ll> dfn(n, -1), low(n), stk;
4 function<void(ll)> tarjan = [&](ll node) {
5     dfn[node] = low[node] = now++; stk.push_back(node);
6     for (auto& ne : g[node]) {
7         if (dfn[ne] == -1) {
8             tarjan(ne);
9             low[node] = min(low[node], low[ne]);
10            if (low[ne] == dfn[node]) {
11                e1.push_back({});
12                while (true) {
13                    auto x = stk.back();
14                    stk.pop_back();
15                    e1[n + cnt].push_back(x);
16                    // e1[x].push_back(n + cnt); // undirected
17                    if (x == ne) break;
18                }
19                e1[node].push_back(n + cnt);
20                // e1[n + cnt].push_back(node); // undirected
21                cnt++;
22            }
23        } else {
24            low[node] = min(low[node], dfn[ne]);
25        }
26    }
27 };

```

Kruskal reconstruct tree

```

1 int _n, m;
2 cin >> _n >> m; // _n: # of node, m: # of edge
3 int n = 2 * _n - 1; // root: n-1
4 vector<array<int, 3>> edges(m);
5 for (auto& [w, u, v] : edges) {
6     cin >> u >> v >> w, u--, v--;
7 }
8 sort(edges.begin(), edges.end());
9 vector<int> p(n);
10 iota(p.begin(), p.end(), 0);
11 function<int(int)> find = [&](int x) { return p[x] == x ? x :
12     ↪ (p[x] = find(p[x])); };
13 auto merge = [&](int x, int y) { p[find(x)] = find(y); };
14 vector<vector<int>> g(n);
15 vector<int> val(m);
16 val.reserve(n);

```



```

16 for (auto [w, u, v] : edges) {
17     u = find(u), v = find(v);
18     if (u == v) continue;
19     val.push_back(w);
20     int node = (int)val.size() - 1;
21     g[node].push_back(u), g[node].push_back(v);
22     merge(u, node), merge(v, node);
23 }

```

Math

Inverse

```

1 ll inv(ll a, ll m) { return a == 1 ? 1 : ((m - m / a) * inv(m
    ↪ % a, m) % m); }
2 // or
3 power(a, MOD - 2)

```

- USAGE: get factorial

```

1 vector<Z> f(MAX_N, 1), rf(MAX_N, 1);
2 for (int i = 2; i < MAX_N; i++) f[i] = f[i - 1] * i % MOD;
3 rf[MAX_N - 1] = power(f[MAX_N - 1], MOD - 2);
4 for (int i = MAX_N - 2; i > 1; i--) rf[i] = rf[i + 1] * (i +
    ↪ 1) % MOD;
5 auto binom = [&](ll n, ll r) -> Z {
6     if (n < 0 || r < 0 || n < r) return 0;
7     return f[n] * rf[n - r] * rf[r];
8 };

```

Mod Class

```

1 constexpr ll norm(ll x) { return (x % MOD + MOD) % MOD; }
2 template <typename T>
3 constexpr T power(T a, ll b, T res = 1) {
4     for (; b; b /= 2, (a *= a) %= MOD)
5         if (b & 1) (res *= a) %= MOD;
6     return res;
7 }
8 struct Z {
9     ll x;
10    constexpr Z(ll _x = 0) : x(norm(_x)) {}
11    // auto operator<=>(const Z &) const = default; // cpp20
    ↪ only
12    Z operator-() const { return Z(norm(MOD - x)); }
13    Z inv() const { return power(*this, MOD - 2); }
14    Z &operator*=(const Z &rhs) { return x = x * rhs.x % MOD,
    ↪ *this; }
15    Z &operator+=(const Z &rhs) { return x = norm(x + rhs.x),
    ↪ *this; }
16    Z &operator-=(const Z &rhs) { return x = norm(x - rhs.x),
    ↪ *this; }
17    Z &operator/=(const Z &rhs) { return *this *= rhs.inv(); }
18    Z &operator%=(const ll &rhs) { return x %= rhs, *this; }
19    friend Z operator*(Z lhs, const Z &rhs) { return lhs * rhs;
    ↪ }
20    friend Z operator+(Z lhs, const Z &rhs) { return lhs + rhs;
    ↪ }
21    friend Z operator-(Z lhs, const Z &rhs) { return lhs - rhs;
    ↪ }
22    friend Z operator/(Z lhs, const Z &rhs) { return lhs / rhs;
    ↪ }
23    friend Z operator%(Z lhs, const ll &rhs) { return lhs %=
    ↪ rhs; }
24    friend auto &operator>>(istream &i, Z &z) { return i >> z.x;
    ↪ }
25    friend auto &operator<<(ostream &o, const Z &z) { return o
    ↪ << z.x; }
26 };

```

- large mod (for NTT to do FFT in ll range without modulo)

```

1 using ll = long long;
2 using i128 = __int128;
3 constexpr i128 MOD = 9223372036737335297;

```

```

4
5 constexpr i128 norm(i128 x) { return x < 0 ? (x + MOD) % MOD :
    ↪ x % MOD; }
6 template <typename T>
7 constexpr T power(T a, i128 b, T res = 1) {
8     for (; b; b /= 2, (a *= a) %= MOD)
9         if (b & 1) (res *= a) %= MOD;
10    return res;
11 }
12 struct Z {
13     i128 x;
14    constexpr Z(i128 _x = 0) : x(norm(_x)) {}
15    Z operator-() const { return Z(norm(MOD - x)); }
16    Z inv() const { return power(*this, MOD - 2); }
17    // auto operator<=>(const Z &) const = default;
18    Z &operator*=(const Z &rhs) { return x = x * rhs.x % MOD,
    ↪ *this; }
19    Z &operator+=(const Z &rhs) { return x = norm(x + rhs.x),
    ↪ *this; }
20    Z &operator-=(const Z &rhs) { return x = norm(x - rhs.x),
    ↪ *this; }
21    Z &operator/=(const Z &rhs) { return *this *= rhs.inv(); }
22    Z &operator%=(const i128 &rhs) { return x %= rhs, *this; }
23    friend Z operator*(Z lhs, const Z &rhs) { return lhs * rhs;
    ↪ }
24    friend Z operator+(Z lhs, const Z &rhs) { return lhs + rhs;
    ↪ }
25    friend Z operator-(Z lhs, const Z &rhs) { return lhs - rhs;
    ↪ }
26    friend Z operator/(Z lhs, const Z &rhs) { return lhs / rhs;
    ↪ }
27    friend Z operator%(Z lhs, const i128 &rhs) { return lhs %=
    ↪ rhs; }
28 };

```

- fastest mod class! be careful with overflow, only use when the time limit is tight

```

1 constexpr int MOD = 998244353;
2
3 constexpr int norm(int x) {
4     if (x < 0) x += MOD;
5     if (x >= MOD) x -= MOD;
6     return x;
7 }
8 template <typename T>
9 constexpr T power(T a, int b, T res = 1) {
10    for (; b; b /= 2, (a *= a) %= MOD)
11        if (b & 1) (res *= a) %= MOD;
12    return res;
13 }
14 struct Z {
15     int x;
16    constexpr Z(int _x = 0) : x(norm(_x)) {}
17    // constexpr auto operator<=>(const Z &) const = default; //
    ↪ cpp20 only
18    constexpr Z operator-() const { return Z(norm(MOD - x)); }
19    constexpr Z inv() const { return power(*this, MOD - 2); }
20    constexpr Z &operator*=(const Z &rhs) { return x = ll(x) *
    ↪ rhs.x % MOD, *this; }
21    constexpr Z &operator+=(const Z &rhs) { return x = norm(x +
    ↪ rhs.x), *this; }
22    constexpr Z &operator-=(const Z &rhs) { return x = norm(x -
    ↪ rhs.x), *this; }
23    constexpr Z &operator/=(const Z &rhs) { return *this *=
    ↪ rhs.inv(); }
24    constexpr Z &operator%=(const ll &rhs) { return x %= rhs,
    ↪ *this; }
25    constexpr friend Z operator*(Z lhs, const Z &rhs) { return
    ↪ lhs * rhs; }
26    constexpr friend Z operator+(Z lhs, const Z &rhs) { return
    ↪ lhs + rhs; }
27    constexpr friend Z operator-(Z lhs, const Z &rhs) { return
    ↪ lhs - rhs; }
28    constexpr friend Z operator/(Z lhs, const Z &rhs) { return
    ↪ lhs / rhs; }
29    constexpr friend Z operator%(Z lhs, const ll &rhs) { return
    ↪ lhs %= rhs; }

```

```

30 friend auto &operator>>(istream &i, Z &z) { return i >> z.x;
↪ }
31 friend auto &operator<<(ostream &o, const Z &z) { return o
↪ << z.x; }
32 };

```

Cancer mod class

- Explanation: for some prime modulo p , maintains numbers of form $p^x * y$, where y is a nonzero remainder mod p
- Be careful with calling `Cancer(x, y)`, it doesn't fix the input if $y > p$

```

1 struct Cancer {
2     ll x; ll y;
3     Cancer() : Cancer(0, 1) {}
4     Cancer(ll _y) {
5         x = 0, y = _y;
6         while(y % MOD == 0) {
7             y /= MOD;
8             x++;
9         }
10    }
11    Cancer(ll _x, ll _y) : x(_x), y(_y) {}
12    Cancer inv() { return Cancer(-x, power(y, MOD - 2)); }
13    Cancer operator*(const Cancer &c) { return Cancer(x + c.x,
↪ (y * c.y) % MOD); }
14    Cancer operator*(ll m) {
15        ll p = 0;
16        while(m % MOD == 0) {
17            m /= MOD;
18            p++;
19        }
20        return Cancer(x + p, (m * y) % MOD);
21    }
22    friend auto &operator<<(ostream &o, Cancer c) { return o <<
↪ c.x << ' ' << c.y; }
23 };

```

NTT, FFT, FWT

- ntt

```

1 void ntt(vector<Z>& a, int f) {
2     int n = int(a.size());
3     vector<Z> w(n);
4     vector<int> rev(n);
5     for (int i = 0; i < n; i++) rev[i] = (rev[i / 2] / 2) | ((i
↪ & 1) * (n / 2));
6     for (int i = 0; i < n; i++) {
7         if (i < rev[i]) swap(a[i], a[rev[i]]);
8     }
9     Z wn = power(f ? (MOD + 1) / 3 : 3, (MOD - 1) / n);
10    w[0] = 1;
11    for (int i = 1; i < n; i++) w[i] = w[i - 1] * wn;
12    for (int mid = 1; mid < n; mid *= 2) {
13        for (int i = 0; i < n; i += 2 * mid) {
14            for (int j = 0; j < mid; j++) {
15                Z x = a[i + j], y = a[i + j + mid] * w[n / (2 * mid) *
↪ j];
16                a[i + j] = x + y, a[i + j + mid] = x - y;
17            }
18        }
19    }
20    if (f) {
21        Z iv = power(Z(n), MOD - 2);
22        for (auto& x : a) x *= iv;
23    }
24 }

```

- USAGE: Polynomial multiplication

```

1 vector<Z> mul(vector<Z> a, vector<Z> b) {
2     int n = 1, m = (int)a.size() + (int)b.size() - 1;

```

```

3     while (n < m) n *= 2;
4     a.resize(n), b.resize(n);
5     ntt(a, 0), ntt(b, 0);
6     for (int i = 0; i < n; i++) a[i] *= b[i];
7     ntt(a, 1);
8     a.resize(m);
9     return a;
10 }

```

- FFT (should prefer NTT, only use this when input is not integer)

```

1 const double PI = acos(-1);
2 auto mul = [&](const vector<double>& aa, const vector<double>&
↪ bb) {
3     int n = (int)aa.size(), m = (int)bb.size(), bit = 1;
4     while ((1 << bit) < n + m - 1) bit++;
5     int len = 1 << bit;
6     vector<complex<double>> a(len), b(len);
7     vector<int> rev(len);
8     for (int i = 0; i < n; i++) a[i].real(aa[i]);
9     for (int i = 0; i < m; i++) b[i].real(bb[i]);
10    for (int i = 0; i < len; i++) rev[i] = (rev[i >> 1] >> 1) |
↪ ((i & 1) << (bit - 1));
11    auto fft = [&](vector<complex<double>>& p, int inv) {
12        for (int i = 0; i < len; i++)
13            if (i < rev[i]) swap(p[i], p[rev[i]]);
14        for (int mid = 1; mid < len; mid *= 2) {
15            auto w1 = complex<double>(cos(PI / mid), (inv ? -1 : 1)
↪ * sin(PI / mid));
16            for (int i = 0; i < len; i += mid * 2) {
17                auto wk = complex<double>(1, 0);
18                for (int j = 0; j < mid; j++, wk = wk * w1) {
19                    auto x = p[i + j], y = wk * p[i + j + mid];
20                    p[i + j] = x + y, p[i + j + mid] = x - y;
21                }
22            }
23        }
24        if (inv == 1) {
25            for (int i = 0; i < len; i++) p[i].real(p[i].real() /
↪ len);
26        }
27    };
28    fft(a, 0), fft(b, 0);
29    for (int i = 0; i < len; i++) a[i] = a[i] * b[i];
30    fft(a, 1);
31    a.resize(n + m - 1);
32    vector<double> res(n + m - 1);
33    for (int i = 0; i < n + m - 1; i++) res[i] = a[i].real();
34    return res;
35 };

```

Polynomial Class

```

1 using ll = long long;
2 constexpr ll MOD = 998244353;
3
4 ll norm(ll x) { return (x % MOD + MOD) % MOD; }
5 template <class T>
6 T power(T a, ll b, T res = 1) {
7     for (; b; b /= 2, (a == a) %= MOD)
8         if (b & 1) (res == a) %= MOD;
9     return res;
10 }
11
12 struct Z {
13     ll x;
14     Z(ll _x = 0) : x(norm(_x)) {}
15     // auto operator<=>(const Z &) const = default;
16     Z operator-() const { return Z(norm(MOD - x)); }
17     Z inv() const { return power(*this, MOD - 2); }
18     Z &operator*=(const Z &rhs) { return x = x * rhs.x % MOD,
↪ *this; }
19     Z &operator+=(const Z &rhs) { return x = norm(x + rhs.x),
↪ *this; }
20     Z &operator-=(const Z &rhs) { return x = norm(x - rhs.x),
↪ *this; }

```

```

21     Z &operator/=(const Z &rhs) { return *this *= rhs.inv(); }
22     Z &operator%=(const ll &rhs) { return x %= rhs, *this; }
23     friend Z operator*(Z lhs, const Z &rhs) { return lhs *= rhs;
↪ }
24     friend Z operator+(Z lhs, const Z &rhs) { return lhs += rhs;
↪ }
25     friend Z operator-(Z lhs, const Z &rhs) { return lhs -= rhs;
↪ }
26     friend Z operator/(Z lhs, const Z &rhs) { return lhs /= rhs;
↪ }
27     friend Z operator%(Z lhs, const ll &rhs) { return lhs %=
↪ rhs; }
28     friend auto &operator>>(istream &i, Z &z) { return i >> z.x;
↪ }
29     friend auto &operator<<(ostream &o, const Z &z) { return o
↪ << z.x; }
30 };
31
32 void ntt(vector<Z> &a, int f) {
33     int n = (int)a.size();
34     vector<Z> w(n);
35     vector<int> rev(n);
36     for (int i = 0; i < n; i++) rev[i] = (rev[i / 2] / 2) | ((i
↪ & 1) * (n / 2));
37     for (int i = 0; i < n; i++)
38         if (i < rev[i]) swap(a[i], a[rev[i]]);
39     Z wn = power(ll(f ? (MOD + 1) / 3 : 3), (MOD - 1) / n);
40     w[0] = 1;
41     for (int i = 1; i < n; i++) w[i] = w[i - 1] * wn;
42     for (int mid = 1; mid < n; mid *= 2) {
43         for (int i = 0; i < n; i += 2 * mid) {
44             for (int j = 0; j < mid; j++) {
45                 Z x = a[i + j], y = a[i + j + mid] * w[n / (2 * mid) *
↪ j];
46                 a[i + j] = x + y, a[i + j + mid] = x - y;
47             }
48         }
49     }
50     if (f) {
51         Z iv = power(Z(n), MOD - 2);
52         for (int i = 0; i < n; i++) a[i] *= iv;
53     }
54 }
55
56 struct Poly {
57     vector<Z> a;
58     Poly() {}
59     Poly(const vector<Z> &a) : a(a) {}
60     int size() const { return (int)a.size(); }
61     void resize(int n) { a.resize(n); }
62     Z operator[](int idx) const {
63         if (idx < 0 || idx >= size()) return 0;
64         return a[idx];
65     }
66     Z &operator[](int idx) { return a[idx]; }
67     Poly mulxk(int k) const {
68         auto b = a;
69         b.insert(b.begin(), k, 0);
70         return Poly(b);
71     }
72     Poly modxk(int k) const { return Poly(vector<Z>(a.begin(),
↪ a.begin() + min(k, size()))); }
73     Poly divxk(int k) const {
74         if (size() <= k) return Poly();
75         return Poly(vector<Z>(a.begin() + k, a.end()));
76     }
77     friend Poly operator+(const Poly &a, const Poly &b) {
78         vector<Z> res(max(a.size(), b.size()));
79         for (int i = 0; i < (int)res.size(); i++) res[i] = a[i] +
↪ b[i];
80         return Poly(res);
81     }
82     friend Poly operator-(const Poly &a, const Poly &b) {
83         vector<Z> res(max(a.size(), b.size()));
84         for (int i = 0; i < (int)res.size(); i++) res[i] = a[i] -
↪ b[i];
85         return Poly(res);
86     }
87     friend Poly operator*(Poly a, Poly b) {
88         if (a.size() == 0 || b.size() == 0) return Poly();
89         int n = 1, m = (int)a.size() + (int)b.size() - 1;
90         while (n < m) n *= 2;
91         a.resize(n), b.resize(n);
92         ntt(a.a, 0), ntt(b.a, 0);
93         for (int i = 0; i < n; i++) a[i] *= b[i];
94         ntt(a.a, 1);
95         a.resize(m);
96         return a;
97     }
98     friend Poly operator*(Z a, Poly b) {
99         for (int i = 0; i < (int)b.size(); i++) b[i] *= a;
100         return b;
101     }
102     friend Poly operator*(Poly a, Z b) {
103         for (int i = 0; i < (int)a.size(); i++) a[i] *= b;
104         return a;
105     }
106     Poly &operator+=(Poly b) { return (*this) = (*this) + b; }
107     Poly &operator-=(Poly b) { return (*this) = (*this) - b; }
108     Poly &operator*=(Poly b) { return (*this) = (*this) * b; }
109     Poly deriv() const {
110         if (a.empty()) return Poly();
111         vector<Z> res(size() - 1);
112         for (int i = 0; i < size() - 1; ++i) res[i] = (i + 1) *
↪ a[i + 1];
113         return Poly(res);
114     }
115     Poly integr() const {
116         vector<Z> res(size() + 1);
117         for (int i = 0; i < size(); ++i) res[i + 1] = a[i] / (i +
↪ 1);
118         return Poly(res);
119     }
120     Poly inv(int m) const {
121         Poly x({a[0].inv()});
122         int k = 1;
123         while (k < m) {
124             k *= 2;
125             x = (x * (Poly({2}) - modxk(k) * x)).modxk(k);
126         }
127         return x.modxk(m);
128     }
129     Poly log(int m) const { return (deriv() *
↪ inv(m)).integr().modxk(m); }
130     Poly exp(int m) const {
131         Poly x({1});
132         int k = 1;
133         while (k < m) {
134             k *= 2;
135             x = (x * (Poly({1}) - x.log(k) + modxk(k))).modxk(k);
136         }
137         return x.modxk(m);
138     }
139     Poly pow(int k, int m) const {
140         int i = 0;
141         while (i < size() && a[i].x == 0) i++;
142         if (i == size() || 1LL * i * k >= m) {
143             return Poly(vector<Z>(m));
144         }
145         Z v = a[i];
146         auto f = divxk(i) * v.inv();
147         return (f.log(m - i * k) * k).exp(m - i * k).mulxk(i * k)
↪ * power(v, k);
148     }
149     Poly sqrt(int m) const {
150         Poly x({1});
151         int k = 1;
152         while (k < m) {
153             k *= 2;
154             x = (x + (modxk(k) * x.inv(k)).modxk(k)) * ((MOD + 1) /
↪ 2);
155         }
156         return x.modxk(m);
157     }

```

```

158 Poly mult(Poly b) const {
159     if (b.size() == 0) return Poly();
160     int n = b.size();
161     reverse(b.a.begin(), b.a.end());
162     return ((*this) * b).divxk(n - 1);
163 }
164 Poly divmod(Poly b) const {
165     auto n = size(), m = b.size();
166     auto t = *this;
167     reverse(t.a.begin(), t.a.end());
168     reverse(b.a.begin(), b.a.end());
169     Poly res = (t * b.inv(n)).modxk(n - m + 1);
170     reverse(res.a.begin(), res.a.end());
171     return res;
172 }
173 vector<Z> eval(vector<Z> x) const {
174     if (size() == 0) return vector<Z>(x.size(), 0);
175     const int n = max(int(x.size()), size());
176     vector<Poly> q(4 * n);
177     vector<Z> ans(x.size());
178     x.resize(n);
179     function<void(int, int, int)> build = [&](int p, int l,
180     ↪ int r) {
181         if (r - l == 1) {
182             q[p] = Poly({1, -x[l]});
183         } else {
184             int m = (l + r) / 2;
185             build(2 * p, l, m), build(2 * p + 1, m, r);
186             q[p] = q[2 * p] * q[2 * p + 1];
187         }
188     };
189     build(1, 0, n);
190     auto work = [&](auto self, int p, int l, int r, const Poly
191     ↪ &num) -> void {
192         if (r - l == 1) {
193             if (l < int(ans.size())) ans[l] = num[0];
194         } else {
195             int m = (l + r) / 2;
196             self(self, 2 * p, l, m, num.mult(q[2 * p + 1]).modxk(m
197     ↪ - 1));
198             self(self, 2 * p + 1, m, r, num.mult(q[2 * p]).modxk(r
199     ↪ - m));
200         }
201     };
202     work(work, 1, 0, n, mult(q[1].inv(n)));
203     return ans;
204 }
205 };

```

Sieve

- linear sieve

```

1 vector<int> min_primes(MAX_N), primes;
2 primes.reserve(1e5);
3 for (int i = 2; i < MAX_N; i++) {
4     if (!min_primes[i]) min_primes[i] = i, primes.push_back(i);
5     for (auto& p : primes) {
6         if (p * i >= MAX_N) break;
7         min_primes[p * i] = p;
8         if (i % p == 0) break;
9     }
10 }

```

- mobius function

```

1 vector<int> min_p(MAX_N), mu(MAX_N), primes;
2 mu[1] = 1, primes.reserve(1e5);
3 for (int i = 2; i < MAX_N; i++) {
4     if (min_p[i] == 0) {
5         min_p[i] = i;
6         primes.push_back(i);
7         mu[i] = -1;
8     }
9     for (auto p : primes) {
10         if (i * p >= MAX_N) break;
11         min_p[i * p] = p;

```

```

12         if (i % p == 0) {
13             mu[i * p] = 0;
14             break;
15         }
16         mu[i * p] = -mu[i];
17     }
18 }

```

- Euler's totient function

```

1 vector<int> min_p(MAX_N), phi(MAX_N), primes;
2 phi[1] = 1, primes.reserve(1e5);
3 for (int i = 2; i < MAX_N; i++) {
4     if (min_p[i] == 0) {
5         min_p[i] = i;
6         primes.push_back(i);
7         phi[i] = i - 1;
8     }
9     for (auto p : primes) {
10         if (i * p >= MAX_N) break;
11         min_p[i * p] = p;
12         if (i % p == 0) {
13             phi[i * p] = phi[i] * p;
14             break;
15         }
16         phi[i * p] = phi[i] * phi[p];
17     }
18 }

```

Gaussian Elimination

```

1 bool is_0(Z v) { return v.x == 0; }
2 Z abs(Z v) { return v; }
3 bool is_0(double v) { return abs(v) < 1e-9; }
4
5 // 1 => unique solution, 0 => no solution, -1 => multiple
6 ↪ solutions
7 template <typename T>
8 int gaussian_elimination(vector<vector<T>> &a, int limit) {
9     if (a.empty() || a[0].empty()) return -1;
10     int h = (int)a.size(), w = (int)a[0].size(), r = 0;
11     for (int c = 0; c < limit; c++) {
12         int id = -1;
13         for (int i = r; i < h; i++) {
14             if (!is_0(a[i][c]) && (id == -1 || abs(a[id][c]) <
15     ↪ abs(a[i][c]))) {
16                 id = i;
17             }
18         }
19         if (id == -1) continue;
20         if (id > r) {
21             swap(a[r], a[id]);
22             for (int j = c; j < w; j++) a[id][j] = -a[id][j];
23         }
24         vector<int> nonzero;
25         for (int j = c; j < w; j++) {
26             if (!is_0(a[r][j])) nonzero.push_back(j);
27         }
28         T inv_a = 1 / a[r][c];
29         for (int i = r + 1; i < h; i++) {
30             if (is_0(a[i][c])) continue;
31             T coeff = -a[i][c] * inv_a;
32             for (int j : nonzero) a[i][j] += coeff * a[r][j];
33         }
34         ++r;
35     }
36     for (int row = h - 1; row >= 0; row--) {
37         for (int c = 0; c < limit; c++) {
38             if (!is_0(a[row][c])) {
39                 T inv_a = 1 / a[row][c];
40                 for (int i = row - 1; i >= 0; i--) {
41                     if (is_0(a[i][c])) continue;
42                     T coeff = -a[i][c] * inv_a;
43                     for (int j = c; j < w; j++) a[i][j] += coeff *
44     ↪ a[row][j];
45                 }
46                 break;
47             }
48         }
49     }
50 }

```

```

44     }
45 }
46 } // not-free variables: only it on its line
47 for(int i = r; i < h; i++) if(!is_0(a[i][limit])) return 0;
48 return (r == limit) ? 1 : -1;
49 }
50
51 template <typename T>
52 pair<int, vector<T>> solve_linear(vector<vector<T>> a, const
    ↪ vector<T> &b, int w) {
53     int h = (int)a.size();
54     for (int i = 0; i < h; i++) a[i].push_back(b[i]);
55     int sol = gaussian_elimination(a, w);
56     if(!sol) return {0, vector<T>()};
57     vector<T> x(w, 0);
58     for (int i = 0; i < h; i++) {
59         for (int j = 0; j < w; j++) {
60             if (!is_0(a[i][j])) {
61                 x[j] = a[i][w] / a[i][j];
62                 break;
63             }
64         }
65     }
66     return {sol, x};
67 }

```

is_prime

- (Miller–Rabin primality test)

```

1  i128 power(i128 a, i128 b, i128 MOD = 1, i128 res = 1) {
2      for (; b; b /= 2, (a *= a) %= MOD)
3          if (b & 1) (res *= a) %= MOD;
4      return res;
5  }
6
7  bool is_prime(ll n) {
8      if (n < 2) return false;
9      static constexpr int A[] = {2, 3, 5, 7, 11, 13, 17, 19, 23};
10     int s = __builtin_ctzll(n - 1);
11     ll d = (n - 1) >> s;
12     for (auto a : A) {
13         if (a == n) return true;
14         ll x = (ll)power(a, d, n);
15         if (x == 1 || x == n - 1) continue;
16         bool ok = false;
17         for (int i = 0; i < s - 1; ++i) {
18             x = ll((i128)x * x % n); // potential overflow!
19             if (x == n - 1) {
20                 ok = true;
21                 break;
22             }
23         }
24         if (!ok) return false;
25     }
26     return true;
27 }
28
29 ll pollard_rho(ll x) {
30     ll s = 0, t = 0, c = rng() % (x - 1) + 1;
31     ll stp = 0, goal = 1, val = 1;
32     for (goal = 1;; goal *= 2, s = t, val = 1) {
33         for (stp = 1; stp <= goal; ++stp) {
34             t = ll(((i128)t * t + c) % x);
35             val = ll(((i128)val * abs(t - s) % x);
36             if ((stp % 127) == 0) {
37                 ll d = gcd(val, x);
38                 if (d > 1) return d;
39             }
40         }
41         ll d = gcd(val, x);
42         if (d > 1) return d;
43     }
44 }
45
46 ll get_max_factor(ll _x) {
47     ll max_factor = 0;

```

```

20 function<void(ll)> fac = [&](ll x) {
21     if (x <= max_factor || x < 2) return;
22     if (is_prime(x)) {
23         max_factor = max_factor > x ? max_factor : x;
24         return;
25     }
26     ll p = x;
27     while (p >= x) p = pollard_rho(x);
28     while ((x % p) == 0) x /= p;
29     fac(x), fac(p);
30 };
31 fac(_x);
32 return max_factor;
33 }

```

Radix Sort

```

1  struct identity {
2      template<typename T>
3      T operator()(const T &x) const {
4          return x;
5      }
6  };
7
8  // A stable sort that sorts in passes of `bits_per_pass` bits
9  ↪ at a time.
10 template<typename T, typename T_extract_key = identity>
11 void radix_sort(vector<T> &data, int bits_per_pass = 10, const
    ↪ T_extract_key &extract_key = identity()) {
12     if (int64_t(data.size()) * (64 -
    ↪ __builtin_clzll(data.size())) < 2 * (1 << bits_per_pass))
13     {
14         stable_sort(data.begin(), data.end(), [&](const T &a,
    ↪ const T &b) {
15             return extract_key(a) < extract_key(b);
16         });
17     }
18     using T_key = decltype(extract_key(data.front()));
19     T_key minimum = numeric_limits<T_key>::max();
20
21     for (T &x : data)
22         minimum = min(minimum, extract_key(x));
23
24     int max_bits = 0;
25
26     for (T &x : data) {
27         T_key key = extract_key(x);
28         max_bits = max(max_bits, key == minimum ? 0 : 64 -
    ↪ __builtin_clzll(key - minimum));
29     }
30
31     int passes = max((max_bits + bits_per_pass / 2) /
    ↪ bits_per_pass, 1);
32
33     if (64 - __builtin_clzll(data.size()) <= 1.5 * passes) {
34         stable_sort(data.begin(), data.end(), [&](const T &a,
    ↪ const T &b) {
35             return extract_key(a) < extract_key(b);
36         });
37     }
38     return;
39 }
40
41 vector<T> buffer(data.size());
42 vector<int> counts;
43 int bits_so_far = 0;
44
45 for (int p = 0; p < passes; p++) {
46     int bits = (max_bits + p) / passes;
47     counts.assign(1 << bits, 0);
48
49     for (T &x : data) {
50         T_key key = T_key(extract_key(x) - minimum);
51         counts[(key >> bits_so_far) & ((1 << bits) -
    ↪ 1)]++;
52     }

```

```

52         int count_sum = 0;
53
54         for (int &count : counts) {
55             int current = count;
56             count = count_sum;
57             count_sum += current;
58         }
59
60         for (T &x : data) {
61             T_key key = T_key(extract_key(x) - minimum);
62             int key_section = int((key >> bits_so_far) & ((1
↪ << bits) - 1));
63             buffer[counts[key_section]++] = x;
64         }
65
66         swap(data, buffer);
67         bits_so_far += bits;
68     }
69 }
70 }

```

• USAGE

```

1 radix_sort(edges, 10, [&](const edge &e) -> int { return
↪ abs(e.weight - x); });

```

lucas

```

1 ll lucas(ll n, ll m, ll p) {
2     if (m == 0) return 1;
3     return (binom(n % p, m % p, p) * lucas(n / p, m / p, p)) %
↪ p;
4 }

```

parity of n choose m

```

1 (n & m) == m <=> odd

```

sosdp

subset sum

```

1 auto f = a;
2 for (int i = 0; i < SZ; i++) {
3     for (int mask = 0; mask < (1 << SZ); mask++) {
4         if (mask & (1 << i)) f[mask] += f[mask ^ (1 << i)];
5     }
6 }

```

String

AC Automaton

```

1 struct AC_automaton {
2     int sz = 26;
3     vector<vector<int>> e = {vector<int>(sz)}; // vector is
↪ faster than unordered_map
4     vector<int> fail = {0}, end = {0};
5     vector<int> fast = {0}; // closest end
6
7     int insert(string& s) {
8         int p = 0;
9         for (auto c : s) {
10             c -= 'a';
11             if (!e[p][c]) {
12                 e.emplace_back(sz);
13                 fail.emplace_back();
14                 end.emplace_back();
15                 fast.emplace_back();
16                 e[p][c] = (int)e.size() - 1;
17             }
18             p = e[p][c];
19         }
20         end[p] += 1;

```

```

21         return p;
22     }
23
24     void build() {
25         queue<int> q;
26         for (int i = 0; i < sz; i++)
27             if (e[0][i]) q.push(e[0][i]);
28         while (!q.empty()) {
29             int p = q.front();
30             q.pop();
31             fast[p] = end[p] ? p : fast[fail[p]];
32             for (int i = 0; i < sz; i++) {
33                 if (e[p][i]) {
34                     fail[e[p][i]] = e[fail[p]][i];
35                     q.push(e[p][i]);
36                 } else {
37                     e[p][i] = e[fail[p]][i];
38                 }
39             }
40         }
41     }
42 };

```

KMP

- nex[i]: length of longest common prefix & suffix for pat[0..i]

```

1 vector<int> get_next(vector<int> &pat) {
2     int m = (int)pat.size();
3     vector<int> nex(m);
4     for (int i = 1, j = 0; i < m; i++) {
5         while (j && pat[j] != pat[i]) j = nex[j - 1];
6         if (pat[j] == pat[i]) j++;
7         nex[i] = j;
8     }
9     return nex;
10 }

```

- kmp match for txt and pat

```

1 auto nex = get_next(pat);
2 for (int i = 0, j = 0; i < n; i++) {
3     while (j && pat[j] != txt[i]) j = nex[j - 1];
4     if (pat[j] == txt[i]) j++;
5     if (j == m) {
6         // do what you want with the match
7         // start index is `i - m + 1`
8         j = nex[j - 1];
9     }
10 }

```

Z function

- z[i]: length of longest common prefix of s and s[i:]

```

1 vector<int> z_function(string s) {
2     int n = (int)s.size();
3     vector<int> z(n);
4     for (int i = 1, l = 0, r = 0; i < n; ++i) {
5         if (i <= r) z[i] = min(r - i + 1, z[i - l]);
6         while (i + z[i] < n && s[z[i]] == s[i + z[i]]) ++z[i];
7         if (i + z[i] - 1 > r) l = i, r = i + z[i] - 1;
8     }
9     return z;
10 }

```

General Suffix Automaton

```

1 constexpr int SZ = 26;
2
3 struct GSAM {
4     vector<vector<int>> e = {vector<int>(SZ)}; // the labeled
↪ edges from node i
5     vector<int> parent = {-1}; // the parent of
↪ i

```



```

6     vector<int> length = {0}; // the length of
   ↳ the longest string
7
8     GSAM(int n) { e.reserve(2 * n), parent.reserve(2 * n),
   ↳ length.reserve(2 * n); };
9     int extend(int c, int p) { // character, last
10        bool f = true; // if already exist
11        int r = 0; // potential new node
12        if (!e[p][c]) { // only extend when not exist
13            f = false;
14            e.push_back(vector<int>(SZ));
15            parent.push_back(0);
16            length.push_back(length[p] + 1);
17            r = (int)e.size() - 1;
18            for (; ~p && !e[p][c]; p = parent[p]) e[p][c] = r; //
   ↳ update parents
19        }
20        if (f || ~p) {
21            int q = e[p][c];
22            if (length[q] == length[p] + 1) {
23                if (f) return q;
24                parent[r] = q;
25            } else {
26                e.push_back(e[q]);
27                parent.push_back(parent[q]);
28                length.push_back(length[p] + 1);
29                int qq = parent[q] = (int)e.size() - 1;
30                for (; ~p && e[p][c] == q; p = parent[p]) e[p][c] =
   ↳ qq;
31                if (f) return qq;
32                parent[r] = qq;
33            }
34        }
35        return r;
36    }
37 };

```

• Topo sort on GSAM

```

1 ll sz = gsam.e.size();
2 vector<int> c(sz + 1);
3 vector<int> order(sz);
4 for (int i = 1; i < sz; i++) c[gsam.length[i]]++;
5 for (int i = 1; i < sz; i++) c[i] += c[i - 1];
6 for (int i = 1; i < sz; i++) order[c[gsam.length[i]]--] = i;
7 reverse(order.begin(), order.end()); // reverse so that large
   ↳ len to small

```

- can be used as an ordinary SAM
- USAGE (the number of distinct substrings)

```

1 int main() {
2     int n, last = 0;
3     string s;
4     cin >> n;
5     auto a = GSAM();
6     for (int i = 0; i < n; i++) {
7         cin >> s;
8         last = 0; // reset last
9         for (auto&& c : s) last = a.extend(c, last);
10    }
11    ll ans = 0;
12    for (int i = 1; i < a.e.size(); i++) {
13        ans += a.length[i] - a.length[a.parent[i]];
14    }
15    cout << ans << endl;
16    return 0;
17 }

```

```

7     int n = t.size(), r = 0, c = 0;
8     vector<int> p(n, 0);
9     for (int i = 1; i < n - 1; i++) {
10        if (i < r + c) p[i] = min(p[2 * c - i], r + c - i);
11        while (t[i + p[i] + 1] == t[i - p[i] - 1]) p[i]++;
12        if (i + p[i] > r + c) r = p[i], c = i;
13    }
14    // s[i] -> p[2 * i + 2] (even), p[2 * i + 2] (odd)
15    // output answer
16    int index = 0;
17    for (int i = 0; i < n; i++)
18        if (p[index] < p[i]) index = i;
19    return s.substr((index - p[index]) / 2, p[index]);
20 }

```

Lyndon

- def: $\text{suf}(s) > s$

```

1 void duval(const string &s) {
2     int n = (int)s.size();
3     for (int i = 0; i < n; i) {
4         int j = i, k = i + 1;
5         for (; j < n && s[j] <= s[k]; j++, k++)
6             if (s[j] < s[k]) j = i - 1;
7
8         while (i <= j) {
9             // cout << s.substr(i, k - j) << '\n';
10            i += k - j;
11        }
12    }
13 }

```

minimal representation

```

1     int k = 0, i = 0, j = 1;
2     while (k < n && i < n && j < n) {
3         if (s[(i + k) % n] == s[(j + k) % n]) {
4             k++;
5         } else {
6             s[(i + k) % n] > s[(j + k) % n] ? i = i + k + 1 : j = j +
   ↳ k + 1;
7             if (i == j) i++;
8             k = 0;
9         }
10    }
11    i = min(i, j); // from 0

```

Manacher

```

1 string longest_palindrome(string& s) {
2     // init "abc" -> "~$a#b#c$"
3     vector<char> t{'^', '#'};
4     for (char c : s) t.push_back(c), t.push_back('#');
5     t.push_back('$');
6     // manacher

```