

API Documentation – Check Transaction Status

Overview

This API allows the client system to check the current status of a payment transaction using its unique transaction ID.

It returns the transaction status, description, and details if available.

Endpoint

URL: <http://198.162.1.51:8040/api/v1/checkStatus>

Method: POST

Content-Type: application/json

Request

Request Body

Field	Type	Required	Description
transactionId	string	Yes	The unique transaction identifier to be checked.

Example

```
{
  "transactionId":123333333
}
```

Response

Success Response (HTTP 200)

Field	Type	Description
responseCode	number	CheckStatusReq return code 0 indicates successful status retrieval.
responseMessage	string	Message describing the response status.
trnStatus	number	Original transaction status code.

		0 indicates successful status retrieval from the provider. 10 indicates failed status retrieval from the provider. 20 indicates pending status retrieval from the provider.
trnStatusDisc	string	Description of the original transaction's status.
transactionId	string	The original transaction ID in the system.
checkReqId	string	The internal reference ID for this check request.
trnDetails	array	List of additional original transaction key–value details.

Example

```
Response (success) :
{
  "responseCode": 0,
  "responseMessage": " Successful",
  "trnStatus": 0,
  "trnStatusDisc": "Successfull",
  "transactionId": "851957960024100",
  "checkReqId": "851957960024100",
  "trnDetails": [
    {
      "key": "mobile",
      "value": "0907812682",
      "displayName": "Phone Number ",
      "id": 1
    },
    {
      "key": "responseMessage",
      "value": "success",
      "displayName": "Response Message",
      "id": 3
    }
  ]
}
```

Failure Response (HTTP 400 or 200 with Error Code)

Field	Type	Description
responseCode	number	Non-zero value indicates an error.
responseMessage	string	Description of the error.
trnStatus	number	null in case of error.
trnStatusDisc	string	null in case of error.

transactionId	string	Transaction reference.
checkReqId	string	Check request reference.
trnDetails	array	Empty list when an error occurs.

Example

```
{
  "responseCode": 10,
  "responseMessage": "Error while checking transaction status",
  "trnStatus": null,
  "trnStatusDisc": null,
  "transactionId": "851957960024100",
  "checkReqId": "851957960024100",
  "trnDetails": []
}
```

Response Codes

Code	Meaning
0	Success – Transaction Status retrieved successfully.
10	indicates failed status retrieval.
20	timeout while getting the transaction status.

Notes

- The **transactionId** should be a valid reference previously generated by the payment system.
- Ensure proper error handling for cases where **responseCode** is non-zero.
- The **trnDetails** array may vary depending additional attributes available.

Version

API Version: 1.0

Last Updated: November 2025