

# KeepDelta: A Python Library for Human-Readable Data Differencing

Aslan Noorghasemi<sup>1</sup> and Christopher McComb<sup>1</sup>

<sup>1</sup> Carnegie Mellon University, Pittsburgh, PA, USA ¶ Corresponding author

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Open Journals](#)

## Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

## License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

## Summary

Efficiently managing evolving data states is crucial in cases like computational simulations and IoT remote sensing, where dynamic data tracking and processing are essential. In simulations, traditional methods of storing complete snapshots (full-state encoding) at each step can be highly storage-intensive, while recalculating states from scratch is computationally expensive. Similarly, in IoT remote sensing, continuously transmitting full data snapshots is inefficient, leading to increased bandwidth consumption and latency. KeepDelta addresses this challenge by providing a lightweight Python library that captures and applies only the changes (deltas) between successive states of complex, nested Python data structures. Designed for clarity and ease of use, KeepDelta produces human-readable outputs, facilitating debugging and analysis in research applications.

## Statement of need

High-frequency data sampling is fundamental in both scientific simulations and real-world sensing applications, where large volumes of evolving data must be efficiently managed. Both domains, whether generating synthetic data through computational models or collecting real-time measurements from physical sensors, face a common challenge: storing, transmitting, and processing dynamic data without excessive redundancy.

Simulation is a widely used methodology across all applied science disciplines, offering a flexible, powerful, and intuitive tool for designing processes or systems and maximizing their efficiency (Kleijnen, 2018). These studies often take the form of computer experiments, where data is generated through pseudo-random sampling from known probability distributions. This approach serves as an invaluable resource for research, particularly in evaluating new methods and comparing alternative approaches (Morris et al., 2019). Computational simulations are invaluable tools for studying complex systems and their behaviors. (Aumann, 2007)

Sensing technologies are also employed across diverse scientific and engineering domains, enabling continuous monitoring and analysis of dynamic environments. It is common for these systems utilize an array of sensors to capture real-time data, which is essential for studying systems behaviors, informed decision-making, and system optimization (Felton et al., 2018) (Al-Qurabat et al., 2021).

Both simulations and sensing require mechanisms to track and store evolving states of data structures over time. In simulations, the naive approach of saving full snapshots at every timestep leads to excessive storage demands, while recalculating states from scratch is computationally expensive. Similarly, in sensing applications, continuously storing or transmitting full data snapshots is impractical, particularly in bandwidth-limited and remote environments. Instead of relying on inefficient methods, KeepDelta introduces an optimized middle ground by saving only the deltas (changes) between states, significantly reducing storage and computation

overhead. This Delta Encoding technique has been successfully applied in other domains where managing evolving data efficiently is critical, such as web development (Hoff et al., 2002) and software version management (Percival, 2003).

Human-readability is crucial for debugging and development in both simulation and sensing projects, and KeepDelta is tailored specifically for this purpose. It is lightweight and has no dependencies, supports native Python data structures, and generates results that are easy to interpret. This makes it an ideal tool for Python developers and researchers seeking a simple yet powerful solution for change management. By providing clear, human-readable output, KeepDelta enhances both the development process and debugging efficiency, making it easier to track and manage changes in complex projects involving both computational models and real-world sensing systems.




Figure 1: caption

## In practice

To install the current version of the KeepDelta package, run the command:

```
pip install keepdelta
```

Then, import it into your project:

```
import keepdelta as kd
```

`create` and `apply` are the two core functionalities of the library.

To *create* the delta between `old` and `new` variables:

```
python
delta = kd.create(old, new)
```

To *apply* the delta to old variable to reconstruct new variable:

```
new = kd.apply(old, delta)
```

KeepDelta supports nested and mixed native Python data structures. Native Python variables types are: - Primitives: integer (`int`), float (`float`), string (`str`), boolean (`bool`), complex

59 (complex), none (None) - Collections: list (list), tuple (tuple), dictionary (dict), set(set)

## 60 Comparison to Existing Tools

61 In the landscape of Python libraries designed for delta encoding, several notable tools have  
62 emerged, each with distinct features and applications. `xdelta3` (Colvin, n.d.) and its predecessor,  
63 `xdelta` (MacDonald, n.d.), are tools that perform delta encoding at the binary level. These  
64 utilities are particularly effective for binary file differencing and are widely used in version  
65 control systems and data synchronization tasks. However, both are considered outdated and  
66 are no longer actively maintained. Their operation at the binary level results in outputs that  
67 are not human-readable, and they are not tailored for Python data structures, limiting their  
68 applicability in Python-centric workflows. `detoos` (Moqvist, n.d.) is a more recent addition,  
69 offering binary delta encoding capabilities within Python applications. It efficiently handles  
70 large binary files and is designed for ease of use. Nevertheless, like `xdelta3` and `xdelta`, `detoos`  
71 operates at the binary level, producing non-human-readable outputs and not being specifically  
72 optimized for Python's native data structures. `deepdiff` (Dehpour, n.d.) is a contemporary  
73 library that facilitates the identification of differences between complex Python data structures,  
74 including dictionaries, lists, and sets. It extends support to external libraries like NumPy (Harris  
75 et al., 2020), enhancing its versatility. However, this integration can lead to outputs that are  
76 less human-readable compared to `KeepDelta`. Additionally, `deepdiff` introduces dependencies  
77 that may not be necessary for all projects. In contrast, `KeepDelta` is a lightweight Python  
78 library optimized for simulations, focusing on efficient delta management for native Python  
79 data structures. It operates directly on Python's native data types, producing human-readable  
80 outputs that facilitate debugging and research applications. Implemented in pure Python,  
81 `KeepDelta` eliminates external dependencies, making it an ideal choice for Python-centric  
82 workflows, particularly in simulations and data analysis tasks.

## 83 References

- 84 Al-Qurabat, A. K. M., Mohammed, Z. A., & Hussein, Z. J. (2021). Data traffic management  
85 based on compression and MDL techniques for smart agriculture in IoT. *Wirel. Pers.*  
86 *Commun.*, 120(3), 2227–2258.
- 87 Aumann, C. A. (2007). A methodology for developing simulation models of complex sys-  
88 tems. *Ecological Modelling*, 202(3), 385–396. [https://doi.org/https://doi.org/10.1016/j.](https://doi.org/https://doi.org/10.1016/j.ecolmodel.2006.11.005)  
89 [ecolmodel.2006.11.005](https://doi.org/https://doi.org/10.1016/j.ecolmodel.2006.11.005)
- 90 Colvin, S. (n.d.). `xdelta3` (Version 0.0.5). <https://github.com/samuelcolvin/xdelta3-python>
- 91 Dehpour, S. (n.d.). `DeepDiff` (Version 8.1.1). <https://github.com/seperman/deepdiff>
- 92 Felton, C. L., Gilbert, B. K., & Haider, C. R. (2018). Data compression via low complexity delta  
93 transition lossless encoding for remote physiological and environmental monitoring. *2018*  
94 *40th Annual International Conference of the IEEE Engineering in Medicine and Biology*  
95 *Society (EMBC)*, 4379–4384. <https://doi.org/10.1109/EMBC.2018.8513277>
- 96 Harris, C. R., Millman, K. J., Walt, S. J. van der, Gommers, R., Virtanen, P., Cournapeau, D.,  
97 Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., Kerkwijk,  
98 M. H. van, Brett, M., Haldane, A., Río, J. F. del, Wiebe, M., Peterson, P., ... Oliphant,  
99 T. E. (2020). Array programming with NumPy. *Nature*, 585(7825), 357–362. <https://doi.org/10.1038/s41586-020-2649-2>
- 100
- 101 Hoff, A. van, Douglass, F., Krishnamurthy, B., Golland, Y. Y., Hellerstein, D. M., Feldmann,  
102 A., & Mogul, J. (2002). *Delta encoding in HTTP* (No. 3229). RFC 3229; RFC Editor.  
103 <https://doi.org/10.17487/RFC3229>
- 104 Kleijnen, J. P. C. (2018). Design and analysis of simulation experiments. In J. Pilz, D. Rasch, V.

- 105 B. Melas, & K. Moder (Eds.), *Statistics and simulation* (pp. 3–22). Springer International  
106 Publishing. ISBN: 978-3-319-76035-3
- 107 MacDonald, J. (n.d.). *xdelta* (Version 3.1.0). <https://github.com/jmacd/xdelta>
- 108 Moqvist, E. (n.d.). *dertools* (Version 0.53.0). <https://github.com/erimoq/dertools>
- 109 Morris, T. P., White, I. R., & Crowther, M. J. (2019). Using simulation studies to evaluate  
110 statistical methods. *Statistics in Medicine*, 38(11), 2074–2102. <https://doi.org/https://doi.org/10.1002/sim.8086>
- 111
- 112 Percival, C. (2003). Naive differences of executable code. *Draft Paper*, [Http://Www.daemonology.net/Bsdiff](http://www.daemonology.net/Bsdiff).  
113

DRAFT