

AsliJobs — API Documentation

Base URL: `/api/v1`
Server: Express 5 (`backend/src/app.ts`)
Auth: Bearer JWT (workspace or job seeker)
Validation: Zod via `validate` middleware
Responses: Centralized success/error helpers (`utils/api-response.ts`)

Complete machine-readable inventory: [AsliJobs API List.xlsx](#)

1. Global endpoints

Method	Path	Auth	Description
GET	<code>/api/v1/health</code>	None	Health check
GET	<code>/uploads/*</code>	None	Static files when <code>STORAGE_PROVIDER=local</code>

2. Authentication module (`/api/v1/auth`)

Method	Path	Description
POST	<code>/workspace/refresh</code>	Refresh employer/team workspace tokens
POST	<code>/workspace/logout</code>	Revoke workspace refresh
POST	<code>/job-seeker/refresh</code>	Refresh job seeker tokens
POST	<code>/job-seeker/logout</code>	Revoke job seeker refresh

JWT roles: `employer` | `team_member` | `job_seeker`

3. Employers (`/api/v1/employers`)

Method	Path	Auth	Notes
POST	<code>/login/send-otp</code>	Public	Rate limited
POST	<code>/login/resend-otp</code>	Public	
POST	<code>/login/verify-otp</code>	Public	Issues workspace tokens
GET	<code>/me</code>	Workspace	Profile
PATCH	<code>/me/profile</code>	Workspace + <code>company_profile.update</code>	
POST	<code>/register</code>	Public	Start registration
POST	<code>/:employerId/otp/resend</code>	Continuation	

POST	/:employerId/otp/verify	Continuation	
POST	/:employerId/company-profile	Continuation + upload	
POST	/:employerId/identity-document	Continuation + upload	

4. Jobs (/api/v1/jobs)

Method	Path	Auth / permission
GET	/public	Optional job seeker
GET	/public/:publicJobId	Optional job seeker
GET	/public/:publicJobId/similar	Optional job seeker
POST	/	jobs.create
POST	/draft	jobs.create
GET	/mine	jobs.read
GET	/mine/stats	jobs.read (+ orphan heal)
POST	/bulk-delete	jobs.delete (cascade)
GET	/:jobId	jobs.read
PUT	/:jobId	jobs.update
PATCH	/:jobId/draft	jobs.update
PUT	/:jobId/publish	jobs.update
PATCH	/:jobId/status	jobs.update
DELETE	/:jobId	jobs.delete (cascade)

5. Job seekers (/api/v1/jobseekers)

Method	Path	Auth
POST	/login/send-otp	Public
POST	/login/resend-otp	Public
POST	/login/verify-otp	Public
GET	/me	Job seeker
PATCH	/me	Job seeker
POST	/me/photo	Job seeker

DELETE	/me/photo	Job seeker
GET	/register/job-roles	Public
POST	/register	Public
POST	/register/resend-otp	Public
POST	/register/verify-otp	Public
POST	/register/preferences	Registration
POST	/register/complete	Registration

6. Resumes (/api/v1/resumes)

Method	Path	Auth
GET	/me	Job seeker
POST	/me/regenerate	Job seeker
GET	/me/pdf	Job seeker

7. Applications (/api/v1/applications)

Job seeker

Method	Path
POST	/apply
GET	/me
GET	/me/stats
GET	/me/:applicationId
POST	/me/:applicationId/withdraw

Employer

Method	Path	Permission
GET	/employer	candidates.read
GET	/employer/stats	candidates.read
GET	/employer/:applicationId	candidates.read
GET	/employer/location-suggestions	candidates.read
PATCH	/employer/:applicationId/status	candidates.update

POST	/employer/:applicationId/shortlist	candidates.update
PATCH	/employer/:applicationId/notes	candidates.update
PATCH	/employer/:applicationId/hiring	candidates.update
PATCH	/employer/:applicationId/interview	interviews.create OR update
PATCH	/employer/:applicationId/interview/cancel	interviews.update
GET	/employer/interviews	interviews.read
GET	/employer/interviews/stats	interviews.read
POST	/employer/export	candidates.export
POST	/employer/export/preview	candidates.export
GET	/employer/:applicationId/pdf	candidates.export
GET	/employer/resume-access/:token/pdf	Public token

8. Saved jobs (/api/v1/saved-jobs)

Method	Path	Auth
GET	/me	Job seeker
GET	/me/stats	Job seeker
GET	/me/ids	Job seeker
POST	/me	Job seeker
DELETE	/me/:publicJobId	Job seeker

9. Saved candidates (/api/v1/saved-candidates)

Method	Path	Typical permission
GET	/	Employer (candidates scope)
GET	/stats	Employer
GET	/ids	Employer
POST	/	Employer
PATCH	/:savedCandidateId	Employer
DELETE	/:savedCandidateId	Employer
DELETE	/by-application/:applicationId	Employer
POST	/export	Employer

POST	/export/preview	Employer
------	-----------------	----------

Shortlisted UI filters with `applicationStatus=shortlisted` and may backfill saved rows for shortlisted applications.

10. Notifications (/api/v1/notifications)

Auth: job seeker **or** employer workspace token (`requireNotificationRecipientAuth`).

Method	Path	Notes
GET	/me	Inbox list
GET	/me/unread-count	Badge
POST	/me/read-all	
POST	/me/clear-all	Soft dismiss
DELETE	/me/:notificationId	
POST	/me/:notificationId/read	
GET	/me/conversations	Employer messages; needs <code>messages.read</code>
GET	/me/conversations/:applicationId/timeline	<code>messages.read</code>
POST	/me/conversations/:applicationId/read	<code>messages.read</code>

11. Team (/api/v1/team)

Public

Method	Path
GET	/invitations/preview
POST	/invitations/accept
POST	/auth/login

Authenticated workspace

Area	Endpoints (prefix <code>/api/v1/team</code>)
RBAC session	GET <code>/rbac/session</code>
Stats / sidebar	GET <code>/stats</code> , GET <code>/sidebar</code>
Roles	CRUD + permissions + archive/activate/duplicate
Members	list, invite, update, transfer, change-role, activate/deactivate, delete, resend/cancel invitation
Departments	CRUD + deactivate

Self	GET /members/me
------	-----------------

Most team routes require `team_management.*` permissions; owners have full access.

12. Controllers / services / validation pattern

Each mounted module typically contains:

- `*.routes.ts` — Express router + middleware chain
- `*.controller.ts` — thin HTTP adapter
- `*.service.ts` — business logic
- `*.validation.ts` — Zod schemas
- `*.model.ts` — Mongoose schema (where persisted)

RBAC engine: `backend/src/modules/rbac/`

Permissions middleware: `backend/src/middleware/permission.middleware.ts`

13. Unmounted / placeholder modules

Folders under `backend/src/modules/` without API mounts: `admin`, `campaigns`, `interviews` (standalone), `placements`, `subscriptions`, `support`, `users`, `shared`. Interview **functionality** is served via Applications routes, not a separate interviews router.