

TREE-BASED MULTIPLE IMPUTATION METHODS

Michael Dellermann, Anatol Sluchych, and Jonah Wermter

1. Motivation

- Parametric MICE methods: conditional models to be specified for *all* variables with missing data (van Buuren & Groothuis-Oudshoorn, 2011)
- Still may fail to capture interactive and nonlinear relations among variables as well as non-standard distributions
- Tree-based methods *automatically* capture interactions, nonlinear relations, and complex distributions with no parametric assumptions or data transformations needed (Burgette & Reiter, 2010)
- Implementation in R: *mice* and *miceRanger* packages

2. Tree-based methods

Classification and regression trees (CART):

- seek to approximate conditional distribution of univariate outcome from multiple predictors
- segment predictor space into non-overlapping regions with relatively homogeneous outcomes
- segments found by recursive binary splits of predictors
- prediction for observations that fall into the same region is mean (or mode) of response values for training observations in region
- may be very non-robust and have relatively low predictive accuracy




Fig. 1: Example of tree structure. Source: Hastie, Tibshirani, & Friedman (2009)

Random forest:

- *ensemble* method that addresses non-robustness and low predictive accuracy
- average predictions from B non-pruned trees constructed using B bootstrapped training sets
- *decorrelates* trees by performing each split on *randomly* chosen subset of predictors
- accurate model to impute missing values (Stekhoven & Bühlmann, 2011)

3. Imputation algorithm

4-steps algorithm:

1. Initial values for the missing values filled in as follows:
 - (a) Define a matrix Z equal to Y_C
 - (b) Impute missing values in Y_i , where $i = 1, \dots, p_1$, using tree-based method on Z and append the completed version of Y_i to Z prior to incrementing i

2. Replace the originally missing values of Y_i , where $i = 1, \dots, p_1$, with tree-based methods on Y_{-i}
3. Repeat l times step 2
4. Repeat steps 1–3 m times and obtain m imputed sets.

4. Comparison mice/miceRanger packages

- both implement van Buuren's multivariate imputation by chained equations
- *mice* supports variety of imputation methods, *miceRanger* only random forest
- *mice* uses common R packages *rpart* and *randomForest* to implement tree-based imputation methods (van Buuren, 2023)
- *miceRanger* uses the *ranger* package instead, which claims to be faster and more efficient with medium and large data sets (Wilson, 2022)
 - ⇒ core functions written in C++ (faster than R, compiled vs. interpreted code) (Wright & Ziegler, 2017)
 - ⇒ lacks pooling function

5. Empirical simulation study

Empirical data set:

- RAND's Health Insurance Experiment: $n = 20185$, $k = 46$

Missing data mechanisms:

- $p=25\%$ and 50%
- MAR with $\rho = 0, \tau = 0$: $P(mdvis_miss \mid xage < 25) = p$, $P(mdvis_miss \mid mhi > 74) = p$
- MCAR: $P(income_miss) = p$, $P(educdec_miss) = p$

Monte Carlo simulation: $R = 1000$, $M = 5$, $n = 2000$, $niter = 10$, $nrtree = 10$

6. Results




Fig. 2: Imputation time per subset per method




Fig. 3: Coverage rate by model

7. Conclusion

- *miceRanger* outperforms other random forest imputation methods, working on average approximately ...% faster per simulation cycle
- With changing the variability of data types, *miceRanger* works on average ...% faster per simulation cycle.
- With changing size of data sets, *miceRanger* works on average ...% fast per simulation cycle

References

- Burgette, L. F., & Reiter, J. P. (2010). Multiple imputation for missing data via sequential regression trees. *American Journal of Epidemiology*, 172(9), 1070–1076. doi:10.1093/aje/kwq260
- Hastie, T., Tibshirani, R., & Friedman, J. H. (2009). *The elements of statistical learning: Data mining, inference, and prediction* (2nd ed.). New York: Springer.
- James, G., Witten, D., Hastie, T., & Tibshirani, R. (2013). *An introduction to statistical learning with applications in R*. New York: Springer.
- Mayer, M. (2023). *Package 'missranger'*. Retrieved from <https://cran.r-project.org/web/packages/missRanger/missRanger.pdf>
- Murphy, K. P. (2022). *Probabilistic machine learning: An introduction*. Cambridge: MIT Press.
- Stekhoven, D. J., & Bühlmann, P. (2011). MissForest—non-parametric missing value imputation for mixed-type data. *Bioinformatics*, 28(1), 112–118. doi:10.1093/bioinformatics/btr597
- van Buuren, S. (2023). *Package 'mice'*. Retrieved from <https://cran.r-project.org/web/packages/mice/mice.pdf>
- van Buuren, S., & Groothuis-Oudshoorn, K. (2011). mice: Multivariate imputation by chained equations in R. *Journal of Statistical Software*, 45(3), 1–67. doi:10.18637/jss.v045.i03
- Wilson, S. (2022). *Package 'miceranger'*. Retrieved from <https://cran.r-project.org/web/packages/miceRanger/miceRanger.pdf>
- Wright, M. N. (2023). *Package 'ranger'*. Retrieved from <https://cran.r-project.org/web/packages/ranger/ranger.pdf>
- Wright, M. N., & Ziegler, A. (2017). ranger: A fast implementation of random forests for high dimensional data in C++ and R. *Journal of Statistical Software*, 77(1). doi:10.18637/jss.v077.i01