

OPENUSD GEOSPATIAL · CO-SUBMISSION PREVIEW

usdGeospatial

a codeless CRS schema for OpenUSD, proven by two runtimes

schema declares · runtime resolves · one real-world coordinate frame

A codeless geospatial CRS schema

- Pure-data schema: a CRS prim + a binding API, skipCodeGeneration=true (no compiled types).
- All resolution behavior lives in the example runtimes, not the schema.
- Same shape as the landed Gaussian / particleField contribution: schema + sample runtime(s) + converter + docs.
- Runtimes here: Python `resolve_runtime.py` and a C++ Hydra scene index.

The design call

Resolve at runtime; keep the authored scene coordinate-neutral.

REPLACE · WRAP · OR COEXIST?

Resolve, don't bake

- `crs:binding` is a relationship resolved at runtime — not references-as-binding, not a baked `resetXformStack`.
- The authored scene stays coordinate-neutral; a runtime reprojects and composes ancestor transforms.
- This is the question the earlier effort stalled on — replace, wrap, or coexist with the `UsdGeomXformable` stack? The answer here is **coexist**.
- Proven, not argued: the baked Esri scene and our neutral scene land the same corner to 0.0 mm.

Anchor injection: inject, don't bake

- A georeferenced anchor with an ordinary Cartesian subtree (a building in local metres) — children have no `crs:position`.
- The runtime injects the anchor's rigid local-frame → ECEF basis (full ENU orientation) at resolve time.
- The subtree then composes under it as ordinary `UsdGeomXformable` — nothing baked into the layer.
- `resetXformStack` lives only on a transient, computed Hydra data source, never the authored scene.

Projected vs geographic anchors

- A GEOGRAPHIC/ECEF anchor's child offsets are local metres → compose through the anchor's true-ENU basis (orientation matters; local +Z = ellipsoidal normal).
- A PROJECTED (UTM/State-Plane) anchor's child offsets live in the grid plane → compose IN-PLANE (grid add + reproject), NOT through ENU.
- UTM grid axes differ from true ENU by grid-convergence + point-scale — lifting grid offsets through ENU bends them ~4.86 m over a ~420 m lever.
- Same neutral authored scene; the runtime picks the frame from the bound CRS type.
Proven 0.0 mm both ways against closed-form geodesy.


The evidence

Three proofs an independent reviewer can check.

PROOF · NO OVERFIT

Real third-party asset on real tiles

Real third-party asset rendered through the codeless resolver — Deutsche Bahn rails on geospatial tiles




An external Deutsche Bahn railway (~1,470 curves) authored in the original Omniverse schema, converted to crs:binding/crs:position, resolved onto three real geospatial tiles near Hamburg — no Hydra, no baking.

PROOF · CO-REGISTRATION Three CRSs, one ECEF point

3D coherence — schema-resolved geometry co-registers with closed-form WGS84 ground truth (independent of PROJ)

Earth-2 t2m cloud (resolve_runtime) on a closed-form WGS84 graticule — field sits on the right latitudes



red dots @ origin = same cloud resolved
IGNORING crs:binding (negative control)

Cross-CRS co-registration at one benchmark (NOAA NCAT)
three CRSs → one ECEF point → matches closed-form GT

Closed-form WGS84 GT

(first principles, no PROJ)

(1334930.899, -4651062.376, 4141331.101)

SiteGeographic (EPSG:4979)

lon/lat from NOAA NCAT

Δ to GT = 0.000 mm

SiteUTM18N (EPSG:32618)

E/N from NOAA NCAT

Δ to GT = 0.537 mm

SiteNYSPC (EPSG:32118)

State-Plane E/N from NOAA NCAT

Δ to GT = 0.361 mm

three independent CRSs co-register to ≤ 0.537 mm — authored from independent NOAA coords,
not by inverting one transform; negative control (ignore binding) lands 6.4×10^6 m off the globe.


The same monument authored three independent ways (geographic / UTM 18N / NY State Plane) from independent NOAA NCAT coordinates co-registers to one ECEF point to $\leq \sim 0.5$ mm — checked against closed-form WGS84 geodesy, not a parallel PROJ call.

One schema, two runtimes

The schema is the contract; the behavior is plural.

PROOF · CONTRACT NOT IMPLEMENTATION Two independent runtimes, 0.0 mm

One codeless schema, two viable runtime implementations — the schema is the contract; the behavior is plural



The Python reference runtime and the compiled C++ Hydra scene index resolve the same authored stage to the same world, agreeing to 0.0 mm. A third runtime plugs into the same seam.

NO EXACT PRECEDENT — BY DESIGN

Where the Python reference runtime sits

- It's the codeless schema's **executable specification / conformance oracle** — 'given this stage, where does each prim end up?'
- NOT proposed for USD core, NOT a runtime dependency, NOT Python-in-the-render-loop, NOT the prescribed consumer.
- Real consumers (Hydra, OpenExec, Omniverse, GPU cuProj) implement the same contract; the Python is the spec they conform to.
- New part: a runnable reference as the normative behavior for a codeless schema whose behavior is deliberately external.

Guard rails

Coexist's costs are asset-structure invariants a validator can enforce — a normal USD conformance surface.

ENFORCEABLE, NOT SHOWSTOPPERS

Guard rails a validator can check

- Coexist has no architectural showstopper — it matches baking to 0 mm when it composes in the CRS-implied frame.
- Its residual costs are a small set of ASSET-STRUCTURE invariants, each mechanically checkable.
- (1) anchor-vs-child is unambiguous; (2) child offsets are authored in the frame the bound CRS implies; (3) a CRS-requiring stage declares it so unaware consumers detect-and-refuse.
- A neutral authored scene PRESERVES the semantic info a validator needs; a baked scene has already collapsed CRS intent into a matrix.

Open questions

What we'd most like the working group's read on.

Open design questions

- 1. Is 'codeless schema + a runnable reference runtime as the behavior contract' the right shape — and where should that reference ultimately live?
- 2. Is **coexist** the right relationship to `UsdGeomXformable` (neutral scene + runtime reconciliation) — versus hooking CRS resolution into `Xformable` directly? Given the head-to-head parity + the guard-rail set, is the residual validation surface acceptable to standardize?

What we need from you

Concrete asks so the next iteration is grounded in your workflows, not our guesses.

What we need from you

- 1. The Redlands BIM prototype scene + its validation script, so we can add a second real, contributor-authored case beside the multi-CRS POC.
- 2. Confirmation / correction of the driving workflows: which of AECO site placement, multi-source GIS twins, multi-zone infrastructure, and geodetic sim must 'coexist' survive first?
- 3. A read on the guard-rail set as a conformance surface (anchor-vs-child, compose-in-CRS-frame, a 'requires-CRS' stage marker + detect-and-refuse) and appetite for a codeless validator plugin.
- 4. Where the reference runtime should live, and whether to abstract 'resetXformStack' out of the proposal text in favor of a behavior contract multiple runtimes honor.