

· Designed for removal and replacement

- arings and oil seals
- Features tapered cone bearing and seal driver tools, manufactured from aluminium for damage free bearing and oil seal replacement
- Available in Metric and SAE

10-42mm

Bush Adapters: 10-42mm

Crankcase Separator Tool 8 Piece

- Simple and effective puller set to suit most two and four stroke engines that have a vertically split crankcase
- Adjustable puller legs allow for a multitude of bolt patterns
- Spread: 50-240mm





Vacuum Pump

& Brake Bleeder Kit

Bleeds hydraulic brake and clutch

systems - one-man operation

Die cast pump body with gauge

Harley-Davidson Gudgeon Pin Remover & Installer Tool

- Manufactured from lightweight aluminium and chrome molybdenum alloy steel
- Applications include Harley-Davidson stock and aftermarket engines, including Twin Cam, and other engine makes with similar piston pin diameter sizes.



Spoke remover releases damaged or rusted spokes easily

Features an o-ring seal in both ends for dust proofing



- Essential tool for removing and installing piston pins without damaging the piston
- provides a firm and comfortable

Chain Breaking And

Riveting Master Kit

Comprehensive tool kit for drive

chain replacement and repair

Provides the ability to break, rivet and





Crankshaft **Installation Kit**

- Designed for installation of the crankshaft into the crank case.
- Suitable for most single cylinder vertically split engines
- Includes 1 x installation pot, 1 x
- pot spacer, 1 x nut & bolt, and 11





Cable Wire Lubrication Tool

Includes rivet function to

to complete the repair

For most 50 series chains and

- Designed to lubricate throttle and clutch cables • Lubricating motorcycle cables prolongs service life and reduces risk of breakage
- Simple operation injects lubricant into cable housing

Spoke Torque Wrench Set

Steel 12 Piece

- Enables tightening and removal of spokes in one piece
- Applies correct and equal tension to the spokes • Spoke remover releases damaged or rusted spokes easily
- Simply tighten the spoke until you hear and feel a click which indicates that the spoke is adjusted correctly
- Takes all the guesswork out of wheel and spoke assembly and maintenance
- Adjustable Torque Wrench 2-10 Nm
- Sizes: 5.0, 5.6, 5.8, 6.0, 6.2, 6.3, 6.5, 6.7, 6.9, 7.1, 7.4mm & Spline drive







Sealing Ring Assembly Tool Set

- Tapered tool set for pulling o'rings or sleeves onto brake components and hydraulic systems without risk
- Size range: 14.4-22.4mm



Carburetor **Adjusting Tool Set**

- Designed for those hard-to-reach air/fuel mixture screws on most multi-cylinder motorcycles
- Special angled drive design assists in aligning he bit with the carburetor adjustment sc
- 9 piece set includes Flat, Phillips, PH#2 & D-type bits
- Supplied in a durable metal case



Cooling System & Radaiator Pressure Test Set

- Hand operated pump builds and displays pressure quickly to locate leaks in cooling and radiator systems
- Dual scale pressure gauge (PSI / Bar) features 300mm hose and push-buttor pressure release valve
- Includes attachments to test both cooling





Pick & Hook Set 4pc

- Durable soft grip pick and hook set ideal for removal of o-rings, seals and bushes in various mechanical applications
- Contains straight, 45 and 90 degree picks plus hook tool

Part No.	Overall Length	Shaft Length	PRICE
BS1234	162mm	76mm	\$19.95
BS0230	214mm	152mm	\$25.95



- alignment
- Designed for universal use, suitable for most motorcycles and ATV's
- Affix to the rear sprocket with alignment rod facing forward to align chain
- Suitable chain sizes 420 630





- for use with slotted retaining rings
- Thin hook can access confined areas in motorcycle steering and suspension (4mm Manufactured from chrom
- vanadium hardened steel


Part No.	Size	PRICE
BS0350	19-51mm (3/4"-2")	\$31.95
BS0351	32-76mm (1 1/4" - 3")	\$47.30
BS0352	51-120mm (2" - 4 3/4")	\$69.95
BS0353	118-158mm (4" - 6")	\$62.95
	- Marie La Company	-



Magneto Flywheel Puller Sets







- Features threaded pullers designed for fixed-point type magneto flywheels Chrome alloy steel ball tip on shaft to reduce friction stress during disassembly
- 1/2" Sq. Dr. (21mm Hex)

Part No.	Style	Qty	Size	PRICE
BS30014	External	14рс	M19 x 1.0 to M33 x 1.5	\$269.95
BS30015	Inter nal	16рс	M24 x 1.0 - M50 x 1.5	\$499.95
BSB00391	External & Internal	15pc	M19 x 1.0 to M42 x 1.5	\$499.95

Wheel Nut Sockets



 Dual size alloy wheel nut socket for front and rear axles

BSE05551

- Maximum torque: 280-320Nm
- 1/2" Sq. Dr.

- / -1					
Part No.	Suits	Diameter	PRICE		
BS5550	Ducati	41 & 46mm	\$67.95		
BS5551	Ducati	30 & 55mm	\$92.95		
BSE05551	Impact - Ducati	30 & 55mm	\$99.95		
BS5552	MV Agusta	26 & 56mm	\$96.95		
BS70012	KTM	60mm	\$99.95		



- · Incorporates thread depth measuring tool
- Includes braided steel hose, swivel chuck and pressure release button.
- Working pressure to 5 Bar (70 PSI)