

- Comprehensive all in one set of kit includes hydraulic flaring tool with dies and punches, debur tool, tube bender and cutter

Suits: Copper, Brass, Aluminium and Mild Steel pipe Pipe Sizing: 3/16", 4.75mm, 5mm, 6mm, 1/4" • Produces: DIN and SAE single and double flares



- **Socket Set** Metric 3pc • Deep impact sockets with removable protective outer shell
- Suitable for alloy, chrome and painted wheels with long or short wheel nuts
- Colour coded for quick identification
- Size: 17mm, 19mm, 21mm

Wheel Nut



- Designed for strength and versatility
- Removable protective plastic outer shell protects against damage to alloy wheels
- Designed to suit standard, alloy and performance wheels
- Colour coded for quick reference to size
- Size: 15, 17, 19, 21, 22mm



- Deep impact sockets with removable protective outer shell • Suitable for alloy, chrome and painted wheels with long or
- short wheel nuts
- Colour coded for quick identification
- Size: 17, 19, 21, 22, 23, 24, 27mm



set features nylon sleeve to prevent scratching

Colour coded 1/2" square drive includes 17, 19 & 21mm



- For the restoration of damaged threads on wheel
- studs and bolts/ bolt holes
- Suitable for most Japanese and European vehicles
- Die Size: M12 x 1.25mm, M12 x 1.5mm. M14 x 1.5mm
- Tap Size: M12 x 1.25mm (psa), M12 x 1.5mm, M12 x 1.75mm, M14



Universal Lock Nut Removal Kit Heavy Duty

- Designed for removing wheel lock nuts on most factory and aftermarket wheels without causing damage
- Conical shaped design allows sockets to fit firmly over the lock nuts
- Heavy duty construction for strength and durability • Size range from (conical socket): Ø19.4, 20.4, 21.4, 22.4, 23.4, 24.4, 25.4, 27.8, 28.8, 29.8mm

Brake Pressure Test Kit Universal 8pc

- Comprehensive kit used for testing and diagnosing hydraulic system faults such as leaks and restrictions within the hydraulics of both anti-lock and conventional braking systems
- Suitable for simultaneous testing on non-ABS systems. ABS systems, Teves systems and Bosch systems, comparative readings of proportional brake pressure for both front and rear brakes, and testing primary vs.
- Includes two 3000 PSI (200 Bar) pressure gauges





- Size range: Ø 18.5 15.6, 19.5 17.6, 20.4 18.5, 21.6 19.7, 22.5 20.6, 23.6 - 21.7, 24.5 - 22.6, 25.5 - 23.6mn



Nut Master Set 16pc • Designed for removing locking wheel nuts

- Universal master set suitable for various factory and
- aftermarket wheels Heat treated chrome vanadium steel for strength and durability







Suitable for all diesel applications Includes various size brushes and adaptors 8



- back kit applicable for both right and left hand threaded pistons Adjustable adaptors suitable to most vehicles
- Adaptor size range: 22 37mm







Brake & Tyre Measuring Tool

- Measures brake disc and brake pad thickness including tyre tread wear
- Suitable for passenger, 4WD and light trucks
- Tyre tread depth range: 0-25mm Brake measuring range: 10-60mm

Compression Tester Kit Petrol 300psi A genuine professional mechanics petrol mpression tester supplied in heavy duty case with foam inlay Dual calibrated gauge stainless steel braided high pressure hose with adaptors Sizes: M10, M12, M14, M16



- Innovative combination of Ratchet Wrench and Extension handle to allow for 3 dynamic angles of leverage $\,$
- Universal set covers all major makes and models with serpentine belt configuration • Sizes: 8, 12, 13, 17, 18, 24mm & 5/8" sockets. 8mm, 8 x 6mm,
- 10 x 8mm hex bits. 3/8" & 1/2" Sq. Dr. adaptors







1 Litre Handy engine oil top up funnel with six adaptor

fittings to allow easy and mess free filling





Cooling System Pressure Test Kit

- Use for diagnosing overheating issues, head
- gasket leakage, loss of coolant, heating and cooling faults For radiators with bayonet style filler necks and screw on cap
- expansion tank style Hand pump provides a maximum of 35psi of pressure
- Thermometer range: -50 to +150 °C / -50 to 300 °F