

Break 10 minutes



internals.tech

TIE
community



Crafting the Ultimate Docker Image for Spring Applications

Pasha Finkelshteyn



Berlin Germany



TIE

Crafting the Ultimate Docker Image for Spring Applications



bellsoft

whoami



whoami

- Pasha Finkelshteyn



whoami

- Pasha Finkelshteyn
- Dev 🥑 at BellSoft



whoami

- Pasha Finkelshteyn
- Dev 🥑 at BellSoft
- ≈10 years in JVM. Mostly ☕ and



whoami

- Pasha Finkelshteyn
- Dev 🥑 at BellSoft
- ≈10 years in JVM. Mostly ☕ and 
- And 



whoami

- Pasha Finkelshteyn
- Dev 🥑 at BellSoft
- ≈10 years in JVM. Mostly ☕ and 
- And 
-  asm0di0



whoami

- Pasha Finkelshteyn
- Dev 🥑 at BellSoft
- ≈10 years in JVM. Mostly ☕ and 
- And 
-  asm0di0
-  @asm0dey@fosstodon.org



BellSoft

- Vendor of Liberica JDK
- Contributor to the OpenJDK
- Author of ARM32 support in JDK
- Own base images
- Own Linux: Alpaquita

Liberica is the JDK officially recommended
by 



BellSoft

- Vendor of Liberica JDK
- Contributor to the OpenJDK
- Author of ARM32 support in JDK
- Own base images
- Own Linux: Alpaquita

Liberica is the JDK officially recommended
by 

We know our stuff!



So, what is ultimate?

- Smallest
- Fatsest startup
- Something inbetween

So, let's look at all of
them!

How do we create an image?

Let's start from trivial.

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

How do we create an image?

Let's start from trivial.

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

How do we create an image?

Let's start from trivial.

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

How do we create an image?

Let's start from trivial.

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

How do we create an image?

Let's start from trivial.

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

Dockerfile directives

1. Each directive creates a layer of the image.
2. Layers are *immutable*
3. Some layers are zero-sized

Dockerfile directives

1. Each directive creates a layer of the image.
2. Layers are *immutable*
3. Some layers are zero-sized

```
1  FROM bash
2
3  COPY . /app
4  RUN rm -rf /app
```

Dockerfile directives

1. Each directive creates a layer of the image.
2. Layers are *immutable*
3. Some layers are zero-sized

```
1 FROM bash
2
3 COPY . /app
4 RUN rm -rf /app
```

Dockerfile directives

1. Each directive creates a layer of the image.
2. Layers are *immutable*
3. Some layers are zero-sized (for example `RUN rm -rf /app`)

```
1 FROM bash
2
3 COPY . /app
4 RUN rm -rf /app
```

Dockerfile directives

1. Each directive creates a layer of the image.
2. Layers are *immutable*
3. Some layers are zero-sized (for example `RUN rm -rf /app`)

```
1 FROM bash
2
3 COPY . /app
4 RUN rm -rf /app
```

4. We would like image to be light, but it's not :(

Our Dockerfile

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

Our Dockerfile

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

Our Dockerfile

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

Our Dockerfile

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

Result

13	<missing>	0B	ARG BUNDLE_TYPE
14	<missing>	0B	ARG BUNDLE_TYPE
15	<missing>	0B	ARG BUNDLE_TYPE
16	<missing>	0B	ARG JAVA_RELEASE
17	<missing>	7.49MiB	CMD ["/bin/sh"]
18	<missing>	0B	9 APK_REPOS= D
19	<missing>	0B	ADD file:a4d77f
20	<missing>	0B	LABEL org.openc
21	<missing>	0B	LABEL org.openc
22	<missing>	0B	LABEL maintaine
23	<missing>	0B	ARG APK_REPOS D
24	<missing>	0B	ARG APK_REPOS L
25	<missing>	0B	ARG APK_REPOS L
26	<missing>	0B	ARG APK_REPOS L
27	<missing>	0B	ARG LIBC MINIRO
28	<missing>	0B	ARG MINIROOTFS

Result

9	<missing>	0B	LABEL org.openc
10	<missing>	0B	LABEL maintaine
11	<missing>	0B	ARG BUNDLE_TYPE
12	<missing>	0B	ARG BUNDLE_TYPE
13	<missing>	0B	ARG BUNDLE_TYPE
14	<missing>	0B	ARG BUNDLE_TYPE
15	<missing>	0B	ARG BUNDLE_TYPE
16	<missing>	0B	ARG JAVA_RELEASE
17	<missing>	7.49MiB	CMD ["/bin/sh"]
18	<missing>	0B	9 APK_REPOS= D
19	<missing>	0B	ADD file:a4d77f
20	<missing>	0B	LABEL org.openc
21	<missing>	0B	LABEL org.openc
22	<missing>	0B	LABEL maintaine
23	<missing>	0B	ARG APK_REPOS D
24	<missing>	0B	ARG APK_REPOS L
25	<missing>	0B	ARG APK_REPOS L

Result

3	74a0788411	512.03MiB	/bin/sh -c cd /
4	7b82eb08ec	67.41MiB	COPY dir:ef251b
5	e4bcf83d29	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB 15 BUNDLE_TYPE
6	<missing>	0B	ENV JAVA_HOME="
7	<missing>	0B	ENV LANG=en_US.
8	<missing>	0B	LABEL org.openc
9	<missing>	0B	LABEL org.openc
10	<missing>	0B	LABEL maintaine
11	<missing>	0B	ARG BUNDLE_TYPE
12	<missing>	0B	ARG BUNDLE_TYPE
13	<missing>	0B	ARG BUNDLE_TYPE
14	<missing>	0B	ARG BUNDLE_TYPE
15	<missing>	0B	ARG BUNDLE_TYPE
16	<missing>	0B	ARG JAVA_RELEASE
17	<missing>	7.49MiB	CMD ["/bin/sh"]
18	<missing>	0B	9 APK_REPOS= D
19	<missing>	0B	ADD file:a4d77f

Result

1	ID	TAG	SIZE	COMMAND
2	cda5201e70	dumb:latest	0B	CMD ["/bin/sh"
3	74a0788411		512.03MiB	/bin/sh -c cd /
4	7b82eb08ec		67.41MiB	COPY dir:ef251b
5	e4bcf83d29	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE
6	<missing>		0B	ENV JAVA_HOME="
7	<missing>		0B	ENV LANG=en_US.
8	<missing>		0B	LABEL org.openc
9	<missing>		0B	LABEL org.openc
10	<missing>		0B	LABEL maintaine
11	<missing>		0B	ARG BUNDLE_TYPE
12	<missing>		0B	ARG BUNDLE_TYPE
13	<missing>		0B	ARG BUNDLE_TYPE
14	<missing>		0B	ARG BUNDLE_TYPE
15	<missing>		0B	ARG BUNDLE_TYPE
16	<missing>		0B	ARG JAVA_RELEAS

Result

1	ID	TAG	SIZE	COMMAND
2	cda5201e70	dumb:latest	0B	CMD ["/bin/sh"
3	74a0788411		512.03MiB	/bin/sh -c cd /
4	7b82eb08ec		67.41MiB	COPY dir:ef251b
5	e4bcf83d29	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE
6	<missing>		0B	ENV JAVA_HOME="
7	<missing>		0B	ENV LANG=en_US.
8	<missing>		0B	LABEL org.openc
9	<missing>		0B	LABEL org.openc
10	<missing>		0B	LABEL maintaine
11	<missing>		0B	ARG BUNDLE_TYPE
12	<missing>		0B	ARG BUNDLE_TYPE
13	<missing>		0B	ARG BUNDLE_TYPE
14	<missing>		0B	ARG BUNDLE_TYPE
15	<missing>		0B	ARG BUNDLE_TYPE
16	<missing>		0B	ARG JAVA_RELEAS

Result

1	ID	TAG	SIZE	COMMAND
2	cda5201e70	dumb:latest	0B	CMD ["/bin/sh"
3	74a0788411		512.03MiB	/bin/sh -c cd /
4	7b82eb08ec		67.41MiB	COPY dir:ef251b
5	e4bcf83d29	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE
6	<missing>		0B	ENV JAVA_HOME="
7	<missing>		0B	ENV LANG=en_US.
8	<missing>		0B	LABEL org.openc
9	<missing>		0B	LABEL org.openc
10	<missing>		0B	LABEL maintaine
11	<missing>		0B	ARG BUNDLE_TYPE
12	<missing>		0B	ARG BUNDLE_TYPE
13	<missing>		0B	ARG BUNDLE_TYPE
14	<missing>		0B	ARG BUNDLE_TYPE
15	<missing>		0B	ARG BUNDLE_TYPE
16	<missing>		0B	ARG JAVA_RELEAS

Result

1	ID	TAG	SIZE	COMMAND
2	cda5201e70	dumb:latest	0B	CMD ["/bin/sh"
3	74a0788411		512.03MiB	/bin/sh -c cd /
4	7b82eb08ec		67.41MiB	COPY dir:ef251b
5	e4bcf83d29	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE
6	<missing>		0B	ENV JAVA_HOME="
7	<missing>		0B	ENV LANG=en_US.
8	<missing>		0B	LABEL org.openc
9	<missing>		0B	LABEL org.openc
10	<missing>		0B	LABEL maintaine
11	<missing>		0B	ARG BUNDLE_TYPE
12	<missing>		0B	ARG BUNDLE_TYPE
13	<missing>		0B	ARG BUNDLE_TYPE
14	<missing>		0B	ARG BUNDLE_TYPE
15	<missing>		0B	ARG BUNDLE_TYPE
16	<missing>		0B	ARG JAVA_RELEAS

579.44 MB are changed on every build!

Why do we care? We care because:

1. `push` takes longer time to start
(update is longer)
2. `pull` takes longer
(update takes longer & scaling takes longer)

Also, more disk pspace is inefficiently used



Optimizing. Round 1.

Let's build it outside of container

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

Optimizing. Round 1.

Let's build it outside of container

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY build/libs/spring-petclinic-3.3.0.jar /app/app.jar
4 CMD java -jar /app/app.jar
```

Optimizing. Round 1.

Let's build it outside of container

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY build/libs/spring-petclinic-3.3.0.jar /app/app.jar
4 CMD java -jar /app/app.jar
```

Just copying the prebuilt `jar` file

Results

1	ID	TAG	SIZE	COMMAND
2	cda5201e70	dumb:latest	0B	CMD ["/bin/sh" "-c" "/app
3	74a0788411		512.03MiB	/bin/sh -c cd /app && ./g
4	7b82eb08ec		67.41MiB	COPY dir:ef251bd1e17ac0af
5	e4bcf83d29	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE=jdk CDS=n
6	<missing>		0B	ENV JAVA_HOME="/usr/lib/j
7	<missing>		0B	ENV LANG=en_US.UTF-8 LANG
8	<missing>		0B	LABEL org.opencontainers.
9	<missing>		0B	LABEL org.opencontainers.
10	<missing>		0B	LABEL maintainer="\$MAINTA
11	<missing>		0B	ARG BUNDLE_TYPE CDS DESCR
12	<missing>		0B	ARG BUNDLE_TYPE CDS JAVA_
13	<missing>		0B	ARG BUNDLE_TYPE CDS JAVA_
14	<missing>		0B	ARG BUNDLE_TYPE CDS JAVA_
15	<missing>		0B	ARG BUNDLE_TYPE JAVA_RELE
16	<missing>		0B	ARG JAVA_RELEASE
17	<missing>		7.49MiB	CMD ["/bin/sh"]

Results

1	ID	TAG	SIZE	COMMAND
2	cefb30e21d	smarter:latest	0B	CMD ["/bin/sh" "-c" "java
3	46d7594000		58.80MiB	COPY file:8d96bee95ae5ce43
4	e4bcf83d29	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE=jdk CDS=no
5	<missing>		0B	ENV JAVA_HOME="/usr/lib/jv
6	<missing>		0B	ENV LANG=en_US.UTF-8 LANGU
7	<missing>		0B	LABEL org.opencontainers.i
8	<missing>		0B	LABEL org.opencontainers.i
9	<missing>		0B	LABEL maintainer="\$MAINTAI
10	<missing>		0B	ARG BUNDLE_TYPE CDS DESCR
11	<missing>		0B	ARG BUNDLE_TYPE CDS JAVA_R
12	<missing>		0B	ARG BUNDLE_TYPE CDS JAVA_R
13	<missing>		0B	ARG BUNDLE_TYPE CDS JAVA_R
14	<missing>		0B	ARG BUNDLE_TYPE JAVA_RELEA
15	<missing>		0B	ARG JAVA_RELEASE
16	<missing>		7.49MiB	CMD ["/bin/sh"]


Saved 500+ MB

But the build is not clean now :(

Saved 500+ MB

But the build is not clean now :(

We have to build everything outside, what if environment affects the build?

A highly detailed, ornate theater stage set. The stage is framed by a grand, dark wood structure with classical columns and intricate carvings. Red velvet curtains hang from the top, framing the stage area. A large, multi-tiered chandelier hangs from the ceiling, casting a warm, golden light. The stage floor is made of dark wood, and a large, patterned rug is laid out in the foreground. The overall atmosphere is one of grandeur and elegance.

Enter build stages

Multi-stage builds

Holy grail of pure builds

- Allow clean builds
- Allow optimal packaging
- Allow different base images

Staged example

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```

Staged example

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```

Staged example

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```

Staged example

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```

Staged example

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```

Staged example

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```

Result

1	ID	TAG	SIZE	COMMAND
2	6ea7ad11af	smarter:latest	0B	CMD ["/bin/sh" "-c
3	d6eb71a5df		58.80MiB	COPY file:8d96bee9
4	c6ede8dac2	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE=jc
5	<missing>		0B	ENV JAVA_HOME="/us
6	<missing>		0B	ENV LANG=en_US.UTF
7	<missing>		0B	LABEL org.opencont
8	<missing>		0B	LABEL org.opencont
9	<missing>		0B	LABEL maintainer='
10	<missing>		0B	ARG BUNDLE_TYPE CI
11	<missing>		0B	ARG BUNDLE_TYPE CI
12	<missing>		0B	ARG BUNDLE_TYPE CI
13	<missing>		0B	ARG BUNDLE_TYPE CI
14	<missing>		0B	ARG BUNDLE_TYPE JA
15	<missing>		0B	ARG JAVA_RELEASE
16	<missing>		7.49MiB	CMD ["/bin/sh"]

Result

1	ID	TAG	SIZE	COMMAND
2	6ea7ad11af	smarter:latest	0B	CMD ["/bin/sh" "-c
3	d6eb71a5df		58.80MiB	COPY file:8d96bee9
4	c6ede8dac2	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE=jc
5	<missing>		0B	ENV JAVA_HOME="/us
6	<missing>		0B	ENV LANG=en_US.UTF
7	<missing>		0B	LABEL org.opencont
8	<missing>		0B	LABEL org.opencont
9	<missing>		0B	LABEL maintainer='
10	<missing>		0B	ARG BUNDLE_TYPE CI
11	<missing>		0B	ARG BUNDLE_TYPE CI
12	<missing>		0B	ARG BUNDLE_TYPE CI
13	<missing>		0B	ARG BUNDLE_TYPE CI
14	<missing>		0B	ARG BUNDLE_TYPE JA
15	<missing>		0B	ARG JAVA_RELEASE
16	<missing>		7.49MiB	CMD ["/bin/sh"]

That's all folks!

That's all folks!

Or is it?

What's these 59 MiB?

We have to pull 59 MiB of petclinic on every small commit!

Is there a way to optimize it?

Layers!

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Diarmode=tools -jar /app/app.jar extract --layers --launcher
```

- Build image

Layers!

```
1 FROM bellsoft/liberica-runtime-container:jre-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --launcher
11
```

- Build image
- Introduce new "optimizer" stage

Layers!

```
4  RUN cd /app && ./gradlew build -x test
5
6  FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8  COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9  WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --launcher
11
12 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
13
14 ENTRYPOINT ["java", "-org.springframework.boot.loader.launch.jarlauncher"]
```

- Build image
- Introduce new "optimizer" stage

Layers!

```
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --launcher
11
12 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/app/dependencies/ /
```

- Build image
- Introduce new "optimizer" stage
- Extract the jar to layered structure

Layers!

```
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --launcher
11
12 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/app/dependencies/ ./
16 COPY --from=optimizer /app/app/spring-boot-loader/ ./
17 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
```

- Build image
- Introduce new "optimizer" stage
- Extract the jar to layered structure

Layers!

```
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --launcher
11
12 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/app/dependencies/ ./
16 COPY --from=optimizer /app/app/spring-boot-loader/ ./
17 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
18 COPY --from=optimizer /app/app/application/ ./
```

- Build image
- Introduce new "optimizer" stage
- Extract the jar to layered structure
- Copy layers

Layers!

```
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --launcher
11
12 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/app/dependencies/ ./
16 COPY --from=optimizer /app/app/spring-boot-loader/ ./
17 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
18 COPY --from=optimizer /app/app/application/ ./
```

- Build image
- Introduce new "optimizer" stage
- Extract the jar to layered structure
- Copy layers

Layers

Because Spring Boot jar is complex!

```
1  Usage:
2    java -Djarmode=tools -jar my-app.jar
3
4  Available commands:
5    extract      Extract the contents from the jar
6    list-layers  List layers from the jar that can be extracted
```

Layers

```
1  app
2  |— application
3  |   |— BOOT-INF
4  |   |   |— classes
5  |   |       |— application-mysql.properties
6  |   |       |— application-postgres.properties
7  |   |       |— application.properties
8  |   |       |— banner.txt
9  |   |       |— db
10 |   |       |— ...
11 |   |       |— org
```

Layers

```
1  app
2  |— application
3  |   |— BOOT-INF
4  |   |   |— classes
5  |   |   |   |— application-mysql.properties
6  |   |   |   |— application-postgres.properties
7  |   |   |   |— application.properties
8  |   |   |   |— banner.txt
9  |   |   |   |— db
10 |   |   |   |— ...
11 |   |   |   |— org
```

Layers

```
2  |— application
3  |   |— BOOT-INF
4  |   |   |— classes
5  |   |   |   |— application-mysql.properties
6  |   |   |   |— application-postgres.properties
7  |   |   |   |— application.properties
8  |   |   |   |— banner.txt
9  |   |   |   |— db
10 |   |   |   |— ...
11 |   |   |   |— org
12 |   |   |   |— springframework
```

Layers



Layers

```
12      └─ springframework
13          └─ aop
14              └─ aspectj
15                  └─ annotation
16                      └─ AnnotationAwareAspectJAutoProxyCreator__BeanDefinitions.
17      └─ com/github/asm0dey/ ...
18      └─ static
19      ....
20      └─ classpath.idx
21      └─ layers.idx
22  └─ META-INF
```

Layers

Layers

```
17 | | | | | com/github/asm0dey/ ...
18 | | | | | — static
19 | | | | | ....
20 | | | | | — classpath.idx
21 | | | | | — layers.idx
22 | | | — META-INF
23 | | | | — MANIFEST.MF
24 | | | | — native-image
25 | | | | | — ch.qos.logback
26 | | | | | | — logback-classic
27 | | | | | | — 1.5.6
```

Layers

```
22  └─ META-INF
23      └─ MANIFEST.MF
24      └─ native-image
25          └─ ch.qos.logback
26              └─ logback-classic
27                  └─ 1.5.6
28                      └─ reflect-config.json
29                      └─ resource-config.json
30      └─ ...
31      └─ sbom
32          └─ application.cdx.json
```

Layers

```
27      └─ 1.5.6
28          └─ reflect-config.json
29          └─ resource-config.json
30      └─ ...
31  └─ sbom
32      └─ application.cdx.json
33  └─ services
34      └─ java.nio.file.spi.FileSystemProvider
35 └─ dependencies
36     └─ BOOT-INF
37         └─ lib
```

Layers

```
30      |— ...
31      |— sbom
32      |   └─ application.cdx.json
33      |— services
34      |   └─ java.nio.file.spi.FileSystemProvider
35  ── dependencies
36      └─ BOOT-INF
37          └─ lib
38              └─ angus-activation-2.0.2.jar
39              └─ ...
40  ── snapshot-dependencies
```

Layers

```
33      └─ services
34          └─ java.nio.file.spi.FileSystemProvider
35 └─ dependencies
36     └─ BOOT-INF
37         └─ lib
38             └─ angus-activation-2.0.2.jar
39             └─ ...
40 └─ snapshot-dependencies
41 └─ spring-boot-loader
42     └─ org
43         └─ springframework
```

Layers

```
35 |— dependencies
36 |   |— BOOT-INF
37 |     |— lib
38 |       |— angus-activation-2.0.2.jar
39 |       |— ...
40 |— snapshot-dependencies
41 |— spring-boot-loader
42 |   |— org
43 |     |— springframework
44 |       |— boot
45 |         |— loader
```

Layers

```
36      └─ BOOT-INF
37          └─ lib
38              └─ angus-activation-2.0.2.jar
39              └─ ...
40 └─ snapshot-dependencies
41 └─ spring-boot-loader
42     └─ org
43         └─ springframework
44             └─ boot
45                 └─ loader
46                     └─ jar
```

Layers

```
145 — ZipContent$Loader.class
146 — ZipContent$Source.class
147 — ZipContent.class
148 — ZipDataDescriptorRecord.class
149 — ZipEndOfCentralDirectoryRecord$Located.class
150 — ZipEndOfCentralDirectoryRecord.class
151 — ZipLocalFileHeaderRecord.class
152 — ZipString$CompareType.class
153 — ZipString.class
154
155 212 directories, 525 files
```

Layered image structure

1	ID	TAG	SIZE	COMMAND
2	618743f6a2	layers:latest	2.96MiB	COPY dir:e0faa63b96544
3	9cca3273f0		0B	COPY dir:acd0d0ac1f7df
4	fe123ee16e		382.56kiB	COPY dir:01225d3c4ef6c
5	dede9bac3d		57.69MiB	COPY dir:755815d928fd9
6	65e3fb4cbf		0B	ENTRYPOINT ["java" "or
7	7130fa5864	bellsoft/liberica-runtime-container:jre-slim-musl	126.80MiB	18 CDS=no DESCRIPTION
8	<missing>		0B	ENV JAVA_HOME="/usr/li
9	<missing>		0B	ENV LANG=en_US.UTF-8 l
10	<missing>		0B	LABEL org.opencontainers

Layered image structure

1	ID	TAG	SIZE	COMMAND
2	618743f6a2	layers:latest	2.96MiB	COPY dir:e0faa63b96544
3	9cca3273f0		0B	COPY dir:acd0d0ac1f7df
4	fe123ee16e		382.56kiB	COPY dir:01225d3c4ef6c
5	dede9bac3d		57.69MiB	COPY dir:755815d928fd9
6	65e3fb4cbf		0B	ENTRYPOINT ["java" "or
7	7130fa5864	bellsoft/liberica-runtime-container:jre-slim-musl	126.80MiB	18 CDS=no DESCRIPTION
8	<missing>		0B	ENV JAVA_HOME="/usr/li
9	<missing>		0B	ENV LANG=en_US.UTF-8 l
10	<missing>		0B	LABEL org.opencontainers

- Dependencies: ~57.7MiB

Layered image structure

1	ID	TAG	SIZE	COMMAND
2	618743f6a2	layers:latest	2.96MiB	COPY dir:e0faa63b96544
3	9cca3273f0		0B	COPY dir:acd0d0ac1f7df
4	fe123ee16e		382.56kiB	COPY dir:01225d3c4ef6c
5	dede9bac3d		57.69MiB	COPY dir:755815d928fd9
6	65e3fb4cbf		0B	ENTRYPOINT ["java" "or
7	7130fa5864	bellsoft/liberica-runtime-container:jre-slim-musl	126.80MiB	18 CDS=no DESCRIPTION
8	<missing>		0B	ENV JAVA_HOME="/usr/li
9	<missing>		0B	ENV LANG=en_US.UTF-8 l
10	<missing>		0B	LABEL org.opencontainers

- Dependencies: ~57.7MiB
- Launcher: 382.56kiB

Layered image structure

1	ID	TAG	SIZE	COMMAND
2	618743f6a2	layers:latest	2.96MiB	COPY dir:e0faa63b96544
3	9cca3273f0		0B	COPY dir:acd0d0ac1f7df
4	fe123ee16e		382.56kiB	COPY dir:01225d3c4ef6c
5	dede9bac3d		57.69MiB	COPY dir:755815d928fd9
6	65e3fb4cbf		0B	ENTRYPOINT ["java" "or
7	7130fa5864	bellsoft/liberica-runtime-container:jre-slim-musl	126.80MiB	18 CDS=no DESCRIPTION
8	<missing>		0B	ENV JAVA_HOME="/usr/li
9	<missing>		0B	ENV LANG=en_US.UTF-8 l
10	<missing>		0B	LABEL org.opencontainers

- Dependencies: ~57.7MiB
- Launcher: 382.56kiB

Layered image structure

1	ID	TAG	SIZE	COMMAND
2	618743f6a2	layers:latest	2.96MiB	COPY dir:e0faa63b96544
3	9cca3273f0		0B	COPY dir:acd0d0ac1f7df
4	fe123ee16e		382.56kiB	COPY dir:01225d3c4ef6c
5	dede9bac3d		57.69MiB	COPY dir:755815d928fd9
6	65e3fb4cbf		0B	ENTRYPOINT ["java" "or
7	7130fa5864	bellsoft/liberica-runtime-container:jre-slim-musl	126.80MiB	18 CDS=no DESCRIPTION
8	<missing>		0B	ENV JAVA_HOME="/usr/li
9	<missing>		0B	ENV LANG=en_US.UTF-8 l
10	<missing>		0B	LABEL org.opencontainers

- Dependencies: ~57.7MiB
- Launcher: 382.56kiB
- Application: ~3MiB

Layered image structure

1	ID	TAG	SIZE	COMMAND
2	618743f6a2	layers:latest	2.96MiB	COPY dir:e0faa63b9654
3	9cca3273f0		0B	COPY dir:acd0d0ac1f7c
4	fe123ee16e		382.56kiB	COPY dir:01225d3c4ef0
5	dede9bac3d		57.69MiB	COPY dir:755815d928fc
6	65e3fb4cbf		0B	ENTRYPOINT ["java" "c
7	7130fa5864	bellsoft/liberica-runtime-container:jre-slim-musl	126.80MiB	18 CDS=no DESCRIPTION
8	<missing>		0B	ENV JAVA_HOME="/usr/1
9	<missing>		0B	ENV LANG=en_US.UTF-8
10	<missing>		0B	LABEL org.opencontainers

- Dependencies: ~57.7MiB
- Launcher: 382.56kiB
- Application: ~3MiB

Together: ~61MiB

61.0MiB > 58.8Mib!



What are we optimizing?

Pull size!

Pull size here is usually only around 3MiB!

We just reinvented how the BellSoft's buildpack works!

And it is amazing

Diversion: buildpacks

<https://paketo.io/>

Trivial usage:

```
1  /usr/sbin/pack build petclinic \  
2    --builder bellsoft/buildpacks.builder \  
3    --path . \  
4    -e BP_JVM_VERSION=21
```

Diversion: buildpacks

<https://paketo.io/>

Trivial usage:

```
1 /usr/sbin/pack build petclinic \  
2   --builder bellsoft/buildpacks.builder \  
3   --path . \  
4   -e BP_JVM_VERSION=21
```

Diversion: buildpacks

<https://paketo.io/>

Trivial usage:

```
1 /usr/sbin/pack build petclinic \  
2   --builder bellsoft/buildpacks.builder \  
3   --path . \  
4   -e BP_JVM_VERSION=21
```

Diversion: buildpacks

<https://paketo.io/>

Trivial usage:

```
1 /usr/sbin/pack build petclinic \  
2   --builder bellsoft/buildpacks.builder \  
3   --path . \  
4   -e BP_JVM_VERSION=21
```

Result

1	ID	TAG	SIZE	COMMAND
2	2774e3f214	petclinic:latest	0B	Buildpacks Process Types
3	<missing>		1.44kiB	Buildpacks Launcher Config
4	<missing>		2.44MiB	Buildpacks Application Launcher
5	<missing>		59.17MiB	Application Layer
6	<missing>		729.21kiB	Software Bill-of-Materials
7	<missing>		97.87MiB	Layer: 'jre', Created by buildpack: bellsoft/buildpack
8	<missing>		200.00B	Layer: 'java-security-properties', Created by buildpack
9	<missing>		4.27MiB	Layer: 'helper', Created by buildpack: bellsoft/buildpack
10	<missing>		2.97kiB	
11	<missing>		7.48MiB	

Result

1	ID	TAG	SIZE	COMMAND
2	2774e3f214	petclinic:latest	0B	Buildpacks Process Types
3	<missing>		1.44kiB	Buildpacks Launcher Config
4	<missing>		2.44MiB	Buildpacks Application Launcher
5	<missing>		59.17MiB	Application Layer
6	<missing>		729.21kiB	Software Bill-of-Materials
7	<missing>		97.87MiB	Layer: 'jre', Created by buildpack: bellsoft/buildpack
8	<missing>		200.00B	Layer: 'java-security-properties', Created by buildpack
9	<missing>		4.27MiB	Layer: 'helper', Created by buildpack: bellsoft/buildpack
10	<missing>		2.97kiB	
11	<missing>		7.48MiB	

Result

1	ID	TAG	SIZE	COMMAND
2	2774e3f214	petclinic:latest	0B	Buildpacks Process Types
3	<missing>		1.44kiB	Buildpacks Launcher Config
4	<missing>		2.44MiB	Buildpacks Application Launcher
5	<missing>		59.17MiB	Application Layer
6	<missing>		729.21kiB	Software Bill-of-Materials
7	<missing>		97.87MiB	Layer: 'jre', Created by buildpack: bellsoft/buildpack
8	<missing>		200.00B	Layer: 'java-security-properties', Created by buildpack
9	<missing>		4.27MiB	Layer: 'helper', Created by buildpack: bellsoft/buildpack
10	<missing>		2.97kiB	
11	<missing>		7.48MiB	

Result

1	ID	TAG	SIZE	COMMAND
2	2774e3f214	petclinic:latest	0B	Buildpacks Process Types
3	<missing>		1.44kiB	Buildpacks Launcher Config
4	<missing>		2.44MiB	Buildpacks Application Launcher
5	<missing>		59.17MiB	Application Layer
6	<missing>		729.21kiB	Software Bill-of-Materials
7	<missing>		97.87MiB	Layer: 'jre', Created by buildpack: bellsoft/buildpack
8	<missing>		200.00B	Layer: 'java-security-properties', Created by buildpack
9	<missing>		4.27MiB	Layer: 'helper', Created by buildpack: bellsoft/buildpack
10	<missing>		2.97kiB	
11	<missing>		7.48MiB	

Buildpacks

Why do we need them?

- Buildpacks transform your application source code into container images
 - The Paketo open source project provides production-ready buildpacks for the most popular languages and frameworks
 - Use Paketo Buildpacks to easily build your apps and keep them updated
- Reminds of s2i images
 - Build better than default
 - Spring-aware

Is this all?

We've optimized pull/push size, right?

Optimization is multidimensional

When startup time is more important...

There are several solutions for the Spring application startup time

1. Class Data Sharing (CDS)
2. Coordinated Restore at Checkpoint
3. Native Image

Class Data Sharing (CDS)

- When: Java 5 (!)
- Why: reduce the startup and memory footprint of multiple JVM instances running on the same host
- How: stores data in an archive

How does it help us?

Class Data Sharing (CDS)

- When: Java 5 (!)
- Why: reduce the startup and memory footprint of multiple JVM instances running on the same host
- How: stores data in an archive

How does it help us?

It does not! 🙄

Class Data Sharing (CDS)

- When: Java 5 (!)
- Why: reduce the startup and memory footprint of multiple JVM instances running on the same host
- How: stores data in an archive

How does it help us?

It does not! 🧐 But

Application Class Data Sharing

- When: Java 10
- Why: add application classes to the archive

And then:

- When: Java 13, JEP 350
- Why: allow addition of classes into the archive upon app exit!

And this helps! How?

How to use AppCDS with Spring?

- `-XX:ArchiveClassesAtExit=application.jsa` to create an archive
- `-Dspring.context.exit=onRefresh` to start and immediately exit the application

NB:

1. Use the same JDK
2. Use the same arguments

And even better!

Spring AOT

Add `-Dspring.aot.enabled=true`

Even more classes!!!

Practice

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --launcher
11
12 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/app/dependencies/ ./
16 COPY --from=optimizer /app/app/spring-boot-loader/ ./
17 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
18 COPY --from=optimizer /app/app/application/ ./
```

Practice

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --launcher
11
12 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/app/dependencies/ ./
16 COPY --from=optimizer /app/app/spring-boot-loader/ ./
17 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
18 COPY --from=optimizer /app/app/application/ ./
```

Practice

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --launcher
11
12 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/app/dependencies/ ./
16 COPY --from=optimizer /app/app/spring-boot-loader/ ./
17 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
18 COPY --from=optimizer /app/app/application/ ./
```

Practice

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --launcher
11
12 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/app/dependencies/ ./
16 COPY --from=optimizer /app/app/spring-boot-loader/ ./
17 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
18 COPY --from=optimizer /app/app/application/ ./
```

Practice

```
1 #omitted
2 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
3
4 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
5 COPY --from=optimizer /app/app/dependencies/ ./
6 COPY --from=optimizer /app/app/spring-boot-loader/ ./
7 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
8 COPY --from=optimizer /app/app/application/ ./
9 RUN java -Dspring.aot.enabled=true \
10     -XX:ArchiveClassesAtExit=./application.jsa \
11     -Dspring.context.exit=onRefresh \
12     org.springframework.boot.loader.launch.JarLauncher
```

Practice

```
1 #omitted
2 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
3
4 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
5 COPY --from=optimizer /app/app/dependencies/ ./
6 COPY --from=optimizer /app/app/spring-boot-loader/ ./
7 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
8 COPY --from=optimizer /app/app/application/ ./
9 RUN java -Dspring.aot.enabled=true \
10     -XX:ArchiveClassesAtExit=./application.jsa \
11     -Dspring.context.exit=onRefresh \
12     org.springframework.boot.loader.launch.JarLauncher
```

Practice

```
1 #omitted
2 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
3
4 ENTRYPOINT ["java", \
5             "-Dspring.aot.enabled=true", \
6             "-XX:SharedArchiveFile=application.jsa", \
7             "org.springframework.boot.loader.launch.JarLauncher"]
8 COPY --from=optimizer /app/app/dependencies / ./
9 COPY --from=optimizer /app/app/spring-boot-loader/ ./
10 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
11 COPY --from=optimizer /app/app/application/ ./
12 RUN java -Dspring.aot.enabled=true \
13     -XX:ArchiveClassesAtExit=./application.jsa \
14     -Dspring.context.exit=onRefresh \
15     org.springframework.boot.loader.launch.JarLauncher
```

Practice

```
1 #omitted
2 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
3
4 ENTRYPOINT ["java", \
5             "-Dspring.aot.enabled=true", \
6             "-XX:SharedArchiveFile=application.jsa", \
7             "org.springframework.boot.loader.launch.JarLauncher"]
8 COPY --from=optimizer /app/app/dependencies / ./
9 COPY --from=optimizer /app/app/spring-boot-loader/ ./
10 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
11 COPY --from=optimizer /app/app/application/ ./
12 RUN java -Dspring.aot.enabled=true \
13       -XX:ArchiveClassesAtExit=./application.jsa \
14       -Dspring.context.exit=onRefresh \
15       org.springframework.boot.loader.launch.JarLauncher
```

What does it cost ?

```
1  -r--r--r--      0:0      81 MB  |— application.jsa
```

Which is not small at all!

What does it cost ?

```
1  -r--r--r--      0:0      81 MB  |— application.jsa
```

Which is not small at all!

But you're trading pull speed for startup speed

How much faster?

Up to 50-60%

Pushing further with CRaC

CRaC: Coordinated Restore at Checkpoint

The CRaC (Coordinated Restore at Checkpoint) Project researches coordination of Java programs with mechanisms to checkpoint (make an image of, snapshot) a Java instance while it is executing. Restoring from the image could be a solution to some of the problems with the start-up and warm-up times. The primary aim of the Project is to develop a new standard mechanism-agnostic API to notify Java programs about the checkpoint and restore events. Other research activities will include, but will not be limited to, integration with existing checkpoint/restore mechanisms and development of new ones, changes to JVM and JDK to make images smaller and ensure they are correct.

<https://openjdk.org/projects/crac/>

In a perfect world it should be:

```
1  FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3  COPY . /app
4  RUN cd /app && ./gradlew build
5
6  FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
7
8  COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9  WORKDIR /app
10 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
11
12 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
13
14 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
15 COPY --from=optimizer /app/app.jar /app/app.jar
16 COPY --from=optimizer /checkpoint /checkpoint
```

In a perfect world it should be:

```
1  FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3  COPY . /app
4  RUN cd /app && ./gradlew build
5
6  FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
7
8  COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9  WORKDIR /app
10 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
11
12 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
13
14 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
15 COPY --from=optimizer /app/app.jar /app/app.jar
16 COPY --from=optimizer /checkpoint /checkpoint
```

In a perfect world it should be:

```
1  FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3  COPY . /app
4  RUN cd /app && ./gradlew build
5
6  FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
7
8  COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9  WORKDIR /app
10 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
11
12 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
13
14 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
15 COPY --from=optimizer /app/app.jar /app/app.jar
16 COPY --from=optimizer /checkpoint /checkpoint
```

But in reality

```
1  #12 6.051      Suppressed: java.lang.RuntimeException: Native checkpoint failed.
2  #12 6.051      at java.base/jdk.crac.Core.translateJVMExceptions(Core.java:114) ~[r
3  #12 6.051      at java.base/jdk.crac.Core.checkpointRestore1(Core.java:192) ~[na:na
4  #12 6.051      at java.base/jdk.crac.Core.checkpointRestore(Core.java:299) ~[na:na
5  #12 6.051      at java.base/jdk.crac.Core.checkpointRestore(Core.java:278) ~[na:na
6  #12 6.051      at java.base/javax.crac.Core.checkpointRestore(Core.java:73) ~[na:na
7  #12 6.051      at java.base/jdk.internal.reflect.DirectMethodHandleAccessor.invoke
8  #12 6.051      at java.base/java.lang.reflect.Method.invoke(Method.java:580) ~[na:r
9  #12 6.051      at org.crac.Core$Compat.checkpointRestore(Core.java:141) ~[crac-1.4.
10 #12 6.051      ... 17 common frames omitted
```

CRaC is hard!

Let's try to fix it with arcane magic

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
11
12 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
13
14 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
15 COPY --from=optimizer /app/app.jar /app/app.jar
16 COPY --from=optimizer /checkpoint /checkpoint
```

CRaC is hard!

Let's try to fix it with arcane magic

```
1 # syntax=docker/dockerfile:1-labs
2 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
3
4 COPY . /app
5 RUN cd /app && ./gradlew build -xtest
6
7 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
8
9 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
10 WORKDIR /app
11 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
12
13 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
14
15 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
16 COPY --from=optimizer /app/app.jar /app/app.jar
17 COPY --from=optimizer /checkpoint /checkpoint
```

CRaC is hard!

Let's try to fix it with arcane magic

```
1 # syntax=docker/dockerfile:1-labs
2 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
3
4 COPY . /app
5 RUN cd /app && ./gradlew build -xtest
6
7 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
8
9 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
10 WORKDIR /app
11 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
12
13 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
14
15 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
16 COPY --from=optimizer /app/app.jar /app/app.jar
17 COPY --from=optimizer /checkpoint /checkpoint
```

CRaC is hard!

Let's try to fix it with arcane magic

```
1 # syntax=docker/dockerfile:1-labs
2 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
3
4 COPY . /app
5 RUN cd /app && ./gradlew build -xtest
6
7 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
8
9 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
10 WORKDIR /app
11 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
12
13 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
14
15 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
16 COPY --from=optimizer /app/app.jar /app/app.jar
17 COPY --from=optimizer /checkpoint /checkpoint
```

CRaC is hard!

Let's try to fix it with arcane magic

```
1 # syntax=docker/dockerfile:1-labs
2 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
3
4 COPY . /app
5 RUN cd /app && ./gradlew build -xtest
6
7 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
8
9 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
10 WORKDIR /app
11 RUN --security=insecure java -Dspring.context.checkpoint=onRefresh \
12     -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
13
14 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
15
16 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
```

CRaC is hard!

Let's try to fix it with arcane magic

```
1 # syntax=docker/dockerfile:1-labs
2 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
3
4 COPY . /app
5 RUN cd /app && ./gradlew build -xtest
6
7 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
8
9 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
10 WORKDIR /app
11 RUN --security=insecure java -Dspring.context.checkpoint=onRefresh \
12     -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar || true
13
14 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
15
16 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
```

And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx create --buildkitd-flags \  
2   '--allow-insecure-entitlement security.insecure' \  
3   --name insecure-builder
```

And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx create --buildkitd-flags \  
2   '--allow-insecure-entitlement security.insecure' \  
3   --name insecure-builder
```

And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx use insecure-builder
```

And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx build \  
2   --allow security.insecure \  
3   -f Dockerfile.crac \  
4   -t pet-crac --output type=docker .
```

And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx build \  
2   --allow security.insecure \  
3   -f Dockerfile.crac \  
4   -t pet-crac --output type=docker .
```

And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx build \  
2   --allow security.insecure \  
3   -f Dockerfile.crac \  
4   -t pet-crac --output type=docker .
```

And this is not all!

Did you hear about `buildx` ?

```
1 docker run --rm -it --privileged pet-crac
```

And this is not all!

Did you hear about `buildx` ?

- 1 Restarting Spring-managed lifecycle beans after JVM restore
- 2 HikariPool-1 - Thread starvation or clock leap detected (housekeeper delta=1d19h37m42s102ms798µs806ns)
- 3 Tomcat started on port 8080 (http) with context path '/'
- 4 Restored PetClinicApplication in 0.186 seconds (process running for 0.19)

And this is not all!

Did you hear about `buildx` ?

```
1 Restarting Spring-managed lifecycle beans after JVM restore
2 HikariPool-1 - Thread starvation or clock leap detected (housekeeper delta=1d19h37m42s102ms798µs806ns)
3 Tomcat started on port 8080 (http) with context path '/'
4 Restored PetClinicApplication in 0.186 seconds (process running for 0.19)
```

Is it a good solution?

It depends

Is it a good solution?

It depends

- If "It Works" is enough for you

Is it a good solution?

It depends

- If "It Works" is enough for you -> YES
- If you need more predictable and maintainable thing

Is it a good solution?

It depends

- If "It Works" is enough for you -> YES
- If you need more predictable and maintainable thing

Is it a good solution?

It depends

- If "It Works" is enough for you -> YES
- If you need more predictable and maintainable thing -> NO

How to make it better?

How to make it better?

1. Build JAR (in docker or not)

How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`

How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`
3. Run the container with capabilities:

How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`
3. Run the container with capabilities:
 1. `CAP_SYS_PTRACE`

How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`
3. Run the container with capabilities:
 1. `CAP_SYS_PTRACE`
 2. `CAP_CHECKPOINT_RESTORE`

How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`
3. Run the container with capabilities:
 1. `CAP_SYS_PTRACE`
 2. `CAP_CHECKPOINT_RESTORE`
4. Container will run and stop

How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`
3. Run the container with capabilities:
 1. `CAP_SYS_PTRACE`
 2. `CAP_CHECKPOINT_RESTORE`
4. Container will run and stop
5. Commit the container like

```
docker commit container-id new-tag
```

Pros and Cons

Pros:

1. Does not require arcane magic
2. Works more predictably
3. Does not depend on unstable features
4. Does not require privileged containers in

Cons:

1. Organization-specific
2. Requires more steps

And now we have all
flavours of ultimate
docker images!

Quick summary?

1. Use layers for faster deployment
2. Use CDS for faster startup without many compromises
3. Use CRaC for a *lightning-fast* startup (with compromises)

Thank you!

Find me @

-  @asm0dey.site
-  @asm0dey@fosstodon.org
-  asm0di0
-  me@asm0dey.site
-     asm0dey



END