Himalayan Peaks of Testing Data Pipelines

Ksenia Tomak, Dodo Engineering Pasha Finkelshteyn, JetBrains

Who we are

What is Big Data

Who are DEs?

4

What is a pipeline?

Who needs pipelines

QA of pipeline

QA ?= QC

QA of pipeline


QA ≠ QC

QA is about processes and not only about software quality.

Pyramid of testing. Unit



Typical pipeline



Unit testing of pipeline

What may we test here?

A pipeline should transform data correctly!

Correctness is a business term

Let's paste fakes!

Fake/mock input data

Reference data at the end of the pipeline


Separate



Tools

<u>holdenk/spark-testing-base</u> ← Tools to run tests <u>MrPowers/spark-daria</u> ← tools to easily create test data


Component testing





TestContainers

Separate



TestContainers


Supported languages:


- Java (and compatibles: Scala, Kotlin, etc.)
- Python
- Go
- Node.js
- Rust
- .NET


Test Containers


```
import sqlalchemy
from testcontainers.mysql import MySqlContainer

with MySqlContainer('mysql:5.7.17') as mysql:
    engine = sqlalchemy.create_engine(mysql.get_connection_url())
    version, = engine.execute("select version()").fetchone()
    print(version) # 5.7.17
```









Real systems

Why are component tests not enough?

- vendor lock tools (DB, processing, etc.)
- external error handling

Real data

get data samples from prod, anonymize it

Real data expectations

Test:

- ✓ no data
- ✓ valid data
- ? invalid data
- illegal data format
- Property-based testing

25

Real data expectations. Tools:

- great expectations,
- <u>Deequ</u>

Monitoring

Why?

@asm0di0 @if_no_then_yes

27

Monitoring

What?


- data volumes,
- counters,
- time,
- dead letter queue monitoring

28

Monitoring

How?

- use Listeners
- use data aggregations



End-to-End tests

Compare with reports, old DWH

Multiple dimensions:

- data
- data latency
- performance, scalability

Performance Tests

SLA

Best performance test - initial data load

How to apply?

Real data, real system

deploy full data backup on stage env, anonymize it

35

Real prod

run a parallel job with different sink

Using production data for testing in a post GDPR world