

# Crafting the Ultimate Docker Image for Spring Applications



**bellsoft**

whoami



Pasha Finkelshteyn  @asm0dey.site  @asm0di0

# whoami

- Pasha Finkelshteyn



# whoami

- Pasha Finkelshteyn
- Dev 🥑 at BellSoft



# whoami

- Pasha Finkelshteyn
- Dev 🥑 at BellSoft
- ≈10 years in JVM. Mostly ☕ and 



# whoami

- Pasha Finkelshteyn
- Dev 🥑 at BellSoft
- ≈10 years in JVM. Mostly ☕ and 
- And 



# whoami

- Pasha Finkelshteyn
- Dev 🥑 at BellSoft
- ≈10 years in JVM. Mostly ☕ and 
- And 
-  asm0di0



# whoami

- Pasha Finkelshteyn
- Dev 🥑 at BellSoft
- ≈10 years in JVM. Mostly ☕ and 
- And 
-  asm0di0
-  @asm0dey@fosstodon.org



# BellSoft

- Vendor of Liberica JDK
- Contributor to the OpenJDK
- Author of ARM32 support in JDK
- Own base images
- Own Linux: Alpaquita

Liberica is the JDK officially recommended  
by 



# BellSoft

- Vendor of Liberica JDK
- Contributor to the OpenJDK
- Author of ARM32 support in JDK
- Own base images
- Own Linux: Alpaquita

Liberica is the JDK officially recommended  
by 

We know our stuff!



# So, what is ultimate?

- Smallest
- Fatsest startup
- Something inbetween

So, let's look at all of  
them!

# How do we create an image?

Let's start from trivial.

```
1 FROM bellsoft/liberica-runtime-container:jdk-25-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

# How do we create an image?

Let's start from trivial.

```
1 FROM bellsoft/liberica-runtime-container:jdk-25-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

# How do we create an image?

Let's start from trivial.

```
1 FROM bellsoft/liberica-runtime-container:jdk-25-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

# How do we create an image?

Let's start from trivial.

```
1 FROM bellsoft/liberica-runtime-container:jdk-25-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

# How do we create an image?

Let's start from trivial.

```
1 FROM bellsoft/liberica-runtime-container:jdk-25-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

# Dockerfile directives

1. Each directive creates a layer of the image.
2. Layers are *immutable*
3. Some layers are zero-sized

# Dockerfile directives

1. Each directive creates a layer of the image.
2. Layers are *immutable*
3. Some layers are zero-sized

```
1 FROM bash
2
3 COPY . /app
4 RUN rm -rf /app
```

# Dockerfile directives

1. Each directive creates a layer of the image.
2. Layers are *immutable*
3. Some layers are zero-sized

```
1 FROM bash
2
3 COPY . /app
4 RUN rm -rf /app
```

# Dockerfile directives

1. Each directive creates a layer of the image.
2. Layers are *immutable*
3. Some layers are zero-sized (for example `RUN rm -rf /app`)

```
1 FROM bash
2
3 COPY . /app
4 RUN rm -rf /app
```

# Dockerfile directives

1. Each directive creates a layer of the image.
2. Layers are *immutable*
3. Some layers are zero-sized (for example `RUN rm -rf /app`)

```
1 FROM bash
2
3 COPY . /app
4 RUN rm -rf /app
```

4. We would like image to be light, but it's not :(

# Our Dockerfile

```
1 FROM bellsoft/liberica-runtime-container:jdk-25-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

# Our Dockerfile

```
1 FROM bellsoft/liberica-runtime-container:jdk-25-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

# Our Dockerfile

```
1 FROM bellsoft/liberica-runtime-container:jdk-25-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

# Our Dockerfile

```
1 FROM bellsoft/liberica-runtime-container:jdk-25-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

# Result

| 1 | Cmp | Size   | Command                           |
|---|-----|--------|-----------------------------------|
| 2 |     | 10 MB  | FROM blobs                        |
| 3 |     | 109 MB | cd /app && ./gradlew build -xtest |
| 4 |     | 85 MB  | (missing)                         |
| 5 |     | 591 MB | (missing)                         |

# Result

| 1 | Cmp | Size   | Command                           |
|---|-----|--------|-----------------------------------|
| 2 |     | 10 MB  | FROM blobs                        |
| 3 |     | 109 MB | cd /app && ./gradlew build -xtest |
| 4 |     | 85 MB  | (missing)                         |
| 5 |     | 591 MB | (missing)                         |

109 MB of Java

# Result

| 1 | Cmp | Size   | Command                           |
|---|-----|--------|-----------------------------------|
| 2 |     | 10 MB  | FROM blobs                        |
| 3 |     | 109 MB | cd /app && ./gradlew build -xtest |
| 4 |     | 85 MB  | (missing)                         |
| 5 |     | 591 MB | (missing)                         |

109 MB of Java

85 MB of the app

# Result

| 1 | Cmp | Size   | Command                           |
|---|-----|--------|-----------------------------------|
| 2 |     | 10 MB  | FROM blobs                        |
| 3 |     | 109 MB | cd /app && ./gradlew build -xtest |
| 4 |     | 85 MB  | (missing)                         |
| 5 |     | 591 MB | (missing)                         |

109 MB of Java

85 MB of the app

591 MB of Java build caches

# 600+ MB are changed on every build!

Why do we care? We care because:

1. `push` takes longer time to start  
(update is longer)
2. `pull` takes longer  
(update takes longer & scaling takes longer)

Also, more disk pspace is inefficiently used



# Optimizing. Round 1.

Let's build it outside of container

```
1 FROM bellsoft/liberica-runtime-container:jdk-25-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```

# Optimizing. Round 1.

Let's build it outside of container

```
1 FROM bellsoft/liberica-runtime-container:jdk-25-musl
2
3 COPY build/libs/spring-petclinic-3.3.0.jar /app/app.jar
4 CMD java -jar /app/app.jar
```

# Optimizing. Round 1.

Let's build it outside of container

```
1 FROM bellsoft/liberica-runtime-container:jdk-25-musl
2
3 COPY build/libs/spring-petclinic-3.3.0.jar /app/app.jar
4 CMD java -jar /app/app.jar
```

Just copying the prebuilt `jar` file

# Results

| 1 | Cmp | Size   | Command                           |
|---|-----|--------|-----------------------------------|
| 2 |     | 10 MB  | FROM blobs                        |
| 3 |     | 109 MB | cd /app && ./gradlew build -xtest |
| 4 |     | 85 MB  | (missing)                         |
| 5 |     | 591 MB | (missing)                         |

No Gradle caches and build dir!

# Results

| 1 | Cmp | Size   | Command    |
|---|-----|--------|------------|
| 2 |     | 10 MB  | FROM blobs |
| 3 |     | 109 MB | (missing)  |
| 4 |     | 69 MB  | (missing)  |

No Gradle caches and build dir!


# Saved 600+ MB

But the build is not clean now :(

# Saved 600+ MB

But the build is not clean now :(

We have to build everything outside, what if environment affects the build?

A highly detailed, ornate theater stage set. The stage is framed by a grand, classical archway supported by columns. Red velvet curtains hang from the top of the arch. In the center of the stage is a large, dark, ornate chair or throne. To the left and right of the center are smaller, similar chairs. The stage is lit by a large, multi-tiered chandelier hanging from the ceiling. The floor is made of dark wood, and a large, patterned rug is laid out in the foreground. The walls are decorated with intricate carvings and sconces. The overall atmosphere is one of grandeur and elegance.

Enter build stages

# Multi-stage builds

Holy grail of pure builds

- Allow clean builds
- Allow optimal packaging
- Allow different base images

# Staged example

```
1 FROM bellsoft/liberica-runtime-container:jdk-25-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-25-musl as runner
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```

# Staged example

```
1  FROM bellsoft/liberica-runtime-container:jdk-25-musl as builder
2
3  COPY . /app
4  RUN cd /app && ./gradlew build -xtest
5
6  FROM bellsoft/liberica-runtime-container:jre-25-musl as runner
7
8  COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```

# Staged example

```
1 FROM bellsoft/liberica-runtime-container:jdk-25-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-25-musl as runner
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```

# Staged example

```
1 FROM bellsoft/liberica-runtime-container:jdk-25-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-25-musl as runner
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```

# Staged example

```
1 FROM bellsoft/liberica-runtime-container:jdk-25-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-25-musl as runner
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```

# Staged example

```
1 FROM bellsoft/liberica-runtime-container:jdk-25-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-25-musl as runner
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```

# Result

- jar - same size
- JRE - 48.28

# That's all folks!

# That's all folks!

Or is it?

# What's these 60 MiB?

We have to pull 60 MiB of petclinic on every small commit!

Is there a way to optimize it?

# Layers!

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Diarmode=tools -jar /app/app.jar extract --layers --destination extracted
```

- Build image

# Layers!

```
1 FROM bellsoft/liberica-runtime-container:jre-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --destination extracted
11
```

- Build image
- Introduce new "optimizer" stage

# Layers!

```
4  RUN cd /app && ./gradlew build -x test
5
6  FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8  COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9  WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --destination extracted
11
12 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
13
14 ENTRYPOINT ["java", "-org.springframework.boot.loader.launch.jarlauncher"]
```

- Build image
- Introduce new "optimizer" stage

# Layers!

```
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --destination extracted
11
12 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/extracted/dependencies/ /
```

- Build image
- Introduce new "optimizer" stage
- Extract the jar to layered structure

# Layers!

```
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --destination extracted
11
12 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/extracted/dependencies/ ./
16 COPY --from=optimizer /app/extracted/spring-boot-loader/ ./
17 COPY --from=optimizer /app/extracted/snapshot-dependencies/ ./
```

- Build image
- Introduce new "optimizer" stage
- Extract the jar to layered structure

# Layers!

```
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --destination extracted
11
12 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/extracted/dependencies/ ./
16 COPY --from=optimizer /app/extracted/spring-boot-loader/ ./
17 COPY --from=optimizer /app/extracted/snapshot-dependencies/ ./
18 COPY --from=optimizer /app/extracted/application/ ./
```

- Build image
- Introduce new "optimizer" stage
- Extract the jar to layered structure
- Copy layers

# Layers!

```
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --destination extracted
11
12 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/extracted/dependencies/ ./
16 COPY --from=optimizer /app/extracted/spring-boot-loader/ ./
17 COPY --from=optimizer /app/extracted/snapshot-dependencies/ ./
18 COPY --from=optimizer /app/extracted/application/ ./
```

- Build image
- Introduce new "optimizer" stage
- Extract the jar to layered structure
- Copy layers

# Layers

Because Spring Boot jar is complex!

```
1  Usage:
2    java -Djarmode=tools -jar my-app.jar
3
4  Available commands:
5    extract      Extract the contents from the jar
6    list-layers  List layers from the jar that can be extracted
```

# Layers

```
1  extracted
2  |— application
3    |— spring-petclinic-4.0.0-SNAPSHOT.jar
4  |— dependencies
5    |— lib
6        |— angus-activation-2.0.2.jar
7        |— antlr4-runtime-4.13.2.jar
8        |— aspectjweaver-1.9.24.jar
9        |— attoparser-2.0.7.RELEASE.jar
10       |— bootstrap-5.3.8.jar
11       |— byte-buddy-1.17.7.jar
12       |— cache-api-1.1.1.jar
13       |— caffeine-3.2.2.jar
14       |— checker-qual-3.49.3.jar
15       |— classmate-1.7.0.jar
16       |— commons-logging-1.3.5.jar
```

# Layers

```
91  — spring-orm-7.0.0-M9.jar
92  — spring-tx-7.0.0-M9.jar
93  — spring-web-7.0.0-M9.jar
94  — spring-webmvc-7.0.0-M9.jar
95  — thymeleaf-3.1.3.RELEASE.jar
96  — thymeleaf-spring6-3.1.3.RELEASE.jar
97  — tomcat-embed-core-11.0.11.jar
98  — tomcat-embed-el-11.0.11.jar
99  — tomcat-embed-websocket-11.0.11.jar
100 — txw2-4.0.5.jar
101 — unescape-1.1.6.RELEASE.jar
102 — webjars-locator-lite-1.1.1.jar
103 — snapshot-dependencies
104 — spring-boot-loader
105
106 6 directories, 98 files
```

# Layers

```
91      — spring-orm-7.0.0-M9.jar
92      — spring-tx-7.0.0-M9.jar
93      — spring-web-7.0.0-M9.jar
94      — spring-webmvc-7.0.0-M9.jar
95      — thymeleaf-3.1.3.RELEASE.jar
96      — thymeleaf-spring6-3.1.3.RELEASE.jar
97      — tomcat-embed-core-11.0.11.jar
98      — tomcat-embed-el-11.0.11.jar
99      — tomcat-embed-websocket-11.0.11.jar
100     — txw2-4.0.5.jar
101     — unescape-1.1.6.RELEASE.jar
102     — webjars-locator-lite-1.1.1.jar
103 — snapshot-dependencies
104 — spring-boot-loader
105
106 6 directories, 98 files
```

# Layers

```
3  spring-petclinic-4.0.0-SNAPSHOT.jar
4  └─ dependencies
5      └─ lib
6          └─ angus-activation-2.0.2.jar
7          └─ antlr4-runtime-4.13.2.jar
8          └─ aspectjweaver-1.9.24.jar
9          └─ attoparser-2.0.7.RELEASE.jar
10         └─ bootstrap-5.3.8.jar
11         └─ byte-buddy-1.17.7.jar
12         └─ cache-api-1.1.1.jar
13         └─ caffeine-3.2.2.jar
14         └─ checker-qual-3.49.3.jar
15         └─ classmate-1.7.0.jar
16         └─ commons-logging-1.3.5.jar
17         └─ context-propagation-1.2.0-M1.jar
18         └─ error_prone_annotations-2.40.0.jar
19         └─ font-awesome-4.7.0.jar
```

# Layers

```
1  extracted
2  |— application
3  |   |— spring-petclinic-4.0.0-SNAPSHOT.jar
4  |— dependencies
5  |   |— lib
6  |       |— angus-activation-2.0.2.jar
7  |       |— antlr4-runtime-4.13.2.jar
8  |       |— aspectjweaver-1.9.24.jar
9  |       |— attoparser-2.0.7.RELEASE.jar
10 |       |— bootstrap-5.3.8.jar
11 |       |— byte-buddy-1.17.7.jar
12 |       |— cache-api-1.1.1.jar
13 |       |— caffeine-3.2.2.jar
14 |       |— checker-qual-3.49.3.jar
15 |       |— classmate-1.7.0.jar
16 |       |— commons-logging-1.3.5.jar
```

# Layered image structure

```
1  > du -h --max-depth=1 extracted
2  66M    extracted/dependencies
3  0      extracted/spring-boot-loader
4  0      extracted/snapshot-dependencies
5  892K   extracted/application
6  66M    extracted
```

# Layered image structure

```
1  > du -h --max-depth=1 extracted
2  66M    extracted/dependencies
3  0      extracted/spring-boot-loader
4  0      extracted/snapshot-dependencies
5  892K   extracted/application
6  66M    extracted
```

- Dependencies: ~66MiB

# Layered image structure

```
1  > du -h --max-depth=1 extracted
2  66M    extracted/dependencies
3  0      extracted/spring-boot-loader
4  0      extracted/snapshot-dependencies
5  892K   extracted/application
6  66M    extracted
```

- Dependencies: ~66MiB
- Application: ~892K

66.0MiB > 60Mib!



# What are we optimizing?

Pull size!

Pull size here is usually only around 1MiB!

# We just reinvented how the BellSoft's buildpack works!

And it is amazing

# Diversion: buildpacks

<https://paketo.io/>

Trivial usage:

```
1  /usr/sbin/pack build petclinic \  
2    --builder bellsoft/buildpacks.builder \  
3    --path . \  
4    -e BP_JVM_VERSION=21
```

# Diversion: buildpacks

<https://paketo.io/>

Trivial usage:

```
1 /usr/sbin/pack build petclinic \  
2   --builder bellsoft/buildpacks.builder \  
3   --path . \  
4   -e BP_JVM_VERSION=21
```

# Diversion: buildpacks

<https://paketo.io/>

Trivial usage:

```
1 /usr/sbin/pack build petclinic \  
2   --builder bellsoft/buildpacks.builder \  
3   --path . \  
4   -e BP_JVM_VERSION=21
```

# Diversion: buildpacks

<https://paketo.io/>

Trivial usage:

```
1 /usr/sbin/pack build petclinic \  
2   --builder bellsoft/buildpacks.builder \  
3   --path . \  
4   -e BP_JVM_VERSION=21
```

# Result

| 1  | ID         | TAG              | SIZE      | COMMAND                                                   |
|----|------------|------------------|-----------|-----------------------------------------------------------|
| 2  | 2774e3f214 | petclinic:latest | 0B        | Buildpacks Process Types                                  |
| 3  | <missing>  |                  | 1.44kiB   | Buildpacks Launcher Config                                |
| 4  | <missing>  |                  | 2.44MiB   | Buildpacks Application Launcher                           |
| 5  | <missing>  |                  | 59.17MiB  | Application Layer                                         |
| 6  | <missing>  |                  | 729.21kiB | Software Bill-of-Materials                                |
| 7  | <missing>  |                  | 97.87MiB  | Layer: 'jre', Created by buildpack: bellsoft/buildpack    |
| 8  | <missing>  |                  | 200.00B   | Layer: 'java-security-properties', Created by buildpack   |
| 9  | <missing>  |                  | 4.27MiB   | Layer: 'helper', Created by buildpack: bellsoft/buildpack |
| 10 | <missing>  |                  | 2.97kiB   |                                                           |
| 11 | <missing>  |                  | 7.48MiB   |                                                           |

# Result

| 1  | ID         | TAG              | SIZE      | COMMAND                                                   |
|----|------------|------------------|-----------|-----------------------------------------------------------|
| 2  | 2774e3f214 | petclinic:latest | 0B        | Buildpacks Process Types                                  |
| 3  | <missing>  |                  | 1.44kiB   | Buildpacks Launcher Config                                |
| 4  | <missing>  |                  | 2.44MiB   | Buildpacks Application Launcher                           |
| 5  | <missing>  |                  | 59.17MiB  | Application Layer                                         |
| 6  | <missing>  |                  | 729.21kiB | Software Bill-of-Materials                                |
| 7  | <missing>  |                  | 97.87MiB  | Layer: 'jre', Created by buildpack: bellsoft/buildpack    |
| 8  | <missing>  |                  | 200.00B   | Layer: 'java-security-properties', Created by buildpack   |
| 9  | <missing>  |                  | 4.27MiB   | Layer: 'helper', Created by buildpack: bellsoft/buildpack |
| 10 | <missing>  |                  | 2.97kiB   |                                                           |
| 11 | <missing>  |                  | 7.48MiB   |                                                           |

# Result

| 1  | ID         | TAG              | SIZE      | COMMAND                                                   |
|----|------------|------------------|-----------|-----------------------------------------------------------|
| 2  | 2774e3f214 | petclinic:latest | 0B        | Buildpacks Process Types                                  |
| 3  | <missing>  |                  | 1.44kiB   | Buildpacks Launcher Config                                |
| 4  | <missing>  |                  | 2.44MiB   | Buildpacks Application Launcher                           |
| 5  | <missing>  |                  | 59.17MiB  | Application Layer                                         |
| 6  | <missing>  |                  | 729.21kiB | Software Bill-of-Materials                                |
| 7  | <missing>  |                  | 97.87MiB  | Layer: 'jre', Created by buildpack: bellsoft/buildpack    |
| 8  | <missing>  |                  | 200.00B   | Layer: 'java-security-properties', Created by buildpack   |
| 9  | <missing>  |                  | 4.27MiB   | Layer: 'helper', Created by buildpack: bellsoft/buildpack |
| 10 | <missing>  |                  | 2.97kiB   |                                                           |
| 11 | <missing>  |                  | 7.48MiB   |                                                           |

# Result

| 1  | ID         | TAG              | SIZE      | COMMAND                                                   |
|----|------------|------------------|-----------|-----------------------------------------------------------|
| 2  | 2774e3f214 | petclinic:latest | 0B        | Buildpacks Process Types                                  |
| 3  | <missing>  |                  | 1.44kiB   | Buildpacks Launcher Config                                |
| 4  | <missing>  |                  | 2.44MiB   | Buildpacks Application Launcher                           |
| 5  | <missing>  |                  | 59.17MiB  | Application Layer                                         |
| 6  | <missing>  |                  | 729.21kiB | Software Bill-of-Materials                                |
| 7  | <missing>  |                  | 97.87MiB  | Layer: 'jre', Created by buildpack: bellsoft/buildpack    |
| 8  | <missing>  |                  | 200.00B   | Layer: 'java-security-properties', Created by buildpack   |
| 9  | <missing>  |                  | 4.27MiB   | Layer: 'helper', Created by buildpack: bellsoft/buildpack |
| 10 | <missing>  |                  | 2.97kiB   |                                                           |
| 11 | <missing>  |                  | 7.48MiB   |                                                           |

# Buildpacks

Why do we need them?

- Buildpacks transform your application source code into container images
  - The Paketo open source project provides production-ready buildpacks for the most popular languages and frameworks
  - Use Paketo Buildpacks to easily build your apps and keep them updated
- Reminds of s2i images
  - Build better than default
  - Spring-aware

# Is this all?

We've optimized pull/push size, right?

# Optimization is multidimensional

When startup time is more important...

There are several solutions for the Spring application startup time

1. Class Data Sharing (CDS)
2. Project Leyden
3. Coordinated Restore at Checkpoint
4. Native Image

# Class Data Sharing (CDS)

- When: Java 5 (!)
- Why: reduce the startup and memory footprint of multiple JVM instances running on the same host
- How: stores data in an archive

How does it help us?

# Class Data Sharing (CDS)

- When: Java 5 (!)
- Why: reduce the startup and memory footprint of multiple JVM instances running on the same host
- How: stores data in an archive

How does it help us?

It does not! 🙄

# Class Data Sharing (CDS)

- When: Java 5 (!)
- Why: reduce the startup and memory footprint of multiple JVM instances running on the same host
- How: stores data in an archive

How does it help us?

It does not! 🤖 But

# Application Class Data Sharing

- When: Java 10
- Why: add application classes to the archive

And then:

- When: Java 13, JEP 350
- Why: allow addition of classes into the archive upon app exit!

And this helps! How?

# How to use AppCDS with Spring?

- `-XX:ArchiveClassesAtExit=application.jsa` to create an archive
- `-Dspring.context.exit=onRefresh` to start and immediately exit the application

NB:

1. Use the same JDK
2. Use the same arguments

# And even better!

Spring AOT

Add `-Dspring.aot.enabled=true`

Even more classes!!!

# Practice

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --launcher
11
12 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/extracted/dependencies/ ./
16 COPY --from=optimizer /app/extracted/spring-boot-loader/ ./
17 COPY --from=optimizer /app/extracted/snapshot-dependencies/ ./
18 COPY --from=optimizer /app/extracted/application/ ./
```

# Practice

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --launcher
11
12 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/extracted/dependencies/ ./
16 COPY --from=optimizer /app/extracted/spring-boot-loader/ ./
17 COPY --from=optimizer /app/extracted/snapshot-dependencies/ ./
18 COPY --from=optimizer /app/extracted/application/ ./
```

# Practice

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --destination extracted
11 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
12
13 ENTRYPOINT ["java", "-jar", "app.jar"]
14 COPY --from=optimizer /app/extracted/dependencies/ ./
15 COPY --from=optimizer /app/extracted/spring-boot-loader/ ./
16 COPY --from=optimizer /app/extracted/snapshot-dependencies/ ./
17 COPY --from=optimizer /app/extracted/application/ ./
```

# Practice

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --destination extracted
11 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
12
13 ENTRYPOINT ["java", "-jar", "app.jar"]
14 COPY --from=optimizer /app/extracted/dependencies/ ./
15 COPY --from=optimizer /app/extracted/spring-boot-loader/ ./
16 COPY --from=optimizer /app/extracted/snapshot-dependencies/ ./
17 COPY --from=optimizer /app/extracted/application/ ./
```

# Practice

```
1 #omitted
2 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
3
4 ENTRYPOINT ["java", "-jar", "app.jar"]
5 COPY --from=optimizer /app/extracted/dependencies/ ./
6 COPY --from=optimizer /app/extracted/spring-boot-loader/ ./
7 COPY --from=optimizer /app/extracted/snapshot-dependencies/ ./
8 COPY --from=optimizer /app/extracted/application/ ./
9 RUN java -Dspring.aot.enabled=true \
10     -XX:ArchiveClassesAtExit=./application.jsa \
11     -Dspring.context.exit=onRefresh \
12     -jar app.jar
```

# Practice

```
1 #omitted
2 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
3
4 ENTRYPOINT ["java", "-jar", "app.jar"]
5 COPY --from=optimizer /app/extracted/dependencies/ ./
6 COPY --from=optimizer /app/extracted/spring-boot-loader/ ./
7 COPY --from=optimizer /app/extracted/snapshot-dependencies/ ./
8 COPY --from=optimizer /app/extracted/application/ ./
9 RUN java -Dspring.aot.enabled=true \
10     -XX:ArchiveClassesAtExit=./application.jsa \
11     -Dspring.context.exit=onRefresh \
12     -jar app.jar
```

# Practice

```
1 #omitted
2 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
3
4 ENTRYPOINT ["java", \
5             "-Dspring.aot.enabled=true", \
6             "-XX:SharedArchiveFile=application.jsa", \
7             "-jar", "app.jar"]
8 COPY --from=optimizer /app/extracted/dependencies / ./
9 COPY --from=optimizer /app/extracted/spring-boot-loader/ ./
10 COPY --from=optimizer /app/extracted/snapshot-dependencies/ ./
11 COPY --from=optimizer /app/extracted/application/ ./
12 RUN java -Dspring.aot.enabled=true \
13     -XX:ArchiveClassesAtExit=./application.jsa \
14     -Dspring.context.exit=onRefresh \
15     -jar app.jar
```

# Practice

```
1 #omitted
2 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
3
4 ENTRYPOINT ["java", \
5             "-Dspring.aot.enabled=true", \
6             "-XX:SharedArchiveFile=application.jsa", \
7             "-jar", "app.jar"]
8 COPY --from=optimizer /app/extracted/dependencies / ./
9 COPY --from=optimizer /app/extracted/spring-boot-loader/ ./
10 COPY --from=optimizer /app/extracted/snapshot-dependencies/ ./
11 COPY --from=optimizer /app/extracted/application/ ./
12 RUN java -Dspring.aot.enabled=true \
13     -XX:ArchiveClassesAtExit=./application.jsa \
14     -Dspring.context.exit=onRefresh \
15     -jar app.jar
```

# Practice

```
1 #omitted
2 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
3
4 ENTRYPOINT ["java", \
5             "-Dspring.aot.enabled=true", \
6             "-XX:AOTCache=app.aot", \
7             "-jar", "app.jar"]
8 COPY --from=optimizer /app/extracted/dependencies / ./
9 COPY --from=optimizer /app/extracted/spring-boot-loader/ ./
10 COPY --from=optimizer /app/extracted/snapshot-dependencies/ ./
11 COPY --from=optimizer /app/extracted/application/ ./
12 RUN java -Dspring.aot.enabled=true \
13     -XX:-XX:AOTCache=app.aot \
14     -Dspring.context.exit=onRefresh \
15     -jar app.jar
```

# Practice

```
1 #omitted
2 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
3
4 ENTRYPOINT ["java", \
5             "-Dspring.aot.enabled=true", \
6             "-XX:AOTCache=app.aot", \
7             "-jar", "app.jar"]
8 COPY --from=optimizer /app/extracted/dependencies / ./
9 COPY --from=optimizer /app/extracted/spring-boot-loader/ ./
10 COPY --from=optimizer /app/extracted/snapshot-dependencies/ ./
11 COPY --from=optimizer /app/extracted/application/ ./
12 RUN java -Dspring.aot.enabled=true \
13     -XX:-XX:AOTCache=app.aot \
14     -Dspring.context.exit=onRefresh \
15     -jar app.jar
```

# What does it cost ?

1 111M Nov 4 23:47 app.aot

Which is not small at all!

# What does it cost ?

1 111M Nov 4 23:47 app.aot

Which is not small at all!

But you're trading pull speed for startup speed

# How much faster?

Up to 50-60%

# Pushing further with CRaC

## CRaC: Coordinated Restore at Checkpoint

The CRaC (Coordinated Restore at Checkpoint) Project researches coordination of Java programs with mechanisms to checkpoint (make an image of, snapshot) a Java instance while it is executing. Restoring from the image could be a solution to some of the problems with the start-up and warm-up times. The primary aim of the Project is to develop a new standard mechanism-agnostic API to notify Java programs about the checkpoint and restore events. Other research activities will include, but will not be limited to, integration with existing checkpoint/restore mechanisms and development of new ones, changes to JVM and JDK to make images smaller and ensure they are correct.

<https://openjdk.org/projects/crac/>

# In a perfect world it should be:

```
1  FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3  COPY . /app
4  RUN cd /app && ./gradlew build
5
6  FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
7
8  COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9  WORKDIR /app
10 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
11
12 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
13
14 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
15 COPY --from=optimizer /app/app.jar /app/app.jar
16 COPY --from=optimizer /checkpoint /checkpoint
```

# In a perfect world it should be:

```
1  FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3  COPY . /app
4  RUN cd /app && ./gradlew build
5
6  FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
7
8  COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9  WORKDIR /app
10 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
11
12 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
13
14 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
15 COPY --from=optimizer /app/app.jar /app/app.jar
16 COPY --from=optimizer /checkpoint /checkpoint
```

# In a perfect world it should be:

```
1  FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3  COPY . /app
4  RUN cd /app && ./gradlew build
5
6  FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
7
8  COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9  WORKDIR /app
10 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
11
12 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
13
14 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
15 COPY --from=optimizer /app/app.jar /app/app.jar
16 COPY --from=optimizer /checkpoint /checkpoint
```

# But in reality

```
1  #12 6.051      Suppressed: java.lang.RuntimeException: Native checkpoint failed.
2  #12 6.051      at java.base/jdk.crac.Core.translateJVMExceptions(Core.java:114) ~[r
3  #12 6.051      at java.base/jdk.crac.Core.checkpointRestore1(Core.java:192) ~[na:na
4  #12 6.051      at java.base/jdk.crac.Core.checkpointRestore(Core.java:299) ~[na:na
5  #12 6.051      at java.base/jdk.crac.Core.checkpointRestore(Core.java:278) ~[na:na
6  #12 6.051      at java.base/javax.crac.Core.checkpointRestore(Core.java:73) ~[na:na
7  #12 6.051      at java.base/jdk.internal.reflect.DirectMethodHandleAccessor.invoke
8  #12 6.051      at java.base/java.lang.reflect.Method.invoke(Method.java:580) ~[na:r
9  #12 6.051      at org.crac.Core$Compat.checkpointRestore(Core.java:141) ~[crac-1.4.
10 #12 6.051      ... 17 common frames omitted
```

# CRaC is hard!

Let's try to fix it with arcane magic

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
11
12 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
13
14 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
15 COPY --from=optimizer /app/app.jar /app/app.jar
16 COPY --from=optimizer /checkpoint /checkpoint
```

# CRaC is hard!

Let's try to fix it with arcane magic

```
1 # syntax=docker/dockerfile:1-labs
2 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
3
4 COPY . /app
5 RUN cd /app && ./gradlew build -xtest
6
7 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
8
9 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
10 WORKDIR /app
11 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
12
13 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
14
15 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
16 COPY --from=optimizer /app/app.jar /app/app.jar
17 COPY --from=optimizer /checkpoint /checkpoint
```

# CRaC is hard!

Let's try to fix it with arcane magic

```
1 # syntax=docker/dockerfile:1-labs
2 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
3
4 COPY . /app
5 RUN cd /app && ./gradlew build -xtest
6
7 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
8
9 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
10 WORKDIR /app
11 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
12
13 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
14
15 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
16 COPY --from=optimizer /app/app.jar /app/app.jar
17 COPY --from=optimizer /checkpoint /checkpoint
```

# CRaC is hard!

Let's try to fix it with arcane magic

```
1 # syntax=docker/dockerfile:1-labs
2 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
3
4 COPY . /app
5 RUN cd /app && ./gradlew build -xtest
6
7 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
8
9 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
10 WORKDIR /app
11 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
12
13 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
14
15 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
16 COPY --from=optimizer /app/app.jar /app/app.jar
17 COPY --from=optimizer /checkpoint /checkpoint
```

# CRaC is hard!

Let's try to fix it with arcane magic

```
1 # syntax=docker/dockerfile:1-labs
2 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
3
4 COPY . /app
5 RUN cd /app && ./gradlew build -xtest
6
7 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
8
9 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
10 WORKDIR /app
11 RUN --security=insecure java -Dspring.context.checkpoint=onRefresh \
12     -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
13
14 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
15
16 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
```

# CRaC is hard!

Let's try to fix it with arcane magic

```
1 # syntax=docker/dockerfile:1-labs
2 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
3
4 COPY . /app
5 RUN cd /app && ./gradlew build -xtest
6
7 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
8
9 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
10 WORKDIR /app
11 RUN --security=insecure java -Dspring.context.checkpoint=onRefresh \
12     -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar || true
13
14 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
15
16 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
```

# And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx create --buildkitd-flags \  
2   '--allow-insecure-entitlement security.insecure' \  
3   --name insecure-builder
```

# And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx create --buildkitd-flags \  
2   '--allow-insecure-entitlement security.insecure' \  
3   --name insecure-builder
```

# And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx use insecure-builder
```

# And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx build \  
2   --allow security.insecure \  
3   -f Dockerfile.crac \  
4   -t pet-crac --output type=docker .
```

# And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx build \  
2   --allow security.insecure \  
3   -f Dockerfile.crac \  
4   -t pet-crac --output type=docker .
```

# And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx build \  
2     --allow security.insecure \  
3     -f Dockerfile.crac \  
4     -t pet-crac --output type=docker .
```

# And this is not all!

Did you hear about `buildx` ?

```
1 docker run --rm -it --privileged pet-crac
```

# And this is not all!

Did you hear about `buildx` ?

```
1 Restarting Spring-managed lifecycle beans after JVM restore
2 HikariPool-1 - Thread starvation or clock leap detected (housekeeper delta=1d19h37m42s102ms798µs806ns)
3 Tomcat started on port 8080 (http) with context path '/'
4 Restored PetClinicApplication in 0.186 seconds (process running for 0.19)
```

# And this is not all!

Did you hear about `buildx` ?

```
1 Restarting Spring-managed lifecycle beans after JVM restore
2 HikariPool-1 - Thread starvation or clock leap detected (housekeeper delta=1d19h37m42s102ms798µs806ns)
3 Tomcat started on port 8080 (http) with context path '/'
4 Restored PetClinicApplication in 0.186 seconds (process running for 0.19)
```

# Is it a good solution?

It depends

# Is it a good solution?

It depends

- If "It Works" is enough for you

# Is it a good solution?

It depends

- If "It Works" is enough for you -> YES
- If you need more predictable and maintainable thing

# Is it a good solution?

It depends

- If "It Works" is enough for you -> YES
- If you need more predictable and maintainable thing -> NO

# How to make it better?

# How to make it better?

1. Build JAR (in docker or not)

# How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`

# How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`
3. Run the container with capabilities:

# How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`
3. Run the container with capabilities:
  1. `CAP_SYS_PTRACE`

# How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`
3. Run the container with capabilities:
  1. `CAP_SYS_PTRACE`
  2. `CAP_CHECKPOINT_RESTORE`

# How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`
3. Run the container with capabilities:
  1. `CAP_SYS_PTRACE`
  2. `CAP_CHECKPOINT_RESTORE`
4. Container will run and stop

# How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`
3. Run the container with capabilities:
  1. `CAP_SYS_PTRACE`
  2. `CAP_CHECKPOINT_RESTORE`
4. Container will run and stop
5. Commit the container like

```
docker commit container-id new-tag
```

# Pros and Cons

## Pros:

1. Does not require arcane magic
2. Works more predictably
3. Does not depend on unstable features
4. Does not require privileged containers in

## Cons:

1. Organization-specific
2. Requires more steps

And now we have all  
flavours of ultimate  
docker images!

# Quick summary?

1. Use layers for faster deployment
2. Use CDS for faster startup without many compromises
3. Use CRaC for a *lightning-fast* startup (with compromises)
4. Use native image if you're prepared to sacrifice some build time

# Thank you!

Find me @

-  <https://asm0dey.site>
-  @asm0dey.site
-  @asm0dey@fosstodon.org
-  asm0di0
-  me@asm0dey.site
-     asm0dey



Pasha Finkelshteyn  @asm0dey.site  @asm0di0



END