

Crafting the Ultimate Docker Image for Spring Applications

The Spring logo is a circular emblem with a teal background. Inside the circle are four stylized, light-colored leaves arranged in a cross pattern, and a small square at the bottom. The logo is surrounded by several green leaves of varying sizes and orientations, creating a floral effect. The background of the entire slide is a dark green with a circuit-like pattern of lines and dots, and various small icons like a Wi-Fi symbol, a globe, and a calendar.

bellsoft

whoami

whoami

- Pasha Finkelshteyn

whoami

- Pasha Finkelshteyn
- Dev 🥑 at BellSoft

whoami

- Pasha Finkelshteyn
- Dev 🥑 at BellSoft
- ≈10 years in JVM. Mostly ☕ and 

whoami

- Pasha Finkelshteyn
- Dev 🥑 at BellSoft
- ≈10 years in JVM. Mostly ☕ and 🏠
- And 🌿

whoami

- Pasha Finkelshteyn
- Dev 🥑 at BellSoft
- ≈10 years in JVM. Mostly ☕ and 🏠
- And 🌿
- 🐦 asm0di0

whoami

- Pasha Finkelshteyn
- Dev 🥑 at BellSoft
- ≈10 years in JVM. Mostly ☕ and 🚩
- And 🌿
- 🐦 asm0di0
- 📧 @asm0dey@fosstodon.org

BellSoft

- Vendor of Liberica JDK
- Contributor to the OpenJDK
- Author of ARM32 support in JDK
- Own base images
- Own Linux: Alpaquita

Liberica is the JDK officially recommended
by 



BellSoft

- Vendor of Liberica JDK
- Contributor to the OpenJDK
- Author of ARM32 support in JDK
- Own base images
- Own Linux: Alpaquita

Liberica is the JDK officially recommended
by 

We know our stuff!



So, what is ultimate?

- Smallest
- Fatsest startup
- Something inbetween

So, let's look at all of them!

How do we create an image?

Let's start from trivial.

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```



How do we create an image?

Let's start from trivial.

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```



How do we create an image?

Let's start from trivial.

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```



How do we create an image?

Let's start from trivial.

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```



How do we create an image?

Let's start from trivial.

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```



Dockerfile directives

1. Each directive creates a layer of the image.
2. Layers are *immutable*
3. Some layers are zero-sized

Dockerfile directives

1. Each directive creates a layer of the image.
2. Layers are *immutable*
3. Some layers are zero-sized

```
1 FROM bash
2
3 COPY . /app
4 RUN rm -rf /app
```



Dockerfile directives

1. Each directive creates a layer of the image.
2. Layers are *immutable*
3. Some layers are zero-sized

```
1 FROM bash
2
3 COPY . /app
4 RUN rm -rf /app
```



Dockerfile directives

1. Each directive creates a layer of the image.
2. Layers are *immutable*
3. Some layers are zero-sized (for example `RUN rm -rf /app`)

```
1 FROM bash
2
3 COPY . /app
4 RUN rm -rf /app
```



Dockerfile directives

1. Each directive creates a layer of the image.
2. Layers are *immutable*
3. Some layers are zero-sized (for example `RUN rm -rf /app`)

```
1 FROM bash
2
3 COPY . /app
4 RUN rm -rf /app
```

4.  We would like image to be light, but it's not :(

Our Dockerfile

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```



Our Dockerfile

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```



Our Dockerfile

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```



Our Dockerfile

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```



Result

1	ID	TAG	SIZE	COMMAND
2	cda5201e70	dumb:latest	0B	CMD ["/bin/sh"
3	74a0788411		512.03MiB	/bin/sh -c cd /
4	7b82eb08ec		67.41MiB	COPY dir:ef251b
5	e4bcf83d29	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE
6	<missing>		0B	ENV JAVA_HOME="
7	<missing>		0B	ENV LANG=en_US.
8	<missing>		0B	LABEL org.openc
9	<missing>		0B	LABEL org.openc
10	<missing>		0B	LABEL maintaine
11	<missing>		0B	ARG BUNDLE_TYPE
12	<missing>		0B	ARG BUNDLE_TYPE
13	<missing>		0B	ARG BUNDLE_TYPE
14	<missing>		0B	ARG BUNDLE_TYPE
15	<missing>		0B	ARG BUNDLE_TYPE
16	<missing>		0B	ARG JAVA_RELEAS

Result

1	ID	TAG	SIZE	COMMAND
2	cda5201e70	dumb:latest	0B	CMD ["/bin/sh"
3	74a0788411		512.03MiB	/bin/sh -c cd /
4	7b82eb08ec		67.41MiB	COPY dir:ef251b
5	e4bcf83d29	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE
6	<missing>		0B	ENV JAVA_HOME="
7	<missing>		0B	ENV LANG=en_US.
8	<missing>		0B	LABEL org.openc
9	<missing>		0B	LABEL org.openc
10	<missing>		0B	LABEL maintaine
11	<missing>		0B	ARG BUNDLE_TYPE
12	<missing>		0B	ARG BUNDLE_TYPE
13	<missing>		0B	ARG BUNDLE_TYPE
14	<missing>		0B	ARG BUNDLE_TYPE
15	<missing>		0B	ARG BUNDLE_TYPE
16	<missing>		0B	ARG JAVA_RELEAS

Result

1	ID	TAG	SIZE	COMMAND
2	cda5201e70	dumb:latest	0B	CMD ["/bin/sh"
3	74a0788411		512.03MiB	/bin/sh -c cd /
4	7b82eb08ec		67.41MiB	COPY dir:ef251b
5	e4bcf83d29	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE
6	<missing>		0B	ENV JAVA_HOME="
7	<missing>		0B	ENV LANG=en_US.
8	<missing>		0B	LABEL org.openc
9	<missing>		0B	LABEL org.openc
10	<missing>		0B	LABEL maintaine
11	<missing>		0B	ARG BUNDLE_TYPE
12	<missing>		0B	ARG BUNDLE_TYPE
13	<missing>		0B	ARG BUNDLE_TYPE
14	<missing>		0B	ARG BUNDLE_TYPE
15	<missing>		0B	ARG BUNDLE_TYPE
16	<missing>		0B	ARG JAVA_RELEAS

Result

1	ID	TAG	SIZE	COMMAND
2	cda5201e70	dumb:latest	0B	CMD ["/bin/sh"
3	74a0788411		512.03MiB	/bin/sh -c cd /
4	7b82eb08ec		67.41MiB	COPY dir:ef251b
5	e4bcf83d29	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE
6	<missing>		0B	ENV JAVA_HOME="
7	<missing>		0B	ENV LANG=en_US.
8	<missing>		0B	LABEL org.openc
9	<missing>		0B	LABEL org.openc
10	<missing>		0B	LABEL maintaine
11	<missing>		0B	ARG BUNDLE_TYPE
12	<missing>		0B	ARG BUNDLE_TYPE
13	<missing>		0B	ARG BUNDLE_TYPE
14	<missing>		0B	ARG BUNDLE_TYPE
15	<missing>		0B	ARG BUNDLE_TYPE
16	<missing>		0B	ARG JAVA_RELEAS

Result

1	ID	TAG	SIZE	COMMAND
2	cda5201e70	dumb:latest	0B	CMD ["/bin/sh"
3	74a0788411		512.03MiB	/bin/sh -c cd /
4	7b82eb08ec		67.41MiB	COPY dir:ef251b
5	e4bcf83d29	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE
6	<missing>		0B	ENV JAVA_HOME="
7	<missing>		0B	ENV LANG=en_US.
8	<missing>		0B	LABEL org.openc
9	<missing>		0B	LABEL org.openc
10	<missing>		0B	LABEL maintaine
11	<missing>		0B	ARG BUNDLE_TYPE
12	<missing>		0B	ARG BUNDLE_TYPE
13	<missing>		0B	ARG BUNDLE_TYPE
14	<missing>		0B	ARG BUNDLE_TYPE
15	<missing>		0B	ARG BUNDLE_TYPE
16	<missing>		0B	ARG JAVA_RELEAS

Result

1	ID	TAG	SIZE	COMMAND
2	cda5201e70	dumb:latest	0B	CMD ["/bin/sh"
3	74a0788411		512.03MiB	/bin/sh -c cd /
4	7b82eb08ec		67.41MiB	COPY dir:ef251b
5	e4bcf83d29	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE
6	<missing>		0B	ENV JAVA_HOME="
7	<missing>		0B	ENV LANG=en_US.
8	<missing>		0B	LABEL org.openc
9	<missing>		0B	LABEL org.openc
10	<missing>		0B	LABEL maintaine
11	<missing>		0B	ARG BUNDLE_TYPE
12	<missing>		0B	ARG BUNDLE_TYPE
13	<missing>		0B	ARG BUNDLE_TYPE
14	<missing>		0B	ARG BUNDLE_TYPE
15	<missing>		0B	ARG BUNDLE_TYPE
16	<missing>		0B	ARG JAVA_RELEAS

Result

1	ID	TAG	SIZE	COMMAND
2	cda5201e70	dumb:latest	0B	CMD ["/bin/sh"
3	74a0788411		512.03MiB	/bin/sh -c cd /
4	7b82eb08ec		67.41MiB	COPY dir:ef251b
5	e4bcf83d29	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE
6	<missing>		0B	ENV JAVA_HOME="
7	<missing>		0B	ENV LANG=en_US.
8	<missing>		0B	LABEL org.openc
9	<missing>		0B	LABEL org.openc
10	<missing>		0B	LABEL maintaine
11	<missing>		0B	ARG BUNDLE_TYPE
12	<missing>		0B	ARG BUNDLE_TYPE
13	<missing>		0B	ARG BUNDLE_TYPE
14	<missing>		0B	ARG BUNDLE_TYPE
15	<missing>		0B	ARG BUNDLE_TYPE
16	<missing>		0B	ARG JAVA_RELEAS

579.44 MB are changed on every build!

Why do we care? We care because:

1. `push` takes longer time to start
(update is longer)
2. `pull` takes longer
(update takes longer & scaling takes longer)

Also, more disk pspace is inefficiently used



Optimizing. Round 1.

Let's build it outside of container

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY . /app
4 RUN cd /app && ./gradlew build
5 ENTRYPOINT java -jar /app/build/libs/spring-petclinic*.jar
```



Optimizing. Round 1.

Let's build it outside of container

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY build/libs/spring-petclinic-3.3.0.jar /app/app.jar
4 CMD java -jar /app/app.jar
```



Optimizing. Round 1.

Let's build it outside of container

```
1 FROM bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl
2
3 COPY build/libs/spring-petclinic-3.3.0.jar /app/app.jar
4 CMD java -jar /app/app.jar
```



Just copying the prebuilt `jar` file

Results

1	ID	TAG	SIZE	COMMAND
2	cda5201e70	dumb:latest	0B	CMD ["/bin/sh" "-
3	74a0788411		512.03MiB	/bin/sh -c cd /ap
4	7b82eb08ec		67.41MiB	COPY dir:ef251bd1
5	e4bcf83d29	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE=j
6	<missing>		0B	ENV JAVA_HOME="/u
7	<missing>		0B	ENV LANG=en_US.UT
8	<missing>		0B	LABEL org.opencon
9	<missing>		0B	LABEL org.opencon
10	<missing>		0B	LABEL maintainer=
11	<missing>		0B	ARG BUNDLE_TYPE C
12	<missing>		0B	ARG BUNDLE_TYPE C
13	<missing>		0B	ARG BUNDLE_TYPE C
14	<missing>		0B	ARG BUNDLE_TYPE C
15	<missing>		0B	ARG BUNDLE_TYPE J
16	<missing>		0B	ARG JAVA_RELEASE
17	<missing>		7.49MiB	CMD ["/bin/sh"]



Results

1	ID	TAG	SIZE	COMMAND
2	cefb30e21d	smarter:latest	0B	CMD ["/bin/sh" "-c
3	46d7594000		58.80MiB	COPY file:8d96bee9
4	e4bcf83d29	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE=jd
5	<missing>		0B	ENV JAVA_HOME="/us
6	<missing>		0B	ENV LANG=en_US.UTF
7	<missing>		0B	LABEL org.opencont
8	<missing>		0B	LABEL org.opencont
9	<missing>		0B	LABEL maintainer="
10	<missing>		0B	ARG BUNDLE_TYPE CD
11	<missing>		0B	ARG BUNDLE_TYPE CD
12	<missing>		0B	ARG BUNDLE_TYPE CD
13	<missing>		0B	ARG BUNDLE_TYPE CD
14	<missing>		0B	ARG BUNDLE_TYPE JA
15	<missing>		0B	ARG JAVA_RELEASE
16	<missing>		7.49MiB	CMD ["/bin/sh"]



Saved 500+ MB


But the build is not clean now :(

Saved 500+ MB

But the build is not clean now :(

We have to build everything outside, what if environment affects the build?

Enter build stages



Multi-stage builds

Holy grail of pure builds

- Allow clean builds
- Allow optimal packaging
- Allow different base images

Staged example

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```



Staged example

```
1  FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3  COPY . /app
4  RUN cd /app && ./gradlew build -xtest
5
6  FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
7
8  COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```



Staged example

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```



Staged example

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```



Staged example

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```



Staged example

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
```



Result

1	ID	TAG	SIZE	COMMAND
2	6ea7ad11af	smarter:latest	0B	CMD ["/bin/sh" "-.
3	d6eb71a5df		58.80MiB	COPY file:8d96bee
4	c6ede8dac2	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE=;
5	<missing>		0B	ENV JAVA_HOME="/i
6	<missing>		0B	ENV LANG=en_US.U
7	<missing>		0B	LABEL org.opencor
8	<missing>		0B	LABEL org.opencor
9	<missing>		0B	LABEL maintainer:
10	<missing>		0B	ARG BUNDLE_TYPE (
11	<missing>		0B	ARG BUNDLE_TYPE (
12	<missing>		0B	ARG BUNDLE_TYPE (
13	<missing>		0B	ARG BUNDLE_TYPE (
14	<missing>		0B	ARG BUNDLE_TYPE :
15	<missing>		0B	ARG JAVA_RELEASE
16	<missing>		7.49MiB	CMD ["/bin/sh"]

Result

1	ID	TAG	SIZE	COMMAND
2	6ea7ad11af	smarter:latest	0B	CMD ["/bin/sh" "-c
3	d6eb71a5df		58.80MiB	COPY file:8d96bee9
4	c6ede8dac2	bellsoft/liberica-runtime-container:jdk-21.0.3_10-musl	98.32MiB	15 BUNDLE_TYPE=jc
5	<missing>		0B	ENV JAVA_HOME="/us
6	<missing>		0B	ENV LANG=en_US.UTF
7	<missing>		0B	LABEL org.opencont
8	<missing>		0B	LABEL org.opencont
9	<missing>		0B	LABEL maintainer='
10	<missing>		0B	ARG BUNDLE_TYPE CI
11	<missing>		0B	ARG BUNDLE_TYPE CI
12	<missing>		0B	ARG BUNDLE_TYPE CI
13	<missing>		0B	ARG BUNDLE_TYPE CI
14	<missing>		0B	ARG BUNDLE_TYPE JA
15	<missing>		0B	ARG JAVA_RELEASE
16	<missing>		7.49MiB	CMD ["/bin/sh"]

That's all folks!

That's all folks!

Or is it?

What's these 59 MiB?

We have to pull 59 MiB of petclinic on every small commit!

Is there a way to optimize it?

Layers!

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Diarmode=tools -jar /app/app.jar extract --layers --launcher
```

- Build image



Layers!

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Diarmode=tools -jar /app/app.jar extract --layers --launcher
```

- Build image
- Introduce new "optimizer" stage



Layers!

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Diarmode=tools -jar /app/app.jar extract --layers --launcher
```

- Build image
- Introduce new "optimizer" stage



Layers!

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Diarmode=tools -jar /app/app.jar extract --layers --launcher
```

- Build image
- Introduce new "optimizer" stage
- Extract the jar to layered structure



Layers!

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Diarmode=tools -jar /app/app.jar extract --layers --launcher
```

- Build image
- Introduce new "optimizer" stage
- Extract the jar to layered structure



Layers!

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Diarmode=tools -jar /app/app.jar extract --layers --launcher
```

- Build image
- Introduce new "optimizer" stage
- Extract the jar to layered structure
- Copy layers



Layers!

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Diarmode=tools -jar /app/app.jar extract --layers --launcher
```

- Build image
- Introduce new "optimizer" stage
- Extract the jar to layered structure
- Copy layers



Layers

Because Spring Boot jar is complex!

```
1  Usage:
2    java -Djarmode=tools -jar my-app.jar
3
4  Available commands:
5    extract      Extract the contents from the jar
6    list-layers  List layers from the jar that can be extracted
```



Layers

```
1  app
2  |— application
3  |   |— BOOT-INF
4  |   |   |— classes
5  |   |   |   |— application-mysql.properties
6  |   |   |   |— application-postgres.properties
7  |   |   |   |— application.properties
8  |   |   |   |— banner.txt
9  |   |   |   |— db
10 |   |   |   |— ...
11 |   |   |   |— org
```

Layers

```
1  app
2  |— application
3  |   |— BOOT-INF
4  |   |   |— classes
5  |   |   |   |— application-mysql.properties
6  |   |   |   |— application-postgres.properties
7  |   |   |   |— application.properties
8  |   |   |   |— banner.txt
9  |   |   |   |— db
10 |   |   |   |— ...
11 |   |   |   |— org
```

Layers

```
1  app
2  |— application
3  |   |— BOOT-INF
4  |   |   |— classes
5  |   |   |   |— application-mysql.properties
6  |   |   |   |— application-postgres.properties
7  |   |   |   |— application.properties
8  |   |   |   |— banner.txt
9  |   |   |   |— db
10 |   |   |   |— ...
11 |   |   |   |— org
```

Layers

```
1  app
2  |— application
3  |   |— BOOT-INF
4  |   |   |— classes
5  |   |   |   |— application-mysql.properties
6  |   |   |   |— application-postgres.properties
7  |   |   |   |— application.properties
8  |   |   |   |— banner.txt
9  |   |   |   |— db
10 |   |   |   |— ...
11 |   |   |— org
```

Layers

```
1  app
2  |— application
3  |   |— BOOT-INF
4  |   |   |— classes
5  |   |   |   |— application-mysql.properties
6  |   |   |   |— application-postgres.properties
7  |   |   |   |— application.properties
8  |   |   |   |— banner.txt
9  |   |   |   |— db
10 |   |   |   |— ...
11 |   |   |   |— org
```

Layers

```
1  app
2  |— application
3  |   |— BOOT-INF
4  |   |   |— classes
5  |   |   |   |— application-mysql.properties
6  |   |   |   |— application-postgres.properties
7  |   |   |   |— application.properties
8  |   |   |   |— banner.txt
9  |   |   |   |— db
10 |   |   |   |— ...
11 |   |   |   |— org
```


Layers

```
1  app
2  |— application
3  |   |— BOOT-INF
4  |   |   |— classes
5  |   |   |   |— application-mysql.properties
6  |   |   |   |— application-postgres.properties
7  |   |   |   |— application.properties
8  |   |   |   |— banner.txt
9  |   |   |   |— db
10 |   |   |   |— ...
11 |   |   |   |— org
```

Layers

```
1  app
2  |— application
3  |   |— BOOT-INF
4  |   |   |— classes
5  |   |   |   |— application-mysql.properties
6  |   |   |   |— application-postgres.properties
7  |   |   |   |— application.properties
8  |   |   |   |— banner.txt
9  |   |   |   |— db
10 |   |   |   |— ...
11 |   |   |   |— org
```

Layers

```
1  app
2  |— application
3  |   |— BOOT-INF
4  |   |   |— classes
5  |   |   |   |— application-mysql.properties
6  |   |   |   |— application-postgres.properties
7  |   |   |   |— application.properties
8  |   |   |   |— banner.txt
9  |   |   |   |— db
10 |   |   |   |— ...
11 |   |   |   |— org
```

Layers

```
1  app
2  |— application
3  |   |— BOOT-INF
4  |   |   |— classes
5  |   |   |   |— application-mysql.properties
6  |   |   |   |— application-postgres.properties
7  |   |   |   |— application.properties
8  |   |   |   |— banner.txt
9  |   |   |   |— db
10 |   |   |   |— ...
11 |   |   |   |— org
```

Layers

```
1  app
2  |— application
3  |   |— BOOT-INF
4  |   |   |— classes
5  |   |       |— application-mysql.properties
6  |   |       |— application-postgres.properties
7  |   |       |— application.properties
8  |   |       |— banner.txt
9  |   |       |— db
10 |   |       |— ...
11 |   |       |— org
```

Layers

```
1  app
2  |— application
3  |   |— BOOT-INF
4  |   |   |— classes
5  |   |   |   |— application-mysql.properties
6  |   |   |   |— application-postgres.properties
7  |   |   |   |— application.properties
8  |   |   |   |— banner.txt
9  |   |   |   |— db
10 |   |   |   |— ...
11 |   |   |   |— org
```

Layers

```
1  app
2  |— application
3  |   |— BOOT-INF
4  |       |— classes
5  |           |— application-mysql.properties
6  |           |— application-postgres.properties
7  |           |— application.properties
8  |           |— banner.txt
9  |           |— db
10 |           |— ...
11 |           |— org
```

Layers

```
1  app
2  |— application
3  |   |— BOOT-INF
4  |       |— classes
5  |           |— application-mysql.properties
6  |           |— application-postgres.properties
7  |           |— application.properties
8  |           |— banner.txt
9  |           |— db
10 |           |— ...
11 |           |— org
```


Layered image structure

1	ID	TAG	SIZE	COMMAND
2	618743f6a2	layers:latest	2.96MiB	COPY dir:e0faa63b9654
3	9cca3273f0		0B	COPY dir:acd0d0ac1f7c
4	fe123ee16e		382.56kiB	COPY dir:01225d3c4ef0
5	dede9bac3d		57.69MiB	COPY dir:755815d928fc
6	65e3fb4cbf		0B	ENTRYPOINT ["java" "c
7	7130fa5864	bellsoft/liberica-runtime-container:jre-slim-musl	126.80MiB	18 CDS=no DESCRIPTION
8	<missing>		0B	ENV JAVA_HOME="/usr/1
9	<missing>		0B	ENV LANG=en_US.UTF-8
10	<missing>		0B	LABEL org.opencontainers



Layered image structure

1	ID	TAG	SIZE	COMMAND
2	618743f6a2	layers:latest	2.96MiB	COPY dir:e0faa63b9654
3	9cca3273f0		0B	COPY dir:acd0d0ac1f70
4	fe123ee16e		382.56kiB	COPY dir:01225d3c4ef0
5	dede9bac3d		57.69MiB	COPY dir:755815d928fc
6	65e3fb4cbf		0B	ENTRYPOINT ["java" "c
7	7130fa5864	bellsoft/liberica-runtime-container:jre-slim-musl	126.80MiB	18 CDS=no DESCRIPTION
8	<missing>		0B	ENV JAVA_HOME="/usr/7
9	<missing>		0B	ENV LANG=en_US.UTF-8
10	<missing>		0B	LABEL org.opencontainers

- Dependencies: ~57.7MiB



Layered image structure

1	ID	TAG	SIZE	COMMAND
2	618743f6a2	layers:latest	2.96MiB	COPY dir:e0faa63b9654
3	9cca3273f0		0B	COPY dir:acd0d0ac1f70
4	fe123ee16e		382.56kiB	COPY dir:01225d3c4ef0
5	dede9bac3d		57.69MiB	COPY dir:755815d928fd
6	65e3fb4cbf		0B	ENTRYPOINT ["java" "c
7	7130fa5864	bellsoft/liberica-runtime-container:jre-slim-musl	126.80MiB	18 CDS=no DESCRIPTION
8	<missing>		0B	ENV JAVA_HOME="/usr/7
9	<missing>		0B	ENV LANG=en_US.UTF-8
10	<missing>		0B	LABEL org.opencontainers

- Dependencies: ~57.7MiB
- Launcher: 382.56kiB



Layered image structure

1	ID	TAG	SIZE	COMMAND
2	618743f6a2	layers:latest	2.96MiB	COPY dir:e0faa63b9654
3	9cca3273f0		0B	COPY dir:acd0d0ac1f70
4	fe123ee16e		382.56kiB	COPY dir:01225d3c4ef0
5	dede9bac3d		57.69MiB	COPY dir:755815d928f0
6	65e3fb4cbf		0B	ENTRYPOINT ["java" "c
7	7130fa5864	bellsoft/liberica-runtime-container:jre-slim-musl	126.80MiB	18 CDS=no DESCRIPTION
8	<missing>		0B	ENV JAVA_HOME="/usr/7
9	<missing>		0B	ENV LANG=en_US.UTF-8
10	<missing>		0B	LABEL org.opencontainers

- Dependencies: ~57.7MiB
- Launcher: 382.56kiB



Layered image structure

1	ID	TAG	SIZE	COMMAND
2	618743f6a2	layers:latest	2.96MiB	COPY dir:e0faa63b9654
3	9cca3273f0		0B	COPY dir:acd0d0ac1f70
4	fe123ee16e		382.56kiB	COPY dir:01225d3c4ef0
5	dede9bac3d		57.69MiB	COPY dir:755815d928f0
6	65e3fb4cbf		0B	ENTRYPOINT ["java" "c
7	7130fa5864	bellsoft/liberica-runtime-container:jre-slim-musl	126.80MiB	18 CDS=no DESCRIPTION
8	<missing>		0B	ENV JAVA_HOME="/usr/7
9	<missing>		0B	ENV LANG=en_US.UTF-8
10	<missing>		0B	LABEL org.opencontainers

- Dependencies: ~57.7MiB
- Launcher: 382.56kiB
- Application: ~3MiB



Layered image structure

1	ID	TAG	SIZE	COMMAND
2	618743f6a2	layers:latest	2.96MiB	COPY dir:e0faa63b9654
3	9cca3273f0		0B	COPY dir:acd0d0ac1f7c
4	fe123ee16e		382.56kiB	COPY dir:01225d3c4ef0
5	dede9bac3d		57.69MiB	COPY dir:755815d928fc
6	65e3fb4cbf		0B	ENTRYPOINT ["java" "c
7	7130fa5864	bellsoft/liberica-runtime-container:jre-slim-musl	126.80MiB	18 CDS=no DESCRIPTION
8	<missing>		0B	ENV JAVA_HOME="/usr/1
9	<missing>		0B	ENV LANG=en_US.UTF-8
10	<missing>		0B	LABEL org.opencontainers

- Dependencies: ~57.7MiB
- Launcher: 382.56kiB
- Application: ~3MiB

Together: ~61MiB



61.0MiB > 58.8Mib!



What are we optimizing?

Pull size!

Pull size here is usually only around 3MiB!

We just reinvented how the BellSoft's buildpack works!

And it is amazing

Diversion: buildpacks

<https://paketo.io/>

Trivial usage:

```
1  /usr/sbin/pack build petclinic \  
2    --builder bellsoft/buildpacks.builder \  
3    --path . \  
4    -e BP_JVM_VERSION=21
```



Diversion: buildpacks

<https://paketo.io/>

Trivial usage:

```
1 /usr/sbin/pack build petclinic \  
2   --builder bellsoft/buildpacks.builder \  
3   --path . \  
4   -e BP_JVM_VERSION=21
```



Diversion: buildpacks

<https://paketo.io/>

Trivial usage:

```
1 /usr/sbin/pack build petclinic \  
2   --builder bellsoft/buildpacks.builder \  
3   --path . \  
4   -e BP_JVM_VERSION=21
```



Diversion: buildpacks

<https://paketo.io/>

Trivial usage:

```
1 /usr/sbin/pack build petclinic \  
2   --builder bellsoft/buildpacks.builder \  
3   --path . \  
4   -e BP_JVM_VERSION=21
```



Result

1	ID	TAG	SIZE	COMMAND
2	2774e3f214	petclinic:latest	0B	Buildpacks Process Types
3	<missing>		1.44kiB	Buildpacks Launcher Config
4	<missing>		2.44MiB	Buildpacks Application Launcher
5	<missing>		59.17MiB	Application Layer
6	<missing>		729.21kiB	Software Bill-of-Materials
7	<missing>		97.87MiB	Layer: 'jre', Created by buildpack: bellsoft/buildpack
8	<missing>		200.00B	Layer: 'java-security-properties', Created by buildpack
9	<missing>		4.27MiB	Layer: 'helper', Created by buildpack: bellsoft/buildpack
10	<missing>		2.97kiB	
11	<missing>		7.48MiB	



Result

1	ID	TAG	SIZE	COMMAND
2	2774e3f214	petclinic:latest	0B	Buildpacks Process Types
3	<missing>		1.44kiB	Buildpacks Launcher Config
4	<missing>		2.44MiB	Buildpacks Application Launcher
5	<missing>		59.17MiB	Application Layer
6	<missing>		729.21kiB	Software Bill-of-Materials
7	<missing>		97.87MiB	Layer: 'jre', Created by buildpack: bellsoft/buildpack
8	<missing>		200.00B	Layer: 'java-security-properties', Created by buildpack
9	<missing>		4.27MiB	Layer: 'helper', Created by buildpack: bellsoft/buildpack
10	<missing>		2.97kiB	
11	<missing>		7.48MiB	



Result

1	ID	TAG	SIZE	COMMAND
2	2774e3f214	petclinic:latest	0B	Buildpacks Process Types
3	<missing>		1.44kiB	Buildpacks Launcher Config
4	<missing>		2.44MiB	Buildpacks Application Launcher
5	<missing>		59.17MiB	Application Layer
6	<missing>		729.21kiB	Software Bill-of-Materials
7	<missing>		97.87MiB	Layer: 'jre', Created by buildpack: bellsoft/buildpack
8	<missing>		200.00B	Layer: 'java-security-properties', Created by buildpack
9	<missing>		4.27MiB	Layer: 'helper', Created by buildpack: bellsoft/buildpack
10	<missing>		2.97kiB	
11	<missing>		7.48MiB	



Result

1	ID	TAG	SIZE	COMMAND
2	2774e3f214	petclinic:latest	0B	Buildpacks Process Types
3	<missing>		1.44kiB	Buildpacks Launcher Config
4	<missing>		2.44MiB	Buildpacks Application Launcher
5	<missing>		59.17MiB	Application Layer
6	<missing>		729.21kiB	Software Bill-of-Materials
7	<missing>		97.87MiB	Layer: 'jre', Created by buildpack: bellsoft/buildpack
8	<missing>		200.00B	Layer: 'java-security-properties', Created by buildpack
9	<missing>		4.27MiB	Layer: 'helper', Created by buildpack: bellsoft/buildpack
10	<missing>		2.97kiB	
11	<missing>		7.48MiB	



Buildpacks

Why do we need them?

- Buildpacks transform your application source code into container images
 - The Paketo open source project provides production-ready buildpacks for the most popular languages and frameworks
 - Use Paketo Buildpacks to easily build your apps and keep them updated
- Reminds of s2i images
 - Build better than default
 - Spring-aware

Is this all?

We've optimized pull/push size, right?

Optimization is multidimensional

When startup time is more important...

There are several solutions for the Spring application startup time

1. Class Data Sharing (CDS)
2. Coordinated Restore at Checkpoint
3. Native Image

Class Data Sharing (CDS)

- When: Java 5 (!)
- Why: reduce the startup and memory footprint of multiple JVM instances running on the same host
- How: stores data in an archive

How does it help us?

Class Data Sharing (CDS)

- When: Java 5 (!)
- Why: reduce the startup and memory footprint of multiple JVM instances running on the same host
- How: stores data in an archive

How does it help us?

It does not! 

Class Data Sharing (CDS)

- When: Java 5 (!)
- Why: reduce the startup and memory footprint of multiple JVM instances running on the same host
- How: stores data in an archive

How does it help us?

It does not!  But

Application Class Data Sharing

- When: Java 10
- Why: add application classes to the archive

And then:

- When: Java 13, JEP 350
- Why: allow addition of classes into the archive upon app exit!

And this helps! How?

How to use AppCDS with Spring?

- `-XX:ArchiveClassesAtExit=application.jsa` to create an archive
- `-Dspring.context.exit=onRefresh` to start and immediately exit the application

NB:

1. Use the same JDK
2. Use the same arguments

And even better!

Spring AOT

Add `-Dspring.aot.enabled=true`

Even more classes!!!

Practice

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --launcher
11
12 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/app/dependencies/ ./
16 COPY --from=optimizer /app/app/spring-boot-loader/ ./
17 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
18 COPY --from=optimizer /app/app/application/ ./
```



Practice

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --launcher
11
12 FROM bellsoft/liberica-runtime-container:jre-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/app/dependencies/ ./
16 COPY --from=optimizer /app/app/spring-boot-loader/ ./
17 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
18 COPY --from=optimizer /app/app/application/ ./
```



Practice

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --launcher
11
12 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/app/dependencies/ ./
16 COPY --from=optimizer /app/app/spring-boot-loader/ ./
17 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
18 COPY --from=optimizer /app/app/application/ ./
```



Practice

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-slim-musl as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Djarmode=tools -jar /app/app.jar extract --layers --launcher
11
12 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
13
14 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
15 COPY --from=optimizer /app/app/dependencies/ ./
16 COPY --from=optimizer /app/app/spring-boot-loader/ ./
17 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
18 COPY --from=optimizer /app/app/application/ ./
```



Practice

```
1  #omitted
2  FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
3
4  ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
5  COPY --from=optimizer /app/app/dependencies/ ./
6  COPY --from=optimizer /app/app/spring-boot-loader/ ./
7  COPY --from=optimizer /app/app/snapshot-dependencies/ ./
8  COPY --from=optimizer /app/app/application/ ./
9  RUN java -Dspring.aot.enabled=true \
10     -XX:ArchiveClassesAtExit=./application.jsa \
11     -Dspring.context.exit=onRefresh \
12     org.springframework.boot.loader.launch.JarLauncher
```



Practice

```
1 #omitted
2 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
3
4 ENTRYPOINT ["java", "org.springframework.boot.loader.launch.JarLauncher"]
5 COPY --from=optimizer /app/app/dependencies/ ./
6 COPY --from=optimizer /app/app/spring-boot-loader/ ./
7 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
8 COPY --from=optimizer /app/app/application/ ./
9 RUN java -Dspring.aot.enabled=true \
10     -XX:ArchiveClassesAtExit=./application.jsa \
11     -Dspring.context.exit=onRefresh \
12     org.springframework.boot.loader.launch.JarLauncher
```



Practice

```
1 #omitted
2 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
3
4 ENTRYPOINT ["java", \
5             "-Dspring.aot.enabled=true", \
6             "-XX:SharedArchiveFile=application.jsa", \
7             "org.springframework.boot.loader.launch.JarLauncher"]
8 COPY --from=optimizer /app/app/dependencies / ./
9 COPY --from=optimizer /app/app/spring-boot-loader/ ./
10 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
11 COPY --from=optimizer /app/app/application/ ./
12 RUN java -Dspring.aot.enabled=true \
13     -XX:ArchiveClassesAtExit=./application.jsa \
14     -Dspring.context.exit=onRefresh \
15     org.springframework.boot.loader.launch.JarLauncher
```



Practice

```
1 #omitted
2 FROM bellsoft/liberica-runtime-container:jre-cds-slim-musl as runner
3
4 ENTRYPOINT ["java", \
5             "-Dspring.aot.enabled=true", \
6             "-XX:SharedArchiveFile=application.jsa", \
7             "org.springframework.boot.loader.launch.JarLauncher"]
8 COPY --from=optimizer /app/app/dependencies / ./
9 COPY --from=optimizer /app/app/spring-boot-loader/ ./
10 COPY --from=optimizer /app/app/snapshot-dependencies/ ./
11 COPY --from=optimizer /app/app/application/ ./
12 RUN java -Dspring.aot.enabled=true \
13       -XX:ArchiveClassesAtExit=./application.jsa \
14       -Dspring.context.exit=onRefresh \
15       org.springframework.boot.loader.launch.JarLauncher
```



What does it cost ?

```
1  -r--r--r--      0:0      81 MB  |— application.jsa
```



Which is not small at all!

What does it cost ?

```
1 -r--r--r-- 0:0 81 MB |— application.jsa
```



Which is not small at all!

But you're trading pull speed for startup speed

How much faster?

Up to 50-60%

Pushing further with CRaC

CRaC: Coordinated Restore at Checkpoint

The CRaC (Coordinated Restore at Checkpoint) Project researches coordination of Java programs with mechanisms to checkpoint (make an image of, snapshot) a Java instance while it is executing. Restoring from the image could be a solution to some of the problems with the start-up and warm-up times. The primary aim of the Project is to develop a new standard mechanism-agnostic API to notify Java programs about the checkpoint and restore events. Other research activities will include, but will not be limited to, integration with existing checkpoint/restore mechanisms and development of new ones, changes to JVM and JDK to make images smaller and ensure they are correct.

<https://openjdk.org/projects/crac/>

In a perfect world it should be:

```
1  FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3  COPY . /app
4  RUN cd /app && ./gradlew build
5
6  FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
7
8  COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9  WORKDIR /app
10 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/ap
11
12 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
13
14 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
15 COPY --from=optimizer /app/app.jar /app/app.jar
16 COPY --from=optimizer /checkpoint /checkpoint
```



In a perfect world it should be:

```
1  FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3  COPY . /app
4  RUN cd /app && ./gradlew build
5
6  FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
7
8  COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9  WORKDIR /app
10 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
11
12 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
13
14 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
15 COPY --from=optimizer /app/app.jar /app/app.jar
16 COPY --from=optimizer /checkpoint /checkpoint
```



In a perfect world it should be:

```
1  FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3  COPY . /app
4  RUN cd /app && ./gradlew build
5
6  FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
7
8  COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9  WORKDIR /app
10 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/ap
11
12 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
13
14 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
15 COPY --from=optimizer /app/app.jar /app/app.jar
16 COPY --from=optimizer /checkpoint /checkpoint
```



But in reality

```
1  #12 6.051      Suppressed: java.lang.RuntimeException: Native checkpoint failed.
2  #12 6.051      at java.base/jdk.crac.Core.translateJVMExceptions(Core.java:114) ~[r
3  #12 6.051      at java.base/jdk.crac.Core.checkpointRestore1(Core.java:192) ~[na:na
4  #12 6.051      at java.base/jdk.crac.Core.checkpointRestore(Core.java:299) ~[na:na
5  #12 6.051      at java.base/jdk.crac.Core.checkpointRestore(Core.java:278) ~[na:na
6  #12 6.051      at java.base/javax.crac.Core.checkpointRestore(Core.java:73) ~[na:na
7  #12 6.051      at java.base/jdk.internal.reflect.DirectMethodHandleAccessor.invoke
8  #12 6.051      at java.base/java.lang.reflect.Method.invoke(Method.java:580) ~[na:r
9  #12 6.051      at org.crac.Core$Compat.checkpointRestore(Core.java:141) ~[crac-1.4.
10 #12 6.051      ... 17 common frames omitted
```



CRaC is hard!

Let's try to fix it with arcane magic

```
1 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
2
3 COPY . /app
4 RUN cd /app && ./gradlew build -xtest
5
6 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
7
8 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
9 WORKDIR /app
10 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app
11
12 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
13
14 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
15 COPY --from=optimizer /app/app.jar /app/app.jar
16 COPY --from=optimizer /checkpoint /checkpoint
```



CRaC is hard!

Let's try to fix it with arcane magic

```
1 # syntax=docker/dockerfile:1-labs
2 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
3
4 COPY . /app
5 RUN cd /app && ./gradlew build -xtest
6
7 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
8
9 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
10 WORKDIR /app
11 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app
12
13 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
14
15 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
16 COPY --from=optimizer /app/app.jar /app/app.jar
17 COPY --from=optimizer /checkpoint /checkpoint
```

CRaC is hard!

Let's try to fix it with arcane magic

```
1 # syntax=docker/dockerfile:1-labs
2 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
3
4 COPY . /app
5 RUN cd /app && ./gradlew build -xtest
6
7 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
8
9 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
10 WORKDIR /app
11 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app
12
13 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
14
15 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
16 COPY --from=optimizer /app/app.jar /app/app.jar
17 COPY --from=optimizer /checkpoint /checkpoint
```

CRaC is hard!

Let's try to fix it with arcane magic

```
1 # syntax=docker/dockerfile:1-labs
2 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
3
4 COPY . /app
5 RUN cd /app && ./gradlew build -xtest
6
7 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
8
9 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
10 WORKDIR /app
11 RUN java -Dspring.context.checkpoint=onRefresh -XX:CRaCCheckpointTo=/checkpoint -jar /app/app
12
13 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
14
15 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
16 COPY --from=optimizer /app/app.jar /app/app.jar
17 COPY --from=optimizer /checkpoint /checkpoint
```

CRaC is hard!

Let's try to fix it with arcane magic

```
1 # syntax=docker/dockerfile:1-labs
2 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
3
4 COPY . /app
5 RUN cd /app && ./gradlew build -xtest
6
7 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
8
9 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
10 WORKDIR /app
11 RUN --security=insecure java -Dspring.context.checkpoint=onRefresh \
12     -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar
13
14 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
15
16 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
```

CRaC is hard!

Let's try to fix it with arcane magic

```
1 # syntax=docker/dockerfile:1-labs
2 FROM bellsoft/liberica-runtime-container:jdk-musl as builder
3
4 COPY . /app
5 RUN cd /app && ./gradlew build -xtest
6
7 FROM bellsoft/liberica-runtime-container:jre-crac-slim as optimizer
8
9 COPY --from=builder /app/build/libs/spring-petclinic-3.3.0.jar /app/app.jar
10 WORKDIR /app
11 RUN --security=insecure java -Dspring.context.checkpoint=onRefresh \
12     -XX:CRaCCheckpointTo=/checkpoint -jar /app/app.jar || true
13
14 FROM bellsoft/liberica-runtime-container:jre-crac-slim as runner
15
16 ENTRYPOINT java -XX:CRaCRestoreFrom=/checkpoint
```


And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx create --buildkitd-flags \  
2   '--allow-insecure-entitlement security.insecure' \  
3   --name insecure-builder
```



And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx create --buildkitd-flags \  
2   '--allow-insecure-entitlement security.insecure' \  
3   --name insecure-builder
```



And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx use insecure-builder
```



And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx build \  
2   --allow security.insecure \  
3   -f Dockerfile.crac \  
4   -t pet-crac --output type=docker .
```



And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx build \  
2     --allow security.insecure \  
3     -f Dockerfile.crac \  
4     -t pet-crac --output type=docker .
```



And this is not all!

Did you hear about `buildx` ?

```
1 docker buildx build \  
2   --allow security.insecure \  
3   -f Dockerfile.crac \  
4   -t pet-crac --output type=docker .
```



And this is not all!

Did you hear about `buildx` ?

```
1 docker run --rm -it --privileged pet-crac
```



And this is not all!

Did you hear about `buildx` ?

```
1 Restarting Spring-managed lifecycle beans after JVM restore
2 HikariPool-1 - Thread starvation or clock leap detected (housekeeper delta=1d19h37m42s102ms798
3 Tomcat started on port 8080 (http) with context path '/'
4 Restored PetClinicApplication in 0.186 seconds (process running for 0.19)
```



And this is not all!

Did you hear about `buildx` ?

```
1 Restarting Spring-managed lifecycle beans after JVM restore
2 HikariPool-1 - Thread starvation or clock leap detected (housekeeper delta=1d19h37m42s102ms798
3 Tomcat started on port 8080 (http) with context path '/'
4 Restored PetClinicApplication in 0.186 seconds (process running for 0.19)
```



Is it a good solution?

It depends

Is it a good solution?

It depends

- If "It Works" is enough for you

Is it a good solution?

It depends

- If "It Works" is enough for you -> YES
- If you need more predictable and maintainable thing

Is it a good solution?

It depends

- If "It Works" is enough for you -> YES
- If you need more predictable and maintainable thing

Is it a good solution?

It depends

- If "It Works" is enough for you -> YES
- If you need more predictable and maintainable thing -> NO

How to make it better?

How to make it better?

1. Build JAR (in docker or not)

How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`

How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`
3. Run the container with capabilities:

How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`
3. Run the container with capabilities:
 1. `CAP_SYS_PTRACE`

How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`
3. Run the container with capabilities:
 1. `CAP_SYS_PTRACE`
 2. `CAP_CHECKPOINT_RESTORE`

How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`
3. Run the container with capabilities:
 1. `CAP_SYS_PTRACE`
 2. `CAP_CHECKPOINT_RESTORE`
4. Container will run and stop

How to make it better?

1. Build JAR (in docker or not)
2. Create new image that will run the JAR with CRaC arguments in `ENTRYPOINT`
3. Run the container with capabilities:
 1. `CAP_SYS_PTRACE`
 2. `CAP_CHECKPOINT_RESTORE`
4. Container will run and stop
5. Commit the container like

```
1  docker commit container-id new-tag
```



Pros and Cons

Pros:

1. Does not require arcane magic
2. Works more predictably
3. Does not depend on unstable features
4. Does not require privileged containers in

Cons:

1. Organization-specific
2. Requires more steps

And now we have all
flavours of ultimate
docker images!

Quick summary?

1. Use layers for faster deployment
2. Use CDS for faster startup without many compromises
3. Use CRaC for a *lightning-fast* startup (with compromises)

Thank you!

Find me @

-  asm0di0
-  @asm0dey@fosstodon.org
-  me@asm0dey.site
-  asm0dey
-  asm0dey
-  asm0dey
-  asm0dey
-  asm0dey



END