

FROM RESEARCH TO INDUSTRY

cea tech



list

ACTIVITY MODELING


Introduction on UML for Industrial Systems

Jérémie Tatibouët, Shuai Li, François Terrier, Sébastien Gérard, [Asma Smaoui](#)

{first_name}.{last_name}@cea.fr

Copyright (c) 2015, CEA LIST, All rights reserved.

Redistribution and use (commercial or non-commercial), of this presentation, with or without modification, is strictly forbidden without explicit and official approval from CEA LIST





Introduction

- What is the purpose of UML activities?
- The different usages of activities that are allowed by UML




Graph like structure and data flow semantics

- Data flow semantics
- Partial execution orders



Activities: syntax and semantics

- Input and output value, base actions, invocation actions
- Nodes to coordinate the execution flow
- Going further



Relation between this course and current research

- fUML
- ALF



Appendix: build a simple example and see how it executes



Introduction

- What is the purpose of UML activities?
- The different usages of activities that are allowed by UML



Graph like structure and data flow semantics

- Data flow semantics
- Partial execution orders



Activities: syntax and semantics

- Input and output value, base actions, invocation actions
- Coordinating the execution flow
- Going further



Relation between this course and current research

- fUML
- ALF




Appendix: build a simple example and see how it executes


Based on UML 2.5


“Activities may describe procedural computation...”

“...in an object-oriented model, they may be invoked indirectly as methods bound to Operations that are directly invoked...”.

“Activities can also be used for information system modeling to specify system level processes...”









Introduction

- What is the purpose of UML activities?
- The different usages of activities that are allowed by UML



Graph like structure and data flow semantics

- Data flow semantics
- Partial execution orders



Activities: syntax and semantics

- Input and output value, base actions, invocation actions
- Coordinating the execution flow
- Going further




Relation between this course and current research

- fUML
- ALF




Appendix: build a simple example and see how it executes



Activity is the container of the graph


Graph composition

- The activity itself is the container of the graph
- The nodes denotes actions to realize
- The edges denote precedence relationships between action nodes
 - Edges in red denote only precedence relationships
- The edges denotes flowing of data between action nodes
 - Edges in blue denote a precedence relationship as well as data flowing from an action to another




Activity nodes specialize into a large set of “action nodes” that all expose a different semantics

ActivityEdge specializes into two kinds of edges: ControlFlow and ObjectFlow. These two kinds of edges are used to materialize precedence relationships and data passing



Execution rules

- A node can be executed when
 - Its control and data dependencies are satisfied
 - **Example:** A4 cannot be executed before A1-A2-A3 are done
- When the activity execution starts
 - Nodes that have no dependencies to satisfy are executed concurrently
 - **Example:** A1 and A5 executes concurrently



We can be sure that:

A2 after A1

A3 after A1

A4 after A2, A3

A6 after A4, A5

However we cannot say that:

A5 after A1 (and reverse)

A3 after A2 (and reverse)

Partial execution order:


A1 and A5 (parallel)

A2 and A3 (parallel or sequence)

A4

A6


Dependent on the model form
(i.e., does parallelism is explicitly
described with a Fork ?)



Question:


- How can we say that A2 will be executed each time after A3 ?





Execution propagation

- Materialized by tokens flowing through edges
 - Control token: propagate across control flows
 - Object token: propagate across the object flows and ships data





Introduction

- What is the purpose of UML activities?
- The different usages of activities that are allowed by UML



Graph like structure and data flow semantics

- Data flow semantics
- Partial execution orders



Activities: syntax and semantics – input and output values




Relation between this course and current research

- fUML
- ALF



Appendix: build a simple example and see how it executes



Activity parameters nodes


- Denote points used to provide an activity with input values
- Denote points used by an activity to provide output values
- They are typed (not mandatory)
 - Can be derived from the parameter attached to the activity parameter node

```


activity main(){
    v = f(5,2)
}
  
```

A valid call for this activity


Direction of a parameter




Direction of Parameter



Direction of Parameter






Actions

- Can consume and/or produced data
 - Data consumed by an action come from its input pin(s)
 - Data produced are placed on its output pin(s)
- Note: it is not mandatory for an action to consume or produce data



Introduction

- What is the purpose of UML activities?
- The different usages of activities that are allowed by UML



Graph like structure and data flow semantics

- Data flow semantics
- Partial execution orders



Activities: syntax and semantics – base actions




Relation between this course and current research

- fUML
- ALF





Appendix: build a simple example and see how it executes




ValueSpecificationAction

- Produce a value on its result output pin from any kind of value specification
 - Expression (e.g. StringExpression, TimeExpression)
 - Literal value (e.g. LiteralInteger)
 - Duration
 - InstanceValue (e.g. an instance of a class)





TestIdentityAction

- Assess the equality between the provided values
 - Two values are equal since they have the same types as well the same values for their properties
 - Two enumeration values are equal since they use the same enumeration literal



Provides a reference on the execution context

- Looks like a “this” instruction in C++ or Java
- If the activity is used in standalone mode
 - The context is the activity itself
- If the activity is used as an implementation for an operation
 - The context is the class instance that was used to make the operation call
- If the activity is used as a classifier behavior
 - The context is the instance of the active class executing the classifier behavior



Read a structural feature that belongs to a classifier instance

- Requires a target to read
 - Basically the object into which the feature must be read
- Provides the result of the reading on its output pin
 - Type of the value is the type of feature



Introduction

- What is the purpose of UML activities?
- The different usages of activities that are allowed by UML



Graph like structure and data flow semantics

- Data flow semantics
- Partial execution orders



Activities: syntax and semantics – invocation actions




Relation between this course and current research

- fUML
- ALF




Appendix: build a simple example and see how it executes




Call to a specific behavior

- Similar to a function call in C for example
- Requires the behavior to be called to be specified
 - This can be realized through the property view of Papyrus
- Eventually requires values for input pins if the called behavior as parameters




Note: the operation call can be asynchronous


Attribute "**msg**" of the instance is updated.




Call to a an operation of class

- Requires a target on which the operation can be called
 - The target is an instance of a classifier
- Requires the operation to be called to be specified
 - This can be realized through the property view of Papyrus
- Eventually requires values for input pins if the called operation as parameters








Send a signal to an instance of an active object

- Requires a target to which the signal is sent
 - It is an instance of a classifier that is active (i.e., has a classifier behavior)
- Requires the signal type to be sent to be specified
 - This can be realized through the property view of Papyrus
- Eventually requires values for input pins if the type of the signal that is sent has structural features



Suspends the classifier behavior that executes this action

- Register an event accepter for the event (SignalEvent, CallEvent,...)
 - The one referenced by the trigger attached to the “AcceptEventAction”
- Execution continues when an occurrence of the expected event arrives at the event pool and gets dispatched
- If the expected event is intended to ship values (e.g., for signal properties)
 - Properties values are placed on output pin(s) of the action
 - Note: this requires the action to specify “isUnmarshall” to true

Event dispatching

- The event dispatching semantics is shared for all kind of behaviors
- Events are placed in the pool according to their order of arrival
- An event that is consumed cannot return in the pool
 - It is considered as lost
 - Exception for specific situation (e.g., deferred events for state-machines)
- Only one event is dispatched (i.e. consumed) at a time
 - This denotes the starting of Run-To-Completion step

Run to completion

- Starts with the consumption of an event
- If the event does not match any trigger the steps completes trivially
- If there is a matched trigger
 - The execution starts from the element to which the trigger is attached.
 - The execution flows propagates while it is possible to do so.
 - When the execution flow stops (e.g., unsatisfied dependencies in the context of an activity) the step completes.



Introduction

- What is the purpose of UML activities?
- The different usages of activities that are allowed by UML



Graph like structure and data flow semantics

- Data flow semantics
- Partial execution orders



Activities: syntax and semantics – nodes to coordinate the execution flow



Relation between this course and current research

- fUML
- ALF




Appendix: build a simple example and see how it executes

Initial Node

- Denotes the starting point of an activity
 - If it is not specified then all nodes in the activity that do not have incoming edges are started concurrently

Final Node

- Denotes the end point of an activity
 - When this node is reached then the containing activity terminates




Fork

- Denotes the beginning of multiple concurrent execution flows
 - Each outgoing edges of the fork fires concurrently
 - Each branch is executed in parallel with the other

Join

- Denotes the end multiple concurrent execution flows
 - To be traversed the join must receive a token from all of its incoming edges




Merge

- Merge multiple incoming flows into a single one
 - If a single incoming edge is traversed then the merge is traversed
 - The execution flow continues on the outgoing edge.

Decision

- Provide the possibility to route the execution flow on a specific path
 - The choice of a specific branch is based on the evaluation of the decision value against guard specifications placed on outgoing edges.
- Decision value can be
 - The values produced by the decision input behavior
 - The values arriving by the incoming object flow if there is no decision input behavior and no input flow.
 - The value arriving by the input flow if there is one but no decision input behavior.





Introduction

- What is the purpose of UML activities?
- The different usages of activities that are allowed by UML



Graph like structure and data flow semantics

- Data flow semantics
- Partial execution orders



Activities: syntax and semantics – going further




Relation between this course and current research

- fUML
- ALF



Appendix: build a simple example and see how it executes



Structured Activity Nodes

- **Conditional Node**
 - Provide a way to structure a sequence of alternatives
- **Loop Node**
 - Provide a way to structure a loop
- **ExpansionRegion**
 - Execute the same content with different semantics



Introduction

- What is the purpose of UML activities?
- The different usages of activities that are allowed by UML




Graph like structure and data flow semantics

- Data flow semantics
- Partial execution orders



Activities: syntax and semantics

- Input and output value, base actions, invocation actions
- Nodes to coordinate the execution flow
- Going further



Relation between this course and current research


- fUML
- ALF



Appendix: build a simple example and see how it executes


Foundational UML

- Formalizes the execution semantics of **Classes** and **Activities**
- Semantics is defined through a semantic model
 - A class model whose elements capture the intended behavior of syntactic elements (operational approach).
- Models built using **Classes + Activities** are executable
 - Let see a demo of the Papyrus model execution framework: Moka



Action Language for Foundational UML

- Textual surface notation to express executable models
 - Limited to the fUML scope
 - Evolutions: alignment with composite structures and state-machines
- Any model specified in Alf can be transformed into an fUML model
 - Any model specified with Alf is executable
 - The execution semantics is the one defined for fUML
- It makes a lot simpler the specification of detailed behaviors in UML



```
activity classifierBehavior(){
    this.tasks->iterate t (t.execute)
}
```

```
activity classifierBehavior(){
    for(task in this.tasks){
        task.execute();
    }
}
```

```
activity classifierBehavior(){
    let i: Integer = 1;
    while(i <= this.tasks->size()){
        this.tasks->at(i).execute();
        i++;
    }
}
```





Introduction

- What is the purpose of UML activities?
- The different usages of activities that are allowed by UML



Graph like structure and data flow semantics

- Data flow semantics
- Partial execution orders



Activities: syntax and semantics

- Input and output value, base actions, invocation actions
- Nodes to coordinate the execution flow
- Going further



Relation between this course and current research

- fUML
- ALF



Appendix: build a simple example and see how it executes

Point
<ul style="list-style-type: none"> - x : Real[1] - y : Real[1] - z : Real[1]
+ distance(p: Point[1]): Real[1]



Objective

- Implement the “distance” operation as an activity
- Syntax elements that need to be used
 - Read Self Action
 - Read Structural Feature Action
 - Call Behavior Action
 - Activity Parameter Node
 - Input Pin
 - Output Pin
 - Control Flow
 - Object Flow
 - Fork Node

