

Package ‘enrichplot’

October 12, 2024

Title Visualization of Functional Enrichment Result

Version 1.25.3

Description The 'enrichplot' package implements several visualization methods for interpreting functional enrichment results obtained from ORA or GSEA analysis. It is mainly designed to work with the 'clusterProfiler' package suite. All the visualization methods are developed based on 'ggplot2' graphics.

Depends R (>= 3.5.0)

Imports aplot (>= 0.2.1), DOSE (>= 3.31.2), ggfun (>= 0.1.3),
ggnewscale, ggplot2, ggraph, graphics, grid, igraph, methods,
plyr, purrr, RColorBrewer, reshape2, rlang, stats, utils,
scatterpie, shadowtext, GOSemSim, magrittr, ggtree, yulab.utils
(>= 0.1.6)

Suggests clusterProfiler, dplyr, europepmc, ggupset, knitr, rmarkdown,
org.Hs.eg.db, prettydoc, tibble, tidyr, ggforce, ggHoriPlot,
AnnotationDbi, ggplotify, ggridges, grDevices, gridExtra,
ggrepel (>= 0.9.0), ggstar, scales, ggtreeExtra, tidydr

Remotes YuLab-SMU/tidydr

VignetteBuilder knitr

License Artistic-2.0

URL <https://yulab-smu.top/biomedical-knowledge-mining-book/>

BugReports <https://github.com/GuangchuangYu/enrichplot/issues>

biocViews Annotation, GeneSetEnrichment, GO, KEGG, Pathways, Software,
Visualization

Encoding UTF-8

RoxygenNote 7.3.2

git_url <https://git.bioconductor.org/packages/enrichplot>

git_branch devel

git_last_commit 018cd2f

git_last_commit_date 2024-10-05

Repository Bioconductor 3.20

Date/Publication 2024-10-11

Author Guangchuang Yu [aut, cre] (<<https://orcid.org/0000-0002-6485-8781>>),
Chun-Hui Gao [ctb] (<<https://orcid.org/0000-0002-1445-7939>>)

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Contents

| | |
|--|-----------|
| enrichplot-package | 2 |
| autofacet | 3 |
| barplot.enrichResult | 3 |
| cnetplot | 4 |
| color_palette | 7 |
| dotplot | 8 |
| dotplot2 | 11 |
| drag_network | 12 |
| emapplot | 13 |
| emapplot_cluster | 18 |
| fortify.compareClusterResult | 18 |
| geom_gsea_gene | 19 |
| ggtable | 20 |
| goplot | 20 |
| gseadist | 22 |
| gseaplot | 22 |
| gseaplot2 | 24 |
| gsearank | 25 |
| gsInfo | 25 |
| heatplot | 26 |
| hplot | 27 |
| pairwise_termsim | 27 |
| plotting.clusterProfile | 29 |
| pmcplot | 30 |
| reexports | 30 |
| ridgeplot | 31 |
| set_enrichplot_color | 32 |
| ssplot | 33 |
| treeplot | 35 |
| upsetplot | 39 |
| volplot | 40 |
| Index | 43 |

| | |
|--------------------|--|
| enrichplot-package | <i>enrichplot: Visualization of Functional Enrichment Result</i> |
|--------------------|--|

Description

The 'enrichplot' package implements several visualization methods for interpreting functional enrichment results obtained from ORA or GSEA analysis. It is mainly designed to work with the 'clusterProfiler' package suite. All the visualization methods are developed based on 'ggplot2' graphics.

Author(s)

Maintainer: Guangchuang Yu <guangchuangyu@gmail.com> ([ORCID](#))

Other contributors:

- Chun-Hui Gao <gaospecial@gmail.com> ([ORCID](#)) [contributor]

See Also

Useful links:

- <https://yulab-smu.top/biomedical-knowledge-mining-book/>
- Report bugs at <https://github.com/GuangchuangYu/enrichplot/issues>

autofacet

automatically split barplot or dotplot into several facets

Description

automatically split barplot or dotplot into several facets

Usage

```
autofacet(by = "row", scales = "free", levels = NULL)
```

Arguments

| | |
|--------|--------------------------|
| by | one of 'row' or 'column' |
| scales | wether 'fixed' or 'free' |
| levels | set facet levels |

Value

a ggplot object

barplot.enrichResult *barplot*

Description

barplot of enrichResult

Usage

```
## S3 method for class 'enrichResult'
barplot(
  height,
  x = "Count",
  color = "p.adjust",
  showCategory = 8,
  font.size = 12,
  title = "",
  label_format = 30,
  ...
)
```

Arguments

| | |
|--------------|---|
| height | enrichResult object |
| x | one of 'Count' and 'GeneRatio' |
| color | one of 'pvalue', 'p.adjust' and 'qvalue' |
| showCategory | number of categories to show |
| font.size | font size |
| title | plot title |
| label_format | a numeric value sets wrap length, alternatively a custom function to format axis labels. by default wraps names longer than 30 characters |
| ... | other parameter, ignored |

Value

ggplot object

Examples

```
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
barplot(x)
# use `showCategory` to select the displayed terms. It can be a number or a vector of terms.
barplot(x, showCategory = 10)
categorys <- c("urinary bladder cancer", "bronchiolitis obliterans",
               "aortic aneurysm", "esophageal cancer")
barplot(x, showCategory = categorys)
```

cnetplot

cnetplot

Description

Gene-Concept Network

Usage

```
cnetplot(x, ...)

## S4 method for signature 'enrichResult'
cnetplot(x, ...)

## S4 method for signature 'list'
cnetplot(x, ...)

## S4 method for signature 'gseaResult'
cnetplot(x, ...)

## S4 method for signature 'compareClusterResult'
```

```

cnetplot(x, ...)

cnetplot.enrichResult(
  x,
  showCategory = 5,
  foldChange = NULL,
  layout = "kk",
  colorEdge = FALSE,
  circular = FALSE,
  node_label = "all",
  cex_category = 1,
  cex_gene = 1,
  cex_label_category = 1,
  cex_label_gene = 1,
  color_category = "#E5C494",
  color_gene = "#B3B3B3",
  shadowtext = "all",
  color.params = list(foldChange = NULL, edge = FALSE, category = "#E5C494", gene =
    "#B3B3B3"),
  cex.params = list(category_node = 1, gene_node = 1, category_label = 1, gene_label = 1),
  hilight.params = list(category = NULL, alpha_hilight = 1, alpha_no_hilight = 0.3),
  ...
)

```

Arguments

| | |
|--------------------|--|
| x | Enrichment result. |
| ... | Additional parameters |
| showCategory | A number or a vector of terms. If it is a number, the first n terms will be displayed. If it is a vector of terms, the selected terms will be displayed. |
| foldChange | Fold Change of nodes, the default value is NULL. If the user provides the Fold Change value of the nodes, it can be used to set the color of the gene node. Will be removed in the next version. |
| layout | Layout of the map, e.g. 'star', 'circle', 'gem', 'dh', 'graphopt', 'grid', 'mds', 'randomly', 'fr', 'kk', 'drl' or 'lgl'. |
| colorEdge | Logical, whether coloring edge by enriched terms, the default value is FALSE. Will be removed in the next version. |
| circular | Logical, whether using circular layout, the default value is FALSE. Will be removed in the next version. |
| node_label | Select which labels to be displayed. one of 'category', 'gene', 'all'(the default) and 'none'. |
| cex_category | Number indicating the amount by which plotting category nodes should be scaled relative to the default, the default value is 1. Will be removed in the next version. |
| cex_gene | Number indicating the amount by which plotting gene nodes should be scaled relative to the default, the default value is 1. Will be removed in the next version. |
| cex_label_category | Scale of category node label size, the default value is 1. Will be removed in the next version. |

| | |
|-----------------------------|---|
| <code>cex_label_gene</code> | Scale of gene node label size, the default value is 1. Will be removed in the next version. |
| <code>color_category</code> | Color of category node. Will be removed in the next version. |
| <code>color_gene</code> | Color of gene node. Will be removed in the next version. |
| <code>shadowtext</code> | select which node labels to use shadow font, one of 'category', 'gene', 'all' and 'none', default is 'all'. |
| <code>color.params</code> | list, the parameters to control the attributes of highlighted nodes and edges. see the <code>color.params</code> in the following. <code>color.params</code> control the attributes of highlight, it can be referred to the following parameters: <ul style="list-style-type: none"> • <code>foldChange</code> Fold Change of nodes for <code>enrichResult</code>, or size of nodes for <code>compareClusterResult</code>, the default value is <code>NULL</code>. • <code>edge</code> Logical, whether coloring edge by enriched terms, the default value is <code>FALSE</code>. • <code>category</code> Color of category node. • <code>gene</code> Color of gene node. |
| <code>cex.params</code> | list, the parameters to control the size of nodes and lables. see the <code>cex.params</code> in the following. <code>cex.params</code> control the attributes of highlight, it can be referred to the following parameters: <ul style="list-style-type: none"> • <code>foldChange</code> only used in <code>compareClusterResult</code> object, fold Change of nodes, the default value is <code>NULL</code>. If the user provides the Fold Change value of the nodes, it can be used to set the size of the gene node. • <code>category_node</code> Number indicating the amount by which plotting category nodes should be scaled relative to the default, the default value is 1. • <code>gene_node</code> Number indicating the amount by which plotting gene nodes should be scaled relative to the default, the default value is 1. • <code>category_label</code> Scale of category node label size, the default value is 1. • <code>gene_label</code> Scale of gene node label size, the default value is 1. |
| <code>hilight.params</code> | list, the parameters to control the attributes of highlighted nodes and edges. see the <code>hilight.params</code> in the following. <code>hilight.params</code> control the attributes of highlight, it can be referred to the following parameters: <ul style="list-style-type: none"> • <code>category</code> category nodes to be highlight. • <code>alpha_hilight</code> alpha of highlighted nodes. • <code>alpha_no_hilight</code> alpha of unhighlighted nodes. |

Details

plot linkages of genes and enriched concepts (e.g. GO categories, KEGG pathways)

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
## Not run:
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
x2 <- pairwise_termsim(x)
cnetplot(x2)
# use `layout` to change the layout of map
cnetplot(x2, layout = "star")
# use `showCategory` to select the displayed terms. It can be a number of a vector of terms.
cnetplot(x2, showCategory = 10)
categorys <- c("pre-malignant neoplasm", "intestinal disease",
               "breast ductal carcinoma", "non-small cell lung carcinoma")
cnetplot(x2, showCategory = categorys)
# 'compareClusterResult' object is also supported.
library(clusterProfiler)
library(DOSE)
library(org.Hs.eg.db)
data(gcSample)
xx <- compareCluster(gcSample, fun="enrichGO", OrgDb="org.Hs.eg.db")
xx2 <- pairwise_termsim(xx)
cnetplot(xx2)

## End(Not run)
```

color_palette

*color_palette***Description**

create color palette for continuous data

Usage

```
color_palette(colors)
```

Arguments

colors colors of length ≥ 2

Value

color vector

Author(s)

guangchuang yu

Examples

```
color_palette(c("red", "yellow", "green"))
```

`dotplot`*dotplot*

Description

dotplot for enrichment result

Usage

```
dotplot(object, ...)
```

```
## S4 method for signature 'enrichResult'
```

```
dotplot(  
  object,  
  x = "GeneRatio",  
  color = "p.adjust",  
  showCategory = 10,  
  size = NULL,  
  split = NULL,  
  font.size = 12,  
  title = "",  
  orderBy = "x",  
  label_format = 30,  
  ...  
)
```

```
## S4 method for signature 'gseaResult'
```

```
dotplot(  
  object,  
  x = "GeneRatio",  
  color = "p.adjust",  
  showCategory = 10,  
  size = NULL,  
  split = NULL,  
  font.size = 12,  
  title = "",  
  orderBy = "x",  
  label_format = 30,  
  ...  
)
```

```
## S4 method for signature 'compareClusterResult'
```

```
dotplot(  
  object,  
  x = "Cluster",  
  color = "p.adjust",  
  showCategory = 5,  
  split = NULL,  
  font.size = 12,  
  title = "",  
  by = "geneRatio",
```



```
    size = NULL,
    includeAll = TRUE,
    label_format = 30,
    ...
)

## S4 method for signature 'enrichResultList'
dotplot(
  object,
  x = "GeneRatio",
  color = "p.adjust",
  showCategory = 10,
  size = NULL,
  split = NULL,
  font.size = 12,
  title = "",
  orderBy = "x",
  label_format = 30,
  ...
)

## S4 method for signature 'gseaResultList'
dotplot(
  object,
  x = "GeneRatio",
  color = "p.adjust",
  showCategory = 10,
  size = NULL,
  split = NULL,
  font.size = 12,
  title = "",
  orderBy = "x",
  label_format = 30,
  ...
)

dotplot.enrichResult(
  object,
  x = "geneRatio",
  color = "p.adjust",
  showCategory = 10,
  size = NULL,
  split = NULL,
  font.size = 12,
  title = "",
  orderBy = "x",
  label_format = 30,
  decreasing = TRUE
)

dotplot.compareClusterResult(
  object,
```

```

x = "Cluster",
colorBy = "p.adjust",
showCategory = 5,
by = "geneRatio",
size = "geneRatio",
split = NULL,
includeAll = TRUE,
font.size = 12,
title = "",
label_format = 30,
group = FALSE,
shape = FALSE,
facet = NULL,
strip_width = 15
)

```

Arguments

| | |
|--------------|--|
| object | compareClusterResult object |
| ... | additional parameters |
| x | variable for x-axis, one of 'GeneRatio' and 'Count' |
| color | variable that used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue' |
| showCategory | A number or a list of terms. If it is a number, the first n terms will be displayed. If it is a list of terms, the selected terms will be displayed. |
| size | variable that used to scale the sizes of categories, one of "geneRatio", "Percentage" and "count" |
| split | apply 'showCategory' to each category specified by the 'split', e.g., "ONTOLOGY", "category" and "intersect". Default is NULL and do nothing |
| font.size | font size |
| title | figure title |
| orderBy | The order of the Y-axis |
| label_format | a numeric value sets wrap length, alternatively a custom function to format axis labels. by default wraps names longer than 30 characters |
| by | one of "geneRatio", "Percentage" and "count" |
| includeAll | logical |
| decreasing | logical. Should the orderBy order be increasing or decreasing? |
| colorBy | variable that used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue' |
| group | a logical value, whether to connect the nodes of the same group with wires. |
| shape | a logical value, whether to use nodes of different shapes to distinguish the group it belongs to |
| facet | apply 'facet_grid' to the plot by specified variable, e.g., "ONTOLOGY", "category" and "intersect". |
| strip_width | width of strip text, a.k.a facet label. |

Value

plot

Author(s)

Guangchuang Yu

Examples

```
## Not run:
  library(DOSE)
  data(geneList)
  de <- names(geneList)[1:100]
  x <- enrichDO(de)
  dotplot(x)
# use `showCategory` to select the displayed terms. It can be a number or a vector of terms.
dotplot(x, showCategory = 10)
categorys <- c("pre-malignant neoplasm", "intestinal disease",
               "breast ductal carcinoma", "non-small cell lung carcinoma")
dotplot(x, showCategory = categorys)
# It can also graph compareClusterResult
data(gcSample)
library(clusterProfiler)
library(DOSE)
library(org.Hs.eg.db)
data(gcSample)
xx <- compareCluster(gcSample, fun="enrichGO", OrgDb="org.Hs.eg.db")
xx2 <- pairwise_termsim(xx)
library(ggstar)
dotplot(xx2)
dotplot(xx2, shape = TRUE)
dotplot(xx2, group = TRUE)
dotplot(xx2, x = "GeneRatio", group = TRUE, size = "count")

## End(Not run)
```

dotplot2

*dotplot2***Description**

compare two clusters in the compareClusterResult object

Usage

```
dotplot2(object, x = "FoldEnrichment", vars = NULL, label = "auto", ...)
```

Arguments

| | |
|--------|---|
| object | a compareClusterResult object |
| x | selected variable to visualize in x-axis |
| vars | selected Clusters to be compared, only length of two is supported |
| label | to label the Clusters in the plot, should be a named vector |
| ... | additional parameters passed to dotplot |

Value

a ggplot object

Author(s)

Guangchuang Yu

| | |
|--------------|--|
| drag_network | <i>Drag the nodes of a network to update the layout of the network</i> |
|--------------|--|

Description

Drag the nodes of a network to update the layout of the network

Usage

```
drag_network(p, g = NULL)
```

Arguments

p the network diagram as a ggplot/gg/ggraph object.

g an corresponding igraph object. Default is to extract from the 'ggraph' attribute.

Value

an updated ggplot/gg/ggraph object

Examples

```
## Not run:
library(igraph)
library(ggraph)

flow_info <- data.frame(from = c(1,2,3,3,4,5,6),
                        to = c(5,5,5,6,7,6,7))
g = graph_from_data_frame(flow_info)
p <- ggraph(g, layout='nicely') + geom_node_point() + geom_edge_link()
pp <- drag_network(p)

## End(Not run)
```

emapplot

*emapplot***Description**

Enrichment Map for enrichment result of over-representation test or gene set enrichment analysis

Usage

```
emapplot(x, ...)

## S4 method for signature 'enrichResult'
emapplot(x, showCategory = 30, ...)

## S4 method for signature 'gseaResult'
emapplot(x, showCategory = 30, ...)

## S4 method for signature 'compareClusterResult'
emapplot(x, showCategory = 30, ...)

emapplot.enrichResult(
  x,
  showCategory = 30,
  layout = NULL,
  coords = NULL,
  color = "p.adjust",
  min_edge = 0.2,
  cex_label_category = 1,
  cex_category = 1,
  cex_line = 1,
  shadowtext = TRUE,
  label_style = "shadowtext",
  repel = FALSE,
  node_label = "category",
  with_edge = TRUE,
  group_category = FALSE,
  group_legend = FALSE,
  cex_label_group = 1,
  nWords = 4,
  label_format = 30,
  clusterFunction = stats::kmeans,
  nCluster = NULL,
  layout.params = list(layout = NULL, coords = NULL),
  edge.params = list(show = TRUE, min = 0.2),
  cex.params = list(category_node = 1, category_label = 1, line = 1),
  hilight.params = list(category = NULL, alpha_hilight = 1, alpha_no_hilight = 0.3),
  cluster.params = list(cluster = FALSE, method = stats::kmeans, n = NULL, legend =
    FALSE, label_style = "shadowtext", label_words_n = 4, label_format = 30),
  ...
)
```

```
emapplot.compareClusterResult(
  x,
  showCategory = 30,
  layout = NULL,
  coords = NULL,
  split = NULL,
  pie = "equal",
  legend_n = 5,
  cex_category = 1,
  cex_line = 1,
  min_edge = 0.2,
  cex_label_category = 1,
  shadowtext = TRUE,
  with_edge = TRUE,
  group_category = FALSE,
  label_format = 30,
  group_legend = FALSE,
  node_label = "category",
  label_style = "shadowtext",
  repel = FALSE,
  cex_label_group = 1,
  nWords = 4,
  clusterFunction = stats::kmeans,
  nCluster = NULL,
  cex_pie2axis = 1,
  pie.params = list(pie = "equal", legend_n = 5),
  layout.params = list(layout = NULL, coords = NULL),
  edge.params = list(show = TRUE, min = 0.2),
  cluster.params = list(cluster = FALSE, method = stats::kmeans, n = NULL, legend =
    FALSE, label_style = "shadowtext", label_words_n = 4, label_format = 30),
  cex.params = list(category_node = 1, category_label = 1, line = 1, pie2axis = 1,
    label_group = 1),
  highlight.params = list(category = NULL, alpha_highlight = 1, alpha_no_highlight = 0.3),
  ...
)
```

Arguments

- | | |
|-----|-----------------------|
| x | Enrichment result. |
| ... | additional parameters |
- additional parameters can refer the following parameters.
- force Force of repulsion between overlapping text labels. Defaults to 1.
 - nudge_x, nudge_y Horizontal and vertical adjustments to nudge the starting position of each text label.
 - direction "both", "x", or "y" – direction in which to adjust position of labels.
 - ellipse_style style of ellipse, one of "ggforce" an "polygon".
 - ellipse_pro numeric indicating confidence value for the ellipses, it can be used only when ellipse_style = "polygon".
 - alpha the transparency of ellipse fill.

| | |
|--------------------|---|
| | <ul style="list-style-type: none"> • type The type of ellipse. The default "t" assumes a multivariate t-distribution, and "norm" assumes a multivariate normal distribution. "euclid" draws a circle with the radius equal to level, representing the euclidean distance from the center. |
| showCategory | A number or a vector of terms. If it is a number, the first n terms will be displayed. If it is a vector of terms, the selected terms will be displayed. |
| layout | Layout of the map, e.g. 'star', 'circle', 'gem', 'dh', 'graphopt', 'grid', 'mds', 'randomly', 'fr', 'kk', 'drl' or 'lgl'. Will be removed in the next version. Will be removed in the next version. |
| coords | a data.frame with two columns: 'x' for X-axis coordinate and 'y' for Y-axis coordinate. Will be removed in the next version. |
| color | Variable that used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue'. |
| min_edge | The minimum similarity threshold for whether two nodes are connected, should between 0 and 1, default value is 0.2. Will be removed in the next version. |
| cex_label_category | Scale of category node label size. Will be removed in the next version. |
| cex_category | Number indicating the amount by which plotting category nodes should be scaled relative to the default. Will be removed in the next version. |
| cex_line | Scale of line width. Will be removed in the next version. |
| shadowtext | a logical value, whether to use shadow font. |
| label_style | style of group label, one of "shadowtext" and "ggforce". Will be removed in the next version. |
| repel | whether to correct the position of the label. Defaults to FALSE. |
| node_label | Select which labels to be displayed, one of 'category', 'group', 'all' and 'none'. |
| with_edge | Logical, if TRUE, draw the edges of the network diagram. Will be removed in the next version. |
| group_category | a logical, if TRUE, group the category. Will be removed in the next version. |
| group_legend | Logical, if TRUE, the grouping legend will be displayed. The default is FALSE. Will be removed in the next version. |
| cex_label_group | Numeric, scale of group labels size, the default value is 1. Will be removed in the next version. |
| nWords | Numeric, the number of words in the cluster tags, the default value is 4. Will be removed in the next version. |
| label_format | a numeric value sets wrap length, alternatively a custom function to format axis labels. Will be removed in the next version. |
| clusterFunction | function of Clustering method, such as stats::kmeans(the default), cluster::clara, cluster::fanny or cluster::pam. Will be removed in the next version. |
| nCluster | Numeric, the number of clusters, the default value is square root of the number of nodes. Will be removed in the next version. |
| layout.params | list, the parameters to control the layout. see the layout.params in the following. layout.params control the attributes of layout, it can be referred to the following parameters: <ul style="list-style-type: none"> • layout Layout of the map, e.g. 'star', 'circle', 'gem', 'dh', 'graphopt', 'grid', 'mds', 'randomly', 'fr', 'kk', 'drl' or 'lgl'.. |

| | |
|-------------------------------|---|
| | <ul style="list-style-type: none"> • <code>coords</code> a data.frame with two columns: 'x' for X-axis coordinate and 'y' for Y-axis coordinate. |
| <code>edge.params</code> | <p>list, the parameters to control the edge. see the <code>edge.params</code> in the following. <code>edge.params</code> control the attributes of edge, it can be referred to the following parameters:</p> <ul style="list-style-type: none"> • <code>show</code> Logical, if TRUE (the default), draw the edges of the network diagram. • <code>min</code> The minimum similarity threshold for whether two nodes are connected, should between 0 and 1, default value is 0.2. |
| <code>cex.params</code> | <p>list, the parameters to control the edge. see the <code>cex.params</code> in the following. <code>cex.params</code> control the attributes of edge, it can be referred to the following parameters:</p> <ul style="list-style-type: none"> • <code>category_node</code> Number indicating the amount by which plotting category nodes should be scaled relative to the default. • <code>category_label</code> Scale of category node label size. • <code>line</code> Scale of line width. • <code>pie2axis</code> It is used to adjust the relative size of the pie chart on the coordinate axis, the default value is 1. • <code>label_group</code> Numeric, scale of group labels size, the default value is 1. |
| <code>highlight.params</code> | <p>list, the parameters to control the attributes of highlighted nodes and edges. see the <code>highlight.params</code> in the following. <code>highlight.params</code> control the attributes of highlight, it can be referred to the following parameters:</p> <ul style="list-style-type: none"> • <code>category</code> category nodes to be highlight. • <code>alpha_highlight</code> alpha of highlighted nodes. • <code>alpha_no_highlight</code> alpha of unhighlighted nodes. |
| <code>cluster.params</code> | <p>list, the parameters to control the attributes of highlighted nodes and edges. see the <code>cluster.params</code> in the following. <code>cluster.params</code> control the attributes of highlight, it can be referred to the following parameters:</p> <ul style="list-style-type: none"> • <code>cluster</code> a logical, if TRUE, group the category. • <code>method</code> function of Clustering method, such as <code>stats::kmeans</code> (the default), <code>cluster::clara</code>, <code>cluster::fanny</code> or <code>cluster::pam</code>. • <code>n</code> Numeric, the number of clusters, the default value is square root of the number of nodes. • <code>legend</code> Logical, if TRUE, the grouping legend will be displayed. The default is FALSE. • <code>label_style</code> style of group label, one of "shadowtext" and "ggforce". • <code>label_words_n</code> Numeric, the number of words in the cluster tags, the default value is 4. • <code>label_format</code> a numeric value sets wrap length, alternatively a custom function to format axis labels. |
| <code>split</code> | separate result by 'category' variable |
| <code>pie</code> | proportion of clusters in the pie chart, one of 'equal' (default) and 'Count' Will be removed in the next version. |
| <code>legend_n</code> | number of circle in legend Will be removed in the next version. |
| <code>cex_pie2axis</code> | It is used to adjust the relative size of the pie chart on the coordinate axis, the default value is 1. Will be removed in the next version. |

pie.params list, the parameters to control the attributes of pie nodes. see the pie.params in the following. pie.params control the attributes of pie nodes, it can be referred to the following parameters:

- pie proportion of clusters in the pie chart, one of 'equal' (default) and 'Count'.
- legend_n number of circle in legend.

Details

This function visualizes gene sets as a network (i.e. enrichment map). Mutually overlapping gene sets tend to cluster together, making it easier for interpretation. When the similarity between terms meets a certain threshold (default is 0.2, adjusted by parameter 'min_edge'), there will be edges between terms. The stronger the similarity, the shorter and thicker the edges. The similarity between terms is obtained by function 'pairwise_termsim', the details of similarity calculation can be found in its documentation: [pairwise_termsim](#).

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
## Not run:
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
x2 <- pairwise_termsim(x)
emapplot(x2)
# use `layout` to change the layout of map
emapplot(x2, layout = "star")
# use `showCategory` to select the displayed terms. It can be a number of a vector of terms.
emapplot(x2, showCategory = 10)
categorys <- c("pre-malignant neoplasm", "intestinal disease",
               "breast ductal carcinoma")
emapplot(x2, showCategory = categorys)

# It can also graph compareClusterResult
library(clusterProfiler)
library(DOSE)
library(org.Hs.eg.db)
data(gcSample)
xx <- compareCluster(gcSample, fun="enrichGO", OrgDb="org.Hs.eg.db")
xx2 <- pairwise_termsim(xx)
emapplot(xx2)

## End(Not run)
```

| | |
|------------------|--|
| emapplot_cluster | <i>Functional grouping network diagram for enrichment result of over-representation test or gene set enrichment analysis</i> |
|------------------|--|

Description

This function has been replaced by ‘emapplot’.

Usage

```
emapplot_cluster(x, ...)
```

Arguments

| | |
|-----|--|
| x | enrichment result |
| ... | additional parameters. Please refer to: emapplot . |

Value

ggplot2 object

| |
|------------------------------|
| fortify.compareClusterResult |
| <i>fortify</i> |

Description

convert compareClusterResult to a data.frame that ready for plot
 convert enrichResult object for ggplot2

Usage

```
## S3 method for class 'compareClusterResult'
fortify(
  model,
  data,
  showCategory = 5,
  by = "geneRatio",
  split = NULL,
  includeAll = TRUE,
  ...
)

## S3 method for class 'enrichResult'
fortify(
  model,
  data,
  showCategory = 5,
  by = "Count",
```

```
    order = FALSE,
    drop = FALSE,
    split = NULL,
    ...
  )
```

Arguments

| | |
|--------------|---|
| model | 'enrichResult' or 'compareClusterResult' object |
| data | not use here |
| showCategory | Category numbers to show |
| by | one of Count and GeneRatio |
| split | separate result by 'split' variable |
| includeAll | logical |
| ... | additional parameter |
| order | logical |
| drop | logical |

Value

data.frame
data.frame

Author(s)

Guangchuang Yu

| | |
|----------------|-----------------------|
| geom_gsea_gene | <i>geom_gsea_gene</i> |
|----------------|-----------------------|

Description

label genes in running score plot

Usage

```
geom_gsea_gene(  
  genes,  
  mapping = NULL,  
  geom = ggplot2::geom_text,  
  ...,  
  geneSet = NULL  
)
```

Arguments

| | |
|---------|--|
| genes | selected genes to be labeled |
| mapping | aesthetic mapping, default is NULL |
| geom | geometric layer to plot the gene labels, default is geom_text |
| ... | additional parameters passed to the 'geom' |
| geneSet | choose which gene set(s) to be label if the plot contains multiple gene sets |

Value

ggplot object

Author(s)

Guangchuang Yu

| | |
|---------|----------------|
| ggtable | <i>ggtable</i> |
|---------|----------------|

Description

plot table

Usage

```
ggtable(d, p = NULL)
```

Arguments

- d data frame
- p ggplot object to extract color to color rownames(d), optional

Value

ggplot object

Author(s)

guangchuang yu

| | |
|--------|---------------|
| goplot | <i>goplot</i> |
|--------|---------------|

Description

plot induced GO DAG of significant terms

Usage

```
goplot(  
  x,  
  showCategory = 10,  
  color = "p.adjust",  
  layout = "sugiyama",  
  geom = "text",  
  ...  
)
```

```
## S4 method for signature 'enrichResult'
goplot(
  x,
  showCategory = 10,
  color = "p.adjust",
  layout = "sugiyama",
  geom = "text",
  ...
)

## S4 method for signature 'gseaResult'
goplot(
  x,
  showCategory = 10,
  color = "p.adjust",
  layout = "sugiyama",
  geom = "text",
  ...
)

goplot.enrichResult(
  x,
  showCategory = 10,
  color = "p.adjust",
  layout = "sugiyama",
  geom = "text",
  ...
)
```

Arguments

| | |
|--------------|---|
| x | enrichment result. |
| showCategory | number of enriched terms to display |
| color | variable that used to color enriched terms, e.g. pvalue, p.adjust or qvalue |
| layout | layout of the map |
| geom | label geom, one of 'label' or 'text' |
| ... | additional parameter |

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
## Not run:
library(clusterProfiler)
data(geneList, package = "DOSE")
de <- names(geneList)[1:100]
```

```
yy <- enrichGO(de, 'org.Hs.eg.db', ont="BP", pvalueCutoff=0.01)
goplot(yy)
goplot(yy, showCategory = 5)

## End(Not run)
```

| | |
|-----------------------|-----------------|
| <code>gseadist</code> | <i>gseadist</i> |
|-----------------------|-----------------|

Description

plot logFC distribution of selected gene sets

Usage

```
gseadist(x, IDs, type = "density")
```

Arguments

| | |
|-------------------|-------------------------------|
| <code>x</code> | GSEA result |
| <code>IDs</code> | gene set IDs |
| <code>type</code> | one of 'density' or 'boxplot' |

Value

distribution plot

Author(s)

Guangchuang Yu

| | |
|-----------------------|-----------------|
| <code>gseaplot</code> | <i>gseaplot</i> |
|-----------------------|-----------------|

Description

visualize analyzing result of GSEA

Usage

```
gseaplot(x, geneSetID, by = "all", title = "", ...)
```

S4 method for signature 'gseaResult'

```
gseaplot(
  x,
  geneSetID,
  by = "all",
  title = "",
  color = "black",
  color.line = "green",
```

```

    color.vline = "#FA5860",
    ...
)

gseaplot.gseaResult(
  x,
  geneSetID,
  by = "all",
  title = "",
  color = "black",
  color.line = "green",
  color.vline = "#FA5860",
  ...
)
```

Arguments

| | |
|-------------|--|
| x | object of gsea result |
| geneSetID | geneSet ID |
| by | one of "runningScore" or "position" |
| title | plot title |
| ... | additional parameters |
| color | color of line segments |
| color.line | color of running enrichment score line |
| color.vline | color of vertical line which indicating the maximum/minimal running enrichment score |

Details

plotting function for gseaResult

Value

ggplot2 object

ggplot2 object

Author(s)

Guangchuang Yu

Examples

```

library(DOSE)
data(geneList)
x <- gseDO(geneList)
gseaplot(x, geneSetID=1)
```

`gseaplot2`*gseaplot2*

Description

GSEA plot that mimic the plot generated by broad institute's GSEA software

Usage

```
gseaplot2(  
  x,  
  geneSetID,  
  title = "",  
  color = "green",  
  base_size = 11,  
  rel_heights = c(1.5, 0.5, 1),  
  subplots = 1:3,  
  pvalue_table = FALSE,  
  ES_geom = "line"  
)
```

Arguments

| | |
|---------------------------|--|
| <code>x</code> | <code>gseaResult</code> object |
| <code>geneSetID</code> | gene set ID |
| <code>title</code> | plot title |
| <code>color</code> | color of running enrichment score line |
| <code>base_size</code> | base font size |
| <code>rel_heights</code> | relative heights of subplots |
| <code>subplots</code> | which subplots to be displayed |
| <code>pvalue_table</code> | whether add pvalue table |
| <code>ES_geom</code> | geom for plotting running enrichment score, one of 'line' or 'dot' |

Value

plot

Author(s)

Guangchuang Yu

`gsearank`*gsearank*

Description

plot ranked list of genes with running enrichment score as bar height

Usage

```
gsearank(x, geneSetID, title = "", output = "plot")
```

Arguments

| | |
|------------------------|---|
| <code>x</code> | <code>gseaResult</code> object |
| <code>geneSetID</code> | gene set ID |
| <code>title</code> | plot title |
| <code>output</code> | one of 'plot' or 'table' (for exporting data) |

Value

ggplot object

Author(s)

Guangchuang Yu

`gsInfo`*gsInfo*

Description

extract gsea result of selected geneSet

Usage

```
gsInfo(object, geneSetID)
```

Arguments

| | |
|------------------------|--------------------------------|
| <code>object</code> | <code>gseaResult</code> object |
| <code>geneSetID</code> | gene set ID |

Value

data.frame

Author(s)

Guangchuang Yu

heatplot

heatplot

Description

heatmap like plot for functional classification

Usage

```
heatplot(x, showCategory = 30, ...)

## S4 method for signature 'enrichResult'
heatplot(x, showCategory = 30, ...)

## S4 method for signature 'gseaResult'
heatplot(x, showCategory = 30, ...)

heatplot.enrichResult(
  x,
  showCategory = 30,
  symbol = "rect",
  foldChange = NULL,
  pvalue = NULL,
  label_format = 30
)
```

Arguments

| | |
|--------------|--|
| x | enrichment result. |
| showCategory | number of enriched terms to display |
| ... | Additional parameters |
| symbol | symbol of the nodes, one of "rect"(the default) and "dot" by default wraps names longer than 30 characters |
| foldChange | fold Change. |
| pvalue | pvalue of genes |
| label_format | a numeric value sets wrap length, alternatively a custom function to format axis labels. |

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
heatplot(x)
```

hplot

*hplot***Description**

Horizontal plot for GSEA result

Usage

```
hplot(x, geneSetID)
```

Arguments

| | |
|-----------|-------------------|
| x | gseaResult object |
| geneSetID | gene set ID |

Value

horizontal plot

Author(s)

Guangchuang Yu

pairwise_termsim

*pairwise_termsim***Description**

Get the similarity matrix

Usage

```
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = 200)

## S4 method for signature 'enrichResult'
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = 200)

## S4 method for signature 'gseaResult'
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = 200)

## S4 method for signature 'compareClusterResult'
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = 200)
```

```

pairwise_termsim.enrichResult(
  x,
  method = "JC",
  semData = NULL,
  showCategory = 200
)

pairwise_termsim.compareClusterResult(
  x,
  method = "JC",
  semData = NULL,
  showCategory = 200
)

```

Arguments

| | |
|--------------|--|
| x | enrichment result. |
| method | method of calculating the similarity between nodes, one of "Resnik", "Lin", "Rel", "Jiang", "Wang" and "JC"(Jaccard similarity coefficient) methods. |
| semData | GOSemSimDATA object, can be obtained through godata function in GOSemSim package. |
| showCategory | number of enriched terms to display, default value is 200. |

Details

This function add similarity matrix to the termsim slot of enrichment result. Users can use the 'method' parameter to select the method of calculating similarity. The Jaccard correlation coefficient(JC) is used by default, and it applies to all situations. When users want to calculate the correlation between GO terms or DO terms, they can also choose "Resnik", "Lin", "Rel" or "Jiang" (they are semantic similarity calculation methods from GOSemSim packages), and at this time, the user needs to provide 'semData' parameter, which can be obtained through [godata](#) function in GOSemSim package.

Examples

```

## Not run:
library(clusterProfiler)
library(org.Hs.eg.db)
library(enrichplot)
library(GOSemSim)
library(DOSE)
data(geneList)
gene <- names(geneList)[abs(geneList) > 2]
ego <- enrichGO(gene = gene,
  universe      = names(geneList),
  OrgDb         = org.Hs.eg.db,
  ont           = "BP",
  pAdjustMethod = "BH",
  pvalueCutoff  = 0.01,
  qvalueCutoff  = 0.05,
  readable      = TRUE)
d <- godata('org.Hs.eg.db', ont="BP")
ego2 <- pairwise_termsim(ego, method="Wang", semData = d)

```

```

    emapplot(ego2)
    emapplot_cluster(ego2)

## End(Not run)

```

```

plotting.clusterProfile
      plotting-clusterProfile

```

Description

Internal plot function for plotting compareClusterResult

Usage

```

plotting.clusterProfile(
  clProf.reshape.df,
  x = ~Cluster,
  type = "dot",
  colorBy = "p.adjust",
  by = "geneRatio",
  title = "",
  font.size = 12
)

```

Arguments

| | |
|-------------------|-------------------------------------|
| clProf.reshape.df | data frame of compareCluster result |
| x | x variable |
| type | one of dot and bar |
| colorBy | one of pvalue or p.adjust |
| by | one of percentage and count |
| title | graph title |
| font.size | graph font size |

Value

ggplot object

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

| | |
|---------|----------------|
| pmcplot | <i>pmcplot</i> |
|---------|----------------|

Description

PubMed Central Trend plot

Usage

```
pmcplot(query, period, proportion = TRUE)
```

Arguments

| | |
|------------|--|
| query | query terms |
| period | period of query in the unit of year |
| proportion | If TRUE, use query_hits/all_hits, otherwise use query_hits |

Value

ggplot object

Author(s)

guangchuang yu

| | |
|-----------|---|
| reexports | <i>Objects exported from other packages</i> |
|-----------|---|

Description

These objects are imported from other packages. Follow the links below to see their documentation.

aplot [plot_list](#)

ggplot2 [facet_grid](#), [ggtitle](#)

ridgeplot

ridgeplot

Description

ridgeline plot for GSEA result

Usage

```
ridgeplot(
  x,
  showCategory = 30,
  fill = "p.adjust",
  core_enrichment = TRUE,
  label_format = 30,
  ...
)

## S4 method for signature 'gseaResult'
ridgeplot(
  x,
  showCategory = 30,
  fill = "p.adjust",
  core_enrichment = TRUE,
  label_format = 30,
  ...
)

ridgeplot.gseaResult(
  x,
  showCategory = 30,
  fill = "p.adjust",
  core_enrichment = TRUE,
  label_format = 30,
  orderBy = "NES",
  decreasing = FALSE
)
```

Arguments

| | |
|-----------------|--|
| x | gseaResult object |
| showCategory | A number or a vector of terms. If it is a number, the first n terms will be displayed. If it is a vector of terms, the selected terms will be displayed. |
| fill | one of "pvalue", "p.adjust", "qvalue" |
| core_enrichment | whether only using core_enriched genes |
| label_format | a numeric value sets wrap length, alternatively a custom function to format axis labels. |
| ... | additional parameters by default wraps names longer than 30 characters |

| | |
|------------|--|
| orderBy | The order of the Y-axis |
| decreasing | logical. Should the orderBy order be increasing or decreasing? |

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
library(DOSE)
data(geneList)
x <- gseDO(geneList)
ridgeplot(x)
```

```
set_enrichplot_color  set_enrichplot_color
```

Description

helper function to set color for enrichplot

Usage

```
set_enrichplot_color(
  colors = get_enrichplot_color(2),
  type = "color",
  name = NULL,
  .fun = NULL,
  reverse = TRUE,
  ...
)
```

Arguments

| | |
|---------|--|
| colors | user provided color vector |
| type | one of 'color', 'colour' or 'fill' |
| name | name of the color legend |
| .fun | force to use user provided color scale function |
| reverse | whether reverse the color scheme, default is TRUE as it is more significant for lower pvalue |
| ... | additional parameter that passed to the color scale function |

Value

a color scale

| | |
|--------|---------------|
| ssplot | <i>ssplot</i> |
|--------|---------------|

Description

Similarity space plot of enrichment analysis results.

Usage

```
ssplot(x, ...)

## S4 method for signature 'enrichResult'
ssplot(x, showCategory = 30, ...)

## S4 method for signature 'gseaResult'
ssplot(x, showCategory = 30, ...)

## S4 method for signature 'compareClusterResult'
ssplot(x, showCategory = 30, ...)

ssplot.enrichResult(
  x,
  showCategory = 30,
  drfun = NULL,
  with_edge = FALSE,
  dr.params = list(),
  group_category = TRUE,
  node_label = "group",
  ...
)

ssplot.compareClusterResult(
  x,
  showCategory = 30,
  split = NULL,
  pie = "equal",
  drfun = NULL,
  with_edge = FALSE,
  cex_pie2axis = 0.0125,
  dr.params = list(),
  group_category = TRUE,
  node_label = "group",
  ...
)
```

Arguments

| | |
|-----|---|
| x | Enrichment result. |
| ... | additional parameters |
| | additional parameters can refer the following parameters. |

- `coords` a data.frame with two columns: 'x' for X-axis coordinate and 'y' for Y-axis coordinate.
- `color` Variable that used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue'. the starting position of each text label.
- `cex_line` Scale of line width.
- `min_edge` The minimum similarity threshold for whether two nodes are connected, should between 0 and 1, default value is 0.2.
- `cex_label_category` Scale of category node label size.
- `cex_category` Number indicating the amount by which plotting category nodes should be scaled relative to the default.
- `shadowtext` a logical value, whether to use shadow font.
- `label_style` style of group label, one of "shadowtext" and "ggforce".
- `repel` whether to correct the position of the label. Defaults to FALSE.
- `group_legend` Logical, if TRUE, the grouping legend will be displayed. The default is FALSE.
- `cex_label_group` Numeric, scale of group labels size, the default value is 1.
- `nWords` Numeric, the number of words in the cluster tags, the default value is 4.
- `label_format` a numeric value sets wrap length, alternatively a custom function to format axis labels.
- `clusterFunction` function of Clustering method, such as `stats::kmeans` (the default), `cluster::clara`, `cluster::fanny` or `cluster::pam`.
- `nCluster` Numeric, the number of clusters, the default value is square root of the number of nodes.

additional parameters can refer the `emapplot` function: [emapplot](#).

| | |
|-----------------------------|--|
| <code>showCategory</code> | A number or a vector of terms. If it is a number, the first n terms will be displayed. If it is a vector of terms, the selected terms will be displayed. |
| <code>drfun</code> | The function used for dimension reduction, e.g. <code>stats::cmdscale</code> (the default), <code>vegan::metaMDS</code> , or <code>ape::pcoa</code> . |
| <code>with_edge</code> | Logical, if TRUE, draw the edges of the network diagram. Will be removed in the next version. |
| <code>dr.params</code> | list, the parameters of <code>tidydr::dr</code> . one of 'category', 'group', 'all' and 'none'. |
| <code>group_category</code> | a logical, if TRUE, group the category. Will be removed in the next version. |
| <code>node_label</code> | Select which labels to be displayed, one of 'category', 'group', 'all' and 'none'. |
| <code>split</code> | separate result by 'category' variable |
| <code>pie</code> | proportion of clusters in the pie chart, one of 'equal' (default) and 'Count' Will be removed in the next version. |
| <code>cex_pie2axis</code> | It is used to adjust the relative size of the pie chart on the coordinate axis, the default value is 0.0125. |

Value

ggplot object

Examples

```
## Not run:
library(clusterProfiler)
library(org.Hs.eg.db)
library(enrichplot)
library(GOsemSim)
library(DOSE)
data(geneList)
gene <- names(geneList)[abs(geneList) > 2]
ego <- enrichGO(gene = gene,
  universe      = names(geneList),
  OrgDb         = org.Hs.eg.db,
  ont           = "BP",
  pAdjustMethod = "BH",
  pvalueCutoff  = 0.01,
  qvalueCutoff  = 0.05,
  readable      = TRUE)
d <- godata('org.Hs.eg.db', ont="BP")
ego2 <- pairwise_termsim(ego, method = "Wang", semData = d)
ssplot(ego2)

## End(Not run)
```

treeplot

treeplot

Description

Functional grouping tree diagram for enrichment result of over-representation test or gene set enrichment analysis.

Usage

```
treeplot(x, ...)

## S4 method for signature 'enrichResult'
treeplot(x, ...)

## S4 method for signature 'gseaResult'
treeplot(x, ...)

## S4 method for signature 'compareClusterResult'
treeplot(x, ...)

treeplot.enrichResult(
  x,
  showCategory = 30,
  color = "p.adjust",
  nWords = 4,
  nCluster = 5,
  cex_category = 1,
  label_format = NULL,
```

```

    label_format_cladelab = 30,
    label_format_tiplab = NULL,
    fontsize = 4,
    offset = rel(1),
    offset_tiplab = rel(1),
    hclust_method = "ward.D",
    group_color = NULL,
    extend = 0.3,
    highlight = TRUE,
    hexpand = 0.1,
    align = "both",
    highlight.params = list(highlight = TRUE, align = "both"),
    offset.params = list(bar_tree = rel(1), tiplab = rel(1), extend = 0.3, hexpand = 0.1),
    cluster.params = list(method = "ward.D", n = 5, color = NULL, label_words_n = 4,
        label_format = 30),
    ...
)

treeplot.compareClusterResult(
  x,
  showCategory = 5,
  color = "p.adjust",
  nWords = 4,
  nCluster = 5,
  cex_category = 1,
  split = NULL,
  label_format = NULL,
  label_format_cladelab = 30,
  label_format_tiplab = NULL,
  fontsize = 4,
  offset = rel(1),
  pie = "equal",
  legend_n = 3,
  offset_tiplab = rel(1),
  hclust_method = "ward.D",
  group_color = NULL,
  extend = 0.3,
  highlight = TRUE,
  geneClusterPanel = "heatMap",
  hexpand = 0.1,
  align = "both",
  cluster.params = list(method = "ward.D", n = 5, color = NULL, label_words_n = 4,
    label_format = 30),
  highlight.params = list(highlight = TRUE, align = "both"),
  clusterPanel.params = list(clusterPanel = "heatMap", pie = "equal", legend_n = 3,
    colnames_angle = 0),
  offset.params = list(bar_tree = rel(1), tiplab = rel(1), extend = 0.3, hexpand = 0.1),
  ...
)

```

Arguments

x enrichment result.

| | |
|-----------------------|--|
| ... | additional parameters |
| showCategory | number of enriched terms to display |
| color | variable that used to color enriched terms, e.g. pvalue, p.adjust or qvalue |
| nWords | The number of words in the cluster tags. Will be removed in the next version. |
| nCluster | The number of clusters, the default value is 5. Will be removed in the next version. |
| cex_category | Number indicating the amount by which plotting category. nodes should be scaled relative to the default. Will be removed in the next version. |
| label_format | a numeric value sets wrap length, alternatively a custom function to format axis labels. |
| label_format_cladelab | label_format for group labels, a numeric value sets wrap length, alternatively a custom function to format axis labels. Will be removed in the next version. |
| label_format_tiplab | label_format for tiplabs, a numeric value sets wrap length, alternatively a custom function to format axis labels. Will be removed in the next version. |
| fontsize | The size of text, default is 4. |
| offset | rel object or numeric value, distance bar and tree, offset of bar and text from the clade, default is rel(1), meaning $1 * 1.2 * x_range_of_tree$ plus distance_between_tree_and_tiplab ($1 * (1.2 * x_range_of_tree + distance_between_tree_and_tiplab)$). Will be removed in the next version. |
| offset_tiplab | tiplab offset, rel object or numeric value, the bigger the number, the farther the distance between the node and the branch. The default is rel(1), when geneClusterPanel = "pie", meaning $1 * max_radius_of_the_pies$; when geneClusterPanel = "heatMap", meaning $1 * 0.16 * column_number_of_heatMap * x_range_of_tree$; when geneClusterPanel = "dotplot", meaning $1 * 0.09 * column_number_of_dotplot * x_range_of_tree$. Will be removed in the next version. |
| hclust_method | Method of hclust. This should be (an unambiguous abbreviation of) one of "ward.D", "ward.D2", "single", "complete", "average" (= UPGMA), "mcquitty" (= WPGMA), "median" (= WPGMC) or "centroid" (= UPGMC). Will be removed in the next version. |
| group_color | A vector of group colors, the length of the vector should be the same as nCluster. Will be removed in the next version. |
| extend | Numeric, extend the length of bar, default is 0.3. Will be removed in the next version. |
| highlight | Logical value, if TRUE(default), add ggtree::geom_highlight() layer. Will be removed in the next version. |
| hexpand | expand x limits by amount of xrange * hexpand. Will be removed in the next version. |
| align | control the align direction of the edge of high light rectangular. Options is 'none', 'left', 'right', 'both (default)'. Will be removed in the next version. |
| highlight.params | list, the parameters to control the attributes of highlight layer. see the highlight.params in the following. highlight.params control the attributes of highlight layer, it can be referred to the following parameters: <ul style="list-style-type: none"> • highlight Logical value, if TRUE(default), add ggtree::geom_highlight() layer. • align control the align direction of the edge of high light rectangular. Options is 'none', 'left', 'right', 'both (default)'. |

| | |
|----------------------------------|--|
| <code>offset.params</code> | <p>list, the parameters to control the offset. see the <code>offset.params</code> in the following. <code>offset.params</code> control the attributes of <code>offset</code>, it can be referred to the following parameters:</p> <ul style="list-style-type: none"> • <code>bar_tree</code> rel object or numeric value, distance bar and tree, offset of bar and text from the clade, default is <code>rel(1)</code>, meaning $1 * 1.2 * x_range_of_tree$ plus <code>distance_between_tree_and_tiplab</code> ($1 * (1.2 * x_range_of_tree + distance_between_tree_and_tiplab)$). • <code>tiplab</code> tiplab offset, rel object or numeric value, the bigger the number, the farther the distance between the node and the branch. The default is <code>rel(1)</code>, when <code>clusterPanel = "pie"</code>, meaning $1 * max_radius_of_the_pies$; when <code>clusterPanel = "heatMap"</code>, meaning $1 * 0.16 * column_number_of_heatMap * x_range_of_tree$; when <code>clusterPanel = "dotplot"</code>, meaning $1 * 0.09 * column_number_of_dotplot * x_range_of_tree$. • <code>extend</code> Numeric, extend the length of bar, default is 0.3. • <code>hexpand</code> expand x limits by amount of <code>xrange * hexpand</code>. |
| <code>cluster.params</code> | <p>list, the parameters to control the attributes of highlighted nodes and edges. see the <code>cluster.params</code> in the following. <code>cluster.params</code> control the attributes of highlight, it can be referred to the following parameters:</p> <ul style="list-style-type: none"> • <code>method</code> function of Clustering method, such as <code>stats::kmeans</code>(the default), <code>cluster::clara</code>, <code>cluster::fanny</code> or <code>cluster::pam</code>. • <code>n</code> Numeric, the number of clusters, the default value is square root of the number of nodes. • <code>color</code> A vector of group colors, the length of the vector should be the same as <code>nCluster</code>. • <code>label_words_n</code> Numeric, the number of words in the cluster tags, the default value is 4. • <code>label_format</code> A numeric value sets wrap length, alternatively a custom function to format axis labels. |
| <code>split</code> | Separate result by 'category' variable. |
| <code>pie</code> | Used only when <code>geneClusterPanel = "pie"</code> , proportion of clusters in the pie chart, one of 'equal' (default) and 'Count'. Will be removed in the next version. |
| <code>legend_n</code> | Number of circle in legend, the default value is 3. Will be removed in the next version. |
| <code>geneClusterPanel</code> | one of "heatMap"(default), "dotplot", "pie". Will be removed in the next version. |
| <code>clusterPanel.params</code> | <p>list, the parameters to control the attributes of cluster panel. see the <code>clusterPanel.params</code> in the following. <code>clusterPanel.params</code> control the attributes of cluster panel, it can be referred to the following parameters:</p> <ul style="list-style-type: none"> • <code>clusterPanel</code> one of "heatMap"(default), "dotplot", "pie". • <code>pie</code> pUsed only when <code>ClusterPanel = "pie"</code>, proportion of clusters in the pie chart, one of 'equal' (default) and 'Count'. • <code>legend_n</code> number of circle in legend. • <code>colnames_angle</code> set the angle of colnames. |

Details

This function visualizes gene sets as a tree. Gene sets with high similarity tend to cluster together, making it easier for interpretation.

Value

ggplot object

Examples

```
## Not run:
library(clusterProfiler)
library(org.Hs.eg.db)
library(enrichplot)
library(GOsemSim)
library(ggplot2)
library(DOSE)
data(geneList)
gene <- names(geneList)[abs(geneList) > 2]
ego <- enrichGO(gene = gene,
  universe = names(geneList),
  OrgDb = org.Hs.eg.db,
  ont = "BP",
  pAdjustMethod = "BH",
  pvalueCutoff = 0.01,
  qvalueCutoff = 0.05,
  readable = TRUE)
d <- godata('org.Hs.eg.db', ont="BP")
ego2 <- pairwise_termsim(ego, method = "Wang", semData = d)
treeplot(ego2, showCategory = 30)
# use `highlight = FALSE` to remove ggtree::geom_highlight() layer.
treeplot(ego2, showCategory = 30, highlight = FALSE)
# use `offset` parameter to adjust the distance of bar and tree.
treeplot(ego2, showCategory = 30, highlight = FALSE, offset = rel(1.5))
# use `offset_tiplab` parameter to adjust the distance of nodes and branches.
treeplot(ego2, showCategory = 30, highlight = FALSE, offset_tiplab = rel(1.5))
keep <- rownames(ego2@termsim)[c(1:10, 16:20)]
keep
treeplot(ego2, showCategory = keep)
treeplot(ego2, showCategory = 20,
  group_color = c("#999999", "#E69F00", "#56B4E9", "#009E73", "#F0E442"))
# It can also graph compareClusterResult
data(gcSample)
xx <- compareCluster(gcSample, fun="enrichKEGG",
  organism="hsa", pvalueCutoff=0.05)
xx <- pairwise_termsim(xx)
treeplot(xx)

# use `geneClusterPanel` to change the gene cluster panel.
treeplot(xx, geneClusterPanel = "dotplot")

treeplot(xx, geneClusterPanel = "pie")

## End(Not run)
```

Description

upsetplot method generics

Usage

```
upsetplot(x, ...)

## S4 method for signature 'enrichResult'
upsetplot(x, n = 10, ...)

## S4 method for signature 'gseaResult'
upsetplot(x, n = 10, ...)
```

Arguments

| | |
|-----|------------------------------------|
| x | object |
| ... | additional parameters |
| n | number of categories to be plotted |

Value

plot

Author(s)

Guangchuang Yu

Examples

```
require(DOSE)
data(geneList)
de=names(geneList)[1:100]
x <- enrichDO(de)
upsetplot(x, 8)
```

volplot

volplot

Description

volcano plot for enrichment result

Usage

```
volplot(
  x,
  color = "zScore",
  xintercept = 1,
  yintercept = 2,
  showCategory = 5,
  label_format = 30,
```



```

    ...
  )

  ## S4 method for signature 'enrichResult'
  volplot(
    x,
    color = "zScore",
    xintercept = 1,
    yintercept = 2,
    showCategory = 5,
    label_format = 30,
    ...
  )

  volplot.enrichResult(
    x,
    color = "zScore",
    xintercept = 1,
    yintercept = 2,
    showCategory = 5,
    label_format = 30,
    font.size = 12,
    size = 5
  )

```

Arguments

| | |
|--------------|--|
| x | enrichment result. |
| color | selected variable to color the dots |
| xintercept | value to set x intercept |
| yintercept | value to set y intercept |
| showCategory | number of most significant enriched terms or selected terms to display determined by the variable selected to color the dots |
| label_format | a numeric value sets wrap length, alternatively a custom function to format axis labels. |
| ... | Additional parameters |
| font.size | font size for 'theme_dose()' |
| size | font size to label selected categories specified by showCategory |

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```

library(DOSE)
data(geneList)

```

```
de <- names(geneList)[1:100]  
x <- enrichDO(de)  
volplot(x)
```

Index

*** internal**
 enrichplot-package, 2
 reexports, 30

autofacet, 3

barplot.enrichResult, 3

cnetplot, 4
cnetplot,compareClusterResult-method
 (cnetplot), 4
cnetplot,enrichResult-method
 (cnetplot), 4
cnetplot,gseaResult-method (cnetplot), 4
cnetplot,list-method (cnetplot), 4
cnetplot.enrichResult (cnetplot), 4
color_palette, 7

dotplot, 8
dotplot,compareClusterResult,ANY-method
 (dotplot), 8
dotplot,compareClusterResult-method
 (dotplot), 8
dotplot,enrichResult-method (dotplot), 8
dotplot,enrichResultList,ANY-method
 (dotplot), 8
dotplot,enrichResultList-method
 (dotplot), 8
dotplot,gseaResult-method (dotplot), 8
dotplot,gseaResultList,ANY-method
 (dotplot), 8
dotplot,gseaResultList-method
 (dotplot), 8
dotplot.compareClusterResult (dotplot),
 8
dotplot.enrichResult (dotplot), 8
dotplot2, 11
drag_network, 12

emapplot, 13, 18, 34
emapplot,compareClusterResult-method
 (emapplot), 13
emapplot,enrichResult-method
 (emapplot), 13
emapplot,gseaResult-method (emapplot),
 13
emapplot.compareClusterResult
 (emapplot), 13
emapplot.enrichResult (emapplot), 13
emapplot_cluster, 18
enrichplot (enrichplot-package), 2
enrichplot-package, 2

facet_grid, 30
facet_grid (reexports), 30
fortify.compareClusterResult, 18
fortify.enrichResult
 (fortify.compareClusterResult),
 18

geom_gsea_gene, 19
ggtable, 20
ggtitle, 30
ggtitle (reexports), 30
godata, 28
goplot, 20
goplot,enrichResult-method (goplot), 20
goplot,gseaResult-method (goplot), 20
goplot.enrichResult (goplot), 20
gseadist, 22
gseaplot, 22
gseaplot,gseaResult-method (gseaplot),
 22
gseaplot.gseaResult (gseaplot), 22
gseaplot2, 24
gsearank, 25
gsInfo, 25

heatplot, 26
heatplot,enrichResult-method
 (heatplot), 26
heatplot,gseaResult-method (heatplot),
 26
heatplot.enrichResult (heatplot), 26
hplot, 27

pairwise_termsim, 17, 27
pairwise_termsim,compareClusterResult-method
 (pairwise_termsim), 27

pairwise_termsim, enrichResult-method
 (pairwise_termsim), 27
pairwise_termsim, gseaResult-method
 (pairwise_termsim), 27
pairwise_termsim.compareClusterResult
 (pairwise_termsim), 27
pairwise_termsim.enrichResult
 (pairwise_termsim), 27
plot_list, 30
plot_list(reexports), 30
plotting.clusterProfile, 29
pmcplot, 30

reexports, 30
ridgeplot, 31
ridgeplot, gseaResult-method
 (ridgeplot), 31
ridgeplot.gseaResult(ridgeplot), 31

set_enrichplot_color, 32
ssplot, 33
ssplot, compareClusterResult-method
 (ssplot), 33
ssplot, enrichResult-method(ssplot), 33
ssplot, gseaResult-method(ssplot), 33
ssplot.compareClusterResult(ssplot), 33
ssplot.enrichResult(ssplot), 33

treepplot, 35
treepplot, compareClusterResult-method
 (treepplot), 35
treepplot, enrichResult-method
 (treepplot), 35
treepplot, gseaResult-method(treepplot),
 35
treepplot.compareClusterResult
 (treepplot), 35
treepplot.enrichResult(treepplot), 35

upsetplot, 39
upsetplot, enrichResult, ANY-method
 (upsetplot), 39
upsetplot, enrichResult-method
 (upsetplot), 39
upsetplot, gseaResult(upsetplot), 39
upsetplot, gseaResult-method
 (upsetplot), 39

volplot, 40
volplot, enrichResult-method(volplot),
 40
volplot.enrichResult(volplot), 40