

Team Reference Document

Heltion

January 23, 2024

Contents

1	Contest	1
1.1	Makefile	1
1.2	.clang-format	1
1.3	debug.h	1
1.4	Template	1
1.5	pbds	1
2	Graph	1
2.1	Connected Components	1
2.1.1	Strongly Connected Components	1
2.1.2	Two-vertex-connected Components	2
2.1.3	Two-edge-connected Components	2
2.1.4	Three-edge-connected Components	2
2.2	Euler Walks	3
2.3	Dominator Tree	4
2.4	Directed Minimum Spanning Tree	4
2.5	K Shortest Paths	5
2.6	Global Minimum Cut	5
2.7	Minimum Perfect Matching on Bipartite Graph	6
2.8	Matching on General Graph	6
2.9	Maximum Flow	7
2.10	Minimum Cost Maximum Flow	8
3	Data Structure	9
3.1	Disjoint Set Union	9
3.2	Sparse Table	9
3.3	Treap	10
3.4	Lines Maximum	10
3.5	Segments Maximum	11
3.6	Segment Beats	11
3.7	Tree	12
3.7.1	Least Common Ancestor	12
3.7.2	Link Cut Tree	12
4	String	13
4.1	Z	13
4.2	Lyndon Factorization	14
4.3	Border	14
4.4	Manacher	14
4.5	Suffix Array	14
4.6	Aho-Corasick Automaton	14
4.7	Suffix Automaton	15
4.8	Palindromic Tree	15
5	Number Theory	16
5.1	Gaussian Integer	16
5.2	Modular Arithmetic	16
5.2.1	Sqrt	16
5.2.2	Logarithm	16
5.3	Chinese Remainder Theorem	16
5.4	Miller Rabin	17
5.5	Pollard Rho	17
5.6	Primitive Root	17
5.7	Sum of Floor	17
5.8	Minimum of Remainder	18
5.9	Stern Brocot Tree	18
5.10	Nim Product	18
6	Numerical	19
6.1	Golden Search	19
6.2	Adaptive Simpson	19
6.3	Simplex	19
6.4	Green's Theorem	20
6.5	Double Integral	20
7	Convolution	20
7.1	Fast Fourier Transform on \mathbb{C}	20
7.2	Formal Power Series on \mathbb{F}_p	20
7.2.1	Newton's Method	20
7.2.2	Arithmetic	20
7.2.3	Interpolation	20
7.2.4	Primes with root 3	21
7.3	Circular Transform	21
7.4	Truncated Transform	21
8	Geometry	21
8.1	Pick's Theorem	21
8.2	2D Geometry	21

1 Contest

1.1 Makefile

```
%.cpp
    g++ $< -o $@ -std=gnu++20 -O2 -Wall -Wextra \
    -D_GLIBCXX_DEBUG -D_GLIBCXX_DEBUG_PEDANTIC
```

1.2 .clang-format

```
BasedOnStyle: Chromium
IndentWidth: 2
TabWidth: 2
AllowShortIfStatementsOnASingleLine: true
AllowShortLoopsOnASingleLine: true
AllowShortBlocksOnASingleLine: true
AllowShortFunctionsOnASingleLine: All
AlwaysBreakTemplateDeclarations: false
ColumnLimit: 77
```

1.3 debug.h

```
#include <bits/stdc++.h>
using namespace std;
template <class T, size_t size = tuple_size<T>::value>
string to_debug(T, string s = "")
    requires(not ranges::range<T>);
string to_debug(auto x)
    requires requires(ostream& os) { os << x; }
{
    return static_cast<ostringstream>(ostringstream() << x).str();
}
string to_debug(ranges::range auto x, string s = "")
    requires(not is_same_v<decltype(x), string>)
{
    for (auto xi : x) { s += ", " + to_debug(xi); }
    return "[" + s.substr(s.empty() ? 0 : 2) + "]";
}
template <class T, size_t size>
string to_debug(T x, string s)
    requires(not ranges::range<T>)
{
    [&]<size_t... I>(index_sequence<I...>) {
        ((s += ", " + to_debug(get<I>(x))), ...);
    }(make_index_sequence<size>());
    return "(" + s.substr(s.empty() ? 0 : 2) + ")";
}
#define debug(...) \
    cerr << __FILE__ ":" << __LINE__ \
    << ": " << #__VA_ARGS__ << " " << to_debug(tuple(__VA_ARGS__)) << "\n"
```

1.4 Template

```
#include <bits/stdc++.h>
using namespace std;
using i64 = int64_t;
#ifndef ONLINE_JUDGE
#include "debug.h"
#else
#define debug(...) 417
#endif
int main() {
    cin.tie(nullptr)->sync_with_stdio(false);
    cout << fixed << setprecision(20);
}
```

1.5 pbds

```
#include <bits/extc++.h>
using namespace std;
using namespace __gnu_cxx;
using namespace __gnu_pbds;
using t = tree<int,
               null_type,
               less<int>,
               rb_tree_tag,
               tree_order_statistics_node_update>;
using p = __gnu_pbds::priority_queue<int, less<int>, pairing_heap_tag>;
```

2 Graph

2.1 Connected Components

2.1.1 Strongly Connected Components

Returns strongly connected components in topologically order.

```
vector<vector<int>>>
strongly_connected_components(const vector<vector<int>>> &g) {
    int n = g.size();
    vector<bool> done(n);
    vector<int> pos(n, -1), stack;
    vector<vector<int>>> res;
    function<int(int)> dfs = [&](int u) {
        int low = pos[u] = stack.size();
        stack.push_back(u);
        for (int v : g[u]) {
            if (not done[v]) { low = min(low, ~pos[v] ? pos[v] : dfs(v)); }
        }
        if (low == pos[u]) {
            res.emplace_back(stack.begin() + low, stack.end());
        }
    };
    for (int i = 0; i < n; i++) {
        if (not done[i]) dfs(i);
    }
    return res;
}
```

```

        for (int v : res.back()) { done[v] = true; }
        stack.resize(low);
    }
    return low;
};
for (int i = 0; i < n; i += 1) {
    if (not done[i]) { dfs(i); }
}
ranges::reverse(res);
return res;
}

```

2.1.2 Two-vertex-connected Components

```

vector<vector<int>>
two_vertex_connected_components(const vector<vector<int>> &g) {
    int n = g.size();
    vector<int> pos(n, -1), stack;
    vector<vector<int>> res;
    function<int(int, int)> dfs = [&](int u, int p) {
        int low = pos[u] = stack.size(), son = 0;
        stack.push_back(u);
        for (int v : g[u]) {
            if (v != p) {
                if (~pos[v]) {
                    low = min(low, pos[v]);
                } else {
                    int end = stack.size(), lowv = dfs(v, u);
                    low = min(low, lowv);
                    if (lowv >= pos[u] and (~p or son++)) {
                        res.emplace_back(stack.begin() + end, stack.end());
                        res.back().push_back(u);
                        stack.resize(end);
                    }
                }
            }
        }
        return low;
    };
    for (int i = 0; i < n; i += 1) {
        if (pos[i] == -1) {
            dfs(i, -1);
            res.emplace_back(move(stack));
        }
    }
    return res;
}

```

2.1.3 Two-edge-connected Components

```

vector<vector<int>> bcc(const vector<vector<int>> &g) {
    int n = g.size();
    vector<int> pos(n, -1), stack;
    vector<vector<int>> res;
    function<int(int, int)> dfs = [&](int u, int p) {
        int low = pos[u] = stack.size(), pc = 0;
        stack.push_back(u);
        for (int v : g[u]) {
            if (~pos[v]) {
                if (v != p or pc++) { low = min(low, pos[v]); }
            } else {
                low = min(low, dfs(v, u));
            }
        }
        if (low == pos[u]) {
            res.emplace_back(stack.begin() + low, stack.end());
            stack.resize(low);
        }
        return low;
    };
    for (int i = 0; i < n; i += 1) {
        if (pos[i] == -1) { dfs(i, -1); }
    }
    return res;
}

```

2.1.4 Three-edge-connected Components

```

vector<vector<int>>
three_edge_connected_components(const vector<vector<int>> &g) {
    int n = g.size(), dft = -1;
    vector<int> pre(n, -1), post(n), path(n, -1), low(n), deg(n);
    DisjointSetUnion dsu(n);
    function<void(int, int)> dfs = [&](int u, int p) {
        int pc = 0;
        low[u] = pre[u] = dft += 1;
        for (int v : g[u]) {
            if (v != u and (v != p or pc++)) {
                if (pre[v] != -1) {
                    if (pre[v] < pre[u]) {
                        deg[u] += 1;
                        low[u] = min(low[u], pre[v]);
                    } else {
                        deg[u] -= 1;
                        for (int &p = path[u];
                            p != -1 and pre[p] <= pre[v] and pre[v] <= post[p];) {
                            dsu.merge(u, p);
                            deg[u] += deg[p];
                            p = path[p];
                        }
                    }
                }
            }
        }
    };
    dfs(0, -1);
    return res;
}

```

```

    } else {
        dfs(v, u);
        if (path[v] == -1 and deg[v] <= 1) {
            low[u] = min(low[u], low[v]);
            deg[u] += deg[v];
        } else {
            if (deg[v] == 0) { v = path[v]; }
            if (low[u] > low[v]) {
                low[u] = min(low[u], low[v]);
                swap(v, path[u]);
            }
            for (; v != -1; v = path[v]) {
                dsu.merge(u, v);
                deg[u] += deg[v];
            }
        }
    }
}
post[u] = dft;
};
for (int i = 0; i < n; i += 1) {
    if (pre[i] == -1) { dfs(i, -1); }
}
vector<vector<int>> _res(n);
for (int i = 0; i < n; i += 1) { _res[dsu.find(i)].push_back(i); }
vector<vector<int>> res;
for (auto &res_i : _res) {
    if (not res_i.empty()) { res.emplace_back(move(res_i)); }
}
return res;
}
}

```

2.2 Euler Walks

```

optional<vector<vector<pair<int, bool>>>>
undirected_walks(int n, const vector<pair<int, int>> &edges) {
    int m = ssize(edges);
    vector<vector<pair<int, bool>>> res;
    if (not m) { return res; }
    vector<vector<pair<int, bool>>> g(n);
    for (int i = 0; i < m; i += 1) {
        auto [u, v] = edges[i];
        g[u].emplace_back(i, true);
        g[v].emplace_back(i, false);
    }
    for (int i = 0; i < n; i += 1) {
        if (g[i].size() % 2) { return {}; }
    }
    vector<pair<int, bool>> walk;
    vector<bool> visited(m);
    vector<int> cur(n);
}

```

```

function<void(int)> dfs = [&](int u) {
    for (int &i = cur[u]; i < ssize(g[u]);) {
        auto [j, d] = g[u][i];
        if (not visited[j]) {
            visited[j] = true;
            dfs(d ? edges[j].second : edges[j].first);
            walk.emplace_back(j, d);
        } else {
            i += 1;
        }
    }
};
for (int i = 0; i < n; i += 1) {
    dfs(i);
    if (not walk.empty()) {
        ranges::reverse(walk);
        res.emplace_back(move(walk));
    }
}
return res;
}
optional<vector<vector<int>>>
directed_walks(int n, const vector<pair<int, int>> &edges) {
    int m = ssize(edges);
    vector<vector<int>> res;
    if (not m) { return res; }
    vector<int> d(n);
    vector<vector<int>> g(n);
    for (int i = 0; i < m; i += 1) {
        auto [u, v] = edges[i];
        g[u].push_back(i);
        d[v] += 1;
    }
    for (int i = 0; i < n; i += 1) {
        if (ssize(g[i]) != d[i]) { return {}; }
    }
    vector<int> walk;
    vector<int> cur(n);
    vector<bool> visited(m);
    function<void(int)> dfs = [&](int u) {
        for (int &i = cur[u]; i < ssize(g[u]);) {
            int j = g[u][i];
            if (not visited[j]) {
                visited[j] = true;
                dfs(edges[j].second);
                walk.push_back(j);
            } else {
                i += 1;
            }
        }
    };
    for (int i = 0; i < n; i += 1) {
        dfs(i);
    }
}

```

```

    if (not walk.empty()) {
        ranges::reverse(walk);
        res.emplace_back(move(walk));
    }
}
return res;
}

```

2.3 Dominator Tree

```

vector<int> dominator(const vector<vector<int>>& g, int s) {
    int n = g.size();
    vector<int> pos(n, -1), p, label(n), dom(n), sdom(n), dsu(n), par(n);
    vector<vector<int>> rg(n), bucket(n);
    function<void(int)> dfs = [&](int u) {
        int t = p.size();
        p.push_back(u);
        label[t] = sdom[t] = dsu[t] = pos[u] = t;
        for (int v : g[u]) {
            if (pos[v] == -1) {
                dfs(v);
                par[pos[v]] = t;
            }
            rg[pos[v]].push_back(t);
        }
    };
    function<int(int, int)> find = [&](int u, int x) {
        if (u == dsu[u]) { return x ? -1 : u; }
        int v = find(dsu[u], x + 1);
        if (v < 0) { return u; }
        if (sdom[label[dsu[u]]] < sdom[label[u]]) { label[u] = label[dsu[u]]; }
        dsu[u] = v;
        return x ? v : label[u];
    };
    dfs(s);
    iota(dom.begin(), dom.end(), 0);
    for (int i = ssize(p) - 1; i >= 0; i -= 1) {
        for (int j : rg[i]) { sdom[i] = min(sdom[i], sdom[find(j, 0)]); }
        if (i) { bucket[sdom[i]].push_back(i); }
        for (int k : bucket[i]) {
            int j = find(k, 0);
            dom[k] = sdom[j] == sdom[k] ? sdom[j] : j;
        }
        if (i > 1) { dsu[i] = par[i]; }
    }
    for (int i = 1; i < ssize(p); i += 1) {
        if (dom[i] != sdom[i]) { dom[i] = dom[dom[i]]; }
    }
    vector<int> res(n, -1);
    res[s] = s;
    for (int i = 1; i < ssize(p); i += 1) { res[p[i]] = p[dom[i]]; }
    return res;
}

```

```

}

```

2.4 Directed Minimum Spanning Tree

```

struct Node {
    Edge e;
    int d;
    Node *l, *r;
    Node(Edge e) : e(e), d(0) { l = r = nullptr; }
    void add(int v) {
        e.w += v;
        d += v;
    }
    void push() {
        if (l) { l->add(d); }
        if (r) { r->add(d); }
        d = 0;
    }
};
Node *merge(Node *u, Node *v) {
    if (not u or not v) { return u ? v : u; }
    if (u->e.w > v->e.w) { swap(u, v); }
    u->push();
    u->r = merge(u->r, v);
    swap(u->l, u->r);
    return u;
}
void pop(Node *&u) {
    u->push();
    u = merge(u->l, u->r);
}
pair<i64, vector<int>>
directed_minimum_spanning_tree(int n, const vector<Edge> &edges, int s) {
    i64 ans = 0;
    vector<Node *> heap(n), edge(n);
    RollbackDisjointSetUnion dsu(n), rbdsu(n);
    vector<pair<Node *, int>> cycles;
    for (auto e : edges) { heap[e.v] = merge(heap[e.v], new Node(e)); }
    for (int i = 0; i < n; i += 1) {
        if (i == s) { continue; }
        for (int u = i;;) {
            if (not heap[u]) { return {}; }
            ans += (edge[u] = heap[u])->e.w;
            edge[u]->add(-edge[u]->e.w);
            int v = rbdsu.find(edge[u]->e.u);
            if (dsu.merge(u, v)) { break; }
            int t = rbdsu.time();
            while (rbdsu.merge(u, v)) {
                heap[rbdsu.find(u)] = merge(heap[u], heap[v]);
                u = rbdsu.find(u);
                v = rbdsu.find(edge[v]->e.u);
            }
        }
    }
}

```

```

        cycles.emplace_back(edge[u], t);
        while (heap[u] and rbdsu.find(heap[u]->e.u) == rbdsu.find(u)) {
            pop(heap[u]);
        }
    }
    for (auto [p, t] : cycles | views::reverse) {
        int u = rbdsu.find(p->e.v);
        rbdsu.rollback(t);
        int v = rbdsu.find(edge[u]->e.v);
        edge[v] = exchange(edge[u], p);
    }
    vector<int> res(n, -1);
    for (int i = 0; i < n; i += 1) { res[i] = i == s ? i : edge[i]->e.u; }
    return {ans, res};
}

```

2.5 K Shortest Paths

```

struct Node {
    int v, h;
    i64 w;
    Node *l, *r;
    Node(int v, i64 w) : v(v), w(w), h(1) { l = r = nullptr; }
};
Node *merge(Node *u, Node *v) {
    if (not u or not v) { return u ? v; }
    if (u->w > v->w) { swap(u, v); }
    Node *p = new Node(*u);
    p->r = merge(u->r, v);
    if (p->r and (not p->l or p->l->h < p->r->h)) { swap(p->l, p->r); }
    p->h = (p->r ? p->r->h : 0) + 1;
    return p;
}
struct Edge {
    int u, v, w;
};
template <typename T>
using minimum_heap = priority_queue<T, vector<T>, greater<T>>;
vector<i64> k_shortest_paths(int n, const vector<Edge> &edges, int s, int t,
                           int k) {
    vector<vector<int>> g(n);
    for (int i = 0; i < ssize(edges); i += 1) { g[edges[i].u].push_back(i); }
    vector<int> par(n, -1), p;
    vector<i64> d(n, -1);
    minimum_heap<pair<i64, int>> pq;
    pq.push({d[s] = 0, s});
    while (not pq.empty()) {
        auto [du, u] = pq.top();
        pq.pop();
        if (du > d[u]) { continue; }
        p.push_back(u);
    }
}

```

```

    for (int i : g[u]) {
        auto [_, v, w] = edges[i];
        if (d[v] == -1 or d[v] > d[u] + w) {
            par[v] = i;
            pq.push({d[v] = d[u] + w, v});
        }
    }
}
if (d[t] == -1) { return vector<i64>(k, -1); }
vector<Node *> heap(n);
for (int i = 0; i < ssize(edges); i += 1) {
    auto [u, v, w] = edges[i];
    if (~d[u] and ~d[v] and par[v] != i) {
        heap[v] = merge(heap[v], new Node(u, d[u] + w - d[v]));
    }
}
for (int u : p) {
    if (u != s) { heap[u] = merge(heap[u], heap[edges[par[u]].u]); }
}
minimum_heap<pair<i64, Node *>> q;
if (heap[t]) { q.push({d[t] + heap[t]->w, heap[t]}); }
vector<i64> res = {d[t]};
for (int i = 1; i < k and not q.empty(); i += 1) {
    auto [w, p] = q.top();
    q.pop();
    res.push_back(w);
    if (heap[p->v]) { q.push({w + heap[p->v]->w, heap[p->v]}); }
    for (auto c : {p->l, p->r}) {
        if (c) { q.push({w + c->w - p->w, c}); }
    }
}
res.resize(k, -1);
return res;
}

```

2.6 Global Minimum Cut

```

i64 global_minimum_cut(vector<vector<i64>> &w) {
    int n = w.size();
    if (n == 2) { return w[0][1]; }
    vector<bool> in(n);
    vector<int> add;
    vector<i64> s(n);
    i64 st = 0;
    for (int i = 0; i < n; i += 1) {
        int k = -1;
        for (int j = 0; j < n; j += 1) {
            if (not in[j]) {
                if (k == -1 or s[j] > s[k]) { k = j; }
            }
        }
        add.push_back(k);
    }
}

```

```

    st = s[k];
    in[k] = true;
    for (int j = 0; j < n; j += 1) { s[j] += w[j][k]; }
}
for (int i = 0; i < n; i += 1) {}
int x = add.rbegin()[1], y = add.back();
if (x == n - 1) { swap(x, y); }
for (int i = 0; i < n; i += 1) {
    swap(w[y][i], w[n - 1][i]);
    swap(w[i][y], w[i][n - 1]);
}
for (int i = 0; i + 1 < n; i += 1) {
    w[i][x] += w[i][n - 1];
    w[x][i] += w[n - 1][i];
}
w.pop_back();
return min(st, stoer_wagner(w));
}

```

2.7 Minimum Perfect Matching on Bipartite Graph

```

minimum_perfect_matching_on_bipartite_graph(const vector<vector<i64>>& w) {
    i64 n = w.size();
    vector<int> rm(n, -1), cm(n, -1);
    vector<i64> pi(n);
    auto resid = [&](int r, int c) { return w[r][c] - pi[c]; };
    for (int c = 0; c < n; c += 1) {
        int r =
            ranges::min(views::iota(0, n), {}, [&](int r) { return w[r][c]; });
        pi[c] = w[r][c];
        if (rm[r] == -1) {
            rm[r] = c;
            cm[c] = r;
        }
    }
    vector<int> cols(n);
    iota(cols.begin(), cols.end(), 0);
    for (int r = 0; r < n; r += 1) {
        if (rm[r] != -1) { continue; }
        vector<i64> d(n);
        for (int c = 0; c < n; c += 1) { d[c] = resid(r, c); }
        vector<int> pre(n, r);
        int scan = 0, label = 0, last = 0, col = -1;
        [&]() {
            while (true) {
                if (scan == label) {
                    last = scan;
                    i64 min = d[cols[scan]];
                    for (int j = scan; j < n; j += 1) {
                        int c = cols[j];
                        if (d[c] <= min) {
                            if (d[c] < min) {

```

```

                                min = d[c];
                                label = scan;
                            }
                        }
                        swap(cols[j], cols[label++]);
                    }
                }
                for (int j = scan; j < label; j += 1) {
                    if (int c = cols[j]; cm[c] == -1) {
                        col = c;
                        return;
                    }
                }
            }
        }();
        int c1 = cols[scan++], r1 = cm[c1];
        for (int j = label; j < n; j += 1) {
            int c2 = cols[j];
            i64 len = resid(r1, c2) - resid(r1, c1);
            if (d[c2] > d[c1] + len) {
                d[c2] = d[c1] + len;
                pre[c2] = r1;
                if (len == 0) {
                    if (cm[c2] == -1) {
                        col = c2;
                        return;
                    }
                    swap(cols[j], cols[label++]);
                }
            }
        }
    }
}

}();
for (int i = 0; i < last; i += 1) {
    int c = cols[i];
    pi[c] += d[c] - d[col];
}
for (int t = col; t != -1;) {
    col = t;
    int r = pre[col];
    cm[col] = r;
    swap(rm[r], t);
}
}
i64 res = 0;
for (int i = 0; i < n; i += 1) { res += w[i][rm[i]]; }
return {res, rm};
}

```

2.8 Matching on General Graph

```

vector<int> matching(const vector<vector<int>> &g) {
    int n = g.size();
    int mark = 0;

```



```

vector<int> matched(n, -1), par(n, -1), book(n);
auto match = [&](int s) {
    vector<int> c(n), type(n, -1);
    iota(c.begin(), c.end(), 0);
    queue<int> q;
    q.push(s);
    type[s] = 0;
    while (not q.empty()) {
        int u = q.front();
        q.pop();
        for (int v : g[u])
            if (type[v] == -1) {
                par[v] = u;
                type[v] = 1;
                int w = matched[v];
                if (w == -1) {
                    [&](int u) {
                        while (u != -1) {
                            int v = matched[par[u]];
                            matched[matched[u] = par[u]] = u;
                            u = v;
                        }
                    }(v);
                    return;
                }
                q.push(w);
                type[w] = 0;
            }
        else if (not type[v] and c[u] != c[v]) {
            int w = [&](int u, int v) {
                mark += 1;
                while (true) {
                    if (u != -1) {
                        if (book[u] == mark) { return u; }
                        book[u] = mark;
                        u = c[par[matched[u]]];
                    }
                    swap(u, v);
                }
            }(u, v);
            auto up = [&](int u, int v, int w) {
                while (c[u] != w) {
                    par[u] = v;
                    v = matched[u];
                    if (type[v] == 1) {
                        q.push(v);
                        type[v] == 0;
                    }
                    if (c[u] == u) { c[u] = w; }
                    if (c[v] == v) { c[v] = w; }
                    u = par[v];
                }
            };
            up(u, v, w);

```

```

        up(v, u, w);
        for (int i = 0; i < n; i += 1) { c[i] = c[c[i]]; }
    }
};
for (int i = 0; i < n; i += 1) {
    if (matched[i] == -1) { match(i); }
}
return matched;
}

```

2.9 Maximum Flow

```

struct HighestLabelPreflowPush {
    int n;
    vector<vector<int>> g;
    vector<Edge> edges;
    HighestLabelPreflowPush(int n) : n(n), g(n) {}
    int add(int u, int v, i64 f) {
        if (u == v) { return -1; }
        int i = ssize(edges);
        edges.push_back({u, v, f});
        g[u].push_back(i);
        edges.push_back({v, u, 0});
        g[v].push_back(i + 1);
        return i;
    }
    i64 max_flow(int s, int t) {
        vector<i64> p(n);
        vector<int> h(n), cur(n), count(n * 2);
        vector<vector<int>> pq(n * 2);
        auto push = [&](int i, i64 f) {
            auto [u, v, _] = edges[i];
            if (not p[v] and f) { pq[h[v]].push_back(v); }
            edges[i].f -= f;
            edges[i ^ 1].f += f;
            p[u] -= f;
            p[v] += f;
        };
        h[s] = n;
        count[0] = n - 1;
        p[t] = 1;
        for (int i : g[s]) { push(i, edges[i].f); }
        for (int hi = 0;;) {
            while (pq[hi].empty()) {
                if (not hi--) { return -p[s]; }
            }
            int u = pq[hi].back();
            pq[hi].pop_back();
            while (p[u] > 0) {
                if (cur[u] == ssize(g[u])) {
                    h[u] = n * 2 + 1;

```

```

    for (int i = 0; i < ssize(g[u]); i += 1) {
        auto [_ , v, f] = edges[g[u][i]];
        if (f and h[u] > h[v] + 1) {
            h[u] = h[v] + 1;
            cur[u] = i;
        }
    }
    count[h[u]] += 1;
    if (not(count[hi] -= 1) and hi < n) {
        for (int i = 0; i < n; i += 1) {
            if (h[i] > hi and h[i] < n) {
                count[h[i]] -= 1;
                h[i] = n + 1;
            }
        }
    }
    hi = h[u];
} else {
    int i = g[u][cur[u]];
    auto [_ , v, f] = edges[i];
    if (f and h[u] == h[v] + 1) {
        push(i, min(p[u], f));
    } else {
        cur[u] += 1;
    }
}
}
}
return i64(0);
};

struct Dinic {
    int n;
    vector<vector<int>>> g;
    vector<Edge> edges;
    vector<int> level;
    Dinic(int n) : n(n), g(n) {}
    int add(int u, int v, i64 f) {
        if (u == v) { return -1; }
        int i = ssize(edges);
        edges.push_back({u, v, f});
        g[u].push_back(i);
        edges.push_back({v, u, 0});
        g[v].push_back(i + 1);
        return i;
    }
    i64 max_flow(int s, int t) {
        i64 flow = 0;
        queue<int> q;
        vector<int> cur;
        auto bfs = [&]() {
            level.assign(n, -1);

```

```

            level[s] = 0;
            q.push(s);
            while (not q.empty()) {
                int u = q.front();
                q.pop();
                for (int i : g[u]) {
                    auto [_ , v, c] = edges[i];
                    if (c and level[v] == -1) {
                        level[v] = level[u] + 1;
                        q.push(v);
                    }
                }
            }
            return ~level[t];
        };
        auto dfs = [&](auto& dfs, int u, i64 limit) -> i64 {
            if (u == t) { return limit; }
            i64 res = 0;
            for (int& i = cur[u]; i < ssize(g[u]) and limit; i += 1) {
                int j = g[u][i];
                auto [_ , v, f] = edges[j];
                if (level[v] == level[u] + 1 and f) {
                    if (i64 d = dfs(dfs, v, min(f, limit))); d {
                        limit -= d;
                        res += d;
                        edges[j].f -= d;
                        edges[j ^ 1].f += d;
                    }
                }
            }
            return res;
        };
        while (bfs()) {
            cur.assign(n, 0);
            while (i64 f = dfs(dfs, s, numeric_limits<i64>::max())) { flow += f; }
        }
        return flow;
    }
};

```

2.10 Minimum Cost Maximum Flow

Constraints: there is no edge with negative cost.

```

struct MinimumCostMaximumFlow {
    template <typename T>
    using minimum_heap = priority_queue<T, vector<T>, greater<T>>;
    int n;
    vector<Edge> edges;
    vector<vector<int>>> g;
    MinimumCostMaximumFlow(int n) : n(n), g(n) {}
    int add_edge(int u, int v, i64 f, i64 c) {
        int i = edges.size();

```

```

edges.push_back({u, v, f, c});
edges.push_back({v, u, 0, -c});
g[u].push_back(i);
g[v].push_back(i + 1);
return i;
}
pair<i64, i64> flow(int s, int t) {
    constexpr i64 inf = numeric_limits<i64>::max();
    vector<i64> d, h(n);
    vector<int> p;
    auto dijkstra = [&]() {
        d.assign(n, inf);
        p.assign(n, -1);
        minimum_heap<pair<i64, int>> q;
        q.emplace(d[s] = 0, s);
        while (not q.empty()) {
            auto [du, u] = q.top();
            q.pop();
            if (du > d[u]) { continue; }
            for (int i : g[u]) {
                auto [_, v, f, c] = edges[i];
                if (f and d[v] > d[u] + h[u] - h[v] + c) {
                    p[v] = i;
                    q.emplace(d[v] = d[u] + h[u] - h[v] + c, v);
                }
            }
        }
        return ~p[t];
    };
    i64 f = 0, c = 0;
    while (dijkstra()) {
        for (int i = 0; i < n; i += 1) { h[i] += d[i]; }
        vector<int> path;
        for (int u = t; u != s; u = edges[p[u]].u) { path.push_back(p[u]); }
        i64 mf =
            edges[ranges::min(path, {}, [&](int i) { return edges[i].f; } )].f;
        f += mf;
        c += mf * h[t];
        for (int i : path) {
            edges[i].f -= mf;
            edges[i ^ 1].f += mf;
        }
    }
    return {f, c};
}
};

```

3 Data Structure

3.1 Disjoint Set Union

```

struct DisjointSetUnion {
    vector<int> dsu;
    DisjointSetUnion(int n) : dsu(n, -1) {}
    int find(int u) { return dsu[u] < 0 ? u : dsu[u] = find(dsu[u]); }
    void merge(int u, int v) {
        u = find(u);
        v = find(v);
        if (u != v) {
            if (dsu[u] > dsu[v]) { swap(u, v); }
            dsu[u] += dsu[v];
            dsu[v] = u;
        }
    }
};

struct RollbackDisjointSetUnion {
    vector<pair<int, int>> stack;
    vector<int> dsu;
    RollbackDisjointSetUnion(int n) : dsu(n, -1) {}
    int find(int u) { return dsu[u] < 0 ? u : find(dsu[u]); }
    int time() { return ssize(stack); }
    bool merge(int u, int v) {
        if ((u = find(u)) == (v = find(v))) { return false; }
        if (dsu[u] < dsu[v]) { swap(u, v); }
        stack.emplace_back(u, dsu[u]);
        dsu[v] += dsu[u];
        dsu[u] = v;
        return true;
    }
    void rollback(int t) {
        while (ssize(stack) > t) {
            auto [u, dsu_u] = stack.back();
            stack.pop_back();
            dsu[dsu[u]] -= dsu_u;
            dsu[u] = dsu_u;
        }
    }
};

```

3.2 Sparse Table

```

struct SparseTable {
    vector<vector<int>> table;
    SparseTable() {}
    SparseTable(const vector<int> &a) {
        int n = a.size(), h = bit_width(a.size());
        table.resize(h);
        table[0] = a;
        for (int i = 1; i < h; i += 1) {
            table[i].resize(n - (1 << i) + 1);
            for (int j = 0; j + (1 << i) <= n; j += 1) {
                table[i][j] = min(table[i - 1][j], table[i - 1][j + (1 << (i - 1))]);
            }
        }
    }
};

```

```

    }
}
}
int query(int l, int r) {
    int h = bit_width(unsigned(r - 1)) - 1;
    return min(table[h][l], table[h][r - (1 << h)]);
}
};
struct DisjointSparseTable {
    vector<vector<int>> table;
    DisjointSparseTable(const vector<int> &a) {
        int h = bit_width(a.size() - 1), n = a.size();
        table.resize(h, a);
        for (int i = 0; i < h; i += 1) {
            for (int j = 0; j + (1 << i) < n; j += (2 << i)) {
                for (int k = j + (1 << i) - 2; k >= j; k -= 1) {
                    table[i][k] = min(table[i][k], table[i][k + 1]);
                }
                for (int k = j + (1 << i) + 1; k < j + (2 << i) and k < n; k += 1) {
                    table[i][k] = min(table[i][k], table[i][k - 1]);
                }
            }
        }
    }
    int query(int l, int r) {
        if (l + 1 == r) { return table[0][l]; }
        int i = bit_width(unsigned(l ^ (r - 1))) - 1;
        return min(table[i][l], table[i][r - 1]);
    }
};

```

3.3 Treap

```

struct Node {
    static constexpr bool persistent = true;
    static mt19937_64 mt;
    Node *l, *r;
    u64 priority;
    int size, v;
    i64 sum;
    Node(const Node &other) { memcpy(this, &other, sizeof(Node)); }
    Node(int v) : v(v), sum(v), priority(mt()), size(1) { l = r = nullptr; }
    Node *update(Node *l, Node *r) {
        Node *p = persistent ? new Node(*this) : this;
        p->l = l;
        p->r = r;
        p->size = (l ? l->size : 0) + 1 + (r ? r->size : 0);
        p->sum = (l ? l->sum : 0) + v + (r ? r->sum : 0);
        return p;
    }
};
mt19937_64 Node::mt;

```

```

pair<Node *, Node *> split_by_v(Node *p, int v) {
    if (not p) { return {}; }
    if (p->v < v) {
        auto [l, r] = split_by_v(p->r, v);
        return {p->update(p->l, l), r};
    }
    auto [l, r] = split_by_v(p->l, v);
    return {l, p->update(r, p->r)};
}
pair<Node *, Node *> split_by_size(Node *p, int size) {
    if (not p) { return {}; }
    int l_size = p->l ? p->l->size : 0;
    if (l_size < size) {
        auto [l, r] = split_by_size(p->r, size - l_size - 1);
        return {p->update(p->l, l), r};
    }
    auto [l, r] = split_by_size(p->l, size);
    return {l, p->update(r, p->r)};
}
Node *merge(Node *l, Node *r) {
    if (not l or not r) { return l ? r; }
    if (l->priority < r->priority) { return r->update(merge(l, r->l), r->r); }
    return l->update(l->l, merge(l->r, r));
}

```

3.4 Lines Maximum

```

struct Line {
    mutable i64 k, b, p;
    bool operator<(const Line& rhs) const { return k < rhs.k; }
    bool operator<(const i64& x) const { return p < x; }
};
struct Lines : multiset<Line, less<>> {
    static constexpr i64 inf = numeric_limits<i64>::max();
    static i64 div(i64 a, i64 b) { return a / b - ((a ^ b) < 0 and a % b); }
    bool isect(iterator x, iterator y) {
        if (y == end()) { return x->p = inf, false; }
        if (x->k == y->k) {
            x->p = x->b > y->b ? inf : -inf;
        } else {
            x->p = div(y->b - x->b, x->k - y->k);
        }
        return x->p >= y->p;
    }
    void add(i64 k, i64 b) {
        auto z = insert({k, b, 0}), y = z++, x = y;
        while (isect(y, z)) { z = erase(z); }
        if (x != begin() and isect(--x, y)) { isect(x, y = erase(y)); }
        while ((y = x) != begin() and (--x)->p >= y->p) { isect(x, erase(y)); }
    }
    optional<i64> get(i64 x) {
        if (empty()) { return {}; }
    }
}

```

```

    auto it = lower_bound(x);
    return it->k * x + it->b;
}
};

```

3.5 Segments Maximum

```

struct Segment {
    i64 k, b;
    i64 get(i64 x) { return k * x + b; }
};

struct Segments {
    struct Node {
        optional<Segment> s;
        Node *l, *r;
    };
    i64 tl, tr;
    Node *root;
    Segments(i64 tl, i64 tr) : tl(tl), tr(tr), root(nullptr) {}
    void add(i64 l, i64 r, i64 k, i64 b) {
        function<void(Node *&, i64, i64, Segment)> rec = [&](Node *&p, i64 tl,
                                                             i64 tr, Segment s) {

            if (p == nullptr) { p = new Node(); }
            i64 tm = midpoint(tl, tr);
            if (tl >= l and tr <= r) {
                if (not p->s) {
                    p->s = s;
                    return;
                }
                auto t = p->s.value();
                if (t.get(tl) >= s.get(tl)) {
                    if (t.get(tr) >= s.get(tr)) { return; }
                    if (t.get(tm) >= s.get(tm)) { return rec(p->r, tm + 1, tr, s); }
                    p->s = s;
                    return rec(p->l, tl, tm, t);
                }
                if (t.get(tr) <= s.get(tr)) {
                    p->s = s;
                    return;
                }
                if (t.get(tm) <= s.get(tm)) {
                    p->s = s;
                    return rec(p->r, tm + 1, tr, t);
                }
                return rec(p->l, tl, tm, s);
            }
            if (l <= tm) { rec(p->l, tl, tm, s); }
            if (r > tm) { rec(p->r, tm + 1, tr, s); }
        };
        rec(root, tl, tr, {k, b});
    }
    optional<i64> get(i64 x) {

```

```

        optional<i64> res = {};
        function<void(Node *, i64, i64)> rec = [&](Node *p, i64 tl, i64 tr) {
            if (p == nullptr) { return; }
            i64 tm = midpoint(tl, tr);
            if (p->s) {
                i64 y = p->s.value().get(x);
                if (not res or res.value() < y) { res = y; }
            }
            if (x <= tm) {
                rec(p->l, tl, tm);
            } else {
                rec(p->r, tm + 1, tr);
            }
        };
        rec(root, tl, tr);
        return res;
    }
};

```

3.6 Segment Beats

```

struct Mv {
    static constexpr i64 inf = numeric_limits<i64>::max() / 2;
    i64 mv, smv, cmv, tmv;
    bool less;
    i64 def() { return less ? inf : -inf; }
    i64 mmv(i64 x, i64 y) { return less ? min(x, y) : max(x, y); }
    Mv(i64 x, bool less) : less(less) {
        mv = x;
        smv = tmv = def();
        cmv = 1;
    }
    void up(const Mv& ls, const Mv& rs) {
        mv = mmv(ls.mv, rs.mv);
        smv = mmv(ls.mv == mv ? ls.smv : ls.mv, rs.mv == mv ? rs.smv : rs.mv);
        cmv = (ls.mv == mv ? ls.cmv : 0) + (rs.mv == mv ? rs.cmv : 0);
    }
    void add(i64 x) {
        mv += x;
        if (smv != def()) { smv += x; }
        if (tmv != def()) { tmv += x; }
    }
};

struct Node {
    Mv mn, mx;
    i64 sum, tsum;
    Node *ls, *rs;
    Node(i64 x = 0) : sum(x), tsum(0), mn(x, true), mx(x, false) {
        ls = rs = nullptr;
    }
    void up() {
        sum = ls->sum + rs->sum;

```

```

    mx.up(ls->mx, rs->mx);
    mn.up(ls->mn, rs->mn);
}
void down(int tl, int tr) {
    if (tsum) {
        int tm = midpoint(tl, tr);
        ls->add(tl, tm, tsum);
        rs->add(tm, tr, tsum);
        tsum = 0;
    }
    if (mn.tmv != mn.def()) {
        ls->ch(mn.tmv, true);
        rs->ch(mn.tmv, true);
        mn.tmv = mn.def();
    }
    if (mx.tmv != mx.def()) {
        ls->ch(mx.tmv, false);
        rs->ch(mx.tmv, false);
        mx.tmv = mx.def();
    }
}
bool cmp(i64 x, i64 y, bool less) { return less ? x < y : x > y; }
void add(int tl, int tr, i64 x) {
    sum += (tr - tl) * x;
    tsum += x;
    mx.add(x);
    mn.add(x);
}
void ch(i64 x, bool less) {
    auto &lms = less ? mn : mx, &rms = less ? mx : mn;
    if (not cmp(x, rms.mv, less)) { return; }
    sum += (x - rms.mv) * rms.cmv;
    if (lms.smv == rms.mv) { lms.smv = x; }
    if (lms.mv == rms.mv) { lms.mv = x; }
    if (cmp(x, rms.tmv, less)) { rms.tmv = x; }
    rms.mv = lms.tmv = x;
}
void add(int tl, int tr, int l, int r, i64 x) {
    if (tl >= l and tr <= r) { return add(tl, tr, x); }
    down(tl, tr);
    int tm = midpoint(tl, tr);
    if (l < tm) { ls->add(tl, tm, l, r, x); }
    if (r > tm) { rs->add(tm, tr, l, r, x); }
    up();
}
void ch(int tl, int tr, int l, int r, i64 x, bool less) {
    auto &lms = less ? mn : mx, &rms = less ? mx : mn;
    if (not cmp(x, rms.mv, less)) { return; }
    if (tl >= l and tr <= r and cmp(rms.smv, x, less)) {
        return ch(x, less);
    }
    down(tl, tr);
    int tm = midpoint(tl, tr);

```

```

    if (l < tm) { ls->ch(tl, tm, l, r, x, less); }
    if (r > tm) { rs->ch(tm, tr, l, r, x, less); }
    up();
}
i64 get(int tl, int tr, int l, int r) {
    if (tl >= l and tr <= r) { return sum; }
    down(tl, tr);
    i64 res = 0;
    int tm = midpoint(tl, tr);
    if (l < tm) { res += ls->get(tl, tm, l, r); }
    if (r > tm) { res += rs->get(tm, tr, l, r); }
    return res;
}
};

```

3.7 Tree

3.7.1 Least Common Ancestor

```

struct LeastCommonAncestor {
    SparseTable st;
    vector<int> p, time, a, par;
    LeastCommonAncestor(int root, const vector<vector<int>> &g) {
        int n = g.size();
        time.resize(n, -1);
        par.resize(n, -1);
        function<void(int)> dfs = [&](int u) {
            time[u] = p.size();
            p.push_back(u);
            for (int v : g[u]) {
                if (time[v] == -1) {
                    par[v] = u;
                    dfs(v);
                }
            }
        };
        dfs(root);
        a.resize(n);
        for (int i = 1; i < n; i += 1) { a[i] = time[par[p[i]]]; }
        st = SparseTable(a);
    }
    int query(int u, int v) {
        if (u == v) { return u; }
        if (time[u] > time[v]) { swap(u, v); }
        return p[st.query(time[u] + 1, time[v] + 1)];
    }
};

```

3.7.2 Link Cut Tree

```

template <class T, class E, class REV, class OP> struct Node {
    T t, st;
    bool reversed;
    Node* par;
    array<Node*, 2> ch;
    Node(T t = E()) : t(t), st(t), reversed(false), par(nullptr) {
        ch.fill(nullptr);
    }
    int get_s() {
        if (par == nullptr) { return -1; }
        if (par->ch[0] == this) { return 0; }
        if (par->ch[1] == this) { return 1; }
        return -1;
    }
    void push_up() {
        st = OP()(ch[0] ? ch[0]->st : E(), OP()(t, ch[1] ? ch[1]->st : E()));
    }
    void reverse() {
        reversed ^= 1;
        st = REV()(st);
    }
    void push_down() {
        if (reversed) {
            swap(ch[0], ch[1]);
            if (ch[0]) { ch[0]->reverse(); }
            if (ch[1]) { ch[1]->reverse(); }
            reversed = false;
        }
    }
    void attach(int s, Node* u) {
        if ((ch[s] = u)) { u->par = this; }
        push_up();
    }
    void rotate() {
        auto p = par;
        auto pp = p->par;
        int s = get_s();
        int ps = p->get_s();
        p->attach(s, ch[s ^ 1]);
        attach(s ^ 1, p);
        if (~ps) { pp->attach(ps, this); }
        par = pp;
    }
    void splay() {
        push_down();
        while (~get_s() and ~par->get_s()) {
            par->par->push_down();
            par->push_down();
            push_down();
            (get_s() == par->get_s() ? par : this)->rotate();
            rotate();
        }
        if (~get_s()) {

```

```

            par->push_down();
            push_down();
            rotate();
        }
    }
    void access() {
        splay();
        attach(1, nullptr);
        while (par != nullptr) {
            auto p = par;
            p->splay();
            p->attach(1, this);
            rotate();
        }
    }
    void make_root() {
        access();
        reverse();
        push_down();
    }
    void link(Node* u) {
        u->make_root();
        access();
        attach(1, u);
    }
    void cut(Node* u) {
        u->make_root();
        access();
        if (ch[0] == u) {
            ch[0] = u->par = nullptr;
            push_up();
        }
    }
    void set(T t) {
        access();
        this->t = t;
        push_up();
    }
    T query(Node* u) {
        u->make_root();
        access();
        return st;
    }
};

```

4 String

4.1 Z

```

vector<int> fz(const string &s) {
    int n = s.size();

```

```
vector<int> z(n);
for (int i = 1, j = 0; i < n; i += 1) {
    z[i] = max(min(z[i - j], j + z[j] - i), 0);
    while (i + z[i] < n and s[i + z[i]] == s[z[i]]) { z[i] += 1; }
    if (i + z[i] > j + z[j]) { j = i; }
}
return z;
}
```

4.2 Lyndon Factorization

```
vector<int> lyndon_factorization(string const &s) {
    vector<int> res = {0};
    for (int i = 0, n = s.size(); i < n;) {
        int j = i + 1, k = i;
        for (; j < n and s[k] <= s[j]; j += 1) { k = s[k] < s[j] ? i : k + 1; }
        while (i <= k) { res.push_back(i += j - k); }
    }
    return res;
}
```

4.3 Border

```
vector<int> fborder(const string &s) {
    int n = s.size();
    vector<int> res(n);
    for (int i = 1; i < n; i += 1) {
        int &j = res[i] = res[i - 1];
        while (j and s[i] != s[j]) { j = res[j - 1]; }
        j += s[i] == s[j];
    }
    return res;
}
```

4.4 Manacher

```
vector<int> manacher(const string &s) {
    int n = s.size();
    vector<int> p(n);
    for (int i = 0, j = 0; i < n; i += 1) {
        if (j + p[j] > i) { p[i] = min(p[j * 2 - i], j + p[j] - i); }
        while (i >= p[i] and i + p[i] < n and s[i - p[i]] == s[i + p[i]]) {
            p[i] += 1;
        }
        if (i + p[i] > j + p[j]) { j = i; }
    }
    return p;
}
```

4.5 Suffix Array

```
pair<vector<int>, vector<int>> binary_lifting(const string &s) {
    int n = s.size(), k = 0;
    vector<int> p(n), rank(n), q, count;
    iota(p.begin(), p.end(), 0);
    ranges::sort(p, {}, [&](int i) { return s[i]; });
    for (int i = 0; i < n; i += 1) {
        rank[p[i]] = i and s[p[i]] == s[p[i - 1]] ? rank[p[i - 1]] : k++;
    }
    for (int m = 1; m < n; m *= 2) {
        q.resize(m);
        iota(q.begin(), q.end(), n - m);
        for (int i : p) {
            if (i >= m) { q.push_back(i - m); }
        }
        count.assign(k, 0);
        for (int i : rank) { count[i] += 1; }
        partial_sum(count.begin(), count.end(), count.begin());
        for (int i = n - 1; i >= 0; i -= 1) { p[count[rank[q[i]]] - 1] = q[i]; }
        auto previous = rank;
        previous.resize(2 * n, -1);
        k = 0;
        for (int i = 0; i < n; i += 1) {
            rank[p[i]] = i and previous[p[i]] == previous[p[i - 1]] and
                previous[p[i] + m] == previous[p[i - 1] + m]
                ? rank[p[i - 1]]
                : k++;
        }
    }
    vector<int> lcp(n);
    k = 0;
    for (int i = 0; i < n; i += 1) {
        if (rank[i]) {
            k = max(k - 1, 0);
            int j = p[rank[i] - 1];
            while (i + k < n and j + k < n and s[i + k] == s[j + k]) { k += 1; }
            lcp[rank[i]] = k;
        }
    }
    return {p, lcp};
}
```

4.6 Aho-Corasick Automaton

```
constexpr int sigma = 26;
struct Node {
    int link;
    array<int, sigma> next;
    Node() : link(0) { next.fill(0); }
};
```



```

struct AhoCorasick : vector<Node> {
    AhoCorasick() : vector<Node>(1) {}
    int add(const string &s, char first = 'a') {
        int p = 0;
        for (char si : s) {
            int c = si - first;
            if (not at(p).next[c]) {
                at(p).next[c] = size();
                emplace_back();
            }
            p = at(p).next[c];
        }
        return p;
    }
    void init() {
        queue<int> q;
        for (int i = 0; i < sigma; i += 1) {
            if (at(0).next[i]) { q.push(at(0).next[i]); }
        }
        while (not q.empty()) {
            int u = q.front();
            q.pop();
            for (int i = 0; i < sigma; i += 1) {
                if (at(u).next[i]) {
                    at(at(u).next[i]).link = at(at(u).link).next[i];
                    q.push(at(u).next[i]);
                } else {
                    at(u).next[i] = at(at(u).link).next[i];
                }
            }
        }
    }
};

```

4.7 Suffix Automaton

```

struct Node {
    int link, len;
    array<int, sigma> next;
    Node() : link(-1), len(0) { next.fill(-1); }
};
struct SuffixAutomaton : vector<Node> {
    SuffixAutomaton() : vector<Node>(1) {}
    int extend(int p, int c) {
        if (~at(p).next[c]) {
            // For online multiple strings.
            int q = at(p).next[c];
            if (at(p).len + 1 == at(q).len) { return q; }
            int clone = size();
            push_back(at(q));
            back().len = at(p).len + 1;
            while (~p and at(p).next[c] == q) {

```

```

                at(p).next[c] = clone;
                p = at(p).link;
            }
            at(q).link = clone;
            return clone;
        }
        int cur = size();
        emplace_back();
        back().len = at(p).len + 1;
        while (~p and at(p).next[c] == -1) {
            at(p).next[c] = cur;
            p = at(p).link;
        }
        if (~p) {
            int q = at(p).next[c];
            if (at(p).len + 1 == at(q).len) {
                back().link = q;
            } else {
                int clone = size();
                push_back(at(q));
                back().len = at(p).len + 1;
                while (~p and at(p).next[c] == q) {
                    at(p).next[c] = clone;
                    p = at(p).link;
                }
                at(q).link = at(cur).link = clone;
            }
        } else {
            back().link = 0;
        }
        return cur;
    }
};

```

4.8 Palindromic Tree

```

struct Node {
    int sum, len, link;
    array<int, sigma> next;
    Node(int len) : len(len) {
        sum = link = 0;
        next.fill(0);
    }
};
struct PalindromicTree : vector<Node> {
    int last;
    vector<int> s;
    PalindromicTree() : last(0) {
        emplace_back(0);
        emplace_back(-1);
        at(0).link = 1;
    }
};

```

```

int get_link(int u, int i) {
    while (i < at(u).len + 1 or s[i - at(u).len - 1] != s[i]) u = at(u).link;
    return u;
}
void extend(int i) {
    int cur = get_link(last, i);
    if (not at(cur).next[s[i]]) {
        int now = size();
        emplace_back(at(cur).len + 2);
        back().link = at(get_link(at(cur).link, i)).next[s[i]];
        back().sum = at(back().link).sum + 1;
        at(cur).next[s[i]] = now;
    }
    last = at(cur).next[s[i]];
}
};

```

5 Number Theory

5.1 Gaussian Integer

```

i64 div_floor(i64 x, i64 y) { return x / y - (x % y < 0); }
i64 div_ceil(i64 x, i64 y) { return x / y + (x % y > 0); }
i64 div_round(i64 x, i64 y) { return div_floor(2 * x + y, 2 * y); }
struct Gauss {
    i64 x, y;
    i64 norm() { return x * x + y * y; }
    bool operator!=(i64 r) { return y or x != r; }
    Gauss operator~() { return {x, -y}; }
    Gauss operator-(Gauss rhs) { return {x - rhs.x, y - rhs.y}; }
    Gauss operator*(Gauss rhs) {
        return {x * rhs.x - y * rhs.y, x * rhs.y + y * rhs.x};
    }
    Gauss operator/(Gauss rhs) {
        auto [x, y] = operator*(~rhs);
        return {div_round(x, rhs.norm()), div_round(y, rhs.norm())};
    }
    Gauss operator%(Gauss rhs) { return operator-(rhs*(operator/(rhs))); }
};

```

5.2 Modular Arithmetic

5.2.1 Sqrt

Find x such that $x^2 \equiv y \pmod{p}$.
Constraints: p is prime and $0 \leq y < p$.

```

i64 sqrt(i64 y, i64 p) {
    static mt19937_64 mt;
    if (y <= 1) { return y; };
}

```

```

if (power(y, (p - 1) / 2, p) != 1) { return -1; }
uniform_int_distribution uid(i64(0), p - 1);
i64 x, w;
do {
    x = uid(mt);
    w = (x * x + p - y) % p;
} while (power(w, (p - 1) / 2, p) == 1);
auto mul = [&](pair<i64, i64> a, pair<i64, i64> b) {
    return pair((a.first * b.first + a.second * b.second % p * w) % p,
        (a.first * b.second + a.second * b.first) % p);
};
pair<i64, i64> a = {x, 1}, res = {1, 0};
for (i64 r = (p + 1) >> 1; r; r >>= 1, a = mul(a, a)) {
    if (r & 1) { res = mul(res, a); }
}
return res.first;
}

```

5.2.2 Logarithm

Find k such that $x^k \equiv y \pmod{n}$.
Constraints: $0 \leq x, y < n$.

```

i64 log(i64 x, i64 y, i64 n) {
    if (y == 1 or n == 1) { return 0; }
    if (not x) { return y ? -1 : 1; }
    i64 res = 0, k = 1 % n;
    for (i64 d; k != y and (d = gcd(x, n)) != 1; res += 1) {
        if (y % d) { return -1; }
        n /= d;
        y /= d;
        k = k * (x / d) % n;
    }
    if (k == y) { return res; }
    unordered_map<i64, i64> mp;
    i64 px = 1, m = sqrt(n) + 1;
    for (int i = 0; i < m; i += 1, px = px * x % n) { mp[y * px % n] = i; }
    i64 ppx = k * px % n;
    for (int i = 1; i <= m; i += 1, ppx = ppx * px % n) {
        if (mp.count(ppx)) { return res + i * m - mp[ppx]; }
    }
    return -1;
}

```

5.3 Chinese Remainder Theorem

```

tuple<i64, i64, i64> exgcd(i64 a, i64 b) {
    i64 x = 1, y = 0, x1 = 0, y1 = 1;
    while (b) {
        i64 q = a / b;
        tie(x, x1) = pair(x1, x - q * x1);
    }
}

```

```

    tie(y, y1) = pair(y1, y - q * y1);
    tie(a, b) = pair(b, a - q * b);
}
return {a, x, y};
}
optional<pair<i64, i64>> linear_equations(i64 a0, i64 b0, i64 a1, i64 b1) {
    auto [d, x, y] = exgcd(a0, a1);
    if ((b1 - b0) % d) { return {}; }
    i64 a = a0 / d * a1, b = (i128)(b1 - b0) / d * x % (a1 / d);
    if (b < 0) { b += a1 / d; }
    b = (i128)(a0 * b + b0) % a;
    if (b < 0) { b += a; }
    return {{a, b}};
}

```

5.4 Miller Rabin

```

bool miller_rabin(i64 n) {
    static constexpr array<int, 9> p = {2, 3, 5, 7, 11, 13, 17, 19, 23};
    if (n == 1) { return false; }
    if (n == 2) { return true; }
    if (not(n % 2)) { return false; }
    int r = countr_zero(u64(n - 1));
    i64 d = (n - 1) >> r;
    for (int pi : p) {
        if (pi >= n) { break; }
        i64 x = power(pi, d, n);
        if (x == 1 or x == n - 1) { continue; };
        for (int j = 1; j < r; j += 1) {
            x = (i128)x * x % n;
            if (x == n - 1) { break; }
        }
        if (x != n - 1) { return false; }
    }
    return true;
};

```

5.5 Pollard Rho

```

vector<i64> pollard_rho(i64 n) {
    static mt19937_64 mt;
    uniform_int_distribution uid(i64(0), n);
    if (n == 1) { return {}; }
    vector<i64> res;
    function<void(i64)> rho = [&](i64 n) {
        if (miller_rabin(n)) { return res.push_back(n); }
        i64 d = n;
        while (d == n) {
            d = 1;
            for (i64 k = 1, y = 0, x = 0, s = 1, c = uid(mt); d == 1;

```

```

            k <= 1, y = x, s = 1) {
                for (int i = 1; i <= k; i += 1) {
                    x = ((i128)x * x + c) % n;
                    s = (i128)s * abs(x - y) % n;
                    if (not(i % 127) or i == k) {
                        d = gcd(s, n);
                        if (d != 1) { break; }
                    }
                }
            }
            rho(d);
            rho(n / d);
        };
        rho(n);
        return res;
    }
}

```

5.6 Primitive Root

Constraints: $n = 2, 4, p^k, 2p^k$ where p is odd prime.

```

i64 phi(i64 n) {
    auto pd = pollard_rho(n);
    ranges::sort(pd);
    pd.erase(ranges::unique(pd).begin(), pd.end());
    for (i64 pi : pd) { n = n / pi * (pi - 1); }
    return n;
}
i64 minimum_primitive_root(i64 n) {
    i64 pn = phi(n);
    auto pd = pollard_rho(pn);
    ranges::sort(pd);
    pd.erase(ranges::unique(pd).begin(), pd.end());
    auto check = [&](i64 r) {
        if (gcd(r, n) != 1) { return false; }
        for (i64 pi : pd) {
            if (power(r, pn / pi, n) == 1) { return false; }
        }
        return true;
    };
    i64 r = 1;
    while (not check(r)) { r += 1; }
    return r;
}

```

5.7 Sum of Floor

Returns $\sum_{i=0}^{n-1} \lfloor \frac{ai+b}{m} \rfloor$.

```

u64 sum_of_floor(u64 n, u64 m, u64 a, u64 b) {
    u64 ans = 0;

```

```

while (n) {
    ans += a / m * n * (n - 1) / 2;
    a %= m;
    ans += b / m * n;
    b %= m;
    u64 y = a * n + b;
    if (y < m) { break; }
    tie(n, m, a, b) = tuple(y / m, a, m, y % m);
}
return ans;
}

```

5.8 Minimum of Remainder

Returns $\min\{(ai + b) \bmod m : 0 \leq i < n\}$.

```

u64 min_of_mod(u64 n, u64 m, u64 a, u64 b, u64 c = 1, u64 p = 1, u64 q = 1) {
    if (a == 0) { return b; }
    if (c % 2) {
        if (b >= a) {
            u64 t = (m - b + a - 1) / a;
            u64 d = (t - 1) * p + q;
            if (n <= d) { return b; }
            n -= d;
            b += a * t - m;
        }
        b = a - 1 - b;
    } else {
        if (b < m - a) {
            u64 t = (m - b - 1) / a;
            u64 d = t * p;
            if (n <= d) { return (n - 1) / p * a + b; }
            n -= d;
            b += a * t;
        }
        b = m - 1 - b;
    }
    u64 d = m / a;
    u64 res = min_of_mod(n, a, m % a, b, c += 1, (d - 1) * p + q, d * p + q);
    return c % 2 ? m - 1 - res : a - 1 - res;
}

```

5.9 Stern Brocot Tree

```

struct Node {
    int a, b;
    vector<pair<int, char>> p;
    Node(int a, int b) : a(a), b(b) {
        // gcd(a, b) == 1
        while (a != 1 or b != 1) {
            if (a > b) {

```

```

                int k = (a - 1) / b;
                p.emplace_back(k, 'R');
                a -= k * b;
            } else {
                int k = (b - 1) / a;
                p.emplace_back(k, 'L');
                b -= k * a;
            }
        }
    }
    Node(vector<pair<int, char>> p, int _a = 1, int _b = 1)
        : p(p), a(_a), b(_b) {
        for (auto [c, d] : p | views::reverse) {
            if (d == 'R') {
                a += c * b;
            } else {
                b += c * a;
            }
        }
    }
};

```

5.10 Nim Product

```

struct NimProduct {
    array<array<u64, 64>, 64> mem;
    NimProduct() {
        for (int i = 0; i < 64; i += 1) {
            for (int j = 0; j < 64; j += 1) {
                int k = i & j;
                if (k == 0) {
                    mem[i][j] = u64(1) << (i | j);
                } else {
                    int x = k & -k;
                    mem[i][j] = mem[i ^ x][j] ^
                        mem[(i ^ x) | (x - 1)][(j ^ x) | (i & (x - 1))];
                }
            }
        }
    }
    u64 nim_product(u64 x, u64 y) {
        u64 res = 0;
        for (int i = 0; i < 64 and x >> i; i += 1) {
            if ((x >> i) % 2) {
                for (int j = 0; j < 64 and y >> j; j += 1) {
                    if ((y >> j) % 2) { res ^= mem[i][j]; }
                }
            }
        }
        return res;
    }
};

```

6 Numerical

6.1 Golden Search

```
template <int step> f64 golden_search(function<f64(f64)> f, f64 l, f64 r) {
    f64 ml = (numbers::phi - 1) * l + (2 - numbers::phi) * r;
    f64 mr = l + r - ml;
    f64 fml = f(ml), fmr = f(mr);
    for (int i = 0; i < step; i += 1)
        if (fml > fmr) {
            l = ml;
            ml = mr;
            fml = fmr;
            fmr = f(mr = (numbers::phi - 1) * r + (2 - numbers::phi) * l);
        } else {
            r = mr;
            mr = ml;
            fmr = fml;
            fml = f(ml = (numbers::phi - 1) * l + (2 - numbers::phi) * r);
        }
    return midpoint(l, r);
}
```

6.2 Adaptive Simpson

```
f64 simpson(function<f64(f64)> f, f64 l, f64 r) {
    return (r - l) * (f(l) + f(r) + 4 * f(midpoint(l, r))) / 6;
}
f64 adaptive_simpson(const function<f64(f64)> &f, f64 l, f64 r, f64 eps) {
    f64 m = midpoint(l, r);
    f64 s = simpson(f, l, r);
    f64 sl = simpson(f, l, m);
    f64 sr = simpson(f, m, r);
    f64 d = sl + sr - s;
    if (abs(d) < 15 * eps) { return (sl + sr) + d / 15; }
    return adaptive_simpson(f, l, m, eps / 2) +
        adaptive_simpson(f, m, r, eps / 2);
}
```

6.3 Simplex

Returns maximum of cx s.t. $ax \leq b$ and $x \geq 0$.

```
struct Simplex {
    int n, m;
    f64 z;
    vector<vector<f64>> a;
    vector<f64> b, c;
    vector<int> base;
    Simplex(int n, int m)
```

```
        : n(n), m(m), a(m, vector<f64>(n)), b(m), c(n), base(n + m), z(0) {
        iota(base.begin(), base.end(), 0);
    }
    void pivot(int out, int in) {
        swap(base[out + n], base[in]);
        f64 f = 1 / a[out][in];
        for (f64 &aij : a[out]) { aij *= f; }
        b[out] *= f;
        a[out][in] = f;
        for (int i = 0; i <= m; i += 1) {
            if (i != out) {
                auto &ai = i == m ? c : a[i];
                f64 &bi = i == m ? z : b[i];
                f64 f = -ai[in];
                if (f < -eps or f > eps) {
                    for (int j = 0; j < n; j += 1) { ai[j] += a[out][j] * f; }
                    ai[in] = a[out][in] * f;
                    bi += b[out] * f;
                }
            }
        }
    }
    bool feasible() {
        while (true) {
            int i = ranges::min_element(b) - b.begin();
            if (b[i] > -eps) { break; }
            int k = -1;
            for (int j = 0; j < n; j += 1) {
                if (a[i][j] < -eps and (k == -1 or base[j] > base[k])) { k = j; }
            }
            if (k == -1) { return false; }
            pivot(i, k);
        }
        return true;
    }
    bool bounded() {
        while (true) {
            int i = ranges::max_element(c) - c.begin();
            if (c[i] < eps) { break; }
            int k = -1;
            for (int j = 0; j < m; j += 1) {
                if (a[j][i] > eps) {
                    if (k == -1) {
                        k = j;
                    } else {
                        f64 d = b[j] * a[k][i] - b[k] * a[j][i];
                        if (d < -eps or (d < eps and base[j] > base[k])) { k = j; }
                    }
                }
            }
            if (k == -1) { return false; }
            pivot(k, i);
        }
    }
}
```

```

    return true;
}
vector<f64> x() const {
    vector<f64> res(n);
    for (int i = n; i < n + m; i += 1) {
        if (base[i] < n) { res[base[i]] = b[i - n]; }
    }
    return res;
}
};

```

6.4 Green's Theorem

$$\oint_C (Pdx + Qdy) = \iint_D \left(\frac{\partial Q}{\partial x} - \frac{\partial P}{\partial y} \right) dxdy.$$

6.5 Double Integral

$$\iint_D f(x, y) dxdy = \iint_D f(x(u, v), y(u, v)) \left| \begin{array}{cc} \frac{\partial x}{\partial u} & \frac{\partial x}{\partial v} \\ \frac{\partial y}{\partial u} & \frac{\partial y}{\partial v} \end{array} \right| dudv.$$

7 Convolution

7.1 Fast Fourier Transform on \mathbb{C}

```

void fft(vector<complex<f64>>& a, bool inverse) {
    int n = a.size();
    vector<int> r(n);
    for (int i = 0; i < n; i += 1) {
        r[i] = r[i / 2] / 2 | (i % 2 ? n / 2 : 0);
    }
    for (int i = 0; i < n; i += 1) {
        if (i < r[i]) { swap(a[i], a[r[i]]); }
    }
    for (int m = 1; m < n; m *= 2) {
        complex<f64> wn(exp((inverse ? 1.i : -1.i) * numbers::pi / (f64)m));
        for (int i = 0; i < n; i += m * 2) {
            complex<f64> w = 1;
            for (int j = 0; j < m; j += 1, w = w * wn) {
                auto &x = a[i + j + m], &y = a[i + j], t = w * x;
                tie(x, y) = pair(y - t, y + t);
            }
        }
    }
    if (inverse) {
        for (auto& ai : a) { ai /= n; }
    }
}

```

7.2 Formal Power Series on \mathbb{F}_p

```

void fft(vector<i64>& a, bool inverse) {
    int n = a.size();
    vector<int> r(n);
    for (int i = 0; i < n; i += 1) {
        r[i] = r[i / 2] / 2 | (i % 2 ? n / 2 : 0);
    }
    for (int i = 0; i < n; i += 1) {
        if (i < r[i]) { swap(a[i], a[r[i]]); }
    }
    for (int m = 1; m < n; m *= 2) {
        i64 wn = power(inverse ? power(g, mod - 2) : g, (mod - 1) / m / 2);
        for (int i = 0; i < n; i += m * 2) {
            i64 w = 1;
            for (int j = 0; j < m; j += 1, w = w * wn % mod) {
                auto &x = a[i + j + m], &y = a[i + j], t = w * x % mod;
                tie(x, y) = pair((y + mod - t) % mod, (y + t) % mod);
            }
        }
    }
    if (inverse) {
        i64 inv = power(n, mod - 2);
        for (auto& ai : a) { ai = ai * inv % mod; }
    }
}

```

7.2.1 Newton's Method

$$h = g(f) \Leftrightarrow G(h) = f - g^{-1}(h) \equiv 0.$$

$$h = h_0 - \frac{G(h_0)}{G'(h_0)}.$$

7.2.2 Arithmetic

- For $f = pg + q$, $p^T = f^T g^T - 1$.
- For $h = \frac{1}{f}$, $h = h_0(2 - h_0 f)$.
- For $h = \sqrt{f}$, $h = \frac{1}{2}(h_0 + \frac{f}{h_0})$.
- For $h = \log f$, $h = \int \frac{df}{f}$.
- For $h = \exp f$, $h = h_0(1 + f - \log h_0)$.

7.2.3 Interpolation

$$g(x) = \prod_i (x - x_i)$$

$$f(x) = \sum_{i=0}^{n-1} y_i \left(\prod_{j \neq i} \frac{x - x_j}{x_i - x_j} \right).$$

$$f(x) = \sum_{i=0}^{n-1} \frac{y_i}{g'(x_i)} \prod_{j \neq i} (x - x_j).$$

7.2.4 Primes with root 3

$$469762049 = 7 \times 2^{26} + 1.$$

$$4179340454199820289 = 29 \times 2^{57} + 1.$$

7.3 Circular Transform

$$A_{ij} = w_k^{ij}, A_{ij}^{-1} = \frac{1}{w_k} w_k^{-ij}.$$

7.4 Truncated Transform

$$\sum_{j=0}^{n-1} \frac{i}{\prod_{k=0}^j m_k} \bmod n \quad \text{for } 0 \leq i < \prod_{j=0}^{n-1} m_k.$$

8 Geometry

8.1 Pick's Theorem

$$\text{Area} = \#\{\text{points inside}\} + \frac{1}{2}\#\{\text{points on the border}\} - 1.$$

8.2 2D Geometry

P: point, L: line, G: convex hull or polygon, C: Circle.

```
template <typename T> T eps = 0;
template <> f64 eps<f64> = 1e-9;
template <typename T> int sign(T x) { return x < -eps<T> ? -1 : x > eps<T>; }
template <typename T> struct P {
    T x, y;
    explicit P(T x = 0, T y = 0) : x(x), y(y) {}
    P operator*(T k) { return P(x * k, y * k); }
    P operator+(P p) { return P(x + p.x, y + p.y); }
    P operator-(P p) { return P(x - p.x, y - p.y); }
    P operator-() { return P(-x, -y); }
    T len2() { return x * x + y * y; }
    T cross(P p) { return x * p.y - y * p.x; }
    T dot(P p) { return x * p.x + y * p.y; }
    bool operator==(P p) { return sign(x - p.x) == 0 and sign(y - p.y) == 0; }
    int arg() { return y < 0 or (y == 0 and x > 0) ? -1 : x or y; }
    P rotate90() { return P(-y, x); }
};
template <typename T> bool argument(P<T> lhs, P<T> rhs) {
    if (lhs.arg() != rhs.arg()) { return lhs.arg() < rhs.arg(); }
    return lhs.cross(rhs) > 0;
}
template <typename T> struct L {
    P<T> a, b;
    explicit L(P<T> a = {}, P<T> b = {}) : a(a), b(b) {}
    P<T> v() { return b - a; }
    bool contains(P<T> p) {
```

```
        return sign((p - a).cross(p - b)) == 0 and sign((p - a).dot(p - b)) <= 0;
    }
    int left(P<T> p) { return sign(v().cross(p - a)); }
    optional<pair<T, T>> intersection(L l) {
        auto y = v().cross(l.v());
        if (sign(y) == 0) { return {}; }
        auto x = (l.a - a).cross(l.v());
        return y < 0 ? pair(-x, -y) : pair(x, y);
    }
};
template <typename T> struct G {
    vector<P<T>> g;
    explicit G(int n) : g(n) {}
    explicit G(const vector<P<T>>& g) : g(g) {}
    optional<int> winding(P<T> p) {
        int n = g.size(), res = 0;
        for (int i = 0; i < n; i += 1) {
            auto a = g[i], b = g[(i + 1) % n];
            L l(a, b);
            if (l.contains(p)) { return {}; }
            if (sign(l.v().y) < 0 and l.left(p) >= 0) { continue; }
            if (sign(l.v().y) == 0) { continue; }
            if (sign(l.v().y) > 0 and l.left(p) <= 0) { continue; }
            if (sign(a.y - p.y) < 0 and sign(b.y - p.y) >= 0) { res += 1; }
            if (sign(a.y - p.y) >= 0 and sign(b.y - p.y) < 0) { res -= 1; }
        }
        return res;
    }
    G convex() {
        ranges::sort(g, {}, [&](P<T> p) { return pair(p.x, p.y); });
        vector<P<T>> h;
        for (auto p : g) {
            while (ssize(h) >= 2 and
                    sign((h.back() - h.end()[-2]).cross(p - h.back())) <= 0) {
                h.pop_back();
            }
            h.push_back(p);
        }
        int m = h.size();
        for (auto p : g | views::reverse) {
            while (ssize(h) > m and
                    sign((h.back() - h.end()[-2]).cross(p - h.back())) <= 0) {
                h.pop_back();
            }
            h.push_back(p);
        }
        h.pop_back();
        return G(h);
    }
};
// Following function are valid only for convex.
T diameter2() {
    int n = g.size();
    T res = 0;
```

```

    for (int i = 0, j = 1; i < n; i += 1) {
        auto a = g[i], b = g[(i + 1) % n];
        while (sign((b - a).cross(g[(j + 1) % n] - g[j])) > 0) {
            j = (j + 1) % n;
        }
        res = max(res, (a - g[j]).len2());
        res = max(res, (a - g[j]).len2());
    }
    return res;
}

optional<bool> contains(P<T> p) {
    if (g[0] == p) { return true; }
    if (g.size() == 1) { return false; }
    if (L(g[0], g[1]).contains(p)) { return true; }
    if (L(g[0], g[1]).left(p) <= 0) { return false; }
    if (L(g[0], g.back()).left(p) > 0) { return false; }
    int i = *ranges::partition_point(views::iota(2, ssize(g)), [&](int i) {
        return sign((p - g[0]).cross(g[i] - g[0])) <= 0;
    });
    int s = L(g[i - 1], g[i]).left(p);
    if (s == 0) { return true; }
    return s > 0;
}

int most(const function<P<T>(P<T>>& f) {
    int n = g.size();
    auto check = [&](int i) {
        return sign(f(g[i]).cross(g[(i + 1) % n] - g[i])) >= 0;
    };
    P<T> f0 = f(g[0]);
    bool check0 = check(0);
    if (not check0 and check(n - 1)) { return 0; }
    return *ranges::partition_point(views::iota(0, n), [&](int i) -> bool {
        if (i == 0) { return true; }
        bool checki = check(i);
        int t = sign(f0.cross(g[i] - g[0]));
        if (i == 1 and checki == check0 and t == 0) { return true; }
        return checki ^ (checki == check0 and t <= 0);
    });
}

pair<int, int> tan(P<T> p) {
    return {most([&](P<T> x) { return x - p; }),
            most([&](P<T> x) { return p - x; })};
}

pair<int, int> tan(L<T> l) {
    return {most([&](P<T> _) { return l.v(); }),
            most([&](P<T> _) { return -l.v(); })};
}

```

```

        most([&](P<T> _) { return -l.v(); })};
    };
};

template <typename T> vector<L<T>> half(vector<L<T>> ls, T bound) {
    // Ranges: bound ~ 6
    auto check = [&](L<T> a, L<T> b, L<T> c) {
        auto [x, y] = b.intersection(c).value();
        a = L(a.a * y, a.b * y);
        return a.left(b.a * y + b.v() * x) < 0;
    };
    ls.emplace_back(P(-bound, (T)0), P(-bound, -(T)1));
    ls.emplace_back(P((T)0, -bound), P((T)1, -bound));
    ls.emplace_back(P(bound, (T)0), P(bound, (T)1));
    ls.emplace_back(P((T)0, bound), P(-(T)1, bound));
    ranges::sort(ls, [&](L<T> lhs, L<T> rhs) {
        if (sign(lhs.v().cross(rhs.v())) == 0 and
            sign(lhs.v().dot(rhs.v())) >= 0) {
            return lhs.left(rhs.a) == -1;
        }
        return argument(lhs.v(), rhs.v());
    });
    deque<L<T>> q;
    for (int i = 0; i < ssize(ls); i += 1) {
        if (i and sign(ls[i - 1].v().cross(ls[i].v())) == 0 and
            sign(ls[i - 1].v().dot(ls[i].v())) == 1) {
            continue;
        }
        while (q.size() > 1 and check(ls[i], q.back(), q.end()[-2])) {
            q.pop_back();
        }
        while (q.size() > 1 and check(ls[i], q[0], q[1])) { q.pop_front(); }
        if (not q.empty() and sign(q.back().v().cross(ls[i].v())) <= 0) {
            return {};
        }
        q.push_back(ls[i]);
    }
    while (q.size() > 1 and check(q[0], q.back(), q.end()[-2])) {
        q.pop_back();
    }
    while (q.size() > 1 and check(q.back(), q[0], q[1])) { q.pop_front(); }
    return vector<L<T>>(q.begin(), q.end());
}

```