# MediFinder Ghana

A plain-language guide to the public site, organization administrators, and the system-wide superadmin

## Who uses MediFinder?

| | |
|---|---|
| **Public visitors** | Search the public directory for health facilities, services, and ambulance providers. No account is needed. |
| **Facility or ambulance admin** | Sign in to update the information for the one organization assigned to that account. |
| **Superadmin** | Oversees the whole system: decides access requests, manages directory records and organization admins, and reviews recorded changes. |

**Important:** the included facility and ambulance entries are demonstration data. Phone numbers are placeholders and may not connect. Do not rely on them in an emergency. The website displays a warning until real information is verified.

This guide explains access and account responsibilities. It is not a medical or emergency-response guide.

# 1. Public visitors and organization admins

## Public visitors

1. Open the public MediFinder website and search for facilities, services, or ambulance providers.
2. No sign-in is needed to search. Admin pages are separate from the public navigation.

## Facility and ambulance admins

1. An organization representative submits an access request at **/admin/register** and chooses the organization they represent.
2. The request is not an active account. The applicant cannot sign in until a superadmin reviews and approves it.
3. After approval, a facility admin can update that facility's bed counts and service availability. An ambulance admin can update that provider's available fleet.
4. An admin can only manage the organization assigned to their account.

## How the superadmin decides

The superadmin checks the applicant and their connection to the selected organization. If appropriate, the superadmin approves the request; otherwise it is rejected. Applicants are not automatically emailed, so the superadmin needs to tell them the outcome.

## The first superadmin account

Public sign-up and demo seeding cannot create a superadmin. An authorized operator creates the first account from the server with this command. The password is prompted interactively and is not placed in the command history:

```
docker compose exec -it app python -m app.superadmins create owner@example.com "System Owner"
```

Replace the example email and name with the real account details. After provisioning, the superadmin signs in at **/superadmin**. Routine approvals do not require Droplet access.

# 2. What the superadmin can manage

The superadmin is the system-wide manager. In the protected **/superadmin** dashboard they can:

1. Review and approve or reject facility and ambulance-provider access requests.
2. View every facility, ambulance provider, and active organization-admin account.
3. Edit facility and provider directory information, including location, contact information, services, insurance, bed or fleet counts, coverage, and verification status.
4. Revoke an organization admin's access.
5. Review recorded organization-admin updates and superadmin directory changes.

## Deleting a facility or ambulance provider

**Deletion is permanent. There is no recycle bin or undo button.** The dashboard asks for confirmation before deleting.

Deleting a facility also deletes its related directory records, active organization-admin accounts, and pending access requests. Deleting an ambulance provider also removes its related fleet and coverage records, its organization admins and pending requests, and clears any facility links to that provider. Check the name and ID carefully before confirming. The public directory changes immediately.

## Change history

The dashboard displays the latest 200 recorded changes. Organization-admin updates are recorded from the time the audit feature was deployed; it cannot show edits made before then. Superadmin edits and deletions are recorded too. A deleted organization's audit entry remains available for review.

# 3. Safe deployment reminders

Deploy the updated application code, then create the superadmin account once. The application creates new tables on startup. Do not reset or reseed a production database to install superadmin management; a seed reset can erase production data.

From the repository on the Droplet, update and rebuild the app with:

```
git pull --ff-only origin main
docker compose up -d --build app
```

Use a strong private password. Only give superadmin access to a person trusted to manage all MediFinder accounts and directory information. Demo admin accounts and placeholder data must be replaced or removed before real use.