Walrus

An Efficient Decentralised Storage Network

Distributed Storage



Distributed Storage



+ Incentives



Two Challenges

- Dynamic availability
- Conflate consensus with proof of storage

Two Challenges

- Dynamic availability
- Conflate consensus with proof of storage


- Slow
- 90% Junk blocks

BFT Quorum




External Chain

blockchain



data















id


blockchain
















Properties


- Honest writer can obtain a PoA
- If honest writer writes B, then honest reader can read B
- If PoA on chain, two honest readers either both read B or both read \perp


Each node adds ~55 TB

Each node adds ~55 TB









Erasure Codes

Efficient Recovery

- Clients can fail
- Nodes can be Byzantine
- Epoch change




from 2f+1 to n




from f+1 to n





primary slivers





secondary slivers













Blob id

Recovery



node 1 node 2 node 3 node 4


node 2 node 1 node 3 node 4



node 2 node 1 node 3 node 4


node 2 node 1 node 3 node 4

node 2 node 1 node 3 node 4



node 2 node 1 node 3 node 4 2f+1

Storage Optimisation



node 1 node 2 node 3 node 4

Storage Overhead


~100x

Blockchain System

Storage Overhead

~100x

Blockchain System



~4.5x

Walrus




Research Gifts



(please keep it short)

Small Blob (1kB)



Large Blob (135MB)

