

Model- and Data-Based Approaches to Wind Compensation for Airship Drones

Alexander Niclas Soukup

Master's Thesis

2026

Supervisor: Sebastian Gieray
M. Sc.

Examiner: Walter Fichter, Univ.-Prof. Dr.-Ing.



University of Stuttgart
Institute of Flight Mechanics and Controls

Erklärungen für Abschlussarbeiten am iFR

Erklärungen bei Ausgabe des Themas der Arbeit

Mir ist bekannt, dass die Arbeit im Online-Katalog der Bibliothek und auf der Institutswebseite erfasst wird, was eine dauerhafte, weltweite Sichtbarkeit der bibliographischen Daten der Arbeit zur Folge hat.

- ☐ Ich stimme der Nennung meines Namens und einer Kurzfassung der Arbeit zu diesem Zweck zu.
- ☐ Ich räume der Universität Stuttgart, Institut für Flugmechanik und Flugregelung, an dieser Arbeit und den im Rahmen dieser Arbeit entstandenen Ergebnissen ein kostenloses, zeitlich und räumlich unbeschränktes, einfaches Nutzungsrecht ein. Dieses erstreckt sich auf sämtliche bekannte Nutzungsarten und umfasst neben dem Recht auf Nutzung in Forschung, Lehre und Studium insbesondere das Recht der Vervielfältigung, Verbreitung und Änderung sowie das Recht der öffentlichen Zugänglichmachung.

Ort, Datum

Alexander Niclas Soukup

Erklärungen bei Abgabe der Arbeit

Hiermit versichere ich, dass ich diese Arbeit selbständig mit Unterstützung der Betreuer angefertigt und keine anderen als die angegebenen Quellen und Hilfsmittel verwendet habe. Fremde Beiträge habe ich als solche gekennzeichnet. Die Arbeit oder wesentliche Bestandteile davon sind weder an dieser noch an einer anderen Bildungseinrichtung bereits Gegenstand einer Prüfungsleistung gewesen und wurden nicht ohne Zustimmung der Prüferin bzw. des Prüfers bereits veröffentlicht. Ich erkläre weiterhin, bei der Erstellung der Arbeit die einschlägigen Bestimmungen entsprechend den Regeln guter wissenschaftlicher Praxis¹ eingehalten zu haben. Ich versichere, dass alle gedruckten Exemplare mit der digitalen Abgabe der Arbeit übereinstimmen.

Sollte ich der Universität Stuttgart, Institut für Flugmechanik und Flugregelung, Nutzungsrechte an dieser Arbeit und den im Rahmen dieser Arbeit entstandenen Ergebnissen eingeräumt haben, versichere ich, eventuell erforderlich gewordene Zustimmungen der Urheber zur Nutzung fremder Beiträge in meiner Arbeit eingeholt zu haben. Ich erkläre mich für den Fall der Verletzung der Rechte Dritter durch meine Arbeit bereit, der Universität Stuttgart einen daraus entstehenden Schaden zu ersetzen bzw. die Universität Stuttgart auf deren Aufforderung von eventuellen Ansprüchen Dritter freizustellen. Zusätzlich zu den vom Prüfer geforderten Exemplaren, übertrage ich der Universität Stuttgart das Eigentum an einem von mir der Bibliothek des Instituts für Flugmechanik und Flugregelung kostenlos zur Verfügung gestellten Exemplar dieser Arbeit.

Ort, Datum

Alexander Niclas Soukup

¹Siehe "Leitlinien zur Sicherung guter wissenschaftlicher Praxis" der DFG bzw. "Satzung der Universität Stuttgart zur Sicherung der Integrität wissenschaftlicher Praxis und zum Umgang mit Fehlverhalten in der Wissenschaft".

Abstract

In here, you should briefly describe the thesis content in the primary language.

Kurzfassung

In here, you should briefly describe the thesis content in the secondary language.

Acknowledgements

Contents

Erklärungen	iii
Kurzfassung / Abstract	v
Acknowledgements	vii
List of Figures	xi
List of Tables	xiii
Nomenclature	xv
1. Introduction	1
1.1. Problem setting	1
1.2. Aim of this work	1
1.3. State of the art / Related work	1
1.4. Airship squid	1
1.5. Simulation Environment / Systematic	1
2. Fundamentals	3
2.1. Coordinate Systems	3
2.2. Airship Model	3
2.2.1. Gravitational and Buoyancy Forces	4
2.2.2. Aerodynamical Forces	4
2.2.3. Propulsion Forces	4
2.3. Wind Model	4
2.3.1. Dryden Turbulence Model	4
2.4. Kalman Filter	5
2.4.1. Extended Kalman Filter	5
2.4.2. Unscented Kalman Filter	5
2.5. Disturbance Feedforward	5
3. model-based wind estimation and compensation	7
3.1. Model	7
3.1.1. Discretization	7
3.2. Kalman Filter	7
3.2.1. discrete state transition function	7
3.2.2. discrete measurement function	7
3.2.3. Process Noise and Measurement Noise	8
3.3. Implementation of UKF	8
3.4. Implementation of EKF	8
3.4.1. Analytical vs Numerical Jacobian	8
3.5. Compensation	8
4. data-driven wind estimation and compensation	9

5. Evaluation and results	11
5.1. Sensitivity to wind parameters	11
5.2. Flight Test	11
6. Conclusion and Outlook	13
Bibliography	15
A. First Appendix	17
A.1. Parameters of the airship squid	17
B. Second Appendix	19

List of Figures

List of Tables

A.1. Example Airship Parameters and Specifications 17

Nomenclature

Abbreviations

COG Center of Gravity

COV Center of Volume

CS Coordinate System

EKF Extended Kalman Filter

KF Kalman Filter

UKF Unscented Kalman Filter

Latin Letters

I Inertia Matrix with respect to the COG

Greek Letters

ω Angular velocity (rad s^{-1})

Indices

$(\cdot)_B$ Quantity describing the body

$_B(\cdot)$ Quantity in body-fixed coordinate system

$_E(\cdot)$ Quantity in Earth coordinate system

1. Introduction

This chapter serves as an overview of existing methods and ...

1.1. Problem setting

1.2. Aim of this work

The Aim of this work is to implement an algorithm for wind estimation and compensation for an unmanned airship. The algorithm should be able to reliably estimate wind speeds in conditions relating to real flight scenarios. Those include: Dynamic wind conditions with Wind gusts of max 30 km/h. Trajectories like forward and sideward flight. Rotation on the spot and forward flight while turning. The compensation should effectively minimize the influence of wind on the aircraft in a direct as possible way.

1.3. State of the art / Related work

[1]

1.4. Airship squid

The airship was designed and built by roboloon and consists of a elastic hull, which is usually filled with Helium. For maneuvering the airships has one stern propeller at the back, four fins and four impellers integrated in the fins totalling 9 control surfaces making the airship an overactuated system.

A full table showing the specifications of the airship can be found in A.1

All further work was carried out and evaluated with respect to the Airship squid.

The airship is controlled by a PID controller ... The airship is equipped with an IMU, GPS and a 1D pitot tube measuring the airspeed in the body-fixed x axis. This pitot tube yields the restriction of only measuring airspeeds above 1.5m/s, below this threshold no measurement is available.

1.5. Simulation Environment / Systematic

All algorithms are first implemented in simulation. This simulation poses a model of the airship as derived in Chapter [and an implementation of the PID controller](#). Additionally uncertainties for the forces are considered. After successful validation in the simulation a real world flight test is carried out.

ref

2. Fundamentals

2.1. Coordinate Systems

For this work two coordinate systems are considered. Firstly the body-fixed coordinate system, which axes align with the body axes according to the North-East-Down (NED) convention. The origin of the body-fixed CS coincides with the Center of Gravity of the Airship.

Secondly the earth coordinate system. For simplicity a flat earth model is assumed. In this coordinate system . The origin refers to an arbitrary point on the earths' surface and is chosen to be at the initial position of the airship. The Earth CS is inertial, which means

why flat earth?

what?

add graphics

2.2. Airship Model

The airship is modeled using a 6DOF Newton Euler approach. Therefore we assume the airship to be a rigid body with constant mass and model the translational and rotational dynamics accordingly. We want to express the dynamics in body-coordinates, which adds some complexity to the derivatives, as we need to consider rotations, but comes in handy for the computation of acting forces and moments. Also important for the implementation of the Kalman Filter, as we have measurements of that state.

The translational dynamics in body-coordinates are given by

$$m {}_B\mathbf{a}_B = {}_B\mathbf{F}_{\text{ext}} \quad (2.1)$$

where ${}_B\mathbf{a}_B$ describes the acceleration of the airship in body-fixed coordinates and ${}_B\mathbf{F}_{\text{ext}}$ represents the sum of forces acting on the COG of the airship, described in body coordinates.

To relate the acceleration of the airship ${}_B\mathbf{a}_B$ to its velocity ${}_B\mathbf{v}_B$ we need to consider the rotational velocity of the body-fixed CS w.r.t. the earth CS. Therefore we apply Eulers Transport Theorem to express the translational dynamics as follows

$${}_B\mathbf{a}_B = {}_B\left(\frac{d}{dt}\mathbf{v}_B\right) = {}_B\dot{\mathbf{v}}_B + ({}_B\boldsymbol{\omega}_{EB} \times {}_B\mathbf{v}_B) \quad (2.2)$$

whereas ${}_B\boldsymbol{\omega}_{EB}$ describes the rotational velocity of the body-fixed CS w.r.t. the Earth CS. As the Earth CS is inertial this simply reduces to the rotational velocity of the airship along its three axes.

$${}_B\boldsymbol{\omega}_{EB} = {}_B\boldsymbol{\omega}_B = \begin{pmatrix} p \\ q \\ r \end{pmatrix} \quad (2.3)$$

Combining these equations in 2.1 yields the following dynamics for the translational motion of the airship in body-fixed coordinates

$$m {}_B\dot{\mathbf{v}}_B = -m ({}_B\boldsymbol{\omega}_B \times {}_B\mathbf{v}_B) + {}_B\mathbf{F}_{\text{ext}} \quad (2.4)$$

The rotational dynamics

$$\text{todo} \quad (2.5)$$

Add rotational Dynamics

We can combine the translational dynamics 2.4 and the rotational dynamics 2.5 into one equation

$$M V = matrix \quad (2.6)$$

where $M = todo$ and $V = todo$. To complete the model we are left to model the acting Forces and Moments. By doing so we add the desired complexity to our assumed rigid body with constant mass, resulting in a way more complex body like an airship is one. The quality of the airship model depends heavily on the precise modeling of the acting forces. Any unmodeled Forces and Moments will lead to an error in the model. As it is impossible to capture all Forces and Moments we will later in our design have to consider these uncertainties.

The Forces and Moments acting on the airship can be classified into four categories: Gravitational, Buoyancy, Aerodynamical and Propulsion.

$${}_B \mathbf{F}_{\text{ext}} = F_G + F_B + F_{\text{aero}} + F_{\text{prop}} \quad (2.7)$$

Their individual contribution to the total force and moment is derived in the following.

2.2.1. Gravitational and Buoyancy Forces

2.2.2. Aerodynamical Forces

As stated in The aerodynamical forces can be further divided upon. As the aim is to achieve an as exact as possible modeling of the airship.

Drag

Added Mass

Viscous Effects

Fins

2.2.3. Propulsion Forces

To be able to compute the Propulsion Components we need to incorporate a Motor Model.

2.3. Wind Model

To make use of these dynamics an accurate wind model is desired. Although the Van Karman Model describes the turbulence spectrum more accurately in most cases this work implements the Dryden Turbulence Model due to its easier implementation. As it results in a linear model. Van Karman is not realizable.

2.3.1. Dryden Turbulence Model

The Dryden wind model can be understood as a random walk with memory. . Inputs of the Dryden wind model is white noise. State transition functions

Parameters

The Dryden Model is specified by the following parameters, W20, wind direction and L and sigmas. In the 1970s the US Army developed methods to specify parameters for the Wind model. Therefore we can directly relate the L and sigmas to the current flight state according to following equations:

as W20 and wind direction are fully determined by the wind environment these cannot be easily related to the current flight status.

2.4. Kalman Filter

2.4.1. Extended Kalman Filter

2.4.2. Unscented Kalman Filter

2.5. Disturbance Feedforward

3. model-based wind estimation and compensation

There exist several estimation methods in control theory. Beginning from simple linear models like the Luenberger Observer etc... The idea is to combine the knowledge about the nonlinear airships dynamics, which have been developed in 2.2 and the wind model into use a state estimation method. Therefore the Kalman Filter proves to be the perfect solution optimally combining dynamics and measurements.

why KF

3.1. Model

First a complete model is required to calculate the state transition function from it. Therefore we augment the six state airship model including any states that have known dynamics and are measured (position + attitude) and the wind states.

State space realization of the wind model. The parameters of the dryden wind model depend on the flight states, so we can easily express them depending on the state. Only the computation of W_{20} and wind direction is not state dependent, so we have to embody estimators for these. a) konstante schätzwerte erwiesen sich hierfür als ausreichend. Der einfluss von abweichenden angenommenen und tatsächlichen parametern erwies sich als klein b) Die Performance der Wind messung hängt stark von den richtigen parameterwerten ab. Daher wurden schätzmethode eingerichtet um die Parameter zu schätzen.

estimators
(wenn
notwendig)
nennen,
Verweis auf
ergebnisse

3.1.1. Discretization

exact discretization of the wind dynamics, approx of model dynamics

3.2. Kalman Filter

To get an Kalman Filter running we need a system in the following form

- discrete state transition function
- discrete measurement function
- Process noise
- Measurement noise

We consider the case of additive process noise, which becomes clear later as we derive the equations.

write down
eq, with f ,
 h , Q , R

3.2.1. discrete state transition function

3.2.2. discrete measurement function

The measurement function directly follows from the sensor equipment on board of the airship

3. model-based wind estimation and compensation

3.2.3. Process Noise and Measurement Noise

we have $Q = [Q_{model}, Q_{wind}]$ uncertainty through unmodeled forces uncertainty coming from wind -> discretization of covariance

measurement noise from sensor specifications Pitot tube only measurements if $u > 1.5m/s$. To account for this we implement a time varying measurement noise, setting $R_{pitottube} \rightarrow \infty$ if airspeed in x-direction is < 1.5 . To understand why this works lets look at the computation of the kalman gain. $R \rightarrow \infty$ simply means that we fully trust our dynamics and basically do not use the measurement.

RUKU vs Euler

3.3. Implementation of UKF

3.4. Implementation of EKF

3.4.1. Analytical vs Numerical Jacobian

3.5. Compensation

To compensate for the wind influence on the airship a disturbance feedforward controller is implemented. The goal is to extend the controller to

$$u = u_{PID} + u_{comp} \quad (3.1)$$

where u_{comp} compensates for the forces created by the prevailing wind ΔF , i.e. fulfilling

$$\Delta F_W = \Delta F_{prop}(u) \quad (3.2)$$

Looking at the dynamical model of the airship one sees that the wind velocity, which directly influences the airspeed via

$$V_A = V_B - V_W \quad (3.3)$$

mainly influences the aerodynamical forces acting on the airship. The

4. data-driven wind estimation and compensation

5. Evaluation and results

First the Performance of the Wind estimation algorithm is assessed in simulation. Later the combination of wind estimation and compensation is compared to the flight envelope without compensation. To evaluate the performance of the Estimation and compensation following flight scenarios are considered

- Forward Flight
 - constant velocity
 - acceleration
- Sideway Flight
 - constant velocity
 - acceleration
- Pure rotation around the yaw axis
- turn while flying forward (Vorgabe von Vorwärtsgeschwindigkeit und Drehgeschwindigkeit)

5.1. Sensitivity to wind parameters

The wind parameters W_{20} and wind direction cannot be measured or computed directly from the states and thus need to be estimated. In the following the sensitivity to the correct parameter is assessed.

5.2. Flight Test

Table:
real wind-speed vs.
assumed
windspeed
RMSE
compari-
sion, one
plot maybe

6. Conclusion and Outlook

Outlook

The model-based approach proves to be a powerful tool for wind estimation given a good model of the system is available. The Dryden wind model does not only provide a mathematical description for the wind speeds acting at the center of gravity but also yields a description for the effect of the wind on the angular rates, which are caused by differences in wind magnitudes within the prevailing wind field.

Including the angular rates induced by the differences in wind speeds within the wind field can improve the performance as the airship is especially vulnerable to wind fields considering the airship's large side surfaces. Angular rates of the wind are described by transition functions of order 2 (for the u-direction) and order 3 (for v, w direction) resulting in a increase of one order for every direction compared to wind speeds. It remains to investigate whether the gain in performance can justify the increased complexity.

The Wind estimation proved to be particularly reliable. This information can be used for advanced control and trajectory planning algorithms like MPC to increase the performance compared to the current PID setup.

Bibliography

- [1] Walter Fichter and Werner Grimm. *Flugmechanik*. Shaker Verlag, 2009.

A. First Appendix

Write your appendix content here.

A.1. Parameters of the airship squid

Table A.1.: Example Airship Parameters and Specifications

Parameter	Symbol	Value	Unit
Overall length	L	75	m
Maximum diameter	D	18	m
Envelope volume	V	10 000	m ³
Total mass	m	8 500	kg
Payload mass	m_p	1 500	kg
Helium mass	m_{He}	1 700	kg
Cruise speed	v_c	90	km/h
Maximum speed	$v_{\max}$	120	km/h
Maximum altitude	$h_{\max}$	3 000	m
Endurance	t_e	24	h
Propulsion power	P	2×150	kW
Number of engines	N_e	2	–
Buoyant force	F_b	98 000	N
Drag coefficient	C_D	0.045	–
Reference area	A	255	m ²
Moment of inertia (roll)	I_{xx}	1.2×10^5	kg m ²
Moment of inertia (pitch)	I_{yy}	8.5×10^5	kg m ²
Moment of inertia (yaw)	I_{zz}	8.9×10^5	kg m ²
Center of buoyancy offset	z_B	0.8	m

B. Second Appendix

Hello, here is some text without a meaning. This text should show what a printed text will look like at this place. If you read this text, you will get no information. Really? Is there no information? Is there a difference between this text and some nonsense like “Huardest gefburn”? Kjift – not at all! A blind text like this gives you information about the selected font, how the letters are written and an impression of the look. This text should contain all letters of the alphabet and it should be written in of the original language. There is no need for special content, but the length of words should match the language.